

1		2		3		4			
Netolované rozměry délek ISO 2768-mK		Netolované rozměry úhlů ISO 2768-mK		Ra 6,3 ✓ (✓)					
Rozsah [mm]	Úchytky [mm]	Délka odvěsny [mm]	Úchytky [°]						
od 2000 do 4000	±2	přes 400	±0°5'						
od 1000 do 2000	±1,2	od 120 do 400	±0°10'						
od 400 do 1000	±0,8	od 50 do 120	±0°20'						
od 120 do 400	±0,5	od 10 do 50	±0°30'						
od 30 do 120	±0,3	do 10	±1°						
od 6 do 30	±0,2								
od 0,5 do 6	±0,1								
B		B		B					
C		C		C					
D		D		D					
E		E		E					
F		F		F					
ODJEHLIT		REV.		POPIS / DESCRIPTION		SCHVALIL / APPROVED		DATUM / DATE	
Materiál: Material:		1.0570 / S355J2G3		Povrchová úprava: Surface treatment:					
Hmotnost (kg): Mass (kg):		73,5		Název: Title:					
Štěpánská 34 110 00 Praha 1 www.ice.cz		ICE		PLECH					
Tato technická dokumentace je duševním vlastnictvím firmy ICE Industrial Services a.s.. Bez souhlasu vlastníka nesmí být kopírována, publikována ani poskytnuta třetí osobě. This technical documentation is the intellectual property of the company ICE Industrial Services a.s.. Copying, publishing or disclosure to third parties without the expressed permission of the owner is forbidden.				Číslo výkresu: Drawing No.:		Revize: Revision:			
Navrhl: Designed:		Dalibor Kunc		TaO-00297		00			
Datum: Date:		20.01.2026							
Schválil: Approved:		Dalibor Kunc							
Datum: Date:		22.01.2026							
1		2		3		4			

