

# Fuse Bowes TB-1



connection box with 4 tracks for feeder cables with cross-section from 4 x 10 mm<sup>2</sup> up 4 x 35 mm<sup>2</sup>

max. 3 cables

the possibility of moving the fuse-sockets


**Number of fuse-sockets:** One fuse-socket mounted on L1 phase, there is a possibility of moving the fuse-socket on phase L3 by screwing-out two bolts

**Material:** integrated terminal strip – made of PTB material (butylene polyterephthalate), with high insulation parameters and high mechanical resistance; connection cover and clamp/cable protection – made of transparent polycarbonate; connection box base – made of polycarbonate reinforced by fibre glass, cable opening/outlets are protected with gaskets



Code	Symbol	Fuse sockets quantity	Protection class	Protection degree	Rated insulation voltage	Withstand stroke voltage rating	Rated current	Weight	Unit volume
324010	TB-1	1	II	IP54	500V	6kV	80A	0,71kg	1,8m <sup>3</sup>

Directive 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014),  
Directive 2011/65/UE



Fuses		
Name	Code	Weight
D01/E14 6A	322006	0,01kg
D01/E14 10A	322010	0.01kg
D01/E14 16A	322016	0.01kg