

SO- UL.ZLATOVSKA-HLAVNA



- | | | | |
|---|---|----------------|-------------------------------------|
| A | AC 16 L;PMB 45/80-55;STN EN 13108-1 | HR.80 mm | |
| | INFILTRACNYI POSTREK 1 kg/m ² ,PI STN 736126 | | |
| | ŠTRKODRVINA 0/63 ; STN EN 13285 | HR.220 mm | |
| | SPOLU: | min. HR.300 mm | /Ep,n=45 MPa/ |
| B | AC 16 L;PMB 45/80-55;STN EN 13108-1 | HR.50 mm | -LIATY SAFALT SA VYBURA V HR. 20 mm |
| | INFILTRACNYI POSTREK 1 kg/m ² ,PI STN 736126 | | |
| | JESTVUJUCA KONSTRUKCIA CHODNIKA | HR.230 mm | |
| C | BETONOVA DLAZBA | HR.60 mm | |
| | ŠTRKODRVA4-8 mm | HR.40 mm | |
| | ŠTRKODRVA | HR.100 mm | |
| | ŠTRKOPIESOK | HR.100 mm | |

Zodp. projektant	Vypracoval	HIP
Ing.Plochan	Ing.Plochan	Ing.Plochan
		
Miesto: Trenčín	Datum: 09/2016	ΣFormátov:
Investor: Mesto Trenčín		
Stavba: "CYKLOTRASY"		

SO- UL.ZLATOVSKA-HLAVNA

Nazov: VZOROVY PRIECNY REZ PFB



Liptovská4	
911 08 Trenčín SK	
Stupeň dok.	DUR-DSP
Z.c.	
Mierka: 1 : 50	Por. č.v. 4