



# Maintenance Program

## SSG-F100-AMP Rev.1

### Phase 07



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 36

215000-00-09 AIR CONDITIONING	Threshold	Interval
ATA : 21 Zone : 254 Ref. Doc. : AMM 21-61-00-710-835 Effectivity : OM-BYB, OM-BYC  AIR CONDITIONING  VISUAL CHECK OF THE PACK ECU FAULT MAGNETIC INDICATORS.		1 000 Hours

241000-00-02-1 IDG OIL SYSTEM	Threshold	Interval
ATA : 24 Zone : 432 Ref. Doc. : AMM 24-13-06-600-813 Effectivity : OM-BYB, OM-BYC  IDG OIL SYSTEM  CHANGE IDG OIL AND FILTER ELEMENT.		1 000 Hours

241000-00-02-2 IDG OIL SYSTEM	Threshold	Interval
ATA : 24 Zone : 442 Ref. Doc. : AMM 24-13-06-600-813 Effectivity : OM-BYB, OM-BYC  IDG OIL SYSTEM  CHANGE IDG OIL AND FILTER ELEMENT.		1 000 Hours

256202-00-03-1 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.1 COCKPIT NON-RECHARGEABLE FLASH LIGHT BATTERY PACK.                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

256202-00-03-2 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.2 COCKPIT NON-RECHARGEABLE FLASH LIGHT BATTERY PACK                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

256202-00-03-3 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.1 REAR CABIN NON-RECHARGEABLE FLASH LIGHT BATTERY PACK                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

256202-00-03-4 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.2 REAR CABIN NON-RECHARGEABLE FLASH LIGHT BATTERY PACK                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

256202-00-03-5 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.1 FWD NON-RECHARGEABLE FLASH LIGHT BATTERY PACK                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

256202-00-03-6 FIRST AID EQUIPMENT	Threshold	Interval
<p>ATA : 25                      Zone : 200                      Ref. Doc. : AMM 25-62-02-000-814                      Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID EQUIPMENT</p> <p>DISCARD NO.2 FWD NON-RECHARGEABLE FLASH LIGHT BATTERY PACK                      NOTE : EFFECTIVITY: TASK ONLY APPLICABLE IF NON-RECHARGEABLE FLASH LIGHTS INSTALLED.</p>		2 Years

315100-00-01 FLIGHT WARNING SYSTEM	Threshold	Interval
ATA : 31 Zone : 200 Ref. Doc. : AMM 31-51-00-710-815 Effectivity : OM-BYB, OM-BYC  FLIGHT WARNING SYSTEM  OPERATIONAL CHECK OF FLIGHT WARNING SYSTEM (FWS) LAMP TEST. NOTE : PERFORM THIS TASK IN ZONES 210, 220 AND 230		1 200 Hours
322100-00-07 NOSE LANDING GEAR	Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : AMM 32-21-03-200-816 Effectivity : OM-BYB, OM-BYC  NOSE LANDING GEAR  FUNCTIONAL CHECK OF TORQUE LINKS CENTER JOINT.		1 500 Cycles
334500-00-01 TAXI LIGHTING	Threshold	Interval
ATA : 33 Zone : 122 Ref. Doc. : AMM 12-21-01-641-823 Effectivity : OM-BYB, OM-BYC  TAXI LIGHTING  LUBRICATION OF THE SECTOR GEAR OF THE TAXI LIGHT.		3 600 Hours

340000-SSG-01	ATC SYSTEM	Threshold	Interval
ATA : 34 Zone : 200 Ref. Doc. : 34-54-00-720-815-B Effectivity : OM-BYB, OM-BYC  ATC SYSTEM  PERFORM THE FOLLOWING: - FUNCTIONAL CHECK OF ATC MODE S TRANSPONDER - USING GROUND TEST EQUIPMENT CONFIRM THE MODE S ADDRESS CODE			24 Months
341600-00-02	AIR DISTUR. DETECTION	Threshold	Interval
ATA : 34 Zone : 220 Ref. Doc. : AMM 34-16-00-710-815 Effectivity : OM-BYB, OM-BYC  AIR DISTUR. DETECTION  OPERATIONAL CHECK OF THE INTERFACE BETWEEN FMS AND EFIS. NOTE : PERFORM THIS TASK IN ZONE 223, 224 AND 250			1 200 Hours
494000-00-01	APU IGN AND STARTING	Threshold	Interval
ATA : 49 Zone : 311 Ref. Doc. : AMM 49-41-02-210-816 Effectivity : OM-BYB, OM-BYC  APU IGN AND STARTING  DETAILED INSPECTION OF APU ENGINE IGNITER PLUG.			1 000 Hours 2 Years

494000-00-02 <b>APU IGN AND STARTING</b>	Threshold	Interval
ATA        : 49 Zone        : 311 Ref. Doc.   : AMM 49-42-03-220-816 Effectivity  : OM-BYB, OM-BYC  APU IGN AND STARTING  FUNCTIONAL CHECK OF STARTER MOTOR BRUSHES.		3 000 Hours 2 Years

521251-00-01 <b>PASSENGER DOOR, EXT</b>	Threshold	Interval
ATA        : 52 Zone        : 811 Ref. Doc.   : Effectivity  : OM-BYB, OM-BYC  PASSENGER DOOR, EXT  GENERAL VISUAL INSPECTION OF PASSENGER DOOR OUTER SKIN EXTERNAL INCLUDING VENT FLAP, CLOSURE FRAMES AND CLOSURE BEAMS EXTERNAL.		2 400 Hours

523351-00-03 <b>LARGE CARGO DOORS, EXTERNAL</b>	Threshold	Interval
ATA        : 52 Zone        : 820 Ref. Doc.   : Effectivity  : OM-BYB, OM-BYC  LARGE CARGO DOORS, EXTERNAL  GENERAL VISUAL INSPECTION OF LARGE CARGO DOORS OUTER SKIN PANEL EXTERNAL, CLOSURE FRAMES AND LOWER CLOSURE BEAM.		2 400 Hours

524151-00-01 <b>FORWARD SERVICE/EMERGENCY DOOR, EXTERNAL</b>	Threshold	Interval
ATA        : 52 Zone        : 821 Ref. Doc.   : Effectivity  : OM-BYB, OM-BYC  FORWARD SERVICE/EMERGENCY DOOR, EXTERNAL  GENERAL VISUAL INSPECTION OF EXTERNAL PARTS OF FWD S/E DOOR OUTER SKIN, INCLUDING VENT FLAP, CLOSURE BEAMS AND CLOSURE FRAMES.		2 400 Hours

531030-00-02 FORWARD FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 120 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  FORWARD FUSELAGE, EXTERNAL  GENERAL VISUAL INSPECTION OF FUSELAGE SKIN EXTERNAL, BELOW STR 16/59 (FLOOR LEVEL), IN AN AREA OF 50 INCHES AROUND THE PASSENGER DOOR OPENING.		2 400 Hours

531031-00-02 FORWARD FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 261 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  FORWARD FUSELAGE, EXTERNAL  GENERAL VISUAL INSPECTION OF FUSELAGE SKIN EXTERNAL, ABOVE STR 16/59 (FLOOR LEVEL), IN AREA OF 50 INCHES AROUND THE PASSENGER DOOR OPENING.		2 400 Hours

533003-00-04-1 CENTER FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 167 Ref. Doc. : AMM 53-63-00-200-826 Effectivity : OM-BYB, OM-BYC  CENTER FUSELAGE, EXTERNAL  DETAILED INSPECTION OF AERODYNAMIC SEAL OF THE WING TO FUSELAGE FAIRINGS. NOTE : PERFORM THIS TASK IN ZONE 167, 173 and 183		2 Years

533003-00-04-2 CENTER FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 168 Ref. Doc. : AMM 53-63-00-200-826 Effectivity : OM-BYB, OM-BYC  CENTER FUSELAGE, EXTERNAL  DETAILED INSPECTION OF AERODYNAMIC SEAL OF THE WING TO FUSELAGE FAIRINGS. NOTE : PERFORM THIS TASK IN ZONE 168, 174 and 184		2 Years

533027-00-01 CENTER FUSELAGE, INTERNAL	Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  CENTER FUSELAGE, INTERNAL  GENERAL VISUAL INSPECTION OF FORWARD AND CENTER LARGE CARGO DOOR OPENING HOOKLATCH FITTING BRACKETS AND BOLTS.		2 400 Hours

533029-00-02 CENTER FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  CENTER FUSELAGE, EXTERNAL  GENERAL VISUAL INSPECTION OF FUSELAGE SKIN EXTERNAL IN AN AREA OF 50 INCHES AROUND THE LARGE FORWARD AND CENTER CARGO DOOR OPENING.		2 400 Hours

534110-00-02 REAR FUSELAGE, EXTERNAL	Threshold	Interval
ATA : 53 Zone : 190 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  REAR FUSELAGE, EXTERNAL  GENERAL VISUAL INSPECTION OF FUSELAGE SKIN EXTERNAL IN AREA OF 50 INCHES AROUND THE REAR CARGO DOOR OPENING, EXCLUDING THE AREA COVERED BY WING TO FUSELAGE FAIRING.		2 400 Hours



534125-00-01 REAR FUSELAGE, INTERNAL	Threshold	Interval
ATA : 53 Zone : 194 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  REAR FUSELAGE, INTERNAL  GENERAL VISUAL INSPECTION OF REAR CARGO DOOR OPENING HOOKLATCH FITTING BRACKETS AND BOLTS.		2 400 Hours

544000-00-01-1 STUBWING, INTERNAL	Threshold	Interval
ATA : 54 Zone : 410 Ref. Doc. : AMM 12-21-04-640-813 Effectivity : OM-BYB, OM-BYC  STUBWING, INTERNAL  LUBRICATION OF: - FORWARD SIDE VIBRATION ISOLATOR TO ENGINE FITTING ATTACHMENT. - FORWARD ENGINE MOUNT LINK ASSEMBLY. - AFT ENGINE MOUNT LINK ASSEMBLY. - ENGINE SUPPORT FITTINGS.		2 Years

544000-00-01-2 STUBWING, INTERNAL	Threshold	Interval
ATA : 54 Zone : 420 Ref. Doc. : AMM 12-21-04-640-813 Effectivity : OM-BYB, OM-BYC  STUBWING, INTERNAL  LUBRICATION OF: - FORWARD SIDE VIBRATION ISOLATOR TO ENGINE FITTING ATTACHMENT. - FORWARD ENGINE MOUNT LINK ASSEMBLY. - AFT ENGINE MOUNT LINK ASSEMBLY. - ENGINE SUPPORT FITTINGS.		2 Years

725200-00-01-1 ENGINE	Threshold	Interval
ATA : 72 Zone : 432 Ref. Doc. : AMM 72-52-24-210-816 Effectivity : OM-BYB, OM-BYC  ENGINE  GENERAL VISUAL INSPECTION OF LP 3 TURBINE BLADES.		1 200 Hours

725200-00-01-2 ENGINE	Threshold	Interval
ATA : 72 Zone : 442 Ref. Doc. : AMM 72-52-24-210-816 Effectivity : OM-BYB, OM-BYC  ENGINE  GENERAL VISUAL INSPECTION OF LP 3 TURBINE BLADES.		1 200 Hours

725300-00-01-1 ENGINE	Threshold	Interval
ATA : 72 Zone : 432 Ref. Doc. : AMM 72-53-10-200-816 Effectivity : AMM 72-53-20-200-816 OM-BYB, OM-BYC  ENGINE  GENERAL VISUAL INSPECTION OF MIXER, EXHAUST CONE AND EXHAUST CASE FAIRINGS.		1 200 Hours

725300-00-01-2 ENGINE	Threshold	Interval
ATA : 72 Zone : 442 Ref. Doc. : AMM 72-53-10-200-816 Effectivity : AMM 72-53-20-200-816 OM-BYB, OM-BYC  ENGINE  GENERAL VISUAL INSPECTION OF MIXER, EXHAUST CONE AND EXHAUST CASE FAIRINGS.		1 200 Hours

801000-00-02	STARTING	Threshold	Interval
ATA : 80 Zone : 432 Ref. Doc. : AMM 12-13-05-600-813 Effectivity : Not Effective  STARTING  CHANGE OIL OF STARTER MOTOR.			1 000 Cycles

801000-00-02-1	STARTING	Threshold	Interval
ATA : 80 Zone : 432 Ref. Doc. : AMM 12-13-05-600-813 Effectivity : OM-BYB  STARTING  CHANGE OIL OF STARTER MOTOR.			1 000 Cycles

801000-00-02-2	STARTING	Threshold	Interval
ATA : 80 Zone : 442 Ref. Doc. : AMM 12-13-05-600-813 Effectivity : OM-BYB  STARTING  CHANGE OIL OF STARTER MOTOR.			1 000 Cycles