



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

1C CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 159

ZL-131-01-1	FORWARD CARGO COMPARTMENT	Threshold	Interval
ATA : 05			3 Years
Zone : 131, 132			
Ref. Doc. : 052130-200-001			
Effectivity : OM-BYA, OM-BYK			

FORWARD CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF FORWARD CARGO COMPARTMENT (AS FAR AS VISIBLE, IF ACTs INSTALLED) (EWIS)

ZL-151-01-1	AFT CARGO COMPARTMENT	Threshold	Interval
ATA : 05			3 Years
Zone : 151, 152			
Ref. Doc. : 052150-200-001			
Effectivity : OM-BYA, OM-BYK			

AFT CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF AFT CARGO COMPARTMENT (AS FAR AS VISIBLE, IF ACT IS INSTALLED) (EWIS)

ZL-161-01-1	BULK CARGO COMPARTMENT	Threshold	Interval
ATA : 05			3 Years
Zone : 161, 162			
Ref. Doc. : 052160-200-001			
Effectivity : OM-BYA, OM-BYK			

BULK CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF BULK CARGO COMPARTMENT (AS FAR AS VISIBLE, IF ACT IS INSTALLED) (EWIS)

ZL-171-01-3 AFT CABIN UNDERFLOOR COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 171, 172 Ref. Doc. : 052170-200-001 Effectivity : OM-BYA, OM-BYK AFT CABIN UNDERFLOOR COMPARTMENT GENERAL VISUAL INSPECTION OF AFT CABIN UNDERFLOOR COMPARTMENT (EWIS)			3 Years
ZL-195-01-1 HYDRAULIC COMPARTMENT AND FAIRINGS		Threshold	Interval
ATA : 05 Zone : 195, 196 Ref. Doc. : 052190-200-005 Effectivity : OM-BYA, OM-BYK HYDRAULIC COMPARTMENT AND FAIRINGS GENERAL VISUAL INSPECTION OF HYDRAULIC COMPARTMENT AND FAIRINGS (EWIS)			3 Years
ZL-200-02-1 UPPER HALF OF FUSELAGE		Threshold	Interval
ATA : 05 Zone : 200 Ref. Doc. : 052200-200-002 Effectivity : OM-BYA, OM-BYK UPPER HALF OF FUSELAGE GENERAL VISUAL INSPECTION OF UPPER HALF OF FUSELAGE			3 Years
ZL-300-02-1 STABILIZERS AND CONE/REAR FUSELAGE		Threshold	Interval
ATA : 05 Zone : 300 Ref. Doc. : 052300-200-002 Effectivity : OM-BYA, OM-BYK STABILIZERS AND CONE/REAR FUSELAGE GENERAL VISUAL INSPECTION OF STABILIZERS AND CONE/REAR FUSELAGE			3 Years

ZL-311-01-1AFT FUSELAGE TAIL SECTION		Threshold	Interval
ATA : 05 Zone : 311, 312 Ref. Doc. : 052310-200-001 Effectivity : OM-BYA, OM-BYK Tags : CRITICAL TASK			3 Years
AFT FUSELAGE TAIL SECTION			
GENERAL VISUAL INSPECTION OF AFT FUSELAGE TAIL SECTION (EWIS)			
ZL-313-01-1TAIL CONE APU AIR INTAKE AREA		Threshold	Interval
ATA : 05 Zone : 313, 314 Ref. Doc. : 052310-200-002 Effectivity : OM-BYA, OM-BYK			3 Years
TAIL CONE APU AIR INTAKE AREA			
GENERAL VISUAL INSPECTION OF TAIL CONE APU AIR INTAKE AREA (EWIS)			
ZL-315-01-2TAIL CONE APU AND ACCESSORY COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 315, 316 Ref. Doc. : 052310-200-003 Effectivity : OM-BYA, OM-BYK			3 Years
TAIL CONE APU AND ACCESSORY COMPARTMENT			
GENERAL VISUAL INSPECTION OF TAIL CONE APU AND ACCESSORY COMPARTMENT (EWIS)			
ZL-325-01-1VERTICAL STABILIZER TRAILING EDGE		Threshold	Interval
ATA : 05 Zone : 325 Ref. Doc. : 052320-200-005 Effectivity : OM-BYA, OM-BYK			3 Years
VERTICAL STABILIZER TRAILING EDGE			
GENERAL VISUAL INSPECTION OF VERTICAL STABILIZER TRAILING EDGE (EWIS)			

ZL-334-01-1 THS TRAILING EDGE		Threshold	Interval
ATA : 05 Zone : 334, 344 Ref. Doc. : 052330-200-004 Effectivity : OM-BYA, OM-BYK THS TRAILING EDGE GENERAL VISUAL INSPECTION OF TRIMMABLE HORIZONTAL STABILIZER TRAILING EDGE (EWIS)			3 Years
ZL-411-01-1-LH LH ENGINE UPPER FORWARD PYLON		Threshold	Interval
ATA : 05 Zone : 411, 413, 414 Ref. Doc. : 052410-200-001 Effectivity : OM-BYA, OM-BYK LH ENGINE UPPER FORWARD PYLON GENERAL VISUAL INSPECTION OF UPPER FORWARD PYLON (EWIS)			3 Years
ZL-411-01-1-RH RH ENGINE UPPER FORWARD PYLON		Threshold	Interval
ATA : 05 Zone : 421, 423, 424 Ref. Doc. : 052410-200-001 Effectivity : OM-BYA, OM-BYK RH ENGINE UPPER FORWARD PYLON GENERAL VISUAL INSPECTION OF UPPER FORWARD PYLON (EWIS)			3 Years
ZL-415-01-1-LH LH ENGINE LOWER PYLON		Threshold	Interval
ATA : 05 Zone : 415, 425 Ref. Doc. : 052410-200-002 Effectivity : OM-BYA, OM-BYK LH ENGINE LOWER PYLON GENERAL VISUAL INSPECTION OF LOWER PYLON (EWIS)			3 Years

ZL-415-01-1-RH	RH ENGINE LOWER PYLON	Threshold	Interval
ATA : 05			3 Years
Zone : 425			
Ref. Doc. : 052410-200-002			
Effectivity : OM-BYA, OM-BYK			
RH ENGINE LOWER PYLON			
GENERAL VISUAL INSPECTION OF LOWER PYLON (EWIS)			

ZL-437-01-1-LH	LH ENGINE FAN COWL	Threshold	Interval
ATA : 05			3 Years
Zone : 437, 438			
Ref. Doc. : 052430-200-003			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
LH ENGINE FAN COWL			
GENERAL VISUAL INSPECTION OF FAN COWL (EWIS)			

ZL-437-01-1-RH	RH ENGINE FAN COWL	Threshold	Interval
ATA : 05			3 Years
Zone : 447, 448			
Ref. Doc. : 052430-200-003			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
RH ENGINE FAN COWL			
GENERAL VISUAL INSPECTION OF FAN COWL (EWIS)			

ZL-451-01-1-LH	LH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 05			3 Years
Zone : 451, 452			
Ref. Doc. : 052450-200-001			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
LH ENGINE THRUST REVERSER			
GENERAL VISUAL INSPECTION OF THRUST REVERSER (EWIS)			
PREPARATION NOTE: THRUST REVERSER PIVOTING DOOR OPENED;			

ZL-451-01-1-RH	RH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 05			3 Years
Zone : 461, 462			
Ref. Doc. : 052450-200-001			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
RH ENGINE THRUST REVERSER			
GENERAL VISUAL INSPECTION OF THRUST REVERSER (EWIS)			
PREPARATION NOTE: THRUST REVERSER PIVOTING DOOR OPENED;			

ZL-453-01-1-LH	LH ENGINE HOT SECTION	Threshold	Interval
ATA : 05			3 Years
Zone : 453, 454			
Ref. Doc. : 052450-200-002			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
LH ENGINE HOT SECTION			
GENERAL VISUAL INSPECTION OF HOT SECTION (EWIS)			

ZL-453-01-1-RH	RH ENGINE HOT SECTION	Threshold	Interval
ATA : 05 Zone : 463, 464 Ref. Doc. : 052450-200-002 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE HOT SECTION			
GENERAL VISUAL INSPECTION OF HOT SECTION (EWIS)			

ZL-471-01-1-LH	LH ENGINE PYLON LEADING EDGE AND LOWER FAIRING	Threshold	Interval
ATA : 05 Zone : 471, 472, 473, 475, 476, 477 Ref. Doc. : 052470-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years
LH ENGINE PYLON LEADING EDGE AND LOWER FAIRING			
GENERAL VISUAL INSPECTION OF PYLON LEADING EDGE AND LOWER FAIRING (EWIS)			

ZL-471-01-1-RH	RH ENGINE PYLON LEADING EDGE AND LOWER FAIRING	Threshold	Interval
ATA : 05 Zone : 481, 482, 483, 485, 486, 487 Ref. Doc. : 052470-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years
RH ENGINE PYLON LEADING EDGE AND LOWER FAIRING			
GENERAL VISUAL INSPECTION OF PYLON LEADING EDGE AND LOWER FAIRING (EWIS)			

ZL-500-02-1	LH AND RH WING LOWER SURFACE	Threshold	Interval
ATA : 05 Zone : 500, 600 Ref. Doc. : 052500-200-002 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years

LH AND RH WING LOWER SURFACE

GENERAL VISUAL INSPECTION OF LH AND RH WING LOWER SURFACE INCLUDING UPPER AND LOWER SURFACES OF SLATS AND FLAPS (EWIS)

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

ZL-500-03-1	LH AND RH WING UPPER SURFACE	Threshold	Interval
ATA : 05 Zone : 500, 600 Ref. Doc. : 052500-200-003 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years

LH AND RH WING UPPER SURFACE

GENERAL VISUAL INSPECTION OF LH AND RH WING UPPER SURFACE INCLUDING SLATS, FLAPS AND SPOILERS (EWIS)

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED; SLATS FULLY EXTENDED;

ZL-531-01-1	LH AND RH WING FLAP TRACK NO 2 AND FAIRING	Threshold	Interval
ATA : 05 Zone : 531, 631 Ref. Doc. : 052530-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years

LH AND RH WING FLAP TRACK NO 2 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 2 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-532-01-1	LH AND RH WING FLAP TRACK NO 3 AND FAIRING	Threshold	Interval
ATA : 05			3 Years
Zone : 532, 632			
Ref. Doc. : 052530-200-002			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH WING FLAP TRACK NO 3 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 3 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-533-01-1	LH AND RH FLAP TRACK NO 4 AND FAIRING	Threshold	Interval
ATA : 05			3 Years
Zone : 533, 633			
Ref. Doc. : 052530-200-003			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH FLAP TRACK NO 4 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 4 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-573-01-1	LH AND RH WING INBOARD FIXED TRAILING EDGE STRUCTURE	Threshold	Interval
ATA : 05			3 Years
Zone : 573, 673			
Ref. Doc. : 052570-200-003			
Effectivity : OM-BYA, OM-BYK			

LH AND RH WING INBOARD FIXED TRAILING EDGE STRUCTURE

GENERAL VISUAL INSPECTION OF INBOARD FIXED TRAILING EDGE STRUCTURE FROM SHROUD BOX TO RIB 9 (EWIS)

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;

ZL-574-01-1 FALSE SPAR BOX		Threshold	Interval
ATA : 05 Zone : 574, 674 Ref. Doc. : 052570-200-004 Effectivity : OM-BYA, OM-BYK FALSE SPAR BOX GENERAL VISUAL INSPECTION OF FALSE SPAR BOX (EWIS) PREPARATION NOTE: PYLON FAIRINGS REMOVED;			3 Years
ZL-575-01-1 LH AND RH WING OUTB FIXED TRAILING EDGE STRUCTURE		Threshold	Interval
ATA : 05 Zone : 575, 675 Ref. Doc. : 052570-200-005 Effectivity : OM-BYA, OM-BYK Tags : EWIS LH AND RH WING OUTB FIXED TRAILING EDGE STRUCTURE GENERAL VISUAL INSPECTION OF OUTBOARD FIXED TRAILING EDGE STRUCTURE FROM RIB 9 TO RIB 27 (EWIS) PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;			3 Years
ZL-734-01-1-LH LH MAIN LANDING GEAR MAIN DOORS		Threshold	Interval
ATA : 05 Zone : 734 Ref. Doc. : 052730-200-004 Effectivity : OM-BYA, OM-BYK LH MAIN LANDING GEAR MAIN DOORS GENERAL VISUAL INSPECTION OF LH MAIN LANDING GEAR MAIN DOORS (EWIS)			3 Years

ZL-734-01-1-RH	RH MAIN LANDING GEAR MAIN DOORS	Threshold	Interval
ATA : 05 Zone : 744 Ref. Doc. : 052730-200-004 Effectivity : OM-BYA, OM-BYK Tags : EWIS			3 Years

RH MAIN LANDING GEAR MAIN DOORS

GENERAL VISUAL INSPECTION OF RH MAIN LANDING GEAR MAIN DOORS (EWIS)

ZL-825-01-1	FORWARD CARGO COMPARTMENT DOOR	Threshold	Interval
ATA : 05 Zone : 825 Ref. Doc. : 052820-200-001 Effectivity : OM-BYA, OM-BYK			3 Years

FORWARD CARGO COMPARTMENT DOOR

GENERAL VISUAL INSPECTION OF FWD CARGO COMPARTMENT DOOR INCLUDING FUSELAGE DOOR SILL, DOOR SEAL AND LOCK FITTINGS, EXTERNAL SURFACE (EWIS)

ZL-826-01-2	AFT CARGO COMPARTMENT DOOR	Threshold	Interval
ATA : 05 Zone : 826 Ref. Doc. : 052820-200-002 Effectivity : OM-BYA, OM-BYK			36 Months

AFT CARGO COMPARTMENT DOOR

GENERAL VISUAL INSPECTION OF AFT CARGO COMPARTMENT DOOR INCLUDING FUSELAGE DOOR SILL, DOOR SEAL AND LOCK FITTINGS (EWIS)

200002-01-1	HIRF/LIGHTNING PROTECTION-THS T/E	Threshold	Interval
	ATA : 20 Zone : 334, 344 Ref. Doc. : 249200-210-018 Effectivity : OM-BYA, OM-BYK HIRF/LIGHTNING PROTECTION-THS T/E GENERAL VISUAL INSPECTION OF ELEMENTS FITTED ON THE FOLLOWING HARNESSSES: - 405VB, 406VB, 407VB, 408VB, 409VB, LH SIDE - 400VB, 401VB, 402VB, 403VB, 404VB, RH SIDE		3 Years
200121-01-1	FORWARD AVIONIC COMPARTMENT	Threshold	Interval
	ATA : 20 Zone : 121, 122 Ref. Doc. : 249200-100-004 Effectivity : OM-BYA, OM-BYK Tags : EWIS FORWARD AVIONIC COMPARTMENT EWIS TASK CLEANING OF EWIS INSTALLED IN THE FORWARD AVIONIC COMPARTMENT (ONLY IF CONTAMINATED)		36 Months
200129-02-1	STAIR BAY	Threshold	Interval
	ATA : 20 Zone : 129 Ref. Doc. : 249200-210-809 Effectivity : OM-BYA, OM-BYK Tags : EWIS STAIR BAY GENERAL VISUAL INSPECTION OF EWIS INSTALLED IN THE STAIR BAY (EWIS) PREPARATION NOTE: GASKET REMOVED; ENTRANCE STAIR DEPLOYED;		36 Months

212141-01-1-1	RECIRCULATION FILTER	Threshold	Interval
ATA : 21			3 Years
Zone : 130			
Ref. Doc. : 212141-920-002			
Effectivity : OM-BYA, OM-BYK			
Tags : TCI (NO ESCALATION ALLOWED)			

RECIRCULATION FILTER

DISCARD FILTER ELEMENTS OF RECIRCULATION SYSTEM

212141-01-1-2	RECIRCULATION FILTER	Threshold	Interval
ATA : 21			3 Years
Zone : 130			
Ref. Doc. : 212141-920-002			
Effectivity : OM-BYA, OM-BYK			
Tags : TCI (NO ESCALATION ALLOWED)			

RECIRCULATION FILTER

DISCARD FILTER ELEMENTS OF RECIRCULATION SYSTEM

212600-01-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21			3 Years
Zone : 210			
Ref. Doc. : 212600-710-001			
Effectivity : OM-BYA, OM-BYK			

AVIONICS EQUIPMENT VENTILATION

OPERATIONAL CHECK OF SYSTEM VIA MCDU

212600-02-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 212600-710-002 Effectivity : OM-BYA, OM-BYK			3 Years
AVIONICS EQUIPMENT VENTILATION			
OPERATIONAL CHECK OF OVERRIDE FUNCTION (BLOWER AND EXTRACT)			

212600-09-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21 Zone : 120 Ref. Doc. : 122113-100-002 Effectivity : OM-BYA, OM-BYK			3 Years
AVIONICS EQUIPMENT VENTILATION			
CLEAN GRID OF RELAY BOX VU PANELS			

212600-11-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21 Zone : 127 Ref. Doc. : 212643-600-016 Effectivity : OM-BYA, OM-BYK			3 Years
AVIONICS EQUIPMENT VENTILATION			
DISCARD DEMISTER FILTER ELEMENT AND FILTER CARTRIDGE (LE BOZEC)			

233000-51-3-1485-A	PASSENGER ADDRESS AND PUBLIC ENTERTAINMENT	Threshold	Interval
ATA : 23			3 Years
Zone : 200			
Ref. Doc. : AMM-S Subtask			
Effectivity : 23-33-00-710-050 Step 10 - 18			
OM-BYK			

PASSENGER ADDRESS AND PUBLIC ENTERTAINMENT

CHECK IFE AUDIO-CANCELLATION FURTHER PA ANNOUNCEMENT INCLUDING EARPHONES.

237100-01-1	COCKPIT VOICE RECORDER	Threshold	Interval
ATA : 23			3 Years
Zone : 210			
Ref. Doc. : 237100-710-001			
Effectivity : OM-BYA, OM-BYK			

COCKPIT VOICE RECORDER

OPERATIONAL CHECK OF CVR AND CVR-CHANNEL RECORDING

237135-02-1	COCKPIT VOICE RECORDER	Threshold	Interval
ATA : 23			3 Years
Zone : 312			
Ref. Doc. : 237100-720-001			
Effectivity : OM-BYA, OM-BYK			

COCKPIT VOICE RECORDER

OPERATIONAL CHECK OF ULB

242100-01-1-LH	LH ENGINE INTEGRATED DRIVE GENERATOR	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 24	Zone : 438	Ref. Doc. : 242100-210-043		3 Years
Effectivity : OM-BYA, OM-BYK	Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
LH ENGINE INTEGRATED DRIVE GENERATOR				
ETOPS SIGNIFICANT SYSTEM				
CHECK TORQUE OF QUICK-ATTACH-DETACH (QAD) TENSION BOLT				

242100-01-1-RH	RH ENGINE INTEGRATED DRIVE GENERATOR	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 24	Zone : 448	Ref. Doc. : 242100-210-043		3 Years
Effectivity : OM-BYA, OM-BYK	Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
RH ENGINE INTEGRATED DRIVE GENERATOR				
ETOPS SIGNIFICANT SYSTEM				
CHECK TORQUE OF QUICK-ATTACH-DETACH (QAD) TENSION BOLT				

243000-13-1	DC GENERATION	Threshold	Interval
ATA : 24	Zone : 124, 126		3 Years
Ref. Doc. : 243200-200-801			
Effectivity : OM-BYA, OM-BYK			
DC GENERATION			
CLEANING OF THE TRANSFORMER RECTIFIER TR1 AND TR2			

243000-14-1	DC GENERATION	Threshold	Interval
ATA : 24 Zone : 125 Ref. Doc. : 243400-100-801 Effectivity : OM-BYA, OM-BYK			3 Years
DC GENERATION			
CLEANING OF THE ESSENTIAL TRANSFORMER RECTIFIER			

252700-01-1-1485-A	DIVANS, CREDENZAS, TABLES STOWAGES, WARDROBE AND SECRETARY AND PARTITIONS (BATHROOM PRIVATE OFFICE /	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : AMM-S Effectivity : 25-27-00-220-801 25-27-00-220-802 OM-BYK			9 000 Hours 3 Years (+3 Months / -3 Months)
DIVANS, CREDENZAS, TABLES STOWAGES, WARDROBE AND SECRETARY AND PARTITIONS (BATHROOM PRIVATE OFFICE / BEDROOM, CONFERENCE ROOM, MINISTERS COMPARTMENT, STAFF SEATING, COMMUNICATIONS CENTER)			
DETAILED VISUAL INSPECTION OF: TABLES, DIVANS AND PARTITIONS TO ATTACHMENT POINTS.			
DETAILED VISUAL INSPECTION OF: BATHROOM ATTACHMENT POINTS.			

256241-04-1	DOOR ESCAPE SLIDE	Threshold	Interval
ATA : 25 Zone : 831, 832, 841, 842 Ref. Doc. : 256200-710-001 Effectivity : OM-BYA, OM-BYK			3 Years
DOOR ESCAPE SLIDE			
OPERATIONAL CHECK OF DOOR/EMERGENCY EXIT/OFFWING ESCAPE SLIDE/RAFT DEPLOYMENT.			

256241-05-1	DOOR ESCAPE SLIDE	Threshold	Interval
ATA : 25 Zone : 221, 222, 261, 262 Ref. Doc. : 531100-210-034 Effectivity : OM-BYA, OM-BYK			3 Years
DOOR ESCAPE SLIDE			
CLEAN DOOR GIRT BAR FITTING STOP LEVERS			

256242-03-1	OFFWING ESCAPE SLIDE	Threshold	Interval
ATA : 25 Zone : 830, 840 Ref. Doc. : 256200-710-002 Effectivity : OM-BYA, OM-BYK			3 Years
OFFWING ESCAPE SLIDE			
OPERATIONAL CHECK OF OFF WING EMERGENCY EXIT ESCAPE SLIDE DEPLOYMENT			
NOTE: PLANNING: - TASK IS NOT APPLICABLE FOR DEACTIVATED EMERGENCY EXITS.			

256535-01-1	FIXED EMERGENCY LOCATOR TRANSMITTER	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 256500-710-001 Effectivity : OM-BYA, OM-BYK			3 Years
FIXED EMERGENCY LOCATOR TRANSMITTER			
OPERATIONAL CHECK OF ELT SYSTEM BY MANUAL ACTIVATION			

256535-04-1	FIXED EMERGENCY LOCATOR TRANSMITTER	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 256500-210-802 Effectivity : OM-BYA, OM-BYK			3 Years
FIXED EMERGENCY LOCATOR TRANSMITTER			
GENERAL VISUAL INSPECTION OF EXTERNAL ELT ANTENNA			

256536-01-1	BEACON - LOW FREQUENCY UNDERWATER LOCATOR	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 256500-710-802 Effectivity : OM-BYA, OM-BYK			3 Years
BEACON - LOW FREQUENCY UNDERWATER LOCATOR			
OPERATIONAL CHECK OF LOW FREQUENCY UNDERWATER LOCATOR BEACON.			

261300-01-1	APU FIRE AND OVERHEAT DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 261300-710-001 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				3 Years
APU FIRE AND OVERHEAT DETECTION				
ETOPS SIGNIFICANT SYSTEM				
OPERATIONAL CHECK OF LOOP/SQUIB				

261700-03-1 LAVATORY SMOKE DETECTION		Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 261700-710-001 Effectivity : OM-BYA, OM-BYK LAVATORY SMOKE DETECTION OPERATIONAL CHECK OF LAVATORY SMOKE DETECTION BY CFDS TO CONFIRM WARNINGS CAN BE DISPLAYED			3 Years
262200-02-1 APU FIRE EXTINGUISHING		Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 262200-710-002 Effectivity : OM-BYA, OM-BYK APU FIRE EXTINGUISHING OPERATIONAL CHECK OF AUTOMATIC FIRE EXTINGUISHING CIRCUIT AND TEST APU LP FUEL VALVE OPERATION USING EACH INDIVIDUAL MOTOR IN TURN AND TEST APU EMERGENCY SHUTDOWN CIRCUIT			3 Years
262541-04-1-1 LAVATORY A FIRE EXTINGUISHER BOTTLE		Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : 262500-200-005 Effectivity : OM-BYA, OM-BYK LAVATORY A FIRE EXTINGUISHER BOTTLE VISUAL CHECK OF FIRE EXTINGUISHER BOTTLE PRESSURE READING			3 Years
262541-04-1-2 LAVATORY D FIRE EXTINGUISHER BOTTLE		Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : 262500-200-005 Effectivity : OM-BYA, OM-BYK LAVATORY D FIRE EXTINGUISHER BOTTLE VISUAL CHECK OF FIRE EXTINGUISHER BOTTLE PRESSURE READING			3 Years

262541-04-1-3	LAVATORY E FIRE EXTINGUISHER BOTTLE	Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : 262500-200-005 Effectivity : OM-BYA, OM-BYK			3 Years
LAVATORY E FIRE EXTINGUISHER BOTTLE			
VISUAL CHECK OF FIRE EXTINGUISHER BOTTLE PRESSURE READING			
271400-01-1	AILERON HYDRAULIC ACTUATION	Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 279600-710-007 Effectivity : OM-BYA, OM-BYK Tags : CMR** (NO ESCALATION)			3 Years
AILERON HYDRAULIC ACTUATION			
OPERATIONAL CHECK OF DAMPING MEASUREMENT BY BITE			
272100-08-1	RUDDER MECHANICAL CONTROL	Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 272143-600-001 Effectivity : OM-BYA, OM-BYK			3 Years
RUDDER MECHANICAL CONTROL			
LUBRICATION OF RUDDER PEDAL ADJUSTMENT MECHANISM			

272100-12-1 RUDDER MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 122227-640-807 Effectivity : OM-BYA, OM-BYK RUDDER MECHANICAL CONTROL LUBRICATION OF RUDDER CONTROL CABLES IN REAR PART.			3 Years
272145-01-1 RUDDER CABLE TENSION REGULATOR		Threshold	Interval
ATA : 27 Zone : 125 Ref. Doc. : 272100-220-002 Effectivity : OM-BYA, OM-BYK RUDDER CABLE TENSION REGULATOR FUNCTIONAL CHECK OF TENSION REGULATOR (POINTER WITHIN THE LIMITS)			3 Years
273400-01-1 ELEVATOR AND HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 279600-710-008 Effectivity : OM-BYA, OM-BYK ELEVATOR AND HYDRAULIC ACTUATION OPERATIONAL CHECK OF DAMPING MEASUREMENT BY BITE			3 Years
274142-01-1 THS TRIM CTL CABLE TENSION COMPENSATOR		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274100-220-001 Effectivity : OM-BYA, OM-BYK THS TRIM CTL CABLE TENSION COMPENSATOR FUNCTIONAL CHECK OF POINTER ON TENSION COMPENSATOR (SCALE WITHIN LIMITS)			3 Years

274451-02-1 THS ACTUATOR	Threshold	Interval
ATA : 27 Zone : 311, 312 Ref. Doc. : 274451-210-004 Effectivity : OM-BYA, OM-BYK THS ACTUATOR CHECK OIL LEVEL OF THS ACTUATOR GEARBOX		3 Years
274451-05-1 THS ACTUATOR	Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274451-220-002 Effectivity : OM-BYA, OM-BYK THS ACTUATOR DETAILED INSPECTION OF UPPER AND LOWER THS ACTUATOR ATTACHMENT (PRIMARY AND SECONDARY)		3 Years
275117-01-1 FLAP/SLAT COMMAND SENSOR UNIT	Threshold	Interval
ATA : 27 Zone : 212 Ref. Doc. : 275117-280-001 Effectivity : OM-BYA, OM-BYK FLAP/SLAT COMMAND SENSOR UNIT REMOVE CSU FOR WORKSHOP CHECK OF FRICTION BRAKE		3 Years
275451-01-1 FLAP POWER CONTROL UNIT	Threshold	Interval
ATA : 27 Zone : 147 Ref. Doc. : 121327-612-002 Effectivity : OM-BYA, OM-BYK FLAP POWER CONTROL UNIT REPLENISH PCU GEARBOX TO CONFIRM FLUID LEVEL		3 Years

278100-03-1	SLATS	Threshold	Interval
ATA : 27			3 Years
Zone : 210			
Ref. Doc. : AMM : 278100-710-001			
Effectivity : OM-BYA, OM-BYK			
SLATS			
OPERATIONAL CHECK OF WTB/POB			

278100-04-1-LH	LH SLATS	Threshold	Interval
ATA : 27			3 Years
Zone : 520			
Ref. Doc. : AMM : 278400-210-002			
Effectivity : OM-BYA, OM-BYK			
LH SLATS			
CHECK OF SLATS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS			

278100-04-1-RH	RH SLATS	Threshold	Interval
ATA : 27			3 Years
Zone : '620			
Ref. Doc. : AMM : 278400-210-002			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR** (NO ESCALATION)			
RH SLATS			
CHECK OF SLATS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS			

278451-01-1	SLAT POWER CONTROL UNIT	Threshold	Interval
ATA : 27			3 Years
Zone : 147			
Ref. Doc. : 121327-612-003			
Effectivity : OM-BYA, OM-BYK			
SLAT POWER CONTROL UNIT			
REPLENISH PCU GEARBOX TO CONFIRM FLUID LEVEL			

281200-01-1	TANK VENTING SYSTEM	Threshold	Interval
ATA : 28 Zone : 500, 600 Ref. Doc. : 281200-210-001 Effectivity : OM-BYA, OM-BYK			3 Years
TANK VENTING SYSTEM			
VISUAL CHECK OF VENT SURGE TANK BURST DISC (EXTERNAL)			
281247-01-1	NACA VENT INTAKE	Threshold	Interval
ATA : 28 Zone : 550, 650 Ref. Doc. : 281247-200-001 Effectivity : OM-BYA, OM-BYK			3 Years
NACA VENT INTAKE			
VISUAL CHECK OF NACA INTAKE FOR SIGNS OF BLOCKAGE			
281800-10-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28 Zone : 122 Ref. Doc. : 281800-710-801 Effectivity : OM-BYA, OM-BYK			3 Years
IGNITION PREVENTION			
OPERATIONAL CHECK OF CENTER TANK FUEL PUMP GFI (SFAR88)			
291000-06-1	MAIN HYDRAULIC POWER	Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 292300-710-003 Effectivity : OM-BYA, OM-BYK			3 Years
MAIN HYDRAULIC POWER			
FUNCTIONAL CHECK OF PTU YELLOW TO GREEN			

291000-20-1	MAIN/AUXILIARY POWER	Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 291000-710-004 Effectivity : OM-BYA, OM-BYK			3 Years
MAIN/AUXILIARY POWER			
OPERATIONAL CHECK OF EDP DEPESSURIZATION			

313300-03-1	DFDR SYSTEM INTERCONNECTION	Threshold	Interval
ATA : 31 Zone : 312 Ref. Doc. : 313300-710-015 Effectivity : OM-BYA, OM-BYK			3 Years
DFDR SYSTEM INTERCONNECTION			
OPERATIONAL CHECK OF ULB			

321111-03-1	MAIN LANDING GEAR	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 32 Zone : 731, 741 Ref. Doc. : 321111-200-001 Effectivity : OM-BYA, OM-BYK				3 Years
MAIN LANDING GEAR				
FUNCTIONAL CHECK OF MLG TORQUE LINK DAMPER FLUID LEVEL				

321113-04-1-LH	LH MAIN LANDING GEAR SHOCK ABSORBER	Threshold	Interval
ATA : 32 Zone : 731 Ref. Doc. : 121432-614-003 Effectivity : OM-BYA, OM-BYK			3 Years
LH MAIN LANDING GEAR SHOCK ABSORBER			
FUNCTIONAL CHECK OF LH MLG SHOCK ABSORBER CHARGE PRESSURE			

321113-04-1-RH	RH MAIN LANDING GEAR SHOCK ABSORBER	Threshold	Interval
ATA : 32			3 Years
Zone : 741			
Ref. Doc. : 121432-614-003			
Effectivity : OM-BYA, OM-BYK			
RH MAIN LANDING GEAR SHOCK ABSORBER			
FUNCTIONAL CHECK OF RH MLG SHOCK ABSORBER CHARGE PRESSURE			

322127-01-1	NOSE LANDING GEAR TORQUE LINK	Threshold	Interval
ATA : 32			5 000 Cycles
Zone : 711			3 Years
Ref. Doc. : 322100-200-003			
Effectivity : OM-BYA, OM-BYK			
NOSE LANDING GEAR TORQUE LINK			
FUNCTIONAL CHECK OF NLG TORQUE LINKS FOR EXCESSIVE PLAY			

323100-01-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32			3 Years
Zone : 210			
Ref. Doc. : 326900-740-001			
Effectivity : OM-BYA, OM-BYK			
NORMAL EXTENSION AND RETRACTION			
BITE CHECK OF LANDING GEAR CONTROL INTERFACE UNIT (LGCIU) USING MCDU (TO ENSURE THAT CONTINUOUS BITE IS OPERATIVE)			

323100-05-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32			3 Years
Zone : 123, 124			
Ref. Doc. : 323000-200-001			
Effectivity : OM-BYA, OM-BYK			
NORMAL EXTENSION AND RETRACTION			
DETAILED INSPECTION OF NOSE GEAR DOOR OPERATING MECHANISM			

323300-05-2	LANDING GEAR FREE FALL EXTENSION	Threshold	Interval
ATA : 32			3 Years
Zone : 210			
Ref. Doc. : 323300-710-001			
Effectivity : OM-BYA, OM-BYK			
LANDING GEAR FREE FALL EXTENSION			
OPERATIONAL CHECK OF FREE-FALL MECHANICAL CONTROL			

324000-14-1	WHEELS AND BRAKES	Threshold	Interval
ATA : 32			3 Years
Zone : 210, 730, 744			
Ref. Doc. : 324200-720-004			
Effectivity : OM-BYA, OM-BYK			
WHEELS AND BRAKES			
FUNCTIONAL CHECK OF THE AUTOMATIC REACTIVATION OF THE NORMAL BRAKING MODE (PARKING BRAKE APPLIED)			
PREPARATION NOTE: HYDRAULIC GROUND POWER;			

324311-01-1	LOW PRESSURE BRAKE RESERVOIR	Threshold	Interval
ATA : 32			1 Year
Zone : 122			
Ref. Doc. : 324311-210-001			
Effectivity : OM-BYK			
LOW PRESSURE BRAKE RESERVOIR			
FUNCTIONAL CHECK OF FLUID LEVEL OF LOW PRESSURE BRAKE RESERVOIR			

324500-01-1 PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM	Threshold	Interval
ATA : 32 Zone : 210, 711, 730, 740 Ref. Doc. : 324500-710-001 Effectivity : OM-BYK PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM OPERATIONAL CHECK OF THE PARKING BRAKE SYSTEM		3 Years
324500-01-2 PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM	Threshold	Interval
ATA : 32 Zone : 210; 711; 730; 740 Ref. Doc. : 324500-710-001 Effectivity : OM-BYA PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM OPERATIONAL CHECK OF THE PARKING BRAKE SYSTEM		3 Years
324500-02-2 PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM	Threshold	Interval
ATA : 32 Zone : 148; 210 Ref. Doc. : 324500-720-002 Effectivity : OM-BYA PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM FUNCTIONAL CHECK OF BRAKE ACCUMULATOR SYSTEM WITH THE PARKING BRAKE APPLIED		9 000 Hours 36 Months
324500-03-1 PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM	Threshold	Interval
ATA : 32 Zone : 210, 730, 740 Ref. Doc. : 324400-720-002 Effectivity : OM-BYK PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM FUNCTIONAL CHECK OF BRAKE ACCUMULATOR SYSTEM WITH THE PARKING BRAKE NOT APPLIED		3 950 Hours 3 Years

331400-01-1	ANNUNCIATOR LIGHT TEST AND DIMMING	Threshold	Interval
ATA : 33 Zone : 210 Ref. Doc. : 331400-710-001 Effectivity : OM-BYA, OM-BYK			3 Years
ANNUNCIATOR LIGHT TEST AND DIMMING			
OPERATIONAL CHECK OF LIGHTS TEST SYSTEM			

332100-01-1-1485-A	VIP AREA FR 20 TO 44 GENERAL ILLUMINATION	Threshold	Interval
ATA : 33 Zone : 200 Ref. Doc. : AMM-S Effectivity : 33-21-00-720-801 OM-BYK			3 Years
VIP AREA FR 20 TO 44 GENERAL ILLUMINATION			
CARRY OUT FUNCTIONAL TEST OF THE GENERAL ILLUMINATION PAX OVERRIDES IN CASE OF DEPRESSURIZATION (LIGHTS BECOME FULL BRIGHT).			

341300-07-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 120 Ref. Doc. : 341000-170-001 Effectivity : OM-BYA, OM-BYK			3 Years
AIR DATA			
FLUSHING OF TOTAL PRESSURE LINES			

341300-13-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 121, 122 Ref. Doc. : 341300-720-010 Effectivity : OM-BYA, OM-BYK			3 Years
AIR DATA			
FUNCTIONAL TEST OF THE ADM ACCURACY			

344200-01-1 RADIO ALTIMETER		Threshold	Interval
ATA : 34 Zone : 152 Ref. Doc. : 344200-750-001 Effectivity : OM-BYA, OM-BYK RADIO ALTIMETER OPERATIONAL CHECK AND DETAILED INSPECTION FOR CONTAMINATION OF RADIO ALTIMETER FAN PLANNING: - TASK IS NOT APPLICABLE IF P/N 822-2365-022 IS INSTALLED.			3 Years
351000-08-1 CREW OXYGEN		Threshold	Interval
ATA : 35 Zone : 210 Ref. Doc. : 351000-720-001 Effectivity : OM-BYA, OM-BYK CREW OXYGEN FUNCTIONAL CHECK OF ECAM OXYGEN CYLINDER CONTENTS INDICATION COMPARED WITH CYLINDER PRESSURE GAUGE			3 Years
353000-07-1 PORTABLE OXYGEN		Threshold	Interval
ATA : 35 Zone : 200 Ref. Doc. : 353000-220-001 Effectivity : OM-BYA, OM-BYK PORTABLE OXYGEN DETAILED INSPECTION OF PORTABLE OXYGEN MASK			3 Years

SB A320-36-1041 (2) R6	INSPECTION OF HIGH PRESSURE UPPER DUCT ASSEMBLY FOR CRACKS	Threshold	Interval
ATA : 36 Zone : Ref. Doc. : SB A320-36-1041 R6 Effectivity : SSG-EO-019 OM-BYK			3 Years

INSPECTION OF HIGH PRESSURE UPPER DUCT ASSEMBLY FOR CRACKS

INSPECTION OF THE WELDED BRACKETS AREA AND LINKS SUPPORT IAW SSG-EO-019 AND SB A320-36-1041.

383100-02-1	VACUUM TOILET SYSTEM	Threshold	Interval
ATA : 38 Zone : 170 Ref. Doc. : 383167-610-001 Effectivity : OM-BYA, OM-BYK			3 Years

VACUUM TOILET SYSTEM

INSPECT WATER SEPARATOR AND ASSOCIATED FILTER ELEMENT, AND CLEAN AS NECESSARY

383100-05-1	VACUUM TOILET SYSTEM	Threshold	Interval
ATA : 38 Zone : 172 Ref. Doc. : 383161-210-001 Effectivity : OM-BYA, OM-BYK			3 Years

VACUUM TOILET SYSTEM

DETAILED INSPECTION OF CLEANLINESS INSIDE WASTE TANK

383100-07-1	VACUUM TOILET SYSTEM	Threshold	Interval
ATA : 38			3 Years
Zone : 200			
Ref. Doc. : 383100-100-004			
Effectivity : SIL 38-020			
OM-BYA, OM-BYK			
VACUUM TOILET SYSTEM			
CORRECTIVE VACUUM WASTE LINE CLEANING.			

491200-A2-1	APU MOUNTS	Threshold	Interval
ATA : 49			3 Years
Zone : 315, 316			
Ref. Doc. : 491200-210-005			
Effectivity : OM-BYA, OM-BYK			
APU MOUNTS			
GENERAL VISUAL INSPECTION OF APU SUSPENSION SYSTEM FOR CONDITION AND SECURITY.			
NOTE:			
INTERVAL:			
- TASK MAY BE ACCOMPLISHED AT OPPORTUNITY OF APU CHANGE.			

491300-A1-1	FIRE SEALS	Threshold	Interval
ATA : 49			3 Years
Zone : 310			
Ref. Doc. : 491300-200-002			
Effectivity : OM-BYA, OM-BYK			
FIRE SEALS			
GENERAL VISUAL INSPECTION OF ALL APU COMPARTMENT FIRE WALLS AND SEALS:			
- COMPARTMENT DOORS			
- FWD AND AFT FIRE WALLS			
- SIDE FIRE WALLS			
- UPPER FIRE WALL			

491600-A1-1 AIR INTAKE SYSTEM		Threshold	Interval
ATA : 49 Zone : 310 Ref. Doc. : 491600-210-002 Effectivity : OM-BYA, OM-BYK AIR INTAKE SYSTEM DETAILED INSPECTION OF APU AIR INTAKE, DIFFUSER ELBOW, SEALS AND FELT METAL			3 Years
494000-A1-1 IGNITION AND STARTING		Threshold	Interval
ATA : 49 Zone : 316 Ref. Doc. : 494141-920-001 Effectivity : OM-BYA, OM-BYK IGNITION AND STARTING REMOVE AND DISCARD IGNITER PLUGS			3 Years
498000-A4-1 EXHAUST		Threshold	Interval
ATA : 49 Zone : 310 Ref. Doc. : 498100-200-016 Effectivity : OM-BYA, OM-BYK EXHAUST GENERAL VISUAL INSPECTION OF APU COMPARTMENT EXHAUST MUFFLER INSULATION COVERS AND BELLOWS			3 Years
521000-02-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-720-001 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR FUNCTIONAL CHECK OF DOOR SUSPENSION			3 Years

521000-04-1	PASSENGER/CREW DOOR	Threshold	Interval
ATA : 52			3 Years
Zone : 831, 832, 841, 842			
Ref. Doc. : 521000-200-002			
Effectivity : OM-BYA, OM-BYK			

PASSENGER/CREW DOOR

DETAILED INSPECTION OF PASSENGER/CREW DOOR FOR INTEGRITY AND GOOD ADJUSTMENT OF MECHANISMS (INCLUDING GIRT BAR)

PREPARATION NOTE: INSULATION REMOVED;

521000-14-1	PASSENGER/CREW DOOR	Threshold	Interval
ATA : 52			3 Years
Zone : 831, 832, 841, 842			
Ref. Doc. : 122252-640-016			
Effectivity : OM-BYA, OM-BYK			

PASSENGER/CREW DOOR

LUBRICATION OF HINGE ARM SUPPORT FITTING BEARINGS

PREPARATION NOTE: DOOR SUPPORT ARM;

521000-20-1	PASSENGER/CREW DOOR	Threshold	Interval
ATA : 52			3 Years
Zone : 831, 832, 841, 842			
Ref. Doc. : 521000-710-004			
Effectivity : OM-BYA, OM-BYK			

PASSENGER/CREW DOOR

OPERATIONAL CHECK OF DOOR DAMPING.

521121-01-1	PASSENGER / CREW DOOR	Threshold	Interval
ATA : 52			3 Years
Zone : 831, 832, 841, 842			
Ref. Doc. : 122252-640-006			
Effectivity : OM-BYA, OM-BYK			
PASSENGER / CREW DOOR			
LUBRICATION OF EXTERIOR CONTROL HANDLE AND TELESCOPIC ARM			

521121-02-1	PASSENGER / CREW DOOR	Threshold	Interval
ATA : 52			36 Months
Zone : 831, 832, 841, 842			
Ref. Doc. : 122252-640-014			
Effectivity : OM-BYA, OM-BYK			
PASSENGER / CREW DOOR			
LUBRICATION OF SAFETY PIN GUIDE FITTING AND DOOR ARMING/DISARMING MECHANISM			

523000-03-1	CARGO COMPARTMENT DOOR	Threshold	Interval
ATA : 52			3 Years
Zone : 825, 826			
Ref. Doc. : 122252-640-009			
Effectivity : OM-BYA, OM-BYK			
CARGO COMPARTMENT DOOR			
LUBRICATION OF EXTERIOR CARGO DOOR HANDLE			
NOTE : INTERVAL MAY NEED TO BE MORE FREQUENT WHEN OPERATING IN HOSTILE ENVIRONMENTS			

524100-02-1	ACCESS DOORS	Threshold	Interval
ATA : 52 Zone : 811, 812, 822, 824 Ref. Doc. : 122252-640-008 Effectivity : OM-BYA, OM-BYK			3 Years
ACCESS DOORS			
LUBRICATION OF EXTERIOR AVIONIC COMPARTMENT DOOR HANDLE			
527100-02-1	DOOR WARNING	Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 122252-640-005 Effectivity : OM-BYA, OM-BYK			3 Years
DOOR WARNING			
LUBRICATION OF DOOR WARNING PROXIMITY SWITCH ACTUATING MECHANISM			
531900-03-1	FUSELAGE DRAINAGE	Threshold	Interval
ATA : 53 Zone : 120, 130, 150 Ref. Doc. : 531900-710-003 Effectivity : OM-BYA, OM-BYK			3 Years
FUSELAGE DRAINAGE			
OPERATIONAL CHECK OF PISTON TYPE DRAIN VALVES IN LOWER FUSELAGE SHELL FROM OUTSIDE			
531900-10-1	FUSELAGE DRAINAGE	Threshold	Interval
ATA : 53 Zone : 110 Ref. Doc. : 531511-210-802 Effectivity : OM-BYA, OM-BYK			3 Years
FUSELAGE DRAINAGE			
GENERAL VISUAL INSPECTION OF DRAIN HOLE AND GAP AT RADOME.			

533900-01-1	FUSELAGE DRAINAGE	Threshold	Interval
ATA : 53 Zone : 140 Ref. Doc. : 533900-210-001 Effectivity : OM-BYA, OM-BYK			3 Years
FUSELAGE DRAINAGE			
OPERATIONAL CHECK OF RUBBER FLAP DRAIN VALVE HOLES IN PRESSURE FLOOR FROM MLG BAY			

535900-01-1	FUSELAGE DRAINAGE	Threshold	Interval
ATA : 53 Zone : 310 Ref. Doc. : 535900-210-001 Effectivity : OM-BYA, OM-BYK			3 Years
FUSELAGE DRAINAGE			
OPERATIONAL CHECK OF SINGLE DRAIN PIPE AFT OF FR 70 FROM OUTSIDE			

545000-01-1-LH	LH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 410 Ref. Doc. : 545000-200-001 Effectivity : OM-BYA, OM-BYK			3 Years
LH PYLONS			
GENERAL VISUAL INSPECTION OF COMPARTMENT A AND F PYLON DRAIN SYSTEM			

545000-01-1-RH	RH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 420 Ref. Doc. : 545000-200-001 Effectivity : OM-BYA, OM-BYK			3 Years
RH PYLONS			
GENERAL VISUAL INSPECTION OF COMPARTMENT A AND F PYLON DRAIN SYSTEM			

545000-06-1-LH LH PYLONS	Threshold	Interval
ATA : 54 Zone : 410 Ref. Doc. : 545000-220-001 Effectivity : OM-BYA, OM-BYK LH PYLONS DETAILED INSPECTION OF THE CAF 4 SEALANT IN PYLON CANTILEVER ZONE A.		3 Years
561200-01-1 SLIDING WINDOWS	Threshold	Interval
ATA : 56 Zone : 210 Ref. Doc. : 561200-220-001 Effectivity : Not Effective SLIDING WINDOWS DETAILED INSPECTION OF WINDOW SEALS		3 Years (+3 Months / -3 Months)
561200-02-1 SLIDING WINDOWS	Threshold	Interval
ATA : 56 Zone : 210 Ref. Doc. : 122256-600-001 Effectivity : OM-BYA, OM-BYK SLIDING WINDOWS LUBRICATION OF COCKPIT SLIDING WINDOW TRACKS		3 Years
SB A320-57-1155 R5 WINGS - INSPECTION OF WING TOP SKIN PANEL	Threshold	Interval
ATA : 57 Zone : Ref. Doc. : SB A320-57-1155 Effectivity : Not Effective WINGS - INSPECTION OF WING TOP SKIN PANEL 2 OVERHANG BETWEEN RIB 4 AND RIB 22 TO INSPECT FOR CORROSION	06-Mar-13	48 Months

SSG-EO-010-1	WINGS - INSPECTION OF WING TOP SKIN PANEL – SDI ULTRASONIC INSPECTION	Threshold	Interval
ATA : 57 Zone : 575, 574 Ref. Doc. : SSG-EO-010-1 Effectivity : AIRBUS SB A320-57-1155 OM-BYK		06-Mar-13	48 Months

WINGS - INSPECTION OF WING TOP SKIN PANEL – SDI ULTRASONIC INSPECTION

PERFORM INSPECTION OF THE WING TOP SKIN PANEL FOR CORROSION IAW SSG-EO-010-1

SSG-EO-010-2	WINGS - INSPECTION OF WING TOP SKIN PANEL – SDI ULTRASONIC INSPECTION	Threshold	Interval
ATA : 57 Zone : 674, 675 Ref. Doc. : SSG-EO-010-2 Effectivity : AIRBUS SB A320-57-1155 OM-BYK		06-Mar-13	48 Months

WINGS - INSPECTION OF WING TOP SKIN PANEL – SDI ULTRASONIC INSPECTION

PERFORM INSPECTION OF THE WING TOP SKIN PANEL FOR CORROSION IAW SSG-EO-010-2

711000-C5-1-LH	LH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 430 Ref. Doc. : 711311-280-802 Effectivity : OM-BYA, OM-BYK			3 Years

LH ENGINE COWLINGS

FUNCTIONAL CHECK OF PRESSURE RELIEF DOOR LATCH TENSION.

711000-C5-1-RH	RH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 440 Ref. Doc. : 711311-280-802 Effectivity : OM-BYA, OM-BYK			3 Years

RH ENGINE COWLINGS

FUNCTIONAL CHECK OF PRESSURE RELIEF DOOR LATCH TENSION.

711000-C7-1-LH	LH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 430 Ref. Doc. : 711311-200-802 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE COWLINGS			
GENERAL VISUAL INSPECTION OF FAN COWL DOOR FIRE SEALS			

711000-C7-1-RH	RH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 440 Ref. Doc. : 711311-200-802 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE COWLINGS			
GENERAL VISUAL INSPECTION OF FAN COWL DOOR FIRE SEALS			

711300-C2-1-LH	LH ENGINE FAN COWLINGS	Threshold	Interval
ATA : 71 Zone : 430 Ref. Doc. : 711313-220-041 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE FAN COWLINGS			
DETAILED INSPECTION OF THE KEEPER ASSY FAN COWL LOCKING DEVICE			

711300-C2-1-RH	RH ENGINE FAN COWLINGS	Threshold	Interval
ATA : 71 Zone : 440 Ref. Doc. : 711313-220-041 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE FAN COWLINGS			
DETAILED INSPECTION OF THE KEEPER ASSY FAN COWL LOCKING DEVICE			

722000-C1-1-LH	LH ENGINE FAN SECTION	Threshold	Interval
ATA : 72 Zone : 430 Ref. Doc. : 722300-210-003 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE FAN SECTION			
DETAILED INSPECTION OF SPINER, ENGINE INLET, FAN BLADES, FAN OUTLET AND ABRADABLE MATERIAL.			

722000-C1-1-RH	RH ENGINE FAN SECTION	Threshold	Interval
ATA : 72 Zone : 440 Ref. Doc. : 722300-210-003 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE FAN SECTION			
DETAILED INSPECTION OF SPINER, ENGINE INLET, FAN BLADES, FAN OUTLET AND ABRADABLE MATERIAL.			

722000-C3-1-LH	LH ENGINE FAN SECTION	Threshold	Interval
ATA : 72 Zone : 430 Ref. Doc. : Effectivity : OM-BYA, OM-BYK			3 000 Cycles 3 Years
LH ENGINE FAN SECTION			
DETAILED INSPECTION AND RELUBRICATION OF FAN BLADE DOVETAILS, MIDSPAN SHROUDS, SPACERS, PLATFORMS AND FAN DISK DOVETAIL SLOTS.			
PREPARATION NOTE: FAN BLADES REMOVED;			

722000-C3-1-RH	RH ENGINE FAN SECTION	Threshold	Interval
ATA : 72 Zone : 440 Ref. Doc. : Effectivity : OM-BYA, OM-BYK			3 000 Cycles 3 Years

RH ENGINE FAN SECTION

DETAILED INSPECTION AND RELUBRICATION OF FAN BLADE DOVETAILS, MIDSPAN SHROUDS, SPACERS, PLATFORMS AND FAN DISK DOVETAIL SLOTS.

PREPARATION NOTE: FAN BLADES REMOVED;

724000-C1-1-LH	LH ENGINE COMBUSTION SECTION	Threshold	Interval
ATA : 72 Zone : 450 Ref. Doc. : 724100-290-001 Effectivity : OM-BYA, OM-BYK			3 Years

LH ENGINE COMBUSTION SECTION

BORESCOPE INSPECTION OF COMBUSTION CHAMBER LINERS, DOME AREAS, HPT NOZZLE VANES AND SHROUDS (AS FAR AS VISIBLE THROUGH TWO OPPOSITE PORTS)

724000-C1-1-RH	RH ENGINE COMBUSTION SECTION	Threshold	Interval
ATA : 72 Zone : 460 Ref. Doc. : 724100-290-001 Effectivity : OM-BYA, OM-BYK			3 Years

RH ENGINE COMBUSTION SECTION

BORESCOPE INSPECTION OF COMBUSTION CHAMBER LINERS, DOME AREAS, HPT NOZZLE VANES AND SHROUDS (AS FAR AS VISIBLE THROUGH TWO OPPOSITE PORTS)

725000-C1-3-LH	LH ENGINE TURBINE SECTION	Threshold	Interval
ATA : 72 Zone : 450 Ref. Doc. : 725200-290-001 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE TURBINE SECTION			
BORESCOPE INSPECTION OF HPT BLADES (FROM THE FRONT AND THE REAR)			

725000-C1-3-RH	RH ENGINE TURBINE SECTION	Threshold	Interval
ATA : 72 Zone : 460 Ref. Doc. : 725200-290-001 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE TURBINE SECTION			
BORESCOPE INSPECTION OF HPT BLADES (FROM THE FRONT AND THE REAR)			

730000-C4-1-LH	LH ENGINE ENGINE FUEL AND CONTROL	Threshold	Interval
ATA : 73 Zone : 435 Ref. Doc. : 731110-920-001 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE FUEL AND CONTROL			
REMOVE, INSPECT AND REPLACE FUEL FILTER ELEMENT			

730000-C4-1-RH	RH ENGINE ENGINE FUEL AND CONTROL	Threshold	Interval
ATA : 73 Zone : 445 Ref. Doc. : 731110-920-001 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE FUEL AND CONTROL			
REMOVE, INSPECT AND REPLACE FUEL FILTER ELEMENT			

783000-C4-1-LH	LH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 450 Ref. Doc. : 783641-210-040 Effectivity : OM-BYA, OM-BYK			3 Years
LH THRUST REVERSER			
GENERAL VISUAL INSPECTION OF THRUST REVERSER HALF TENSION HOOK LATCH AND ADJACENT STRUCTURE (C DUCTS OPEN)			

783000-C4-1-RH	RH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 460 Ref. Doc. : 783641-210-040 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE THRUST REVERSER			
GENERAL VISUAL INSPECTION OF THRUST REVERSER HALF TENSION HOOK LATCH AND ADJACENT STRUCTURE (C DUCTS OPEN)			

792000-C4-2-LH	LH ENGINE DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 435 Ref. Doc. : 792110-920-002 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE DISTRIBUTION			
REMOVE AND DISCARD SUPPLY FILTER			

792000-C4-2-RH	RH ENGINE DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 445 Ref. Doc. : 792110-920-002 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE DISTRIBUTION			
REMOVE AND DISCARD SUPPLY FILTER			

792000-C7-1-LH	LH ENGINE DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 435 Ref. Doc. : 790000-281-003 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE DISTRIBUTION			
CHECK OF FWD SUMP, AFT SUMP, AGB, AND TGB SCAVENGE SCREENS			

792000-C7-1-RH	RH ENGINE DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 445 Ref. Doc. : 790000-281-003 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE DISTRIBUTION			
CHECK OF FWD SUMP, AFT SUMP, AGB, AND TGB SCAVENGE SCREENS			

792000-C9-1-LH	LH ENGINE OIL DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 435 Ref. Doc. : 790000-200-001 Effectivity : OM-BYA, OM-BYK			3 Years
LH ENGINE OIL DISTRIBUTION			
OPERATIONAL CHECK OF THE MASTER CHIP DETECTOR REMOTE INDICATION			

792000-C9-1-RH	RH ENGINE OIL DISTRIBUTION	Threshold	Interval
ATA : 79 Zone : 445 Ref. Doc. : 790000-200-001 Effectivity : OM-BYA, OM-BYK			3 Years
RH ENGINE OIL DISTRIBUTION			
OPERATIONAL CHECK OF THE MASTER CHIP DETECTOR REMOTE INDICATION			



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

2C CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 158

ZL-110-01-1	RADOME	Threshold	Interval
ATA : 05			6 Years
Zone : 110			
Ref. Doc. : 052110-200-001			
Effectivity : OM-BYA, OM-BYK			
RADOME			
GENERAL VISUAL INSPECTION OF RADOME (EWIS)			

ZL-121-02-1	AVIONIC COMPARTMENT	Threshold	Interval
ATA : 05			6 Years
Zone : 121, 122			
Ref. Doc. : 052120-200-007			
Effectivity : OM-BYA, OM-BYK			
FORWARD AVIONIC COMPARTMENT			
GENERAL VISUAL INSPECTION OF FORWARD AVIONIC COMPARTMENT (EWIS)			
PREPARATION NOTE: INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;			

ZL-125-02-2	LATERAL AVIONIC COMPARTMENT	Threshold	Interval
ATA : 05			6 Years
Zone : 125, 126, 129			
Ref. Doc. : 052120-200-008			
Effectivity : OM-BYA, OM-BYK			
LATERAL AVIONIC COMPARTMENT			
GENERAL VISUAL INSPECTION OF LATERAL AVIONIC COMPARTMENT (EWIS)			
PREPARATION NOTE: FLOOR PANELS FROM FR 16 TO FR 20; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; GASKET REMOVED; ENTRANCE STAIR DEPLOYED;			

ZL-127-02-2 REAR AVIONIC COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 127, 128 Ref. Doc. : 052120-200-010 Effectivity : OM-BYA, OM-BYK REAR AVIONIC COMPARTMENT GENERAL VISUAL INSPECTION OF REAR AVIONIC COMPARTMENT (EWIS) PREPARATION NOTE: INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; PARTITION, CEILING PANELS AT FR24A;			6 Years
ZL-131-02-3 FORWARD CARGO COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 131, 132 Ref. Doc. : 052130-200-004 Effectivity : OM-BYA, OM-BYK FORWARD CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF FORWARD CARGO COMPARTMENT (EWIS) PREPARATION NOTE: ACT(S) NO.4 AND NO.6 REMOVED (IF INSTALLED);			6 Years
ZL-133-01-1 UNDERFLOOR BAY OF FWD CARGO COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 133, 134 Ref. Doc. : 052130-200-002 Effectivity : OM-BYA, OM-BYK UNDERFLOOR BAY OF FWD CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF UNDERFLOOR BAY OF FWD CARGO COMPARTMENT (EWIS) PREPARATION NOTE: FLOOR PANELS FROM FR 24 TO FR 34;			6 Years

ZL-137-01-1 BAY BEHIND FWD CARGO COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 137, 138 Ref. Doc. : 052130-200-003 Effectivity : OM-BYA, OM-BYK BAY BEHIND FWD CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF BAY BEHIND FWD CARGO COMPARTMENT (EWIS) PREPARATION NOTE: ACT(S) NO.4 AND NO.6 REMOVED (IF INSTALLED); INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;			6 Years
ZL-145-01-1 ZONE UNDER CABIN FLOOR		Threshold	Interval
ATA : 05 Zone : 145, 146 Ref. Doc. : 052140-200-002 Effectivity : OM-BYA, OM-BYK ZONE UNDER CABIN FLOOR GENERAL VISUAL INSPECTION OF ZONE UNDER CABIN FLOOR (EWIS) PREPARATION NOTE: FLOOR PANELS FROM FR 36 TO FR 46; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;			6 Years
ZL-147-03-1 MLG-WELL AND HYDRAULIC COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 147, 148 Ref. Doc. : 052140-200-005 Effectivity : OM-BYA, OM-BYK MLG-WELL AND HYDRAULIC COMPARTMENT GENERAL VISUAL INSPECTION OF MLG-WELL AND HYDRAULIC COMPARTMENT (EWIS)			6 Years

ZL-151-02-5AFT CARGO COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 151, 152 Ref. Doc. : 052150-200-003 Effectivity : OM-BYA, OM-BYK AFT CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF AFT CARGO COMPARTMENT (EWIS) PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED);			6 Years
ZL-153-01-1UNDERFLOOR BAY OF AFT CARGO COMPTMENT		Threshold	Interval
ATA : 05 Zone : 153, 154 Ref. Doc. : 052150-200-002 Effectivity : OM-BYA, OM-BYK UNDERFLOOR BAY OF AFT CARGO COMPTMENT GENERAL VISUAL INSPECTION OF UNDERFLOOR BAY OF AFT CARGO COMPARTMENT (EWIS) PREPARATION NOTE: FLOOR PANELS FROM FR 46 TO FR 59; ACT(S) REMOVED (IF INSTALLED);			6 Years
ZL-161-02-4BULK CARGO COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 161, 162 Ref. Doc. : AMM : 052160-200-003 Effectivity : OM-BYA, OM-BYK BULK CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF BULK CARGO COMPARTMENT (EWIS)			6 Years

ZL-163-01-2 UNDERFLOOR BAY OF BULK CARGO COMPTMENT		Threshold	Interval
ATA : 05 Zone : 163, 164 Ref. Doc. : 052160-200-002 Effectivity : OM-BYA, OM-BYK UNDERFLOOR BAY OF BULK CARGO COMPTMENT GENERAL VISUAL INSPECTION OF UNDERFLOOR BAY OF BULK CARGO COMPARTMENT (EWIS) PREPARATION NOTE: FLOOR PANELS FROM FR 59 TO FR 65; ACT(S) REMOVED (IF INSTALLED);			6 Years
ZL-171-02-1 AFT CABIN UNDERFLOOR COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 171, 172 Ref. Doc. : 052170-200-002 Effectivity : OM-BYA, OM-BYK AFT CABIN UNDERFLOOR COMPARTMENT GENERAL VISUAL INSPECTION OF AFT CABIN UNDERFLOOR COMPARTMENT (EWIS) PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;			6 Years
ZL-191-02-1 AIR CONDITIONING COMPARTMENT AND FAIRINGS		Threshold	Interval
ATA : 05 Zone : 191, 192 Ref. Doc. : 052190-200-009 Effectivity : OM-BYA, OM-BYK AIR CONDITIONING COMPARTMENT AND FAIRINGS GENERAL VISUAL INSPECTION OF AIR CONDITIONING COMPARTMENT AND FAIRINGS (EWIS)			6 Years

ZL-193-01-1 UPPER WING FAIRING SLIDE STOWAGE		Threshold	Interval
ATA : 05 Zone : 193, 194 Ref. Doc. : 052190-200-003 Effectivity : OM-BYA, OM-BYK UPPER WING FAIRING SLIDE STOWAGE GENERAL VISUAL INSPECTION OF UPPER WING FAIRING SLIDE STOWAGE (EWIS) PREPARATION NOTE: ESCAPE SLIDE STOWAGE CONTAINER REMOVED;			6 Years
ZL-197-01-3 REAR FAIRING		Threshold	Interval
ATA : 05 Zone : 197, 198 Ref. Doc. : 052190-200-007 Effectivity : OM-BYA, OM-BYK REAR FAIRING GENERAL VISUAL INSPECTION OF REAR FAIRING (EWIS)			6 Years
ZL-211-01-1 COCKPIT		Threshold	Interval
ATA : 05 Zone : 211, 212 Ref. Doc. : 052210-200-001 Effectivity : OM-BYA, OM-BYK COCKPIT GENERAL VISUAL INSPECTION OF COCKPIT (EWIS)			6 Years
ZL-317-01-1 TAIL CONE/APU EXHAUST AREA		Threshold	Interval
ATA : 05 Zone : 317 Ref. Doc. : 052310-200-004 Effectivity : OM-BYA, OM-BYK TAIL CONE/APU EXHAUST AREA GENERAL VISUAL INSPECTION OF TAIL CONE APU EXHAUST AREA (EWIS)			72 Months

ZL-325-02-1	VERTICAL STABILIZER TRAILING EDGE	Threshold	Interval
ATA : 05 Zone : 325 Ref. Doc. : 052320-200-007 Effectivity : OM-BYA, OM-BYK			72 Months
VERTICAL STABILIZER TRAILING EDGE			
GENERAL VISUAL INSPECTION OF VERTICAL STABILIZER TRAILING EDGE (EWIS)			

ZL-331-01-1	THS LEADING EDGE	Threshold	Interval
ATA : 05 Zone : 331, 341 Ref. Doc. : 052330-200-001 Effectivity : OM-BYA, OM-BYK			72 Months
THS LEADING EDGE			
GENERAL VISUAL INSPECTION OF TRIMMABLE HORIZONTAL STABILIZER LEADING EDGE (EWIS)			

ZL-334-02-1	THS TRAILING EDGE	Threshold	Interval
ATA : 05 Zone : 334, 344 Ref. Doc. : 052330-200-007 Effectivity : OM-BYA, OM-BYK			72 Months
THS TRAILING EDGE			
GENERAL VISUAL INSPECTION OF TRIMMABLE HORIZONTAL STABILIZER TRAILING EDGE (EWIS)			

ZL-335-01-1	ELEVATOR	Threshold	Interval
ATA : 05 Zone : 335, 345 Ref. Doc. : 052330-200-005 Effectivity : OM-BYA, OM-BYK			6 Years
ELEVATOR			
GENERAL VISUAL INSPECTION OF ELEVATOR (EWIS)			

ZL-433-01-1-LH	LH ENGINE AIR INTAKE LIP	Threshold	Interval
ATA : 05 Zone : 433, 434 Ref. Doc. : 052430-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			6 Years

LH ENGINE AIR INTAKE LIP

GENERAL VISUAL INSPECTION OF AIR INTAKE LIP (EWIS)

ZL-433-01-1-RH	RH ENGINE AIR INTAKE LIP	Threshold	Interval
ATA : 05 Zone : 443, 444 Ref. Doc. : 052430-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			72 Months

RH ENGINE AIR INTAKE LIP

GENERAL VISUAL INSPECTION OF AIR INTAKE LIP (EWIS)

ZL-521-01-1	LH AND RH WING INBOARD FIXED LEADING EDGE STRUCTURE	Threshold	Interval
ATA : 05 Zone : 521, 621 Ref. Doc. : 052520-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			6 Years

LH AND RH WING INBOARD FIXED LEADING EDGE STRUCTURE

GENERAL VISUAL INSPECTION OF INBOARD FIXED LEADING EDGE STRUCTURE (EWIS)

PREPARATION NOTE: SLATS FULLY EXTENDED;

ZL-522-01-1	LH AND RH WING OUTBOARD FIXED LEADING EDGE STRUCTURE	Threshold	Interval
ATA : 05			6 Years
Zone : 522, 622			
Ref. Doc. : 052520-200-002			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH WING OUTBOARD FIXED LEADING EDGE STRUCTURE

GENERAL VISUAL INSPECTION OF OUTBOARD FIXED LEADING EDGE STRUCTURE (EWIS)

PREPARATION NOTE: SLATS FULLY EXTENDED;

ZL-531-02-1	LH AND RH WING FLAP TRACK NO 2 AND FAIRING	Threshold	Interval
ATA : 05			6 Years
Zone : 531, 631			
Ref. Doc. : 052530-200-005			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH WING FLAP TRACK NO 2 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 2 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-532-02-1	LH AND RH FLAP TRACK NO 3 AND FAIRING	Threshold	Interval
ATA : 05			6 Years
Zone : 532, 632			
Ref. Doc. : 052530-200-006			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH FLAP TRACK NO 3 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 3 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-533-02-1	LH AND RH FLAP TRACK NO 4 AND FAIRING	Threshold	Interval
ATA : 05			6 Years
Zone : 533, 633			
Ref. Doc. : 052530-200-007			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH FLAP TRACK NO 4 AND FAIRING

GENERAL VISUAL INSPECTION OF FLAP TRACK NO 4 AND FAIRING (EWIS)

PREPARATION NOTE: FLAPS EXTENDED;

ZL-534-01-2	LH AND RH WING TIP	Threshold	Interval
ATA : 05			6 Years
Zone : 534, 634			
Ref. Doc. : 052530-200-004			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH WING TIP

GENERAL VISUAL INSPECTION OF WING TIP (EWIS)

ZL-540-01-1	LH AND RH WING FUEL TANK	Threshold	Interval
ATA : 05			6 Years
Zone : 540, 640			
Ref. Doc. : 052540-200-005			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH AND RH WING FUEL TANK

GENERAL VISUAL INSPECTION OF WING FUEL TANK (EWIS)

NOTE: INTERVAL MAY BE ADJUSTED BY INDIVIDUAL OPERATORS IN CONSIDERATION OF THEIR OWN INSERVICE EXPERIENCE AND OPERATIONAL ENVIRONMENT.

ZL-571-02-1 LH AND RH MAIN LANDING GEAR BAY		Threshold	Interval
ATA : 05 Zone : 571, 671 Ref. Doc. : 052570-200-006 Effectivity : OM-BYA, OM-BYK LH AND RH MAIN LANDING GEAR BAY GENERAL VISUAL INSPECTION OF MLG BAY (EWIS)			6 Years
ZL-572-01-2 SHROUD BOX		Threshold	Interval
ATA : 05 Zone : 572, 672 Ref. Doc. : 052570-200-002 Effectivity : OM-BYA, OM-BYK SHROUD BOX GENERAL VISUAL INSPECTION OF SHROUD BOX (EWIS) PREPARATION NOTE: FLAPS EXTENDED;			6 Years
ZL-590-01-1 LH AND RH WING AILERON		Threshold	Interval
ATA : 05 Zone : 590, 690 Ref. Doc. : 052590-200-001 Effectivity : OM-BYA, OM-BYK LH AND RH WING AILERON GENERAL VISUAL INSPECTION OF AILERON (EWIS)			72 Months
ZL-811-01-1 FWD AVIONICS COMPARTMENT DOOR		Threshold	Interval
ATA : 05 Zone : 811 Ref. Doc. : 052810-200-001 Effectivity : OM-BYA, OM-BYK FWD AVIONICS COMPARTMENT DOOR GENERAL VISUAL INSPECTION OF FWD AVIONICS COMPARTMENT DOOR (EWIS) (INCLUDING EXTERNAL SURFACE)			6 Years

ZL-812-01-1 LATERAL AVIONICS COMPARTMENT DOORS		Threshold	Interval
ATA : 05 Zone : 812, 822 Ref. Doc. : 052810-200-003 Effectivity : OM-BYA, OM-BYK LATERAL AVIONICS COMPARTMENT DOORS GENERAL VISUAL INSPECTION OF LATERAL AVIONICS COMPARTMENT DOORS (EWIS) (INCLUDING EXTERNAL SURFACE)			6 Years
ZL-824-01-1 REAR AVIONIC COMPARTMENT DOOR		Threshold	Interval
ATA : 05 Zone : 824 Ref. Doc. : 052820-200-007 Effectivity : OM-BYA, OM-BYK REAR AVIONIC COMPARTMENT DOOR GENERAL VISUAL INSPECTION OF REAR AVIONIC COMPARTMENT DOOR (EWIS) (INCLUDING EXTERNAL SURFACE)			6 Years
ZL-834-06-1 EMERGENCY EXITS		Threshold	Interval
ATA : 05 Zone : 834, 844 Ref. Doc. : 052830-200-014 Effectivity : OM-BYA, OM-BYK OVERWING EMERGENCY EXITS GENERAL VISUAL INSPECTION OF OVERWING EMERGENCY EXITS INCLUDING DOOR SURROUND ON FUSELAGE AND DOOR SEALS, EXTERNAL SURFACE (EWIS)			6 Years

200001-02-1 HIRF/LIGHTNING PROTECTION-WING	Threshold	Interval
<p>ATA : 20 Zone : 511, 520, 611, 620 Ref. Doc. : 249200-210-023 Effectivity : OM-BYA, OM-BYK</p> <p>HIRF/LIGHTNING PROTECTION-WING</p> <p>CHECK THAT THE CONNECTOR IS CORRECTLY TIGHTENED BY MEASUREMENT OF THE RESISTANCE WITH A LOOP TESTER:</p> <p>- 4005VC, 4007VC, 4009VC, 4011VC, LH SIDE - 4013VC, 4015VC, 4017VC, 4019VC, LH SIDE - 4006VC, 4008VC, 4010VC, 4012VC, RH SIDE - 4014VC, 4016VC, 4018VC, 4020VC, RH SIDE</p> <p>PREPARATION NOTE: SLATS FULLY EXTENDED</p>		6 Years
200003-01-1 HIRF/LIGHTNING PROTECTION-VERTICAL FIN	Threshold	Interval
<p>ATA : 20 Zone : 321 Ref. Doc. : 249200-210-019 Effectivity : OM-BYA, OM-BYK</p> <p>HIRF/LIGHTNING PROTECTION-VERTICAL FIN</p> <p>GENERAL VISUAL INSPECTION OF ELEMENTS FITTED ON THE FOLLOWING HARNESSSES:</p> <p>- 4202VB, 4204VB</p>		6 Years
200003-02-1 HIRF/LIGHTNING PROTECTION-VERTICAL FIN	Threshold	Interval
<p>ATA : 20 Zone : 322 Ref. Doc. : 249200-210-020 Effectivity : OM-BYA, OM-BYK</p> <p>HIRF/LIGHTNING PROTECTION-VERTICAL FIN</p> <p>GENERAL VISUAL INSPECTION OF ELEMENTS FITTED ON THE FOLLOWING HARNESSSES:</p> <p>- 4202VB, 4204VB</p>		6 Years

200003-03-1	HIRF/LIGHTNING PROTECTION-VERTICAL FIN	Threshold	Interval
ATA : 20 Zone : 324 Ref. Doc. : 249200-210-021 Effectivity : OM-BYA, OM-BYK			6 Years (+3 Months / -3 Months)

HIRF/LIGHTNING PROTECTION-VERTICAL FIN

GENERAL VISUAL INSPECTION OF ELEMENTS FITTED ON THE FOLLOWING HARNESSSES:
- 4202VB, 4204VB

200121-03-1	FORWARD AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20 Zone : 121, 122 Ref. Doc. : 249200-210-028 Effectivity : OM-BYA, OM-BYK Tags : EWIS			6 Years

FORWARD AVIONIC COMPARTMENT

EWIS TASK

GENERAL VISUAL INSPECTION OF 90, 108, 109 VU IN THE FORWARD AVIONIC COMPARTMENT

200121-04-1	FORWARD AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20 Zone : 121, 122 Ref. Doc. : 249200-220-005 Effectivity : OM-BYA, OM-BYK Tags : EWIS			6 Years

FORWARD AVIONIC COMPARTMENT

DETAILED INSPECTION OF G, E AND P ROUTES IN THE FORWARD AVIONIC COMPARTMENT (EWIS)

200125-02-1	LATERAL AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 125, 126			
Ref. Doc. : 249200-100-028			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LATERAL AVIONIC COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE LATERAL AVIONIC COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: FLOOR PANELS FROM FR 16 TO FR 20; GASKET REMOVED; ENTRANCE STAIR DEPLOYED;

200125-05-1	LATERAL AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 125, 126			
Ref. Doc. : 249200-210-030			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LATERAL AVIONIC COMPARTMENT

GENERAL VISUAL INSPECTION OF 105, 106, 103, 107 AND 70 VUS INSTALLED IN THE LATERAL AVIONIC COMPARTMENT (EWIS)

PREPARATION NOTE: 103VU; 105VU; 106VU; 107VU;

200125-07-1	LATERAL AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 125, 126			
Ref. Doc. : 249200-220-009			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LATERAL AVIONIC COMPARTMENT

DETAILED INSPECTION OF G, E AND P ROUTES INSTALLED IN THE LATERAL AVIONIC COMPARTMENT (EWIS)

PREPARATION NOTE: FLOOR PANELS FROM FR 9 TO FR 20; GASKET REMOVED; ENTRANCE STAIR DEPLOYED;

200127-02-1	REAR AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 127, 128			
Ref. Doc. : 249200-100-013			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

REAR AVIONIC COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE REAR AVIONIC COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

200127-05-1	REAR AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 127, 128			(+3 Months / -3 Months)
Ref. Doc. : 249200-210-034			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

REAR AVIONIC COMPARTMENT

GENERAL VISUAL INSPECTION OF 80, 63, 187, 188 VU INSTALLED IN THE REAR AVIONIC COMPARTMENT (EWIS)

PREPARATION NOTE: PARTITION WALL PANELS ON FR 24A; 63VU;

200127-07-1	REAR AVIONIC COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 127, 128			
Ref. Doc. : 249200-220-007			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

REAR AVIONIC COMPARTMENT

DETAILED INSPECTION OF G, E AND P ROUTES INSTALLED IN THE REAR AVIONIC COMPARTMENT (EWIS)

PREPARATION NOTE: FLOOR PANELS FROM FR 20 TO FR 24;

200129-01-1	STAIR BAY	Threshold	Interval
ATA : 20			6 Years
Zone : 129			
Ref. Doc. : 249200-100-032			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

STAIR BAY

CLEANING OF EWIS INSTALLED IN THE STAIR BAY (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: GASKET REMOVED; ENTRANCE STAIR DEPLOYED;

200129-03-1	STAIR BAY	Threshold	Interval
ATA : 20			6 Years
Zone : 129			
Ref. Doc. : 249200-220-010			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

STAIR BAY

DETAILED INSPECTION OF G, E AND P ROUTES INSTALLED IN THE STAIR BAY (EWIS)

PREPARATION NOTE: FLOOR PANELS FROM FR 16 TO FR 20; GASKET REMOVED; ENTRANCE STAIR DEPLOYED;

200131-01-1	FORWARD CARGO COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 131, 132			
Ref. Doc. : 249200-100-025			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD CARGO COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE FORWARD CARGO COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: SIDEWALL AND CEILING PANELS REMOVED;

200131-03-1	FORWARD CARGO COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 131, 132			
Ref. Doc. : 249200-210-048			
Effectivity : OM-BYA			
Tags : EWIS			

FORWARD CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS INSTALLED AT THE ACT(S) (EWIS)

NOTE: THIS TASK COULD BE PERFORMED AT THE OPPORTUNITY OF R/I

PREPARATION NOTE: ACT;

200133-01-1	UNDERFLOOR BAY OF FWD CARGO COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 133, 134			
Ref. Doc. : 249200-100-024			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

UNDERFLOOR BAY OF FWD CARGO COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE UNDERFLOOR BAY OF FORWARD CARGO COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: FLOOR PANELS REMOVED;

200137-01-1	BAY BEHIND FWD CARGO COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 137, 138			
Ref. Doc. : 249200-100-029			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

BAY BEHIND FWD CARGO COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE BAY BEHIND FWD CARGO COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: ACT(S) NO.4 AND NO.6 REMOVED (IF INSTALLED);

200145-01-1	ZONE UNDER CABIN FLOOR	Threshold	Interval
ATA : 20	Zone : 145, 146		6 Years
Ref. Doc. : 249200-100-015	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

ZONE UNDER CABIN FLOOR

CLEANING OF EWIS INSTALLED IN THE ZONE UNDER CABIN FLOOR (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: FLOOR PANELS FROM FR 36 TO FR 46;

200151-01-1	AFT CARGO COMPARTMENT	Threshold	Interval
ATA : 20	Zone : 151, 152		6 Years
Ref. Doc. : 249200-100-026	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

AFT CARGO COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE AFT CARGO COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: SIDEWALL PANELS FROM FR 46 TO FR 59; ACT(S) REMOVED (IF INSTALLED);

200151-03-1	AFT CARGO COMPARTMENT	Threshold	Interval
ATA : 20	Zone : 151, 152		6 Years
Ref. Doc. : 249200-210-046	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

AFT CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS INSTALLED AT THE ACT(S) (EWIS)

NOTE: THIS TASK COULD BE PERFORMED AT THE OPPORTUNITY OF R/I

PREPARATION NOTE: ACT;

200161-01-1	BULK CARGO COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 161, 162			
Ref. Doc. : 249200-100-030			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

BULK CARGO COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE BULK CARGO COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: SIDEWALL PANELS FROM FR 59 TO FR 65; ACT(S) REMOVED (IF INSTALLED);

200191-01-1	AIR CONDITIONING COMPARTMENT AND FAIRINGS	Threshold	Interval
ATA : 20			6 Years
Zone : 191, 192			
Ref. Doc. : 249200-100-027			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AIR CONDITIONING COMPARTMENT AND FAIRINGS

CLEANING OF EWIS INSTALLED IN THE AIR CONDITIONING COMPARTMENT AND FAIRINGS (ONLY IF CONTAMINATED) (EWIS)

200211-02-1	COCKPIT	Threshold	Interval
ATA : 20			6 Years
Zone : 211, 212			
Ref. Doc. : 249200-100-017			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

COCKPIT

CLEANING OF EWIS INSTALLED IN 49VU AND 120VU (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: 120VU; 49VU;

200231-03-1	FORWARD PASSENGER COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 231, 232			
Ref. Doc. : 249200-210-036			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD PASSENGER COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS CONNECTIONS, ATTACHMENT POINTS AND ELECTRICAL CONNECTORS BETWEEN SEAT AND A/C INSTALLED IN THE FORWARD PASSENGER COMPARTMENT (EWIS)

200241-04-1	CENTER PASSENGER COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 241, 242			
Ref. Doc. : 249200-210-037			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

CENTER PASSENGER COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS CONNECTIONS, ATTACHMENT POINTS AND ELECTRICAL CONNECTORS BETWEEN SEATS AND A/C INSTALLED IN THE CENTER PASSENGER COMPARTMENT (EWIS)

200251-03-1	AFT PASSENGER COMPARTMENT	Threshold	Interval
ATA : 20			6 Years
Zone : 251, 252			
Ref. Doc. : 249200-210-039			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT PASSENGER COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS CONNECTIONS, ATTACHMENT POINTS AND ELECTRICAL CONNECTORS BETWEEN SEATS AND A/C INSTALLED IN THE AFT PASSENGER COMPARTMENT (EWIS)

200261-03-1	AFT CABIN UTILITY AREA	Threshold	Interval
ATA : 20	Zone : 261, 262		6 Years
Ref. Doc. : 249200-210-040	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

AFT CABIN UTILITY AREA

GENERAL VISUAL INSPECTION OF EWIS CONNECTIONS, ATTACHMENT POINTS AND ELECTRICAL CONNECTORS BETWEEN SEATS AND A/C INSTALLED IN THE AFT CABIN UTILITY AREA (EWIS)

200315-01-1	TAIL CONE AND APU ACCESSORY COMPARTMENT	Threshold	Interval
ATA : 20	Zone : 315, 316		6 Years
Ref. Doc. : 249200-210-025	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

TAIL CONE AND APU ACCESSORY COMPARTMENT

GENERAL VISUAL INSPECTION OF G AND P ROUTES INSTALLED IN THE TAIL CONE AND APU ACCESSORY COMPARTMENT (EWIS)

200413-01-1-LH	LH ENGINE UPPER FORWARD PYLON	Threshold	Interval
ATA : 20	Zone : 413, 414		6 Years
Ref. Doc. : 249200-220-001	Effectivity : OM-BYA, OM-BYK		
Tags : EWIS			

LH ENGINE UPPER FORWARD PYLON

DETAILED INSPECTION OF EWIS INSTALLED IN THE UPPER FORWARD PYLON (EWIS)

200413-01-1-RH	RH ENGINE UPPER FORWARD PYLON	Threshold	Interval
ATA : 20 Zone : 423, 424 Ref. Doc. : 249200-220-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			6 Years

RH ENGINE UPPER FORWARD PYLON

DETAILED INSPECTION OF EWIS INSTALLED IN THE UPPER FORWARD PYLON (EWIS)

215200-01-1-3	NO.2 AIR CONDITIONING PACK-PRIMARY HEAT EXCHANGER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21 Zone : 192 Ref. Doc. : 215200-100-001 Effectivity : OM-BYA, OM-BYK Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				6 Years

AIR CONDITIONING PACK

ETOPS SIGNIFICANT ITEM

REMOVE PRIMARY HEAT EXCHANGER (FIN 11HM6) FOR IN SHOP CLEANING.

215200-01-1-4	NO.2 AIR CONDITIONING PACK-MAIN HEAT EXCHANGER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21 Zone : 192 Ref. Doc. : 215200-100-001 Effectivity : OM-BYA, OM-BYK Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				6 Years

AIR CONDITIONING PACK

ETOPS SIGNIFICANT ITEM

REMOVE MAIN HEAT EXCHANGER (FIN 11HM7) FOR IN SHOP CLEANING.

215200-02-2-2	NO.2 AIR CONDITIONING PACK-REHEATER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 192	Ref. Doc. : 215200-100-002		9 Years
Effectivity : OM-BYA, OM-BYK	Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
AIR CONDITIONING PACK				
ETOPS SIGNIFICANT ITEM				
REMOVE REHEATER (FIN 11HM3) FOR IN SHOP CLEANING.				

215222-01-1-2	NO.2 AIR CONDITIONING PACK - PLENUM CHAMBER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 192	Ref. Doc. : 215200-200-001		6 Years
Effectivity : OM-BYA, OM-BYK	Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
NO.2 AIR CONDITIONING PACK - PLENUM CHAMBER				
ETOPS SIGNIFICANT SYSTEM				
DETAILED INSPECTION OF INTERIOR AND EXTERIOR OF PLENUM CHAMBER (10HM5 AND 11HM5) FOR SIGNS OF DELAMINATION				

216000-01-1		AIR COOLING AND TEMPERATURE CONTROL		Threshold	Interval
		ATA	: 21		6 Years
		Zone	: 200		
		Ref. Doc.	: 216300-100-801		
		Effectivity	: OM-BYA, OM-BYK		
		AIR COOLING AND TEMPERATURE CONTROL			
		CLEANING OF CABIN SENSOR DUCT AND TEMPERATURE SENSOR.			

245000-01-1-1485-C	POWER OUTLETS	Threshold	Interval
ATA : 24			6 Years
Zone : 200			(+3 Months / -3 Months)
Ref. Doc. : AMM-S			
Effectivity : 24-50-00-710-002			
OM-BYK			

POWER OUTLETS

OPERATIONAL TEST OF THE GROUND FAULT CIRCUIT INTERRUPTERS

253000-01-1	BUFFET AND GALLEY	Threshold	Interval
ATA : 25			6 Years
Zone : 200			
Ref. Doc. : 253000-210-001			
Effectivity : OM-BYA, OM-BYK			

BUFFET AND GALLEY

DETAILED INSPECTION OF ATTACHMENT POINTS

NOTE: FOR MSN 2550, THE TASK IS TO BE CARRIED OUT AS PER BELOW PROCEDURE:

TASK 25-30-00-210-001-A

Detailed Visual Inspection of the Galley Attachment Points

1. Reason for the Job

Refer to the MPD TASK: 253000-01

DETAILED INSPECTION OF ATTACHMENT POINTS

2. Job Set-up

Subtask 25-30-00-010-051-CS

A. There is no special job set-up for this task.

3. Procedure

Subtask 25-30-00-210-050-CS

A. General Information

NOTE: This AMM task is only applicable for aircraft which have galleys installed in accordance with Airbus installation procedures.

253000-02-1	BUFFET AND GALLEY	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 253000-920-001 Effectivity : OM-BYK			6 Years
BUFFET AND GALLEY			
REMOVE AND DISCARD FILTER ELEMENT			

254000-01-1	LAVATORIES	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 254000-210-001 Effectivity : OM-BYA, OM-BYK			6 Years
LAVATORIES			
DETAILED INSPECTION OF WASTE COMPARTMENT INCLUDING WASTE FLAP AND OPERATIONAL CHECK OF WASTE FLAP			

254000-02-2	LAVATORIES	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 254000-210-002 Effectivity : OM-BYA, OM-BYK			6 Years
LAVATORIES			
DETAILED INSPECTION OF UPPER AND LOWER LAVATORY ATTACHMENT POINTS.			

254000-04-1	LAVATORIES	Threshold	Interval
ATA : 25			72 Months
Zone : 200			
Ref. Doc. : 254000-210-004			
Effectivity : OM-BYK			
LAVATORIES			
DETAILED INSPECTION OF LAVATORY FLOOR PAN			

255000-23-1	CARGO COMPARTMENTS	Threshold	Interval
ATA : 25			6 Years
Zone : 130, 150			
Ref. Doc. : 255000-200-022			
Effectivity : OM-BYA, OM-BYK			
CARGO COMPARTMENTS			
GENERAL VISUAL INSPECTION OF CRASHSTOPPERS			
NOTE:			
- IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.			
- TASK IS INCLUDED IN THE ACT INSTALLATION PROCEDURE. CREDIT CAN BE TAKEN FOR ACCOMPLISHMENT OF THE TASK AT THIS OPPORTUNITY			
PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED)			

256141-01-1	DESCENT DEVICE EMERGENCY	Threshold	Interval
ATA : 25			6 Years
Zone : 210			
Ref. Doc. : 256141-200-001			
Effectivity : OM-BYA, OM-BYK			
DESCENT DEVICE EMERGENCY			
DETAILED INSPECTION OF EMERGENCY ESCAPE ROPE AND ROPE ATTACHMENT			

256242-01-1	OFFWING ESCAPE SLIDE	Threshold	Interval
ATA : 25 Zone : 151, 152 Ref. Doc. : 256200-750-002 Effectivity : Not Effective			5 Years
OFFWING ESCAPE SLIDE			
REMOVE OFFWING ESCAPE SLIDE INFLATION RESERVOIR FOR HYDROSTATIC TEST			
NOTE: PLANNING: - TASK IS NOT APPLICABLE FOR DEACTIVATED EMERGENCY EXITS. INTERVAL: - INTERVAL TO BE MANAGED AT COMPONENT LEVEL. REFER TO SYSTEM SECTION INTRODUCTION FOR ADDITIONAL GUIDANCE.			
PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			

262100-04-1-LH	LH ENGINE FIRE EXTINGUISHING	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 415 Ref. Doc. : 262100-720-003 Effectivity : OM-BYA, OM-BYK Tags : CMR* (NO ESCALATION)				6 Years
LH ENGINE FIRE EXTINGUISHING				
CHECK DISTRIBUTION PIPING TO DETECT LEAKAGE AND OBSTRUCTION.				

262100-04-1-RH	RH ENGINE FIRE EXTINGUISHING	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26	Zone : 425	Ref. Doc. : 262100-720-003		6 Years
Effectivity : OM-BYA, OM-BYK				
Tags : CMR* (NO ESCALATION)				

262300-05-1	CARGO COMPARTMENT FIRE EXTINGUISHING	Threshold	Interval
ATA : 26	Zone : 132, 162, 172, 210		6 Years
Ref. Doc. : 262300-710-004			
Effectivity : OM-BYA, OM-BYK			

PERFORM FUNCTIONAL CHECK OF TIME DELAY FOR ILLUMINATION OF "DISCH AGENT 2" REMINDER LIGHT

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

262300-06-5		CARGO COMPARTMENT FIRE EXTINGUISHING		Threshold	Interval
ATA	:	26			6 Years
Zone	:	132, 162, 172, 210			
Ref. Doc.	:	262300-710-003			
Effectivity	:	OM-BYA, OM-BYK			
Tags	:	CMR* (NO ESCALATION)			

CHECK FIRING CIRCUIT CONTINUITY AND PERFORM OPERATIONAL CHECK OF PRIORITY SWITCHING

262541-01-1 LAVATORY FIRE EXTINGUISHER		Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : 262500-200-002 Effectivity : OM-BYA, OM-BYK LAVATORY FIRE EXTINGUISHER DETAILED INSPECTION OF LAVATORY FIRE EXTINGUISHER FOR SIGNS OF LEAKAGE/DISCHARGE			6 Years
272100-02-1 RUDDER MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 100 Ref. Doc. : 272100-210-002 Effectivity : OM-BYA, OM-BYK RUDDER MECHANICAL CONTROL DETAILED INSPECTION OF CONTROL CABLES PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED);			6 Years
272100-05-1 RUDDER MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 272100-710-001 Effectivity : OM-BYA, OM-BYK RUDDER MECHANICAL CONTROL OPERATIONAL CHECK OF CENTERING SPRING ROD			6 Years
272100-07-1 RUDDER MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 325 Ref. Doc. : 272100-210-003 Effectivity : OM-BYA, OM-BYK RUDDER MECHANICAL CONTROL DETAILED INSPECTION OF MECHANICAL CONTROL LINKAGE IN FIN			6 Years

274000-03-1	TRIMMABLE HORIZONTAL STABILIZER (THS)	Threshold	Interval
ATA : 27			6 Years
Zone : 210			
Ref. Doc. : 274400-710-001			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR* (NO ESCALATION)			

TRIMMABLE HORIZONTAL STABILIZER (THS)

OPERATIONAL CHECK OF THS ACTUATOR JAMMING PROTECTION DEVICE

275100-01-3	FLAPS	Threshold	Interval
ATA : 27			72 Months
Zone : 210			
Ref. Doc. : 275100-710-001			
Effectivity : Not Effective			

FLAPS

OPERATIONAL CHECK OF WTB/POB

NOTE:
FLAP SURFACES MOVE AUTOMATICALLY

275100-03-2-LH	LH FLAPS	Threshold	Interval
ATA : 27			72 Months
Zone : 575			
Ref. Doc. : 275400-210-002			
Effectivity : Not Effective			

LH FLAPS

CHECK OF LH WING FLAPS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS.

PREPARATION NOTE: FLAPS EXTENDED;

275100-03-2-RH	RH FLAPS	Threshold	Interval
ATA : 27 Zone : 675 Ref. Doc. : 275400-210-002 Effectivity : OM-BYA, OM-BYK			72 Months

RH FLAPS

CHECK OF RH WING FLAPS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS.

PREPARATION NOTE: FLAPS EXTENDED;

275400-01-1-LH	LH WING FLAP TRANSMISSION ASSY	Threshold	Interval
ATA : 27 Zone : 570 Ref. Doc. : 275400-200-001 Effectivity : OM-BYA, OM-BYK			6 Years

LH WING FLAP TRANSMISSION ASSY

DETAILED INSPECTION OF TRANSMISSION ASSY

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

275400-01-1-RH	RH WING FLAP TRANSMISSION ASSY	Threshold	Interval
ATA : 27 Zone : 670 Ref. Doc. : 275400-200-001 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING FLAP TRANSMISSION ASSY

DETAILED INSPECTION OF TRANSMISSION ASSY

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

275446-02-1-LH	LH FLAP TRACKS	Threshold	Interval
ATA : 27			6 Years
Zone : 530			
Ref. Doc. : 275446-200-001			
Effectivity : OM-BYA, OM-BYK			

LH FLAP TRACKS

DETAILED INSPECTION OF LH WING TRACKS, ROLLERS AND SPHERICAL BEARINGS (AS FAR AS VISIBLE).

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

275446-02-1-RH	RH FLAP TRACKS	Threshold	Interval
ATA : 27			6 Years
Zone : 630			
Ref. Doc. : 275446-200-001			
Effectivity : OM-BYA, OM-BYK			

RH FLAP TRACKS

DETAILED INSPECTION OF RH WING TRACKS, ROLLERS AND SPHERICAL BEARINGS (AS FAR AS VISIBLE).

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

275449-06-1-LH	ACTUATOR ASSEMBLY	Threshold	Interval
ATA : 27			6 Years
Zone : 575			
Ref. Doc. : 121327-612-005			
Effectivity : OM-BYA, OM-BYK			

ACTUATOR ASSEMBLY

DRAIN AND REFILL LH WING FLAP ACTUATOR ASSEMBLIES WITH SEMI-FLUID

275449-06-1-RH ACTUATOR ASSEMBLY		Threshold	Interval
ATA : 27 Zone : 675 Ref. Doc. : 121327-612-005 Effectivity : OM-BYA, OM-BYK ACTUATOR ASSEMBLY DRAIN AND REFILL RH WING FLAP ACTUATOR ASSEMBLIES WITH SEMI-FLUID			6 Years
278400-01-1-LH LH SLAT TRANSMISSION ASSY		Threshold	Interval
ATA : 27 Zone : 147, 520 Ref. Doc. : 278400-200-001 Effectivity : OM-BYA, OM-BYK LH SLAT TRANSMISSION ASSY DETAILED INSPECTION OF LH WING TRANSMISSION ASSY			6 Years
278400-01-1-RH RH SLAT TRANSMISSION ASSY		Threshold	Interval
ATA : 27 Zone : 147, 190, 620 Ref. Doc. : 278400-200-001 Effectivity : OM-BYA, OM-BYK RH SLAT TRANSMISSION ASSY DETAILED INSPECTION OF RH WING TRANSMISSION ASSY			6 Years
278468-02-1-LH LH SLAT TRACKS		Threshold	Interval
ATA : 27 Zone : 520 Ref. Doc. : 278400-210-001 Effectivity : OM-BYA, OM-BYK LH SLAT TRACKS DETAILED INSPECTION OF LH WING SLAT TRACKS, ROLLER BEARINGS, PINION BEARINGS AND CURVED RACK GEARS - AS VISIBLE. PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;			6 Years

278468-02-1-RH	RH SLAT TRACKS	Threshold	Interval
ATA : 27 Zone : 620 Ref. Doc. : 278400-210-001 Effectivity : OM-BYA, OM-BYK			6 Years

RH SLAT TRACKS

DETAILED INSPECTION OF RH WING SLAT TRACKS, ROLLER BEARINGS, PINION BEARINGS AND CURVED RACK GEARS - AS VISIBLE.

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

281500-01-1	INTERCELL TRANSFER SYSTEM	Threshold	Interval
ATA : 28 Zone : 210 Ref. Doc. : 281500-710-002 Effectivity : OM-BYA, OM-BYK Tags : CMR** (NO ESCALATION)			6 Years

INTERCELL TRANSFER SYSTEM

OPERATIONAL CHECK OF INDIVIDUAL TRANSFER VALVES TO ENSURE VALVE SHAFT ROTATES VALVE TO OPEN POSITION

281800-01-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28 Zone : 137, 138 Ref. Doc. : 281800-700-001 Effectivity : OM-BYA, OM-BYK			6 Years

IGNITION PREVENTION

FUNCTIONAL CHECK OF TANK VAPOUR SEAL AND VENT DRAIN SYSTEM (SFAR88)

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

281800-02-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28			6 Years
Zone : 191, 192			
Ref. Doc. : 281800-200-001			
Effectivity : OM-BYA, OM-BYK			
IGNITION PREVENTION			
DETAILED INSPECTION OF VAPOUR SEAL (SFAR88)			

281800-05-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28			6 Years
Zone : 137, 138			
Ref. Doc. : 281852-210-001			
Effectivity : OM-BYA, OM-BYK			
IGNITION PREVENTION			
GENERAL VISUAL INSPECTION OF CENTER TANK FWD CARGO BAY INSULATION BLANKETS (SFAR88).			
PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			

282100-04-1	MAIN FUEL PUMP SYSTEM	Threshold	Interval
ATA : 28			6 Years
Zone : 210			
Ref. Doc. : 282100-710-005			
Effectivity : OM-BYA, OM-BYK			
Taqs : CMR** (NO ESCALATION)ETOPS SIGNIFICANT SYSTEM			
MAIN FUEL PUMP SYSTEM			
OPERATIONAL CHECK TO ENSURE THAT BOTH CENTER TANK PUMPS FEED FOR 2 MINUTES AFTER ENGINE START			

282300-01-1	CROSSFEED SYSTEM	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA	: 28			6 Years
Zone	: 210			
Ref. Doc.	: 282300-720-001			
Effectivity	: OM-BYA, OM-BYK			
Tags	: ETOPS SIGNIFICANT SYSTEM			

CROSSFEED SYSTEM

ETOPS SIGNIFICANT SYSTEM

OPERATIONAL CHECK OF CROSSFEED VALVE USING INDIVIDUAL MOTORS AND CHECK FUEL FLOW IN "OPEN" AND FUEL SHUT OFF IN "CLOSED" POSITIONS

282541-01-1	COUPLING REFUEL/DEFUEL	Threshold	Interval
ATA	: 28		6 Years
Zone	: 522, 622		
Ref. Doc.	: 282541-200-001		
Effectivity	: OM-BYA, OM-BYK		

COUPLING REFUEL/DEFUEL

DETAILED INSPECTION OF COUPLING REFUEL/DEFUEL.

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

282800-58-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA	: 28		6 Years
Zone	: 150		
Ref. Doc.	: 282800-710-009		
Effectivity	: OM-BYA, OM-BYK		

ADDITIONAL CENTER TANK TRANSFER SYSTEM

OPERATIONAL CHECK OF ACT(S) INWARD RELIEF VALVE

NOTE:

- IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.
- ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT AIRCRAFT AGE.

291000-04-1	MAIN HYDRAULIC POWER	Threshold	Interval
ATA : 29			6 Years
Zone : 210			
Ref. Doc. : 292300-710-002			
Effectivity : OM-BYA, OM-BYK			
MAIN HYDRAULIC POWER			
FUNCTIONAL CHECK OF PTU GREEN TO YELLOW			

291000-26-1	MAIN AND AUXILIARY HYDRAULIC POWER	Threshold	Interval
ATA : 29			6 Years
Zone : 195, 196			
Ref. Doc. : 123229-281-804			
Effectivity : OM-BYA, OM-BYK			
MAIN AND AUXILIARY HYDRAULIC POWER			
ANALYZE HYDRAULIC FLUID FOR CHLORINE, DENSITY, VISCOSITY AND CONDUCTIVITY CONTAMINATON			

321113-03-1	MAIN LANDING GEAR SHOCK ABSORBER	Threshold	Interval
ATA : 32			6 Years
Zone : 731, 741			
Ref. Doc. : 121232-611-004			
Effectivity : OM-BYA, OM-BYK			
MAIN LANDING GEAR SHOCK ABSORBER			
FUNCTIONAL CHECK OF MLG SHOCK ABSORBER FLUID LEVEL			

323000-17-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32			6 Years
Zone : 210			
Ref. Doc. : 323100-720-008			
Effectivity : OM-BYA, OM-BYK			
NORMAL EXTENSION AND RETRACTION			
FUNCTIONAL CHECK OF LGCIU POWER SUPPLY RELAYS.			

323300-01-1 LANDING GEAR FREE FALL EXTENSION		Threshold	Interval
ATA : 32 Zone : 100, 200 Ref. Doc. : 323300-200-002 Effectivity : OM-BYA, OM-BYK LANDING GEAR FREE FALL EXTENSION DETAILED INSPECTION OF FREE-FALL MECHANISM INCLUDING CABLES PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			6 Years
323300-04-1 LANDING GEAR FREE FALL EXTENSION		Threshold	Interval
ATA : 32 Zone : 100 Ref. Doc. : 323300-200-001 Effectivity : OM-BYA, OM-BYK LANDING GEAR FREE FALL EXTENSION FUNCTIONAL CHECK OF FREE-FALL MECHANISM CABLE TENSION PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			6 Years
351000-10-1 CREW OXYGEN		Threshold	Interval
ATA : 35 Zone : 122 Ref. Doc. : 351300-200-802 Effectivity : OM-BYA, OM-BYK CREW OXYGEN REMOVE PRESSURE REGULATOR TRANSMITTER FOR IN SHOP FUNCTIONAL CHECK			6 Years

351000-11-1	CREW OXYGEN	Threshold	Interval
ATA : 35			6 Years
Zone : 122			
Ref. Doc. : 351000-720-002			
Effectivity : OM-BYA, OM-BYK			
CREW OXYGEN			
REMOVE LP SOLENOID VALVE FOR IN SHOP FUNCTIONAL CHECK			

351351-01-1	OXYGEN SUPPLY VALVE	Threshold	Interval
ATA : 35			6 Years
Zone : 210			
Ref. Doc. : 351200-710-001			
Effectivity : OM-BYA, OM-BYK			
OXYGEN SUPPLY VALVE			
FUNCTIONAL CHECK OF LOW PRESSURE SWITCH			

352000-01-1	PASSENGER OXYGEN SYSTEM (CHEMICAL)	Threshold	Interval
ATA : 35			6 Years
Zone : 200			
Ref. Doc. : 352300-710-001			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR** (NO ESCALATION)			
PASSENGER OXYGEN SYSTEM			
OPERATIONAL CHECK OF MANUAL MASK RELEASE			

352000-01-1-1485-C	PASSENGER OXYGEN	Threshold	Interval
ATA : 35 Zone : 200 Ref. Doc. : AMM-S Effectivity : 35-20-00-710-001 OM-BYK			6 Years
PASSENGER OXYGEN			
OPERATIONAL TEST OF THE MANUAL OXYGEN MASK DEPLOYMENT			

352000-02-1	PASSENGER OXYGEN SYSTEM (CHEMICAL)	Threshold	Interval
ATA : 35 Zone : 200 Ref. Doc. : 352300-720-003 Effectivity : OM-BYA, OM-BYK			6 Years
PASSENGER OXYGEN SYSTEM			
FUNCTIONAL CHECK OF AUTOMATIC MASK RELEASE, DETAILED INSPECTION OF MASKS AND VISUAL CHECK OF CHEMICAL OXYGEN GENERATORS			

352000-02-1-1485-C	PASSENGER OXYGEN	Threshold	Interval
ATA : 35 Zone : 200 Ref. Doc. : AMM-S Effectivity : 35-20-00-710-001 35-20-00-220-001 OM-BYK			6 Years
PASSENGER OXYGEN			
OPERATIONAL TEST OF THE AUTOMATIC OXYGEN MASK DEPLOYMENT, DETAILED INSPECTION OF MASKS AND VISUAL CHECK OF CHEMICAL OXYGEN GENERATORS			

361141-03-1-LH	LH ENGINE IP BLEED CHECK VALVE	Threshold	Interval
ATA : 36			6 Years
Zone : 453			
Ref. Doc. : 361141-200-001			
Effectivity : OM-BYA, OM-BYK			
Tags : ETOPS SIGNIFICANT SYSTEM			

LH ENGINE IP BLEED CHECK VALVE

CHECK OF LH ENGINE IP BLEED CHECK VALVE FOR CONDITION

361141-03-1-RH	RH ENGINE IP BLEED CHECK VALVE	Threshold	Interval
ATA : 36			6 Years
Zone : 463			
Ref. Doc. : 361141-200-001			
Effectivity : OM-BYA, OM-BYK			
Tags : ETOPS SIGNIFICANT SYSTEM			

RH ENGINE IP BLEED CHECK VALVE

CHECK OF RH ENGINE IP BLEED CHECK VALVE FOR CONDITION

361143-01-1-LH	LH ENGINE THERMOSTAT - FAN AIR VALVE CONTROL	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 36				6 Years
Zone : 413				
Ref. Doc. : 361143-100-001				
Effectivity : OM-BYA, OM-BYK				
Tags : TCI (NO ESCALATION ALLOWED)ETOPS SIGNIFICANT SYSTEM				

LH ENGINE THERMOSTAT - FAN AIR VALVE CONTROL

REMOVE THE LH ENGINE THERMOSTAT-FILTER OF THE FAN AIR VALVE-CONTROL FOR CLEANING.

361143-01-1-RH		RH ENGINE THERMOSTAT - FAN AIR VALVE CONTROL	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA	:	36			6 Years
Zone	:	423			
Ref. Doc.	:	361143-100-001			
Effectivity	:	OM-BYA, OM-BYK			
Tags	:	TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM			

RH ENGINE THERMOSTAT - FAN AIR VALVE CONTROL

REMOVE THE RH ENGINE THERMOSTAT-FILTER OF THE FAN AIR VALVE-CONTROL FOR CLEANING.

361200-01-1	AIR BLEED AIR SUPPLY & CROSSBLEED SYST	Threshold	Interval
ATA : 36			6 Years
Zone : 210			
Ref. Doc. : 361200-710-002			
Effectivity : OM-BYA, OM-BYK			

AIR BLEED AIR SUPPLY & CROSSBLEED SYST

OPERATIONAL CHECK OF CROSSBLEED VALVE IN MANUAL MODE

384142-01-1	AIR FILTER	Threshold	Interval
ATA : 38			6 Years
Zone : 137, 171			
Ref. Doc. : 384100-610-001			
Effectivity : OM-BYA, OM-BYK			

AIR FILTER

DISCARD SYSTEM FILTER ELEMENT

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

521000-05-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-720-003 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR FUNCTIONAL CHECK OF LOCKING MECHANISM			6 Years
521000-06-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-720-005 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR FUNCTIONAL CHECK OF ESCAPE SLIDE RELEASE MECHANISM			6 Years
521000-08-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-710-002 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR OPERATIONAL CHECK OF INTERLOCK MECHANISM TO ENSURE THAT EMERGENCY ESCAPE HANDLE STAYS IN DISARMED POSITION WHEN DOOR IS UP AND OUTSIDE OF FRAME			6 Years

521000-10-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-710-001 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR OPERATIONAL CHECK OF DAMPING DURING OPENING/CLOSING			6 Years
521000-11-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-710-003 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR OPERATIONAL CHECK OF STRIKER MECHANISM			6 Years
521000-12-1 PASSENGER/CREW DOOR		Threshold	Interval
ATA : 52 Zone : 831, 832, 841, 842 Ref. Doc. : 521000-720-002 Effectivity : OM-BYA, OM-BYK PASSENGER/CREW DOOR OPERATIONAL CHECK OF ESCAPE SLIDE DISARMING WHEN DOOR IS OPENED FROM THE OUTSIDE			6 Years

521000-17-1	PASSENGER/CREW DOOR	Threshold	Interval
ATA : 52			6 Years
Zone : 832, 842			
Ref. Doc. : 521000-220-009			
Effectivity : Not Effective			
PASSENGER/CREW DOOR			
DETAILED INSPECTION OF AFT DOOR SEALS			

523100-01-1	FORWARD CARGO COMPARTMENT DOOR	Threshold	Interval
ATA : 52			6 Years
Zone : 825			
Ref. Doc. : 523100-720-001			
Effectivity : OM-BYA, OM-BYK			
FORWARD CARGO COMPARTMENT DOOR			
FUNCTIONAL CHECK OF FORWARD CARGO COMPARTMENT DOOR, COMPRISING FUNCTIONAL CHECKS OF:			
- LOCKING MECHANISM			
- INTERLOCK MECHANISM			
- DRIFT PIN MECHANISM			
- SAFETY MECHANISM			

523200-01-1	AFT CARGO COMPARTMENT DOOR	Threshold	Interval
ATA : 52			6 Years
Zone : 826			
Ref. Doc. : 523200-720-001			
Effectivity : OM-BYA, OM-BYK			
AFT CARGO COMPARTMENT DOOR			
FUNCTIONAL CHECK OF AFT CARGO COMPARTMENT DOOR, COMPRISING FUNCTIONAL CHECKS OF:			
- LOCKING MECHANISM			
- INTERLOCK MECHANISM			
- DRIFT PIN MECHANISM			
- SAFETY MECHANISM			

524100-01-1	ACCESS DOORS	Threshold	Interval
ATA : 52 Zone : 811, 812, 822, 824 Ref. Doc. : 524100-210-001 Effectivity : OM-BYA, OM-BYK			6 Years
ACCESS DOORS			
DETAILED INSPECTION OF DOOR SEALS			

525111-02-1	COCKPIT DOOR	Threshold	Interval
ATA : 52 Zone : 220 Ref. Doc. : 525100-720-002 Effectivity : OM-BYA, OM-BYK			6 Years
COCKPIT DOOR			
OPERATIONAL CHECK OF ALL PRESSURE SENSING CHANNELS FOR RAPID DECOMPRESSION.			

525111-04-1	COCKPIT DOOR	Threshold	Interval
ATA : 52 Zone : 220 Ref. Doc. : 525100-710-005 Effectivity : OM-BYA, OM-BYK			6 Years
COCKPIT DOOR			
OPERATIONAL CHECK OF DOOR OPENING IN CASE OF POWER OFF.			

525111-05-1	COCKPIT DOOR	Threshold	Interval
ATA : 52 Zone : 220 Ref. Doc. : 525100-710-006 Effectivity : OM-BYA, OM-BYK			6 Years
COCKPIT DOOR			
OPERATIONAL CHECK OF DOOR OPENING BY USING THE EMERGENCY CODE.			

526000-01-1 ENTRANCE STAIRS		Threshold	Interval
ATA : 52 Zone : 210 Ref. Doc. : 526100-710-001 Effectivity : OM-BYA, OM-BYK ENTRANCE STAIRS OPERATIONAL CHECK OF STAIRS DEPLOYMENT INHIBITION CIRCUIT			6 Years
527100-01-1 DOOR WARNING		Threshold	Interval
ATA : 52 Zone : 210 Ref. Doc. : 527100-710-001 Effectivity : OM-BYA, OM-BYK DOOR WARNING OPERATIONAL CHECK OF DOOR WARNING SYSTEM			6 Years
527300-01-1 EMERGENCY ESCAPE SLIDE RELEASE AND OVERPRESSURE WARNING SYSTEMS		Threshold	Interval
ATA : 52 Zone : 210 Ref. Doc. : 527300-710-003 Effectivity : OM-BYA, OM-BYK EMERGENCY ESCAPE SLIDE RELEASE AND OVERPRESSURE WARNING SYSTEMS OPERATIONAL CHECK OF EMERGENCY ESCAPE SLIDE RELEASE WARNING			6 Years
527300-02-1 EMERGENCY ESCAPE SLIDE RELEASE AND OVERPRESSURE WARNING SYSTEMS		Threshold	Interval
ATA : 52 Zone : 122 Ref. Doc. : 527300-720-003 Effectivity : OM-BYA, OM-BYK EMERGENCY ESCAPE SLIDE RELEASE AND OVERPRESSURE WARNING SYSTEMS OPERATIONAL CHECK OF RESIDUAL CABIN PRESSURE WARNING AND FUNCTIONAL CHECK OF DIFFERENTIAL PRESSURE SWITCH			6 Years

530000-01-1 FUSELAGE DRAINAGE		Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : 530000-210-001 Effectivity : OM-BYA, OM-BYK FUSELAGE DRAINAGE REMOVE AND DETAILED INSPECTION OF PISTON TYPE DRAIN VALVES IN LOWER FUSELAGE SHELL			6 Years
531900-02-1 FUSELAGE DRAINAGE		Threshold	Interval
ATA : 53 Zone : 120 Ref. Doc. : 531900-710-001 Effectivity : Not Effective *** TASK DELETED ***			72 Months
781100-C2-1-LH LH ENGINE HOT EXHAUST		Threshold	Interval
ATA : 78 Zone : 450 Ref. Doc. : 781111-210-043 Effectivity : OM-BYA, OM-BYK LH ENGINE HOT EXHAUST GENERAL VISUAL INSPECTION OF INNER AND OUTER SEALS			6 Years
781100-C2-1-RH RH ENGINE HOT EXHAUST		Threshold	Interval
ATA : 78 Zone : 460 Ref. Doc. : 781111-210-043 Effectivity : OM-BYA, OM-BYK RH ENGINE HOT EXHAUST GENERAL VISUAL INSPECTION OF INNER AND OUTER SEALS			6 Years

783000-C8-1-LH LH ENGINE THRUST REVERSER		Threshold	Interval
ATA : 78 Zone : 450 Ref. Doc. : 783211-220-040 Effectivity : OM-BYA, OM-BYK LH ENGINE THRUST REVERSER GENERAL VISUAL INSPECTION OF INNER BARREL HEATSHIELD, FIRE PROTECTIVE COATING AND FIRE SEALS (C DUCTS OPEN)			6 Years
783000-C8-1-RH RH ENGINE THRUST REVERSER		Threshold	Interval
ATA : 78 Zone : 460 Ref. Doc. : 783211-220-040 Effectivity : OM-BYA, OM-BYK RH ENGINE THRUST REVERSER GENERAL VISUAL INSPECTION OF INNER BARREL HEATSHIELD, FIRE PROTECTIVE COATING AND FIRE SEALS (C DUCTS OPEN)			6 Years
783100-C7-1-LH LH ENGINE THRUST REVERSER CONTROL AND INDICATING		Threshold	Interval
ATA : 78 Zone : 437, 438 Ref. Doc. : 783100-210-041 Effectivity : OM-BYA, OM-BYK LH ENGINE THRUST REVERSER CONTROL AND INDICATING GENERAL VISUAL INSPECTION OF PRIMARY LATCH MECHANISM (BLOCKER DOORS DEPLOYED) PREPARATION NOTE: BLOCKER DOORS DEPLOYMENT;			6 Years

783100-C7-1-RH	RH ENGINE THRUST REVERSER CONTROL AND INDICATING	Threshold	Interval
ATA : 78			6 Years
Zone : 447, 448			
Ref. Doc. : 783100-210-041			
Effectivity : OM-BYA, OM-BYK			

RH ENGINE THRUST REVERSER CONTROL AND INDICATING

GENERAL VISUAL INSPECTION OF PRIMARY LATCH MECHANISM (BLOCKER DOORS DEPLOYED)

PREPARATION NOTE: BLOCKER DOORS DEPLOYMENT;



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

3C CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 82

212100-01-1	AIR DISTRIBUTION AND RECIRCULATION	Threshold	Interval
ATA : 21 Zone : 131 Ref. Doc. : 212149-100-001 Effectivity : OM-BYA, OM-BYK			9 Years

AIR DISTRIBUTION AND RECIRCULATION

CLEAN COCKPIT AIR SUPPLY DUCTING GRID

212600-03-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 212600-710-003 Effectivity : OM-BYA, OM-BYK			9 Years

AVIONICS EQUIPMENT VENTILATION

OPERATIONAL CHECK OF SMOKE CONFIGURATION CONTROL CIRCUIT

213100-01-1	PRESSURE CONTROL AND MONITORING	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 213100-710-002 Effectivity : OM-BYA, OM-BYK			9 Years

PRESSURE CONTROL AND MONITORING

OPERATIONAL CHECK OF SYSTEM VIA MCDU

213100-02-1	PRESSURE CONTROL AND MONITORING	Threshold	Interval
ATA : 21			9 Years
Zone : 210			
Ref. Doc. : 213100-710-003			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR* (NO ESCALATION)			

PRESSURE CONTROL AND MONITORING

OPERATIONAL CHECK OF MANUAL MODE SELECTION AND MANUAL MODE PRESSURE CONTROL AND FUNCTIONAL CHECK OF MANUAL MODE CABIN ALTITUDE INDICATION AND OUTFLOW VALVE POSITION INDICATION

215000-03-2	PACK RAM AIR INLET	Threshold	Interval
ATA : 21			9 Years
Zone : 190			
Ref. Doc. : 216151-200-001			
Effectivity : OM-BYA, OM-BYK			

PACK RAM AIR INLET

DETAILED INSPECTION OF ACTUATOR MECHANISM AND INLET FLAP FOR EXCESSIVE PLAY AND CHECK GAP BETWEEN INLET NOSE AND DIFFUSER RAMP

215200-01-1-1	NO.1 AIR CONDITIONING PACK-PRIMARY HEAT EXCHANGER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21				9 Years
Zone : 191				
Ref. Doc. : 215200-100-001				
Effectivity : OM-BYA, OM-BYK				
Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				

AIR CONDITIONING PACK

ETOPS SIGNIFICANT SYSTEM

REMOVE PRIMARY HEAT EXCHANGER (FIN 10HM6) FOR IN SHOP CLEANING.

215200-01-1-2	NO.1 AIR CONDITIONING PACK-MAIN HEAT EXCHANGER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 191	Ref. Doc. : 215200-100-001		9 Years
Effectivity : OM-BYA, OM-BYK				
Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				
AIR CONDITIONING PACK				
ETOPS SIGNIFICANT ITEM				
REMOVE MAIN HEAT EXCHANGER (FIN 10HM7) FOR IN SHOP CLEANING.				

215200-02-2-1	NO.1 AIR CONDITIONING PACK-REHEATER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 191	Ref. Doc. : 215200-100-002		9 Years
Effectivity : OM-BYA, OM-BYK				
Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				
AIR CONDITIONING PACK				
ETOPS SIGNIFICANT SYSTEM				
REMOVE REHEATER (FIN 10HM3) FOR IN SHOP CLEANING.				

215222-01-1-1	NO.1 AIR CONDITIONING PACK - PLENUM CHAMBER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 191	Ref. Doc. : 215200-200-001		9 Years
Effectivity : OM-BYA, OM-BYK				
Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				
NO.1 AIR CONDITIONING PACK - PLENUM CHAMBER				
ETOPS SIGNIFICANT SYSTEM				
DETAILED INSPECTION OF INTERIOR AND EXTERIOR OF PLENUM CHAMBER (10HM5 AND 11HM5) FOR SIGNS OF DELAMINATION				

216000-02-1	AIR COOLING AND TEMPERATURE CONTROL	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 216300-710-002 Effectivity : OM-BYK			9 Years
AIR COOLING AND TEMPERATURE CONTROL			
OPERATIONAL CHECK OF ZONE CONTROLLER (BACK UP SWITCHING) VIA CFDS/MCDU			
216242-01-1	AIR COOLING AND TEMPERATURE CONTROL	Threshold	Interval
ATA : 21 Zone : 191 Ref. Doc. : 216342-210-001 Effectivity : OM-BYA, OM-BYK			9 Years
AIR COOLING AND TEMPERATURE CONTROL			
DETAILED INSPECTION OF TRIM AIR CHECK VALVES FLAPPERS FOR CONDITION AND OPERATION			
PREPARATION NOTE: CHECK VALVE;			
242200-01-1	AC GENERATION	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 242200-710-002 Effectivity : OM-BYA, OM-BYK			9 Years
AC GENERATION			
OPERATIONAL CHECK OF TRANSFER INHIBITION			
242500-01-1	AC GENERATION	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 242500-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
AC GENERATION			
OPERATIONAL CHECK OF AC ESS GENERATION SWITCHING			

243200-01-1	DC GENERATION	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 243200-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
DC GENERATION			
OPERATIONAL CHECK OF DC GENERATION SWITCHING			

243400-01-1	DC GENERATION	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 243400-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
DC GENERATION			
OPERATIONAL CHECK OF "DC EMERG. CONFIG" CAUTION			

252200-01-1	CABIN ATTENDANT SEATS	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 252200-210-001 Effectivity : OM-BYA, OM-BYK			9 Years
CABIN ATTENDANT SEATS			
DETAILED INSPECTION OF CABIN ATTENDANT SEAT ATTACHMENTS, SEAT STRUCTURE AND SEAT BELT (INCL. SEAT BELT ATTACHMENTS AND BUCKLES).			

254000-04-2	LAVATORIES	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 254000-210-004 Effectivity : OM-BYA			9 Years
LAVATORIES			
DETAILED INSPECTION OF LAVATORY FLOOR PAN			

261500-03-1	AVIONICS COMPARTMENT SMOKE DETECTION	Threshold	Interval
ATA : 26			9 Years
Zone : 128			
Ref. Doc. : 261500-100-001			
Effectivity : OM-BYA, OM-BYK			
AVIONICS COMPARTMENT SMOKE DETECTION			
CLEAN AVIONICS SMOKE DETECTION PICCOLO TUBES			

261700-04-1-1	LAVATORY A SMOKE DETECTION	Threshold	Interval
ATA : 26			9 Years
Zone : 200			
Ref. Doc. : 261715-100-003			
Effectivity : OM-BYA, OM-BYK			
LAVATORY A SMOKE DETECTION			
REMOVE SMOKE DETECTOR FOR CLEANING			
REINSTALL SMOKE DETECTOR AFTER CLEANING			

261700-04-1-2	LAVATORY D SMOKE DETECTION	Threshold	Interval
ATA : 26			9 Years
Zone : 200			
Ref. Doc. : 261715-100-003			
Effectivity : OM-BYA, OM-BYK			
LAVATORY D SMOKE DETECTION			
REMOVE SMOKE DETECTOR FOR CLEANING			
REINSTALL SMOKE DETECTOR AFTER CLEANING			

261700-04-1-3 LAVATORY E SMOKE DETECTION		Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : 261715-100-003 Effectivity : OM-BYA, OM-BYK LAVATORY E SMOKE DETECTION REMOVE SMOKE DETECTOR FOR CLEANING INSTALL SMOKE DETECTOR AFTER CLEANING			9 Years
262100-02-1 ENGINE FIRE EXTINGUISHING		Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 262100-710-002 Effectivity : OM-BYA, OM-BYK ENGINE FIRE EXTINGUISHING OPERATIONAL CHECK OF BOTTLE LOW PRESSURE INDICATING CIRCUIT			9 Years
262300-07-1 CARGO COMPARTMENT FIRE EXTINGUISHING		Threshold	Interval
ATA : 26 Zone : 132, 162, 172 Ref. Doc. : 262300-200-003 Effectivity : OM-BYA, OM-BYK Tags : CMR* (NO ESCALATION) CARGO COMPARTMENT FIRE EXTINGUISHING REMOVE THE PRESSURE REDUCER FOR IN-SHOP FUNCTIONAL CHECK INCLUDING CHECK OF FIRE EXTINGUISHING LINES FOR LEAKAGE AND OBSTRUCTION PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			9 Years

262300-08-1	CARGO COMPARTMENT FIRE EXTINGUISHING	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA	: 26			9 Years
Zone	: 132, 162, 172			
Ref. Doc.	: 262300-200-002			
Effectivity	: OM-BYA, OM-BYK			
Tags	: CMR* (NO ESCALATION)			

CARGO COMPARTMENT FIRE EXTINGUISHING

-REMOVE HALON FILTER, CHECK VALVE AND DIAPHRAGM
-INSPECT HALON FILTER -DO A DETAILED INSPECTION OF CHECK VALVE
-DO A DETAILED INSPECTION OF DIAPHRAGM
-REINSTALL HALON FILTER, CHECK VALVE AND DIAPHRAGM

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION

272100-10-1	RUDDER MECHANICAL CONTROL	Threshold	Interval
ATA : 27			9 Years
Zone : 320			
Ref. Doc. : 272149-200-001			
Effectivity : OM-BYA, OM-BYK			

RUDDER MECHANICAL CONTROL

FUNCTIONAL CHECK OF RUDDER SERVOCONTROL ACTUATING SPRING RODS

272100-11-1	RUDDER MECHANICAL CONTROL	Threshold	Interval
ATA : 27			9 Years
Zone : 325			
Ref. Doc. : 272100-220-004			
Effectivity : OM-BYA, OM-BYK			

RUDDER MECHANICAL CONTROL

DETAILED INSPECTION OF RUDDER SERVOCONTROL ACTUATING SPRING RODS AND RUDDER SERVOCONTROL FEEDBACK ROD ATTACHMENTS

274100-01-1 THS MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 100, 310 Ref. Doc. : 274100-210-001 Effectivity : OM-BYA, OM-BYK THS MECHANICAL CONTROL DETAILED INSPECTION OF THS MECHANICAL CONTROL PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); CEILING PANELS REMOVED; FLOOR PANELS REMOVED;			9 Years
274451-04-1 THS ACTUATOR		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274451-220-001 Effectivity : OM-BYA, OM-BYK THS ACTUATOR DETAILED INSPECTION OF THS ACTUATOR BALL SCREW NUT BODY AND SCREW AND CLAW STOPS			9 Years
274451-06-1 THS ACTUATOR		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274451-210-002 Effectivity : OM-BYA, OM-BYK THS ACTUATOR VISUAL CHECK OF THS ACTUATOR THREADED NUT (FAIL SAFE NUT)			9 Years
274451-08-1 THS ACTUATOR		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274451-280-001 Effectivity : OM-BYA, OM-BYK THS ACTUATOR CHECK INTEGRITY OF THS ACTUATOR BALL SCREW SHAFT (PRIMARY AND SECONDARY LOAD PATH)			9 Years

275100-01-2	FLAPS	Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : AMM : 275100-710-001 Effectivity : OM-BYA, OM-BYK FLAPS OPERATIONAL CHECK OF WTB/POB			9 Years

275100-02-1	FLAPS	Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 275100-710-002 Effectivity : OM-BYA, OM-BYK FLAPS OPERATIONAL CHECK OF FLAP INTERCONNECTING STRUT AND FLAP DISCONNECT PROXIMITY SENSORS			9 Years

275100-03-1-LH	LH FLAPS	Threshold	Interval
ATA : 27 Zone : 575 Ref. Doc. : AMM : 275400-210-002 Effectivity : OM-BYA, OM-BYK Tags : CMR** (NO ESCALATION) LH FLAPS CHECK OF FLAPS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS			9 Years

275100-03-1-RH	RH FLAPS	Threshold	Interval
ATA : 27			9 Years
Zone : 675			
Ref. Doc. : AMM : 275400-210-002			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR** (NO ESCALATION)			

RH FLAPS

CHECK OF FLAPS TRANSMISSION SHAFTING INTEGRITY, INCLUDING INSPECTION OF SEAL WITNESS DRAINS

275144-01-1-LH	LH FLAP INTERCONNECTING STRUT	Threshold	Interval
ATA : 27			9 Years
Zone : 580			
Ref. Doc. : 275144-200-001			
Effectivity : OM-BYA, OM-BYK			

LH FLAP INTERCONNECTING STRUT

DETAILED INSPECTION OF INTERCONNECTING STRUT AND ATTACHMENTS

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

275144-01-1-RH	RH FLAP INTERCONNECTING STRUT	Threshold	Interval
ATA : 27			9 Years
Zone : 680			
Ref. Doc. : 275144-200-001			
Effectivity : OM-BYA, OM-BYK			

RH FLAP INTERCONNECTING STRUT

DETAILED INSPECTION OF INTERCONNECTING STRUT AND ATTACHMENTS

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

281600-01-1 FUEL RECIRCULATION COOLING		Threshold	Interval
ATA : 28 Zone : 471, 481 Ref. Doc. : 281600-710-002 Effectivity : OM-BYA, OM-BYK FUEL RECIRCULATION COOLING OPERATIONAL CHECK OF PYLON CHECK VALVE TO ENSURE VALVE NOT FAILED OPEN			9 Years
282100-05-1 FUEL PUMP SYSTEM		Threshold	Interval
ATA : 28 Zone : 410, 420, 520, 620 Ref. Doc. : 282100-790-002 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM FUEL PUMP SYSTEM VISUAL CHECK OF PIPES, COUPLINGS AND LP VALVE EXTERNAL TO TANK FROM FRONT SPAR TO DISCONNECT PANEL FOR LEAKS WITH BOOSTER PUMP ON AND LP VALVE OPEN PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			9 Years
282400-01-1 ENGINE LOW PRESSURE SHUT OFF [SAFETY CRITICAL TASK]		Threshold	Interval
ATA : 28 Zone : 210, 520, 620 Ref. Doc. : 282400-790-003 Effectivity : OM-BYA, OM-BYK ENGINE LOW PRESSURE SHUT OFF OPERATIONAL CHECK OF LP SHUT OFF VALVES AND THEIR CONTROLS TO ENSURE NO FLOW WHEN SELECTED CLOSED WITH BOOSTER PUMP ON NOTE: INTERVAL: - TASK MAY BE PERFORMED AT OPPORTUNITY OF ENGINE REMOVAL PROVIDED INTERVAL NOT EXCEEDED			9 Years

282800-06-1 ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
<p>ATA : 28 Zone : 150 Ref. Doc. : 282839-920-001 Effectivity : OM-BYA, OM-BYK</p> <p>ADDITIONAL CENTER TANK TRANSFER SYSTEM</p> <p>REPLACE ACT AIR INLET FILTER</p> <p>NOTE: INTERVAL: - IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.</p> <p>PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;</p>		9 Years
291000-09-1 MAIN HYDRAULIC POWER	Threshold	Interval
<p>ATA : 29 Zone : 574, 674 Ref. Doc. : 291000-710-001 Effectivity : OM-BYA, OM-BYK</p> <p>MAIN HYDRAULIC POWER</p> <p>OPERATIONAL CHECK OF HYDRAULIC FIRE SHUT OFF VALVES AND ASSOCIATED INDICATING SYSTEM.</p> <p>NOTE: APPLICABLE FOR PRE 22155 IF ACTUATOR P/N E0 1100 AMENDMENT A, OR P/N E0 1100 AMENDMENT AB, OR P/N E01100 AMENDMENT AC, OR P/N E0 1100 AMENDMENT BC, OR P/N E0 1100 AMENDMENT C, OR P/N A06 A00 IS INSTALLED</p>		9 Years
291000-19-1 MAIN/AUXILIARY POWER	Threshold	Interval
<p>ATA : 29 Zone : 210 Ref. Doc. : 292300-710-006 Effectivity : OM-BYA</p> <p>MAIN/AUXILIARY POWER</p> <p>OPERATIONAL CHECK OF PTU IN-FLIGHT INHIBITION LOGIC</p>		9 Years

291000-25-1	MAIN AND AUXILIARY HYDRAULIC POWER	Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 291000-710-005 Effectivity : OM-BYA, OM-BYK			9 Years
MAIN AND AUXILIARY HYDRAULIC POWER			
OPERATIONAL CHECK OF PORT D CHECK VALVE OF PTU MANIFOLD IN GREEN AND YELLOW HYDRAULIC SYSTEM			
291900-02-1	MAIN AND AUXILIARY HYDRAULIC POWER	Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 291000-220-002 Effectivity : OM-BYA, OM-BYK Tags : CMR* (NO ESCALATION)			9 Years
MAIN AND AUXILIARY HYDRAULIC POWER			
FUNCTIONAL CHECK TO MONITOR INTERNAL LEAK RATE OF BLUE HYDRAULIC SYSTEM			
292000-07-1	MAIN AND AUXILIARY HYDRAULIC POWER	Threshold	Interval
ATA : 29 Zone : 190 Ref. Doc. : 292200-280-002 Effectivity : OM-BYA, OM-BYK			9 Years
MAIN AND AUXILIARY HYDRAULIC POWER			
FUNCTIONAL CHECK OF ANTI-ICING DEVICE MAGNETS			
293400-01-1	RESERVOIR PRESSURIZATION INDICATING	Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 293400-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
RESERVOIR PRESSURIZATION INDICATING			
OPERATIONAL CHECK OF RESERVOIR LOW AIR PRESSURE WARNING			

302149-C1-1-LH	LH ENGINE AIR INTAKE ICE PROTECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 30	Zone : 438	Ref. Doc. : 302149-200-001		9 Years
Effectivity : OM-BYA, OM-BYK	Tags : ETOPS SIGNIFICANT SYSTEM			

LH ENGINE AIR INTAKE ICE PROTECTION

DETAILED INSPECTION OF LH ENGINE INLET COWL ANTI-ICE SUPPLY DUCTS AND ASSOCIATED HARDWARE IN THE CORE AND FAN COMPARTMENTS.

302149-C1-1-RH	RH ENGINE AIR INTAKE ICE PROTECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 30	Zone : 448	Ref. Doc. : 302149-200-001		9 Years
Effectivity : OM-BYA, OM-BYK	Tags : ETOPS SIGNIFICANT SYSTEM			

RH ENGINE AIR INTAKE ICE PROTECTION

DETAILED INSPECTION OF RH ENGINE INLET COWL ANTI-ICE SUPPLY DUCTS AND ASSOCIATED HARDWARE IN THE CORE AND FAN COMPARTMENTS.

315000-01-1	CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS)	Threshold	Interval
ATA : 31 Zone : 210 Ref. Doc. : 316000-740-005 Effectivity : OM-BYA			9 Years

CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS)

OPERATIONAL CHECK OF CORRECT OPERATION OF PFD-ND AND ECAM-ND MANUAL TRANSFER

315000-02-1 CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS)	Threshold	Interval
ATA : 31 Zone : 210 Ref. Doc. : 316000-710-005 Effectivity : OM-BYA CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS) OPERATIONAL CHECK OF CORRECT OPERATION OF EFIS AND ECAM DMC AUTOMATIC AND MANUAL TRANSFER		9 Years
315000-04-1 CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS)	Threshold	Interval
ATA : 31 Zone : 210 Ref. Doc. : 316000-710-006 Effectivity : OM-BYA CENTRAL WARNING SYSTEMS/ELECTRONIC INSTRUMENT SYSTEM (EIS) OPERATIONAL CHECK OF DMC3 POWER SUPPLY TRANSFER WHEN BUSBAR 101XP IS LOST		9 Years
316000-01-1 ELECTRONIC INSTRUMENT SYSTEM	Threshold	Interval
ATA : 31 Zone : 210 Ref. Doc. : 316000-710-002 Effectivity : OM-BYK ELECTRONIC INSTRUMENT SYSTEM OPERATIONAL CHECK OF EFIS/ECAM SWITCHING FUNCTIONS: - MANUAL DMC 1 + 2 TO DMC 3 SWITCHING - MANUAL PFD/ND TRANSFER - MANUAL ECAM/ND TRANSFER - AUTOMATIC UPPER DU/LOWER DU TRANSFER - AUTOMATIC PFD/ND TRANSFER		9 Years

323100-06-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32 Zone : 210 Ref. Doc. : 326100-710-001 Effectivity : OM-BYA, OM-BYK			9 Years

NORMAL EXTENSION AND RETRACTION

BITE CHECK USING MCDU TO ENSURE "GEAR NOT DOWN FOR LANDING" WARNINGS OPERATIVE

323105-04-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32 Zone : 731, 741 Ref. Doc. : 323100-720-803 Effectivity : OM-BYA, OM-BYK			9 000 Cycles 9 Years

NORMAL EXTENSION AND RETRACTION

FUNCTIONAL CHECK OF THE MLG DOOR ACTUATING CYLINDER.

323105-05-1	NORMAL EXTENSION AND RETRACTION	Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 323100-720-804 Effectivity : OM-BYA, OM-BYK			9 000 Cycles 9 Years

NORMAL EXTENSION AND RETRACTION

FUNCTIONAL CHECK OF THE NLG DOOR ACTUATING CYLINDER.

324000-15-1	WHEELS AND BRAKES	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 32	Zone : 148, 210	Ref. Doc. : 324400-720-002		9 Years
Effectivity : OM-BYA	Tags : ETOPS SIGNIFICANT SYSTEM			

WHEELS AND BRAKES

FUNCTIONAL CHECK TO MONITOR INTERNAL LEAK RATE OF BRAKING SYSTEM COMPONENTS.(PARK BRAKE SELECTOR VALVE, PRESSURE RELIEF VALVE AND ALTERNATE BRAKE SELECTOR VALVE)

ETOPS SIGNIFICANT SYSTEM

PREPARATION NOTE: HYDRAULIC GROUND POWER;

324000-15-2	WHEELS AND BRAKES	Threshold	Interval
ATA : 32	Zone : 148, 210		9 Years
Ref. Doc. : 324400-720-002	Effectivity : OM-BYA		

WHEELS AND BRAKES

FUNCTIONAL CHECK TO MONITOR INTERNAL LEAK RATE OF BRAKING SYSTEM COMPONENTS.(PARK BRAKE SELECTOR VALVE, PRESSURE RELIEF VALVE AND ALTERNATE BRAKE SELECTOR VALVE)

NOTE:
FOR ETOPS: TASK COVERS 324000-15-1.

PREPARATION NOTE: HYDRAULIC GROUND POWER;

324000-17-1	WHEELS AND BRAKES	Threshold	Interval
ATA : 32	Zone : 210, 730, 740		9 Years
Ref. Doc. : 324400-720-002	Effectivity : OM-BYA, OM-BYK		

WHEELS AND BRAKES

FUNCTIONAL CHECK OF BRAKE ACCUMULATOR SYSTEM.

324300-01-1 ALTERNATE BRAKING SYSTEM		Threshold	Interval
ATA : 32 Zone : 210, 730, 740 Ref. Doc. : 324300-710-802 Effectivity : OM-BYK ALTERNATE BRAKING SYSTEM OPERATIONAL CHECK OF ALTERNATE BRAKING SYSTEM NOTE: TASK MAY BE ACCOMPLISHED AT BRAKE CHANGE.			9 Years
324300-01-3 ALTERNATE BRAKING SYSTEM		Threshold	Interval
ATA : 32 Zone : 210, 730, 740 Ref. Doc. : 324300-710-802 Effectivity : OM-BYA ALTERNATE BRAKING SYSTEM OPERATIONAL CHECK OF ALTERNATE BRAKING SYSTEM NOTE: TASK MAY BE ACCOMPLISHED AT BRAKE CHANGE.			9 Years
324300-02-1 ALTERNATE BRAKING SYSTEM		Threshold	Interval
ATA : 32 Zone : 210 Ref. Doc. : 324200-710-003 Effectivity : OM-BYA, OM-BYK ALTERNATE BRAKING SYSTEM OPERATIONAL CHECK OF ANTISKID INHIBITION			6 Years

324500-02-1	PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM	Threshold	Interval
ATA : 32 Zone : 148, 210 Ref. Doc. : 324500-720-002 Effectivity : OM-BYK			9 Years
PARKING/ULTIMATE EMERGENCY BRAKING SYSTEM			
FUNCTIONAL CHECK OF BRAKE ACCUMULATOR SYSTEM WITH THE PARKING BRAKE APPLIED			
335100-12-1	CABIN EMERGENCY LIGHTING	Threshold	Interval
ATA : 33 Zone : 220, 230, 240, 260 Ref. Doc. : 335100-200-801 Effectivity : OM-BYA, OM-BYK			9 Years
CABIN EMERGENCY LIGHTING			
GENERAL VISUAL INSPECTION OF PHOTOLUMINESCENT FLOOR PATH MARKING SYSTEM UNITS			
341300-05-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 341000-710-009 Effectivity : OM-BYA, OM-BYK			9 Years
AIR DATA			
OPERATIONAL CHECK OF THE 5-MINUTE TIME DELAY OF ADIRU 2 AND 3 POWER DISCONNECTION IN EMERGENCY CONFIGURATION			
342200-01-1	STANDBY COMPASS	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 342200-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
STANDBY COMPASS			
OPERATIONAL CHECK OF THE STANDBY COMPASS INCLUDING LIGHT TEST AND VISUAL CHECK			

342200-05-1 STANDBY NAVIGATION SYSTEMS (INCLUDING ISIS)		Threshold	Interval
ATA : 34 Zone : 120 Ref. Doc. : 342225-790-001 Effectivity : OM-BYA, OM-BYK Tags : THIS TASK IS COVERED BY TASK 342200-02-1			9 Years
STANDBY NAVIGATION SYSTEMS (INCLUDING ISIS)			
LOW RANGE LEAK TEST OF STANDBY PNEUMATIC CIRCUITS			
NOTE: PLANNING: - THIS TASK IS COVERED BY TASK 342200-02-1.			
344800-01-1 GROUND PROXIMITY WARNING SYSTEM		Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 344800-710-001 Effectivity : OM-BYA, OM-BYK			9 Years
GROUND PROXIMITY WARNING SYSTEM			
OPERATIONAL CHECK OF GROUND SELF TEST SYSTEM			
522100-01-1 PASSENGER COMPARTMENT EMERGENCY EXIT		Threshold	Interval
ATA : 52 Zone : 151, 152, 241, 242, 833, 834, 843, 844 Ref. Doc. : 522100-710-003 Effectivity : OM-BYA, OM-BYK			9 Years
PASSENGER COMPARTMENT EMERGENCY EXIT			
OPERATIONAL CHECK OF UNLOCKING AND OPENING FROM INSIDE IN ARMED MODE.			
PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;			

525111-08-1	COCKPIT DOOR	Threshold	Interval
ATA : 52 Zone : 220 Ref. Doc. : 525100-710-010 Effectivity : OM-BYA, OM-BYK			9 Years
COCKPIT DOOR			
OPERATIONAL CHECK OF MANUAL RELEASE OF PIP-PINS			

526000-06-1	ENTRANCE STAIRS	Threshold	Interval
ATA : 52 Zone : 129 Ref. Doc. : 526100-710-802 Effectivity : OM-BYA, OM-BYK			9 Years
ENTRANCE STAIRS			
OPERATIONAL CHECK OF AIRSTAIRS CARRIAGE IMMOBILIZATION BY LOCKING MECHANISM AND MOTOR BRAKING CAPABILITY.			

545000-02-1-LH	LH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 410 Ref. Doc. : 545000-200-002 Effectivity : OM-BYA, OM-BYK			9 Years
LH PYLONS			
FLOW CHECK OF INDIVIDUAL DRAIN LINES OF PYLON SYSTEM			

545000-02-1-RH	RH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 420 Ref. Doc. : 545000-200-002 Effectivity : OM-BYA, OM-BYK			9 Years
RH PYLONS			
FLOW CHECK OF INDIVIDUAL DRAIN LINES OF PYLON SYSTEM			

545000-04-1-LH	LH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 410 Ref. Doc. : 545000-220-002 Effectivity : OM-BYA, OM-BYK LH ENGINE PYLONS DETAILED INSPECTION OF PYLON COMPARTMENT C DRAIN SYSTEM. PREPARATION NOTE: LOWER AFT PYLON FAIRING REMOVED;			9 Years

545000-04-1-RH	RH ENGINE PYLONS	Threshold	Interval
ATA : 54 Zone : 420 Ref. Doc. : 545000-220-002 Effectivity : OM-BYA, OM-BYK RH ENGINE PYLONS DETAILED INSPECTION OF PYLON COMPARTMENT C DRAIN SYSTEM. PREPARATION NOTE: LOWER AFT PYLON FAIRING REMOVED;			9 Years

545000-05-1-LH	LH PYLONS	Threshold	Interval
ATA : 54 Zone : 413, 414, 415, 423 Ref. Doc. : 545000-220-807 Effectivity : OM-BYA, OM-BYK LH PYLONS DETAILED INSPECTION OF PYLON FIRE SEALS			9 Years

545000-05-1-RH	RH PYLONS	Threshold	Interval
ATA : 54 Zone : 424, 425, 473, 483 Ref. Doc. : 545000-220-807 Effectivity : OM-BYA, OM-BYK			9 Years
RH PYLONS			
DETAILED INSPECTION OF PYLON FIRE SEALS			

711000-C1-1-LH	LH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 430 Ref. Doc. : 711100-210-041 Effectivity : OM-BYA, OM-BYK			9 Years
LH ENGINE COWLINGS			
GENERAL VISUAL INSPECTION OF AIR INTAKE COWL AFT BULKHEAD			

711000-C1-1-RH	RH ENGINE COWLINGS	Threshold	Interval
ATA : 71 Zone : 440 Ref. Doc. : 711100-210-041 Effectivity : OM-BYA, OM-BYK			9 Years
RH ENGINE COWLINGS			
GENERAL VISUAL INSPECTION OF AIR INTAKE COWL AFT BULKHEAD			

783000-C2-1-LH	LH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 450 Ref. Doc. : 783241-210-042 Effectivity : OM-BYA, OM-BYK			9 Years
LH ENGINE THRUST REVERSER			
GENERAL VISUAL INSPECTION OF BLOCKER DOOR SEALS (BLOCKER DOORS DEPLOYED)			
PREPARATION NOTE: BLOCKER DOORS DEPLOYMENT;			

783000-C2-1-RH	RH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 460 Ref. Doc. : 783241-210-042 Effectivity : OM-BYA, OM-BYK RH ENGINE THRUST REVERSER GENERAL VISUAL INSPECTION OF BLOCKER DOOR SEALS (BLOCKER DOORS DEPLOYED) PREPARATION NOTE: BLOCKER DOORS DEPLOYMENT;			9 Years
783000-C9-1-LH	LH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 400 Ref. Doc. : 783200-210-829 Effectivity : OM-BYA, OM-BYK LH ENGINE THRUST REVERSER DETAILED INSPECTION OF TRU STRUTS.			9 Years
783000-C9-1-RH	RH ENGINE THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 400 Ref. Doc. : 783200-210-829 Effectivity : OM-BYA, OM-BYK RH ENGINE THRUST REVERSER DETAILED INSPECTION OF TRU STRUTS.			9 Years



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

4C CHECK



Category : All Categories		Chapters: All Chapters		Effectivity : All Tasks		Total : 100	
ZL-131-03-1				FORWARD CARGO COMPARTMENT		Threshold	Interval
ATA : 05							12 Years
Zone : 131, 132							
Ref. Doc. : 052130-200-006							
Effectivity : OM-BYA, OM-BYK							
FORWARD CARGO COMPARTMENT							
GENERAL VISUAL INSPECTION OF FORWARD CARGO COMPARTMENT (EWIS)							
PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); CEILING PANELS FROM FR 24 TO FR 34; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SIDEWALL PANELS FROM FR 24 TO FR 34;							
ZL-141-01-1				CENTER WING BOX		Threshold	Interval
ATA : 05							12 Years
Zone : 141, 142							
Ref. Doc. : 052140-200-001							
Effectivity : OM-BYA, OM-BYK							
CENTER WING BOX							
GENERAL VISUAL INSPECTION OF CENTER WING BOX (EWIS)							
ZL-151-03-7				AFT CARGO COMPARTMENT		Threshold	Interval
ATA : 05							12 Years
Zone : 151, 152							
Ref. Doc. : 052150-200-004							
Effectivity : OM-BYA, OM-BYK							
AFT CARGO COMPARTMENT							
GENERAL VISUAL INSPECTION OF AFT CARGO COMPARTMENT (EWIS)							
PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); CEILING PANELS FROM FR 46 TO FR 59; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SIDEWALL PANELS FROM FR 46 TO FR 59;							

ZL-161-03-1	BULK CARGO COMPARTMENT	Threshold	Interval
ATA : 05 Zone : 161, 162 Ref. Doc. : 052160-200-004 Effectivity : OM-BYA, OM-BYK			12 Years
BULK CARGO COMPARTMENT			
GENERAL VISUAL INSPECTION OF BULK CARGO COMPARTMENT (EWIS)			
PREPARATION NOTE: CEILING PANELS FROM FR 59 TO FR 65; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SIDEWALL PANELS FROM FR 59 TO FR 65; ACT(S) REMOVED (IF INSTALLED);			
ZL-211-02-1	COCKPIT	Threshold	Interval
ATA : 05 Zone : 211, 212 Ref. Doc. : 052210-200-002 Effectivity : OM-BYA, OM-BYK			12 Years
COCKPIT			
GENERAL VISUAL INSPECTION OF COCKPIT (EWIS)			
PREPARATION NOTE: INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;			
ZL-221-02-1	FORWARD CABIN UTILITY AREA	Threshold	Interval
ATA : 05 Zone : 221, 222 Ref. Doc. : 052220-200-006 Effectivity : AMM-S 05-22-20-210-801 (OM-BYK) OM-BYA, OM-BYK			12 Years
FORWARD CABIN UTILITY AREA			
GENERAL VISUAL INSPECTION OF FWD CABIN UTILITY AREAS INCLUDING FLOOR STRUCTURE (EWIS)			
PREPARATION NOTE: DOOR FRAME LINING REMOVED; FLOOR PANELS FROM FR 12 TO FR 20; FURNISHINGS FROM FR 12 TO FR 20; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SEATS REMOVED; TOILET REMOVAL/INSTALLATION ;			

ZL-223-01-1 FWD CABIN UTILITY AREA OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 05 Zone : 223, 224 Ref. Doc. : 052220-200-003 Effectivity : AMM-S 05-22-20-210-802 (OM-BYK) OM-BYA, OM-BYK		12 Years

FWD CABIN UTILITY AREA OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF FWD CABIN UTILITY AREA OVERHEAD COMPARTMENT (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 12 TO FR 20; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION;
OVERHEAD STOWAGE COMPARTMENTS REMOVED; TOILET REMOVAL/INSTALLATION ;

ZL-231-01-3 FORWARD PASSENGER COMPARTMENT	Threshold	Interval
ATA : 05 Zone : 231, 232 Ref. Doc. : 052230-200-001 Effectivity : OM-BYA, OM-BYK		12 Years

FORWARD PASSENGER COMPARTMENT

GENERAL VISUAL INSPECTION OF FWD PASSENGER COMPARTMENT (EWIS) (INCLUDING FLOOR STRUCTURE)

PREPARATION NOTE: DOOR FRAME LINING REMOVED; FURNISHING REMOVED; GALLEYS AND TOILETS REMOVED IF INSTALLED; INSULATION TO BE DISPLACED AS
REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SEATS REMOVED; SIDEWALL AND FLOOR PANELS FROM FR 20 TO FR 35 REMOVED;

ZL-233-01-1 FWD PASSENGER OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 05 Zone : 233, 234 Ref. Doc. : 052230-200-003 Effectivity : OM-BYA, OM-BYK		12 Years

FWD PASSENGER OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF FWD PASSENGER OVERHEAD COMPARTMENT (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 20 TO FR 35; GALLEYS AND TOILETS REMOVED IF INSTALLED; INSULATION TO BE DISPLACED AS REQUIRED TO
COMPLETE THE REQUIRED INSPECTION; OVERHEAD STOWAGE COMPARTMENTS REMOVED;

ZL-241-01-3 CENTER PASSENGER COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 241, 242 Ref. Doc. : 052240-200-001 Effectivity : OM-BYA, OM-BYK CENTER PASSENGER COMPARTMENT GENERAL VISUAL INSPECTION OF CENTER PASSENGER COMPARTMENT (EWIS) (INCLUDING FLOOR STRUCTURE) PREPARATION NOTE: GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; FURNISHING, SIDEWALL (EXCEPT EMERGENCY EXIT PANELS) AND FLOOR PANELS FROM FR 35 TO FR 47 REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years
ZL-243-01-1 CENTER PASSENGER OVERHEAD COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 243, 244 Ref. Doc. : 052240-200-003 Effectivity : OM-BYA, OM-BYK CENTER PASSENGER OVERHEAD COMPARTMENT GENERAL VISUAL INSPECTION OF CENTER PASSENGER OVERHEAD COMPARTMENT (EWIS) PREPARATION NOTE: CEILING PANELS FROM FR 35 TO FR 47; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; OVERHEAD STOWAGE COMPARTMENTS REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years
ZL-251-01-3 AFT PASSENGER COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 251, 252 Ref. Doc. : 052250-200-001 Effectivity : OM-BYA, OM-BYK AFT PASSENGER COMPARTMENT GENERAL VISUAL INSPECTION OF AFT PASSENGER COMPARTMENT (EWIS) (INCLUDING FLOOR STRUCTURE) PREPARATION NOTE: GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; FURNISHING, SIDEWALL AND FLOOR PANELS FROM FR 47 TO FR 64 REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years

ZL-253-01-1 AFT PASSENGER OVERHEAD COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 253, 254 Ref. Doc. : 052250-200-003 Effectivity : OM-BYA, OM-BYK AFT PASSENGER OVERHEAD COMPARTMENT GENERAL VISUAL INSPECTION OF AFT PASSENGER OVERHEAD COMPARTMENT (EWIS) PREPARATION NOTE: CEILING PANELS FROM FR 47 TO FR 64; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; OVERHEAD STOWAGE COMPARTMENTS REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years
ZL-261-02-1 AFT CABIN UTILITY AREAS		Threshold	Interval
ATA : 05 Zone : 261, 262 Ref. Doc. : 052260-200-004 Effectivity : OM-BYA, OM-BYK AFT CABIN UTILITY AREAS GENERAL VISUAL INSPECTION OF AFT CABIN UTILITY AREAS INCLUDING FLOOR STRUCTURE (EWIS) PREPARATION NOTE: FLOOR PANELS BETWEEN FR 64 TO 70; FURNISHINGS BETWEEN FR 64 TO 70; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; SEATS REMOVED; SIDEWALL/DOOR FRAME LINING REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years
ZL-263-01-1 AFT CABIN OVERHEAD COMPARTMENT		Threshold	Interval
ATA : 05 Zone : 263, 264 Ref. Doc. : 052260-200-003 Effectivity : OM-BYA, OM-BYK AFT CABIN OVERHEAD COMPARTMENT GENERAL VISUAL INSPECTION OF AFT CABIN OVERHEAD COMPARTMENT (EWIS) PREPARATION NOTE: CEILING PANELS FROM FR 64 TO FR 70; GALLEYS; INSULATION TO BE DISPLACED AS REQUIRED TO COMPLETE THE REQUIRED INSPECTION; OVERHEAD STOWAGE COMPARTMENTS REMOVED; TOILET REMOVAL/INSTALLATION ;			12 Years

ZL-321-01-1 DORSAL FIN		Threshold	Interval
ATA : 05 Zone : 321 Ref. Doc. : 052320-200-001 Effectivity : OM-BYA, OM-BYK DORSAL FIN GENERAL VISUAL INSPECTION OF DORSAL FIN (EWIS)			12 Years
ZL-322-01-1 VERTICAL STABILIZER LEADING EDGE		Threshold	Interval
ATA : 05 Zone : 322 Ref. Doc. : 052320-200-002 Effectivity : OM-BYA, OM-BYK VERTICAL STABILIZER LEADING EDGE GENERAL VISUAL INSPECTION OF VERTICAL STABILIZER LEADING EDGE (EWIS)			12 Years
ZL-323-01-1 VERTICAL STABILIZER SPAR BOX		Threshold	Interval
ATA : 05 Zone : 323 Ref. Doc. : 052320-200-003 Effectivity : OM-BYA, OM-BYK VERTICAL STABILIZER SPAR BOX GENERAL VISUAL INSPECTION OF VERTICAL STABILIZER SPAR BOX (EWIS) PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;			12 Years
ZL-324-01-1 VERTICAL STABILIZER TIP		Threshold	Interval
ATA : 05 Zone : 324 Ref. Doc. : 052320-200-004 Effectivity : OM-BYA, OM-BYK VERTICAL STABILIZER TIP GENERAL VISUAL INSPECTION OF VERTICAL STABILIZER TIP (EWIS)			12 Years

ZL-326-02-1		RUDDER	Threshold	Interval
		ATA : 05 Zone : 326 Ref. Doc. : 052320-200-008 Effectivity : OM-BYA, OM-BYK		12 Years
		RUDDER		
		GENERAL VISUAL INSPECTION OF RUDDER (EWIS)		
		PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;		
ZL-332-01-1		THS TIP	Threshold	Interval
		ATA : 05 Zone : 332, 342 Ref. Doc. : 052330-200-002 Effectivity : OM-BYA, OM-BYK		12 Years
		THS TIP		
		GENERAL VISUAL INSPECTION OF TRIMMABLE HORIZONTAL STABILIZER TIP (EWIS)		
ZL-333-01-1		THS SPAR BOX	Threshold	Interval
		ATA : 05 Zone : 333, 343 Ref. Doc. : 052330-200-003 Effectivity : OM-BYA, OM-BYK		12 Years
		THS SPAR BOX		
		GENERAL VISUAL INSPECTION OF TRIMMABLE HORIZONTAL STABILIZER SPAR BOX (EWIS)		
		PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;		

ZL-540-02-2	LH AND RH WING FUEL TANK	Threshold	Interval
ATA : 05 Zone : 540, 640 Ref. Doc. : 052540-200-004 Effectivity : OM-BYA, OM-BYK Tags : EWIS			12 Years

LH AND RH WING FUEL TANK

GENERAL VISUAL INSPECTION OF WING FUEL TANK (EWIS)

NOTE: ALTERNATIVE COMPLIANCE FOR THE DRY BAY AREA IS SHOWN BY PERFORMING TASKS 572050-02-1, 572050-02-2, 572050-02-4, 572050-02-5 AND 572050-02-6 AT THE SAME TIME. ACCESS PANELS 540/640CZ AND 540/640DZ NEED NOT TO BE REMOVED IN THIS CASE

ZL-550-01-1	LH AND RH WING VENT SURGE TANK	Threshold	Interval
ATA : 05 Zone : 550, 650 Ref. Doc. : 052550-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			12 Years

LH AND RH WING VENT SURGE TANK

GENERAL VISUAL INSPECTION OF VENT SURGE TANK (EWIS)

ZL-560-01-1	LH AND RH WING DRY BAY	Threshold	Interval
ATA : 05 Zone : 560, 660 Ref. Doc. : 052560-200-001 Effectivity : OM-BYA, OM-BYK Tags : EWIS			12 Years

LH AND RH WING DRY BAY

GENERAL VISUAL INSPECTION OF DRY BAY (OUTBOARD) (EWIS)

ZL-811-02-1 FWD AVIONICS COMPARTMENT DOOR		Threshold	Interval
ATA : 05 Zone : 811 Ref. Doc. : 052810-200-002 Effectivity : OM-BYA, OM-BYK FWD AVIONICS COMPARTMENT DOOR GENERAL VISUAL INSPECTION OF FWD AVIONICS COMPARTMENT DOOR (EWIS) PREPARATION NOTE: DOOR PANELS REMOVED;			12 Years
ZL-825-02-1 FWD CARGO COMPARTMENT DOOR		Threshold	Interval
ATA : 05 Zone : 825 Ref. Doc. : 052820-200-004 Effectivity : OM-BYA, OM-BYK FWD CARGO COMPARTMENT DOOR GENERAL VISUAL INSPECTION OF FWD CARGO COMPARTMENT DOOR (EWIS) PREPARATION NOTE: INSULATION REMOVED;			12 Years
ZL-826-02-2 AFT CARGO COMPARTMENT DOOR		Threshold	Interval
ATA : 05 Zone : 826 Ref. Doc. : 052820-200-005 Effectivity : OM-BYA, OM-BYK AFT CARGO COMPARTMENT DOOR GENERAL VISUAL INSPECTION OF AFT CARGO COMPARTMENT DOOR (EWIS) PREPARATION NOTE: INSULATION REMOVED;			12 Years

ZL-831-02-1 FWD AND AFT PASSENGER/CREW DOOR		Threshold	Interval
ATA : 05 Zone : 831, 832, 841, 842 Ref. Doc. : 052830-200-005 Effectivity : OM-BYA, OM-BYK FWD AND AFT PASSENGER/CREW DOOR GENERAL VISUAL INSPECTION OF FWD AND AFT PASSENGER/CREW DOORS (EWIS) PREPARATION NOTE: INSULATION REMOVED;			12 Years
200131-02-1 FORWARD CARGO COMPARTMENT		Threshold	Interval
ATA : 20 Zone : 131, 132 Ref. Doc. : 249200-210-805 Effectivity : OM-BYA, OM-BYK Tags : EWIS			12 Years
FORWARD CARGO COMPARTMENT GENERAL VISUAL INSPECTION OF G, E AND P ROUTES INSTALLED IN THE FORWARD CARGO COMPARTMENT (EWIS) PREPARATION NOTE: SIDEWALL AND CEILING PANELS REMOVED;			
200141-01-1 WING CENTRE BOX		Threshold	Interval
ATA : 20 Zone : 141, 142 Ref. Doc. : 249200-210-026 Effectivity : OM-BYA, OM-BYK Tags : EWIS			12 Years
WING CENTRE BOX GENERAL VISUAL INSPECTION OF EXPOSED EWIS INSTALLED IN THE WING CENTRE BOX (EWIS)			

200151-02-1	AFT CARGO COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 151, 152			
Ref. Doc. : 249200-210-806			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT CARGO COMPARTMENT

GENERAL VISUAL INSPECTION OF P ROUTES INSTALLED IN AFT CARGO COMPARTMENT (EWIS)

PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); CEILING PANELS FROM FR 46 TO FR 59; SIDEWALL PANELS FROM FR 46 TO FR 59;

200171-01-1	AFT CABIN UNDERFLOOR COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 171, 172			
Ref. Doc. : 249200-100-001			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT CABIN UNDERFLOOR COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE AFT CABIN UNDERFLOOR COMPARTMENT (ONLY IF CONTAMINATED)(EWIS)

PREPARATION NOTE: ACT NO.5 REMOVED (IF INSTALLED); CABIN FLOOR PANELS FROM FR 65 TO FR 70;

200211-01-1	COCKPIT	Threshold	Interval
ATA : 20			12 Years
Zone : 211, 212			
Ref. Doc. : 249200-100-016			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

COCKPIT

CLEANING OF EWIS INSTALLED IN THE COCKPIT (ONLY IF CONTAMINATED) (EWIS)

200211-03-1	COCKPIT	Threshold	Interval
ATA : 20			12 Years
Zone : 211, 212			
Ref. Doc. : 249200-210-035			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

COCKPIT

GENERAL VISUAL INSPECTION OF EWIS OF 49VU AND THE 120VU (EWIS)

PREPARATION NOTE: 120VU; 49VU;

200221-01-1	FORWARD CABIN UTILITY AREA	Threshold	Interval
ATA : 20			12 Years
Zone : 221, 222			
Ref. Doc. : 249200-100-007			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD CABIN UTILITY AREA

CLEANING OF EWIS INSTALLED IN THE FORWARD CABIN UTILITY AREA (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: DOOR FRAME LINING REMOVED; FLOOR PANELS FROM FR 12 TO FR 20; FURNISHINGS FROM FR 12 TO FR 20; GALLEYS AND TOILETS REMOVED; SEATS REMOVED;

200223-01-1	FORWARD CABIN OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 223, 224			
Ref. Doc. : 249200-100-010			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD CABIN OVERHEAD COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE FORWARD CABIN OVERHEAD COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 12 TO FR 20; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE COMPARTMENTS REMOVED;

200223-02-1	FORWARD CABIN OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 223, 224			
Ref. Doc. : 249200-210-029			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD CABIN OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF EWIS OF THE 2000VU (EWIS)

PREPARATION NOTE: 2000VU;

200231-01-1	FORWARD PASSENGER COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 231, 232			
Ref. Doc. : 249200-100-002			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD PASSENGER COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE FORWARD PASSENGER COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: DOOR FRAME LINING REMOVED; FURNISHINGS; GALLEYS; SEATS REMOVED; SIDEWALL PANELS FROM FR 20 TO FR 35; TOILET REMOVAL/INSTALLATION ;

200233-01-1	FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 233, 234			
Ref. Doc. : 249200-100-005			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 20 TO FR 35; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE COMPARTMENTS REMOVED;

200233-03-1	FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT	Threshold	Interval
ATA	: 20		12 Years
Zone	: 233, 234		
Ref. Doc.	: 249200-210-810		
Effectivity	: OM-BYA, OM-BYK		
Tags	: EWIS		

FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF ALL G & P ROUTES INSTALLED IN THE FORWARD PASSENGER COMPARTMENT OVERHEAD COMPARTMENT (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 20 TO FR 35; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE COMPARTMENTS REMOVED;

200241-01-1	CENTER PASSENGER COMPARTMENT	Threshold	Interval
ATA	: 20		12 Years
Zone	: 241, 242		
Ref. Doc.	: 249200-100-003		
Effectivity	: OM-BYA, OM-BYK		
Tags	: EWIS		

CENTER PASSENGER COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE CENTER PASSENGER COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: FURNISHINGS; GALLEYS; SEATS REMOVED; SIDEWALL PANELS FROM FR 35 TO FR 47; TOILET REMOVAL/INSTALLATION ;

200241-03-1	CENTER PASSENGER COMPARTMENT	Threshold	Interval
ATA	: 20		12 Years
Zone	: 241, 242		
Ref. Doc.	: 249200-210-031		
Effectivity	: OM-BYA, OM-BYK		
Tags	: EWIS		

CENTER PASSENGER COMPARTMENT

GENERAL VISUAL INSPECTION OF G ROUTES INSTALLED AROUND FR 47/51 (A319)(EWIS)

PREPARATION NOTE: GALLEYS AND TOILETS REMOVED; LINING AT FR 47, RH ONLY;

200243-01-1	CENTER PASSENGER OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 243, 244			
Ref. Doc. : 249200-100-009			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

CENTER PASSENGER OVERHEAD COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE CENTER PASSENGER OVERHEAD COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: CEILING PANELS FROM FR 35 TO FR 47; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE BINS FROM FR 35 TO FR 47;

200243-03-1	CENTER PASSENGER OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 243, 244			
Ref. Doc. : 249200-210-041			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

CENTER PASSENGER OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF G AND P ROUTES INSTALLED IN THE CENTER PASSENGER OVERHEAD COMPARTMENT (EWIS)

PREPARATION NOTE: CEILING PANELS REMOVED; OVERHEAD STOWAGE BINS FROM FR 35 TO FR 47;

200251-02-1	AFT PASSENGER COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 251, 252			
Ref. Doc. : 249200-100-019			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT PASSENGER COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE AFT PASSENGER COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: GALLEYS AND TOILETS REMOVED; SIDEWALL PANELS FROM FR 47 TO FR 64 REMOVED;

200253-01-1	AFT PASSENGER OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 253, 254			
Ref. Doc. : 249200-100-021			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT PASSENGER OVERHEAD COMPARTMENT

CLEANING OF EWIS INSTALLED IN THE AFT PASSENGER OVERHEAD COMPARTMENT (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: CEILING PANELS REMOVED; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE BINS FROM FR 47 TO FR 64 REMOVED;

200253-02-1	AFT PASSENGER OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 253, 254			
Ref. Doc. : 249200-210-042			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT PASSENGER OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF G AND P ROUTES INSTALLED IN THE AFT PASSENGER OVERHEAD COMPARTMENT (EWIS)

PREPARATION NOTE: CEILING PANELS REMOVED; OVERHEAD STOWAGE BINS FROM FR 47 TO FR 64 REMOVED;

200261-01-1	AFT CABIN UTILITY AREA	Threshold	Interval
ATA : 20			12 Years
Zone : 261, 262			
Ref. Doc. : 249200-100-022			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT CABIN UTILITY AREA

CLEANING OF EWIS INSTALLED IN THE AFT CABIN UTILITY AREA (ONLY IF CONTAMINATED) (EWIS)

PREPARATION NOTE: GALLEYS AND TOILETS REMOVED; SEATS REMOVED; SIDEWALL PANELS FROM FR 64 TO FR 70;

200261-02-1 AFT CABIN UTILITY AREA	Threshold	Interval
ATA : 20 Zone : 261, 262 Ref. Doc. : 249200-210-044 Effectivity : OM-BYA Tags : EWIS		12 Years
AFT CABIN UTILITY AREA GENERAL VISUAL INSPECTION OF EWIS CONNECTIONS, ATTACHMENT POINTS AND ELECTRICAL CONNECTORS BETWEEN SEATS AND A/C INSTALLED IN THE AFT CABIN UTILITY AREA (EWIS) NOTE: THIS TASK IS APPLICABLE FOR A/C VERSIONS WITH SEATS AND WITH EWIS CONNECTIONS BETWEEN SEAT AND A/C ONLY		

200263-01-1 AFT CABIN OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20 Zone : 263, 264 Ref. Doc. : 249200-100-023 Effectivity : OM-BYA, OM-BYK Tags : EWIS		12 Years
AFT CABIN OVERHEAD COMPARTMENT CLEANING OF EWIS INSTALLED IN THE AFT CABIN OVERHEAD COMPARTMENT (ONLY IF CONTAMINATED) (EWIS) PREPARATION NOTE: CEILING PANELS REMOVED; GALLEYS AND TOILETS REMOVED; OVERHEAD STOWAGE BINS FROM FR 64 TO FR 70;		

200263-02-1 AFT CABIN OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20 Zone : 263, 264 Ref. Doc. : 249200-210-043 Effectivity : OM-BYA, OM-BYK Tags : EWIS		12 Years
AFT CABIN OVERHEAD COMPARTMENT GENERAL VISUAL INSPECTION OF G AND P ROUTES INSTALLED IN THE AFT CABIN OVERHEAD COMPARTMENT (EWIS) PREPARATION NOTE: CEILING PANELS REMOVED; OVERHEAD STOWAGE BINS FROM FR 64 TO FR 70;		

200263-03-1	AFT CABIN OVERHEAD COMPARTMENT	Threshold	Interval
ATA : 20			12 Years
Zone : 263, 264			
Ref. Doc. : 249200-210-045			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

AFT CABIN OVERHEAD COMPARTMENT

GENERAL VISUAL INSPECTION OF ALL EWIS OF 2001 VU (EWIS)

PREPARATION NOTE: CIRCUIT BREAKER PANEL;

200540-02-1-LH	LH WING FUEL TANK	Threshold	Interval
ATA : 20			12 Years
Zone : 540			
Ref. Doc. : 249200-210-801			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH WING FUEL TANK

GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE WING FUEL TANK (EWIS)

200540-02-1-RH	RH WING FUEL TANK	Threshold	Interval
ATA : 20			12 Years
Zone : 640			
Ref. Doc. : 249200-210-801			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

RH WING FUEL TANK

GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE WING FUEL TANK (EWIS)

200550-01-1-LH	LH WING VENT SURGE TANK	Threshold	Interval
ATA : 20			12 Years
Zone : 550			
Ref. Doc. : 249200-210-802			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH WING VENT SURGE TANK

GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE VENT SURGE TANK (EWIS)

200550-01-1-RH	RH WING VENT SURGE TANK	Threshold	Interval
ATA : 20			12 Years
Zone : 650			
Ref. Doc. : 249200-210-802			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

RH WING VENT SURGE TANK

GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE VENT SURGE TANK (EWIS)

200560-01-1-LH	LH WING DRY BAY (OUTBOARD)	Threshold	Interval
ATA : 20			12 Years
Zone : 560			
Ref. Doc. : 249200-210-803			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			

LH WING DRY BAY (OUTBOARD)

GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE DRY BAY (OUTBOARD) (EWIS)

200560-01-1-RH	RH WING DRY BAY (OUTBOARD)	Threshold	Interval
ATA : 20			12 Years
Zone : 660			
Ref. Doc. :			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
RH WING DRY BAY (OUTBOARD)			
GENERAL VISUAL INSPECTION OF EXPOSED EWIS WITHIN THE DRY BAY (OUTBOARD) (EWIS)			

200571-01-1-LH	LH MLG BAY	Threshold	Interval
ATA : 20			12 Years
Zone : 571			
Ref. Doc. : 249200-210-804			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
LH MLG BAY			
GENERAL VISUAL INSPECTION OF P ROUTE PUMP FEEDER (EWIS)			
PREPARATION NOTE: PUMP WIRING FAIRINGS			

200571-01-1-RH	RH MLG BAY	Threshold	Interval
ATA : 20			12 Years
Zone : 671			
Ref. Doc. : 249200-210-804			
Effectivity : OM-BYA, OM-BYK			
Tags : EWIS			
RH MLG BAY			
GENERAL VISUAL INSPECTION OF P ROUTE PUMP FEEDER (EWIS)			
PREPARATION NOTE: PUMP WIRING FAIRINGS			

212100-02-1-1485-C AIR DISTRIBUTION AND RECIRCULATION		Threshold	Interval
ATA : 21 Zone : 200 Ref. Doc. : AMM-S Effectivity : 21-21-00-210-001 OM-BYK			12 Years
AIR DISTRIBUTION AND RECIRCULATION			
GENERAL VISUAL INSPECTION OF RISER DUCTS IN THE PASSENGER COMPARTMENT			
212641-01-1 AVIONICS EQUIPMENT VENTILATION		Threshold	Interval
ATA : 21 Zone : 128 Ref. Doc. : 212641-210-001 Effectivity : OM-BYA, OM-BYK			12 Years
AVIONICS EQUIPMENT VENTILATION			
DETAILED INSPECTION OF CHECK VALVE FLAPPERS FOR CONDITION AND OPERATION			
215000-02-1 AIR COOLING AND TEMPERATURE CONTROL		Threshold	Interval
ATA : 21 Zone : 130, 190 Ref. Doc. : 215243-210-001 Effectivity : OM-BYA, OM-BYK			12 Years
AIR COOLING AND TEMPERATURE CONTROL			
DETAILED INSPECTION OF PACK AIR CHECK VALVES FLAPPERS FOR CONDITION AND OPERATION			

215200-04-1-1	NO.1 AIR CONDITIONING PACK-CONDENSER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 191	Ref. Doc. : 215200-790-001		12 Years
Effectivity : OM-BYA, OM-BYK	Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
AIR CONDITIONING PACK				
ETOPS SIGNIFICANT SYSTEM				
REMOVE CONDENSER (FIN 10HM2) FOR IN SHOP LEAK CHECK				

215200-04-1-2	NO.2 AIR CONDITIONING PACK-CONDENSER	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 21	Zone : 192	Ref. Doc. : 215200-790-001		12 Years
Effectivity : OM-BYA, OM-BYK	Tags : TCI (NO ESCALATION ALLOWED) ETOPS SIGNIFICANT SYSTEM CRITICAL TASK			
AIR CONDITIONING PACK				
ETOPS SIGNIFICANT ITEM				
REMOVE CONDENSER (FIN 11HM2) FOR IN SHOP LEAK CHECK				

252100-01-1	PASSENGER COMPARTMENT SEATS	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : SSG-EO-043 Effectivity : OM-BYA, OM-BYK			12 Years
PASSENGER COMPARTMENT SEATS			
DETAILED INSPECTION OF SEAT ATTACHMENTS, SEAT STRUCTURE, SEAT BELTS, BUCKLES AND BAGGAGE BAR.			

252200-03-1	CABIN ATTENDANT SEATS	Threshold	Interval
ATA : 25 Zone : 200 Ref. Doc. : 252200-710-801 Effectivity : OM-BYA, OM-BYK			12 Years
CABIN ATTENDANT SEATS			
OPERATIONAL CHECK OF SEAT BELTS (INCLUDING HARNESS ROLL-UP MECHANISM).			

261600-05-1-1	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 130, 150, 160 Ref. Doc. : 261615-100-001 (REMOVAL) Effectivity : 261615-400-001 (INSTALLATION) OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				12 Years
CARGO COMPARTMENT SMOKE DETECTION				
ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY)				
REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING				

261600-05-1-2	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 130, 150, 160 Ref. Doc. : 261615-100-001 (REMOVAL) Effectivity : 261615-400-001 (INSTALLATION) OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				12 Years
CARGO COMPARTMENT SMOKE DETECTION				
ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY)				
REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING				

261600-05-1-3	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 130, 150, 160 Ref. Doc. : 261615-100-001 (REMOVAL) Effectivity : 261615-400-001 (INSTALLATION) OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				12 Years
CARGO COMPARTMENT SMOKE DETECTION				
ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY)				
REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING				

261600-05-1-4	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26 Zone : 130, 150, 160 Ref. Doc. : 261615-100-001 (REMOVAL) Effectivity : 261615-400-001 (INSTALLATION) OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				12 Years
CARGO COMPARTMENT SMOKE DETECTION				
ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY)				
REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING				

261600-05-1-5	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26	CARGO COMPARTMENT SMOKE DETECTION ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY) REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING			12 Years
Zone : 130, 150, 160				
Ref. Doc. : 261615-100-001 (REMOVAL)				
Effectivity : 261615-400-001 (INSTALLATION)				
OM-BYA, OM-BYK				
Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				

261600-05-1-6	CARGO COMPARTMENT SMOKE DETECTION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 26	CARGO COMPARTMENT SMOKE DETECTION ETOPS SIGNIFICANT SYSTEM (INSTALLATION ONLY) REMOVE CARGO COMPARTMENT SMOKE DETECTORS FOR CLEANING REINSTALL CARGO COMPARTMENT SMOKE DETECTORS AFTER CLEANING			12 Years
Zone : 130, 150, 160				
Ref. Doc. : 261615-100-001 (REMOVAL)				
Effectivity : 261615-400-001 (INSTALLATION)				
OM-BYA, OM-BYK				
Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK				

262100-03-1-LH	LH ENGINE FIRE EXTINGUISHING	Threshold	Interval
ATA : 26	LH ENGINE FIRE EXTINGUISHING CHECK FIRING CIRCUIT CONTINUITY		12 Years
Zone : 415			
Ref. Doc. : 262100-720-001			
Effectivity : OM-BYA, OM-BYK			

262100-03-1-RH RH ENGINE FIRE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 425 Ref. Doc. : 262100-720-001 Effectivity : OM-BYA, OM-BYK RH ENGINE FIRE EXTINGUISHING CHECK FIRING CIRCUIT CONTINUITY		12 Years
262100-05-1 ENGINE FIRE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 262100-710-004 Effectivity : OM-BYA, OM-BYK ENGINE FIRE EXTINGUISHING OPERATIONAL CHECK OF FIRE CONTROL PUSH BUTTON SWITCH SUB FUNCTIONS RELATED TO ENGINE SHUTDOWN AND ISOLATION		12 Years
262300-03-1 CARGO COMPARTMENT FIRE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 132, 162, 172 Ref. Doc. : 262300-200-001 Effectivity : Not Effective CARGO COMPARTMENT FIRE EXTINGUISHING CHECK FIRE EXTINGUISHING LINES FOR LEAKAGE AND OBSTRUCTION		12 Years
271400-02-2-LH LH AILERON HYDRAULIC ACTUATION	Threshold	Interval
ATA : 27 Zone : 575 Ref. Doc. : 271400-220-001 Effectivity : OM-BYA, OM-BYK LH AILERON HYDRAULIC ACTUATION CHECK AILERON SERVO CONTROL AND HINGE BEARINGS FOR EXCESSIVE PLAY AND CONDITION		12 Years

272400-02-1 RUDDER HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 325 Ref. Doc. : 272400-200-001 Effectivity : OM-BYA, OM-BYK RUDDER HYDRAULIC ACTUATION CHECK RUDDER SERVOCONTROL AND HINGE BEARINGS FOR EXCESSIVE PLAY AND CONDITION			12 Years
274451-09-1 THS ACTUATOR		Threshold	Interval
ATA : 27 Zone : 310 Ref. Doc. : 274451-610-001 Effectivity : OM-BYA, OM-BYK THS ACTUATOR DRAIN AND REFILL THS ACTUATOR GEARBOX			12 Years
276400-02-1-LH LH SPOILER AND HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 575 Ref. Doc. : 276400-200-001 Effectivity : OM-BYA, OM-BYK LH SPOILER AND HYDRAULIC ACTUATION CHECK LH WING SPOILER SERVOCONTROL BEARING AND HINGE BEARINGS FOR EXCESSIVE PLAY AND CONDITION PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;			12 Years

276400-02-1-RH	RH SPOILER AND HYDRAULIC ACTUATION	Threshold	Interval
ATA : 27 Zone : 675 Ref. Doc. : 276400-200-001 Effectivity : OM-BYA, OM-BYK			12 Years

RH SPOILER AND HYDRAULIC ACTUATION

CHECK RH WING SPOILER SERVOCONTROL BEARING AND HINGE BEARINGS FOR EXCESSIVE PLAY AND CONDITION

PREPARATION NOTE: FLAPS EXTENDED; SLATS FULLY EXTENDED;

281800-03-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28 Zone : 140, 540, 550, 640, 650 Ref. Doc. : 281800-200-002 Effectivity : OM-BYA, OM-BYK			12 Years

IGNITION PREVENTION

DETAILED INSPECTION OF TANK BONDING LEADS (SFAR88)

PREPARATION NOTE: 147AZ

281800-04-1	IGNITION PREVENTION	Threshold	Interval
ATA : 28 Zone : 140, 540, 550, 640, 650 Ref. Doc. : 281844-210-001 Effectivity : OM-BYA, OM-BYK			12 Years

IGNITION PREVENTION

GENERAL VISUAL INSPECTION OF INTERNAL TANK WIRING AND PROBE ATTACHMENTS (SFAR88)

PREPARATION NOTE: 147AZ

281800-06-1 IGNITION PREVENTION		Threshold	Interval
ATA : 28 Zone : 145, 146 Ref. Doc. : 281842-210-001 Effectivity : OM-BYA, OM-BYK IGNITION PREVENTION GENERAL VISUAL INSPECTION OF WIRING HARNESSSES ABOVE CENTER TANK (SFAR88) PREPARATION NOTE: FLOOR PANELS FROM FR 36 TO FR 46;			12 Years
281800-07-1 IGNITION PREVENTION		Threshold	Interval
ATA : 28 Zone : 520, 570, 620, 670 Ref. Doc. : 281841-210-001 Effectivity : OM-BYA, OM-BYK IGNITION PREVENTION GENERAL VISUAL INSPECTION OF WING LEADING EDGE AND TRAILING EDGE ELECTRICAL WIRING AND CONNECTIONS (SFAR88)			12 Years
281800-08-1 IGNITION PREVENTION		Threshold	Interval
ATA : 28 Zone : 540, 640 Ref. Doc. : 281843-210-001 Effectivity : OM-BYA, OM-BYK IGNITION PREVENTION GENERAL VISUAL INSPECTION OF WING FUEL PUMP ELECTRICAL CONNECTIONS AND UNDERWING ELECTRICAL SUPPLY CABLE (SFAR88) PREPARATION NOTE: FUEL PUMP FAIRINGS;			12 Years

281800-09-1	Threshold	Interval
IGNITION PREVENTION ATA : 28 Zone : 140, 540, 640 Ref. Doc. : 281851-210-001 Effectivity : OM-BYA, OM-BYK IGNITION PREVENTION GENERAL VISUAL INSPECTION OF FUEL PUMP CANISTERS (SFAR88)		12 Years
282100-10-1	Threshold	Interval
MAIN FUEL PUMP SYSTEM ATA : 28 Zone : 540, 640 Ref. Doc. : 282100-720-802 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM MAIN FUEL PUMP SYSTEM REMOVE AIR RELEASE VALVE FOR FUNCTIONAL CHECK OF FLOAT PREPERATION NOTE: TANK DEFUELING;		12 Years
282802-01-1	Threshold	Interval
ACT INTERNAL STRUCTURE ATA : 28 Zone : 151, 152 Ref. Doc. : 282800-200-005 Effectivity : OM-BYA, OM-BYK ACT INTERNAL STRUCTURE DETAILED INSPECTION OF ADDITIONAL CENTER TANK (ACT), INTERNAL STRUCTURE NOTE: ACT SERIAL NUMBER TO BE TRACKED, SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT ACCESS PANEL REMOVED; ACT REMOVED; BLADDER TANK REMOVED; INTEGRATED IMPACT WALL REMOVED;		12 Years (+3 Months / -3 Months)

291000-08-1 MAIN HYDRAULIC POWER		Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 291000-720-002 Effectivity : OM-BYA, OM-BYK MAIN HYDRAULIC POWER FUNCTIONAL CHECK OF PRIORITY VALVES IN GREEN, BLUE AND YELLOW SYSTEM			12 Years
323100-03-1 NORMAL EXTENSION AND RETRACTION		Threshold	Interval
ATA : 32 Zone : 210 Ref. Doc. : 323100-710-001 Effectivity : OM-BYA, OM-BYK NORMAL EXTENSION AND RETRACTION OPERATIONAL CHECK OF RETRACTION INHIBITION BAULK			12 Years
323100-04-1 NORMAL EXTENSION AND RETRACTION		Threshold	Interval
ATA : 32 Zone : 210 Ref. Doc. : 323100-710-005 Effectivity : OM-BYA, OM-BYK NORMAL EXTENSION AND RETRACTION OPERATIONAL CHECK TO ENSURE SAFETY VALVE CLOSING AT 260 KNOTS			12 Years
344200-04-1 RADIO ALTIMETER		Threshold	Interval
ATA : 34 Zone : 150 Ref. Doc. : 344200-720-802 Effectivity : OM-BYA, OM-BYK RADIO ALTIMETER DETAILED INSPECTION AND FUNCTIONAL CHECK OF RADIO ALTIMETER ANTENNAS AND COAXIAL CABLES			12 Years

572900-01-1 MISCELLANEOUS (DRAINS) FOR OUTER WING		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 572900-210-002 Effectivity : OM-BYA, OM-BYK MISCELLANEOUS (DRAINS) FOR OUTER WING OPERATIONAL CHECK OF DRAIN HOLES AND HOSES FOR CLOGGING			12 Years
573900-01-1 MISCELLANEOUS (DRAINS) FOR WING TIP		Threshold	Interval
ATA : 57 Zone : 530, 630 Ref. Doc. : 573900-200-002 Effectivity : OM-BYA, OM-BYK MISCELLANEOUS (DRAINS) FOR WING TIP VISUAL CHECK OF DRAIN HOLES FOR CLOGGING			12 Years
575900-01-1 MISCELLANEOUS (DRAINS) FOR LEADING/TRAILING EDGE AND LEADING/TRAILING EDGE DEVICES		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 575900-200-002 Effectivity : OM-BYA, OM-BYK MISCELLANEOUS (DRAINS) FOR LEADING/TRAILING EDGE AND LEADING/TRAILING EDGE DEVICES VISUAL CHECK OF DRAIN HOLES FOR CLOGGING			12 Years

725000-C6-1-LH	LH ENGINE TURBINE SECTION	Threshold	Interval
ATA : 72 Zone : 450 Ref. Doc. : 712212-210-001 Effectivity : OM-BYA, OM-BYK			36 000 Hours 12 Years
LH ENGINE TURBINE SECTION			
SURVEILLANCE INSPECTION OF TURBINE FRAME AFT ENGINE MOUNT LUGS			
NOTE: INTERVAL: - TASK TO BE PERFORMED AT OPPORTUNITY OF ENGINE SHOP VISIT.			
PREPARATION NOTE: ENGINE REMOVED;			

725000-C6-1-RH	RH ENGINE TURBINE SECTION	Threshold	Interval
ATA : 72 Zone : 460 Ref. Doc. : 712212-210-001 Effectivity : OM-BYA, OM-BYK			36 000 Hours 12 Years
RH ENGINE TURBINE SECTION			
SURVEILLANCE INSPECTION OF TURBINE FRAME AFT ENGINE MOUNT LUGS			
NOTE: INTERVAL: - TASK TO BE PERFORMED AT OPPORTUNITY OF ENGINE SHOP VISIT.			
PREPARATION NOTE: ENGINE REMOVED;			



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

5C CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 52

212600-04-1	AVIONICS EQUIPMENT VENTILATION	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 212600-710-004 Effectivity : OM-BYA, OM-BYK			15 Years
AVIONICS EQUIPMENT VENTILATION			
OPERATIONAL CHECK OF DITCHING CONFIGURATION CONTROL CIRCUIT			
213100-03-1	PRESSURE CONTROL AND MONITORING	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 213100-710-004 Effectivity : OM-BYA, OM-BYK			15 Years
PRESSURE CONTROL AND MONITORING			
OPERATIONAL CHECK OF OUTFLOW VALVE CLOSING IN DITCHING CONFIGURATION			
213100-04-1	PRESSURE CONTROL AND MONITORING	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 213100-710-005 Effectivity : OM-BYA, OM-BYK			15 Years
PRESSURE CONTROL AND MONITORING			
OPERATIONAL CHECK OF OUTFLOW VALVE PARTIAL OPENING BY EMERGENCY RAM AIR SWITCH			
PLANNING NOTE : TASK MAY BE COMBINED WITH TASK 215500-01-1.			

215500-01-1	EMERGENCY RAM AIR INLET	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 215500-710-001 Effectivity : OM-BYA, OM-BYK			15 Years
EMERGENCY RAM AIR INLET			
OPERATIONAL CHECK OF EMERGENCY RAM AIR INLET SYSTEM			

215500-02-1	EMERGENCY RAM AIR INLET	Threshold	Interval
ATA : 21 Zone : 210 Ref. Doc. : 215500-710-002 Effectivity : OM-BYA, OM-BYK			15 Years
EMERGENCY RAM AIR INLET			
OPERATIONAL CHECK OF EMERGENCY RAM AIR INLET AND FLOW CONTROL VALVE CLOSING IN DITCHING CONFIGURATION			

221000-01-1	AUTO PILOT/FLIGHT DIRECTOR (AP/FD)	Threshold	Interval
ATA : 22 Zone : 210 Ref. Doc. : 221000-710-002 Effectivity : OM-BYA, OM-BYK			15 Years
AUTO PILOT/FLIGHT DIRECTOR (AP/FD)			
OPERATIONAL CHECK OF AP DISENGAGEMENT AND LOCKING DEVICES OF SIDE STICK CONTROLLER AND RUDDER PEDALS			

235100-01-1	AUDIO MANAGEMENT	Threshold	Interval
ATA : 23 Zone : 210 Ref. Doc. : 235100-710-003 Effectivity : OM-BYA, OM-BYK			15 Years
AUDIO MANAGEMENT			
OPERATIONAL CHECK OF CAPT. AND F/O AUDIO CONTROL PANELS SWITCHING TO THIRD AUDIO CONTROL PANEL			

237100-02-1	COCKPIT VOICE RECORDER	Threshold	Interval
ATA : 23 Zone : 210 Ref. Doc. : 237100-710-002 Effectivity : OM-BYA, OM-BYK COCKPIT VOICE RECORDER OPERATIONAL CHECK OF CVR RECORDING LOGIC INCLUDING TIME DELAY RELAY			15 Years

242400-02-1	AC GENERATION	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 242400-710-002 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM CRITICAL TASK AC GENERATION ETOPS SIGNIFICANT SYSTEM OPERATIONAL CHECK OF EMERGENCY GCU VIA CFDS				15 Years

242600-02-1	AC GENERATION	Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 242600-710-002 Effectivity : OM-BYA, OM-BYK AC GENERATION OPERATIONAL CHECK OF MANUAL AND AUTOMATIC GALLEY AND BUS SHEDDING			15 Years

245100-01-1 AC/DC ELECTRICAL LOAD DISTRIBUTION		Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 242200-710-001 Effectivity : OM-BYA, OM-BYK AC/DC ELECTRICAL LOAD DISTRIBUTION OPERATIONAL CHECK OF GENERATOR LINE CONTACTOR OPENING			15 Years
245100-02-1 AC/DC ELECTRICAL LOAD DISTRIBUTION		Threshold	Interval
ATA : 24 Zone : 210 Ref. Doc. : 245100-710-001 Effectivity : OM-BYA AC/DC ELECTRICAL LOAD DISTRIBUTION OPERATIONAL CHECK OF COMMERCIAL ELECTRIC LOAD SHEDDING			15 Years
255000-60-2 LOWER DECK CARGO LOADING		Threshold	Interval
ATA : 25 Zone : 150 Ref. Doc. : 255000-200-019 Effectivity : OM-BYA, OM-BYK LOWER DECK CARGO LOADING REMOVE XZ-ENDSTOPS AND YZ-LATCHES FOR DETAILED INSPECTION.			15 Years

255000-61-1	LOWER DECK CARGO LOADING	Threshold	Interval
ATA : 25 Zone : 150 Ref. Doc. : 255000-200-020 Effectivity : OM-BYA, OM-BYK			15 Years
LOWER DECK CARGO LOADING			
REMOVE XZ-LATCHES ACT FOR DETAILED INSPECTION			

262200-03-1	APU FIRE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 262200-720-001 Effectivity : OM-BYA, OM-BYK			15 Years
APU FIRE EXTINGUISHING			
CHECK FIRING CIRCUIT CONTINUITY			

262200-04-1	APU FIRE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 313 Ref. Doc. : 262200-210-001 Effectivity : OM-BYA, OM-BYK			15 Years
APU FIRE EXTINGUISHING			
DETAILED INSPECTION OF DISTRIBUTION PIPING AND DISCHARGE NOZZLE			

262200-05-1 APU FIRE EXTINGUISHING		Threshold	Interval
ATA : 26 Zone : 210 Ref. Doc. : 262200-710-003 Effectivity : OM-BYA, OM-BYK APU FIRE EXTINGUISHING OPERATIONAL CHECK OF LOW PRESSURE INDICATING CIRCUIT			15 Years
271400-03-1-LH LH AILERON HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 575 Ref. Doc. : 271400-220-002 Effectivity : OM-BYA, OM-BYK LH AILERON HYDRAULIC ACTUATION CHECK FLUID RESERVE PISTON POSITION WITH HYDRAULIC RESERVOIR DEPRESSURIZED			15 Years
271400-03-1-RH RH AILERON HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 675 Ref. Doc. : 271400-220-002 Effectivity : OM-BYA, OM-BYK RH AILERON HYDRAULIC ACTUATION CHECK FLUID RESERVE PISTON POSITION WITH HYDRAULIC RESERVOIR DEPRESSURIZED			15 Years
272100-04-1 RUDDER MECHANICAL CONTROL		Threshold	Interval
ATA : 27 Zone : 325 Ref. Doc. : 272641-280-001 Effectivity : OM-BYA, OM-BYK RUDDER MECHANICAL CONTROL REMOVE YAW DAMPER SPRING ROD FOR IN SHOP OPERATIONAL CHECK.			15 Years

273400-03-1-LH LH ELEVATOR AND HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 334 Ref. Doc. : 273400-220-001 Effectivity : OM-BYA, OM-BYK LH ELEVATOR AND HYDRAULIC ACTUATION CHECK FLUID RESERVE PISTON POSITION WITH HYDRAULIC RESERVOIR DEPRESSURIZED.			15 Years
273400-03-1-RH RH ELEVATOR AND HYDRAULIC ACTUATION		Threshold	Interval
ATA : 27 Zone : 344 Ref. Doc. : 273400-220-001 Effectivity : OM-BYA, OM-BYK RH ELEVATOR AND HYDRAULIC ACTUATION CHECK FLUID RESERVE PISTON POSITION WITH HYDRAULIC RESERVOIR DEPRESSURIZED.			15 Years
274000-04-1 TRIMMABLE HORIZONTAL STABILIZER		Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 279600-710-006 Effectivity : OM-BYA, OM-BYK TRIMMABLE HORIZONTAL STABILIZER OPERATIONAL CHECK OF THS ACTUATOR WITH ELECTRICAL MOTOR NO 3			15 Years
274000-24-1 TRIMMABLE HORIZONTAL STABILIZER		Threshold	Interval
ATA : 27 Zone : 210 Ref. Doc. : 274400-710-004 Effectivity : OM-BYA, OM-BYK TRIMMABLE HORIZONTAL STABILIZER OPERATIONAL CHECK OF THS ACTUATOR OVERRIDE MECHANISM.			15 Years

274400-03-1	THS ACTUATOR	Threshold	Interval
ATA : 27			15 Years
Zone : 310			
Ref. Doc. : 274451-710-001			
Effectivity : OM-BYA, OM-BYK			
THS ACTUATOR			
OPERATIONAL CHECK OF THS ACTUATOR NO-BACK DEVICE			

282100-02-1	MAIN FUEL PUMP SYSTEM	Threshold	Interval
ATA : 28			15 Years
Zone : 140			
Ref. Doc. : 282100-710-003			
Effectivity : OM-BYA, OM-BYK			
Tags : ETOPS SIGNIFICANT SYSTEM			
MAIN FUEL PUMP SYSTEM			
OPERATIONAL CHECK OF CENTER TANK PUMP CANISTER CHECK VALVES			

282400-02-1	ENGINE LOW PRESSURE SHUT OFF	Threshold	Interval
ATA : 28			15 Years
Zone : 210			
Ref. Doc. : 282400-710-803			
Effectivity : OM-BYA, OM-BYK			
ENGINE LOW PRESSURE SHUT OFF			
OPERATIONAL CHECK OF LP SHUT OFF VALVES INCLUDING OPERATION BY INDIVIDUAL MOTORS			

282800-04-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28			15 Years
Zone : 200			
Ref. Doc. : 282800-710-002			
Effectivity : OM-BYA, OM-BYK			
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
OPERATIONAL CHECK OF MOTOR 1 OF TRANSFER VALVE			
NOTE:			
INTERVAL:			
- IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.			

282800-07-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28			15 Years
Zone : 150			
Ref. Doc. : 282800-720-001			
Effectivity : OM-BYA, OM-BYK			
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
FUNCTIONAL CHECK OF ACT PRESSURE REDUCING VALVE			
NOTE:			
INTERVAL:			
- IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.			

282800-55-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28			15 Years
Zone : 210			
Ref. Doc. : 282800-710-007			
Effectivity : OM-BYA, OM-BYK			
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
OPERATIONAL CHECK OF THE ACT MANUAL TRANSFER SYSTEM			
NOTE:			
- IF NO ACT(S) ARE FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT INSTALLATION.			
- TASK IS INCLUDED IN THE ACT INSTALLATION PROCEDURE.			

291000-10-1 MAIN HYDRAULIC POWER		Threshold	Interval
ATA : 29 Zone : 210 Ref. Doc. : 291000-720-001 Effectivity : OM-BYA, OM-BYK MAIN HYDRAULIC POWER FUNCTIONAL CHECK OF HYDRAULIC FIRE SHUT OFF VALVES NOTE: INTERVAL: - TASK MAY BE PERFORMED AT OPPORTUNITY OF ENGINE REMOVAL PROVIDED INTERVAL NOT EXCEEDED			15 Years
301151-01-2 WING ANTI-ICE CONTROL VALVE		Threshold	Interval
ATA : 30 Zone : 522, 622 Ref. Doc. : 301151-960-001 Effectivity : OM-BYA, OM-BYK Tags : TCI (NO ESCALATION ALLOWED) WING ANTI-ICE CONTROL VALVE REPLACE WING ANTI-ICING FILTER			15 Years
322144-01-1 NOSE LANDING GEAR PARTS		Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 322100-200-012 Effectivity : Not Effective NOSE LANDING GEAR PARTS DETAILED INSPECTION OF NOSE LANDING GEAR, LOCK LINK UPPER AND LOCK LINK LOWER - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.			6 Years

335100-11-1	CABIN EMERGENCY LIGHTING	Threshold	Interval
ATA : 33 Zone : 220 Ref. Doc. : 335100-710-804 Effectivity : OM-BYA, OM-BYK			15 Years
CABIN EMERGENCY LIGHTING			
OPERATIONAL CHECK OF MANUAL EMERGENCY LIGHTING ACTIVATION			

341300-01-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 341300-710-002 Effectivity : OM-BYA, OM-BYK			15 Years
AIR DATA			
OPERATIONAL CHECK OF OVERSPEED WARNING VMO/MMO USING CFDS.			

341300-02-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 341300-710-001 Effectivity : OM-BYA, OM-BYK			15 Years
AIR DATA			
OPERATIONAL CHECK OF AIR DATA SWITCHING FUNCTION			

341300-03-1	AIR DATA	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 341300-710-007 Effectivity : OM-BYA, OM-BYK			15 Years
AIR DATA			
OPERATIONAL CHECK OF OVERSPEED WARNINGS VFE/VLE USING CFDS.			

342000-03-1	STANDBY NAVIGATION SYSTEMS (INCLUDING ISIS)	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 342225-710-001 Effectivity : OM-BYA, OM-BYK			15 Years
STANDBY NAVIGATION SYSTEMS (INCLUDING ISIS)			
OPERATIONAL CHECK OF ISIS DC HOT BUS SUPPLY			

345200-02-1	ATC SYSTEM	Threshold	Interval
ATA : 34 Zone : 210 Ref. Doc. : 345200-720-006 Effectivity : OM-BYA, OM-BYK			15 Years
ATC SYSTEM			
FUNCTIONAL CHECK OF ATC ANTENNAS			

361148-01-1	AIR BLEED DUCTS,WING	[SAFETY CRITICAL TASK]	Threshold	Interval
ATA : 36 Zone : 500, 600 Ref. Doc. : 361148-790-001 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM				15 Years
AIR BLEED DUCTS,WING				
LEAK CHECK ON BLEED AIR DUCTING IN WING AREA BETWEEN BLEED AIR PRECOOLER, WING ANTI ICE VALVE AND WING/FUSELAGE CONNECTION				

361200-02-1 APU BLEED AIR SUPPLY & CROSSBLEED SYST	Threshold	Interval
ATA : 36 Zone : 150, 160, 190, 310 Ref. Doc. : 361200-790-002 Effectivity : OM-BYA, OM-BYK APU BLEED AIR SUPPLY & CROSSBLEED SYST PERFORM LEAK CHECK ON APU BLEED AIR DUCTING (UPSTREAM THE APU BLEED CHECK VALVE) PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;		15 Years
361200-03-1 APU BLEED AIR SUPPLY & CROSSBLEED SYST	Threshold	Interval
ATA : 36 Zone : 191, 192 Ref. Doc. : 361200-790-003 Effectivity : OM-BYA, OM-BYK APU BLEED AIR SUPPLY & CROSSBLEED SYST LEAK CHECK OF BLEED AIR DUCTING IN FUSELAGE AREA BETWEEN APU BLEED CHECK VALVE, AIR CONDITIONING PACK AND WING/FUSELAGE CONNECTION		15 Years
361251-01-1 APU BLEED CHECK VALVE	Threshold	Interval
ATA : 36 Zone : 192 Ref. Doc. : 361251-200-001 Effectivity : Not Effective APU BLEED CHECK VALVE REMOVE AND CHECK AUXILIARY POWER UNIT BLEED CHECK VALVE FOR CONDITION		24 000 Hours 180 Months

361251-01-3	APU BLEED CHECK VALVE	Threshold	Interval
ATA : 36			15 Years
Zone : 192			
Ref. Doc. : 361251-200-001			
Effectivity : OM-BYA, OM-BYK			
Tags : CMR* (NO ESCALATION)			

APU BLEED CHECK VALVE

REMOVE AND CHECK AUXILIARY POWER UNIT BLEED CHECK VALVE FOR CONDITION

522100-02-5	PASSENGER COMPARTMENT EMERGENCY EXIT	Threshold	Interval
ATA : 52			15 Years
Zone : 151, 152, 241, 242, 833, 834, 843, 844			
Ref. Doc. : 522100-720-001			
Effectivity : OM-BYA, OM-BYK			

PASSENGER COMPARTMENT EMERGENCY EXIT

FUNCTIONAL CHECK OF MANUAL AND AUTOMATIC SLIDE RELEASE SIGNAL.

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

522100-07-5	PASSENGER COMPARTMENT EMERGENCY EXIT	Threshold	Interval
ATA : 52			15 Years
Zone : 151, 152, 241, 242, 833, 834, 843, 844			
Ref. Doc. : 522100-710-004			
Effectivity : OM-BYA, OM-BYK			

PASSENGER COMPARTMENT EMERGENCY EXIT

OPERATIONAL CHECK OF UNLOCKING AND OPENING FROM OUTSIDE IN ARMED MODE.

PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;

522100-08-1 PASSENGER COMPARTMENT EMERGENCY EXIT	Threshold	Interval
<p>ATA : 52 Zone : 151, 152, 241, 242, 833, 834, 843, 844 Ref. Doc. : 522100-710-005 Effectivity : OM-BYA, OM-BYK</p> <p>PASSENGER COMPARTMENT EMERGENCY EXIT</p> <p>- OPERATIONAL CHECK OF UNLOCKING AND OPENING FROM INSIDE AND OUTSIDE IN DISARMED POSITION - OPERATIONAL CHECK OF CLOSING AND LOCKING FROM INSIDE - OPERATIONAL CHECK OF ESCAPE SLIDE ARMING AND DISARMING.</p> <p>PREPARATION NOTE: REFER TO AMM FOR ACCESS/PREPARATION;</p>		180 Months
525111-01-1 COCKPIT DOOR	Threshold	Interval
<p>ATA : 52 Zone : 220 Ref. Doc. : 525100-220-001 Effectivity : OM-BYA, OM-BYK</p> <p>COCKPIT DOOR</p> <p>DETAILED INSPECTION OF MECHANICAL PARTS OF DOOR LOCKING SYSTEMS</p>		15 Years
552600-01-1 ELEVATOR ATTACH FITTINGS	Threshold	Interval
<p>ATA : 55 Zone : 335, 345 Ref. Doc. : 552600-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>ELEVATOR ATTACH FITTINGS</p> <p>FUNCTIONAL CHECK OF ELEVATOR HINGE LINE BEARINGS AND ATTACHMENTS FOR EXCESSIVE FREE PLAY AND CONDITION.</p>		15 Years

553600-01-1	RUDDER ATTACH FITTINGS	Threshold	Interval
ATA : 55 Zone : 325 Ref. Doc. : 554600-200-802 Effectivity : OM-BYA, OM-BYK			15 Years
RUDDER ATTACH FITTINGS			
FUNCTIONAL CHECK OF RUDDER HINGE LINE BEARINGS AND ATTACHMENTS FOR EXCESSIVE PLAY AND CONDITION			

783100-C6-1-LH	LH ENGINE THRUST REVERSER CONTROL AND INDICATING	Threshold	Interval
ATA : 78 Zone : 450 Ref. Doc. : 783141-720-040 Effectivity : OM-BYA, OM-BYK			15 Years
LH ENGINE THRUST REVERSER CONTROL AND INDICATING			
OPERATIONAL CHECK OF ACTUATOR SECONDARY LOCK MECHANISM			

783100-C6-1-RH	RH ENGINE THRUST REVERSER CONTROL AND INDICATING	Threshold	Interval
ATA : 78 Zone : 460 Ref. Doc. : 783141-720-040 Effectivity : OM-BYA, OM-BYK			15 Years
RH ENGINE THRUST REVERSER CONTROL AND INDICATING			
OPERATIONAL CHECK OF ACTUATOR SECONDARY LOCK MECHANISM			



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

3 YE STRUCTURAL CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 8

531151-02-1	DOOR STOP FITTINGS	Threshold	Interval
ATA : 53 Zone : 221, 222 Ref. Doc. : 531100-220-825 Effectivity : OM-BYA, OM-BYK			3 Years

DOOR STOP FITTINGS

DETAILED INSPECTION OF DOOR STOP FITTINGS PROTRUDING PART NOT COVERED BY THE LINING ON FRAME 16 AND FRAME 20, LH/RH.

531176-02-1	COCKPIT SIDE WINDOWS FRAMEWORK	Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 531100-210-823 Effectivity : OM-BYA, OM-BYK			3 Years

COCKPIT SIDE WINDOWS FRAMEWORK

GENERAL VISUAL INSPECTION OF COCKPIT SIDE WINDOWS, EXTERNAL VISIBLE PORTION OF FRAMEWORK, BETWEEN FR 4 AND FR 12, LH/RH.

531178-02-1	COCKPIT WINDSHIELD RETAINERS	Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 531100-210-824 Effectivity : OM-BYA, OM-BYK			3 Years

COCKPIT WINDSHIELD RETAINERS

GENERAL VISUAL INSPECTION OF COCKPIT WINDSHIELD, EXTERNAL VISIBLE PORTION OF FRAMEWORK AND EXTERNAL VISIBLE PORTION OF RETAINERS.

531182-02-1 WINDSHIELD SLIDING WINDOW FRAME	Threshold	Interval
<p>ATA : 53 Zone : 211, 212 Ref. Doc. : 531100-220-821 Effectivity : OM-BYA, OM-BYK</p> <p>WINDSHIELD SLIDING WINDOW FRAME</p> <p>DETAILED INSPECTION OF SLIDING WINDOW FRAME, UPPER AND LOWER FRAMES AND FR4 AND FR8 FRAMES, INTERNAL STRUCTURE FROM FR4 TO FR8 LH/RH.</p>		3 Years
534134-02-1 DOOR STOP FITTINGS FR 66 AND 68	Threshold	Interval
<p>ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-220-832 Effectivity : OM-BYA, OM-BYK</p> <p>DOOR STOP FITTINGS FR 66 AND 68</p> <p>DETAILED INSPECTION OF DOOR STOP FITTINGS PROTRUDING PART NOT COVERED BY THE LINING ON FRAME 66 AND FRAME 68, LH/RH.</p>		3 Years
712111-01-3-LH LH ENGINE - FORWARD ENGINE MOUNT	Threshold	Interval
<p>ATA : 71 Zone : 450 Ref. Doc. : 712111-210-040 Effectivity : OM-BYA, OM-BYK</p> <p>LH ENGINE FORWARD ENGINE MOUNT</p> <p>DETAILED INSPECTION OF FORWARD ENGINE MOUNT INSTALLATION</p>		3 Years
712111-01-3-RH RH ENGINE - FORWARD ENGINE MOUNT	Threshold	Interval
<p>ATA : 71 Zone : 460 Ref. Doc. : 712111-210-040 Effectivity : OM-BYA, OM-BYK</p> <p>RH ENGINE FORWARD ENGINE MOUNT</p> <p>DETAILED INSPECTION OF FORWARD ENGINE MOUNT INSTALLATION</p>	9 700 Hours 2 200 Cycles	9 700 Hours 2 200 Cycles 3 Years

712211-03-RH	RH ENGINE - AFT ENGINE MOUNT	Threshold	Interval
ATA : 71			3 Years
Zone : 460			
Ref. Doc. : 712211-210-042			
Effectivity : Not Effective			
RH ENGINE AFT ENGINE MOUNT			
DETAILED INSPECTION OF AFT ENGINE MOUNT INSTALLATION			



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

5 YE STRUCTURAL CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 2

534143-01-1	FUSELAGE INTERNAL STRUCTURE FR 66-68	Threshold	Interval
ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-210-834 Effectivity : OM-BYA, OM-BYK			5 Years

FUSELAGE INTERNAL STRUCTURE FR 66-68

DETAILED INSPECTION OF AFT PASSENGER/CREW DOOR CUTOUT
LOWER CORNERS INTERNAL STRUCTURE, ABOVE CABIN FLOOR
LEVEL, AT FR 66 AND FR 68 FROM STRINGER 22 TO
STRINGER 23 AND AROUND GIRT BAR FITTINGS, LH/RH

PREPARATION NOTE: LINING AND INSULATION REMOVED; GIRT BAR FITTING REMOVED; BLANKING PLATE REMOVED;

534195-01-1	CABIN FLOOR STRUCTURE AFT ENTRANCE AREA	Threshold	Interval
ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-210-835 Effectivity : OM-BYK			5 Years

CABIN FLOOR STRUCTURE AFT ENTRANCE AREA

DETAILED INSPECTION OF CABIN FLOOR STRUCTURE AND STRUCTURE BELOW AFT ENTRANCE AREA; BETWEEN FR 66 AND FR 68 AND LATERAL SHEAR PLATES
BETWEEN FR 68 AND FR 70.

NOTE: IN CASE SUFFICIENT ACCESS TO LATERAL SHEAR WEBS IS NOT POSSIBLE DUE TO GALLEY CONFIGURATION, THE GALLEY MUST BE REMOVED TO GET
ACCESS TO THE INSPECTION AREA.

PREPARATION NOTE: CABIN ATTENDANT SEAT REMOVED; FLOOR PANELS FROM FR 66 TO FR 68; LATERAL GALLEY LINING REMOVED; LOWER DOOR FRAME LINING
REMOVED;



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

6 YE STRUCTURAL CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 194

282801-01-1 ACT 1	ACT No. 1 EXTERNAL SURFACE	Threshold	Interval
ATA : 28 Zone : 152 Ref. Doc. : 282800-200-004 Effectivity : OM-BYA, OM-BYK ACT No. 1 EXTERNAL SURFACE DETAILED INSPECTION OF No. 1 ADDITIONAL CENTER TANK (ACT), EXTERNAL SURFACE NOTE: ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT; INTEGRATED IMPACT WALL REMOVED;			6 Years

282801-01-1 ACT 2	ACT No. 2 EXTERNAL SURFACE	Threshold	Interval
ATA : 28 Zone : 152 Ref. Doc. : 282800-200-004 Effectivity : OM-BYA, OM-BYK ACT No. 2 EXTERNAL SURFACE DETAILED INSPECTION OF No. 2 ADDITIONAL CENTER TANK (ACT), EXTERNAL SURFACE NOTE: ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT; INTEGRATED IMPACT WALL REMOVED;			6 Years

282801-01-1 ACT 3 ACT No. 3 EXTERNAL SURFACE		Threshold	Interval
ATA : 28 Zone : 152 Ref. Doc. : 282800-200-004 Effectivity : OM-BYK ACT No. 3 EXTERNAL SURFACE DETAILED INSPECTION OF No. 3 ADDITIONAL CENTER TANK (ACT), EXTERNAL SURFACE NOTE: ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT; INTEGRATED IMPACT WALL REMOVED;			6 Years
282801-01-1 ACT 4 ACT No.4 EXTERNAL SURFACE		Threshold	Interval
ATA : 28 Zone : 151 Ref. Doc. : 282800-200-004 Effectivity : OM-BYA ACT No. 4 EXTERNAL SURFACE DETAILED INSPECTION OF No. 4 ADDITIONAL CENTER TANK (ACT), EXTERNAL SURFACE NOTE: ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT; INTEGRATED IMPACT WALL REMOVED;			6 Years
282801-01-1 ACT 6 ACT No. 6 EXTERNAL SURFACE		Threshold	Interval
ATA : 28 Zone : 151 Ref. Doc. : 282800-200-004 Effectivity : OM-BYA ACT No. 6 EXTERNAL SURFACE DETAILED INSPECTION OF No. 6 ADDITIONAL CENTER TANK (ACT), EXTERNAL SURFACE NOTE: ACT SERIAL NUMBER TO BE TRACKED SINCE TASK ACCOMPLISHMENT IS A FUNCTION OF ACT AGE AND NOT OF AIRCRAFT AGE PREPARATION NOTE: ACT; INTEGRATED IMPACT WALL REMOVED;			6 Years

321101-01-2-LH	LH MAIN LANDING GEAR	Threshold	Interval
ATA : 32		6 Years	6 Years
Zone : 731			
Ref. Doc. : 321100-200-008			
Effectivity : Not Effective			

LH MAIN LANDING GEAR

DETAILED INSPECTION OF LH MAIN LANDING GEAR, SLIDING TUBE (TWIN WHEEL), BRAKE ATTACHMENT FLANGE, UPPER AND LOWER TORQUE LINKS, UPPER AND LOWER TORQUE LINK PINS AND APEX PIN & NUT - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.

PREPARATION NOTE: AIRCRAFT JACKED, SLIDING TUBE FULLY EXTENDED

321101-01-2-RH	RH MAIN LANDING GEAR	Threshold	Interval
ATA : 32			6 Years
Zone : 741			
Ref. Doc. : 321100-200-008			
Effectivity : Not Effective			

RH MAIN LANDING GEAR

DETAILED INSPECTION OF RH MAIN LANDING GEAR, SLIDING TUBE (TWIN WHEEL), BRAKE ATTACHMENT FLANGE, UPPER AND LOWER TORQUE LINKS, UPPER AND LOWER TORQUE LINK PINS AND APEX PIN & NUT - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.

321103-01-1 LH	LH MAIN LANDING GEAR	Threshold	Interval
ATA : 32			6 Years
Zone : 731			
Ref. Doc. : 321100-200-009			
Effectivity : Not Effective			

LH MAIN LANDING GEAR

DETAILED INSPECTION OF LH MAIN LANDING GEAR, MAIN FITTING, FORWARD PINTLE PIN, FORWARD PINTLE PIN LOCK/ STUB BOLTS, REAR PINTLE PIN & NUT, RETRACTION ACTUATOR ATTACHMENT PINS & UPPER DIAPHRAGM CROSS PIN - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS & BUSH FLANGES.

321103-01-1 RH	RH MAIN LANDING GEAR	Threshold	Interval
ATA : 32 Zone : 741 Ref. Doc. : 321100-200-009 Effectivity : Not Effective			6 Years

RH MAIN LANDING GEAR

DETAILED INSPECTION OF RH MAIN LANDING GEAR, MAIN FITTING, FORWARD PINTLE PIN, FORWARD PINTLE PIN LOCK/ STUB BOLTS, REAR PINTLE PIN & NUT, RETRACTION ACTUATOR ATTACHMENT PINS & UPPER DIAPHRAGM CROSS PIN - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS & BUSH FLANGES.

321146-01-1 LH	LH MAIN LANDING GEAR PARTS	Threshold	Interval
ATA : 32 Zone : 731 Ref. Doc. : 321100-200-018 Effectivity : Not Effective			6 Years

LH MAIN LANDING GEAR PARTS

DETAILED INSPECTION OF LH MAIN LANDING GEAR, RETRACTION ACTUATOR - EXTERNAL SURFACE, EXCEPT WHERE COVERED BY DRESSINGS & BUSH FLANGES.

321146-01-1 RH	RH MAIN LANDING GEAR PARTS	Threshold	Interval
ATA : 32 Zone : 741 Ref. Doc. : 321100-200-018 Effectivity : Not Effective			6 Years

RH MAIN LANDING GEAR PARTS

DETAILED INSPECTION OF RH MAIN LANDING GEAR, RETRACTION ACTUATOR - EXTERNAL SURFACE, EXCEPT WHERE COVERED BY DRESSINGS & BUSH FLANGES.

321156-01-2 LH	LH MAIN LANDING GEAR PARTS	Threshold	Interval
ATA : 32			6 Years
Zone : 731			(+3 Months / -3 Months)
Ref. Doc. : 321100-200-019			
Effectivity : Not Effective			

LH MAIN LANDING GEAR PARTS

DETAILED INSPECTION OF LH MAIN LANDING GEAR, UPPER & LOWER SIDESTAY, UPPER & LOWER CARDANS AND NUTS, UPPER & LOWER LOCK LINKS, LOCKSTAY CARDAN, CUFF, TRIANGULATION LINK, BANANA LINKS, UPPER & LOWER CARDAN PINS, SIDESTAY PIVOT PIN, UPPER PIN (SPRINGS), LOCKSTAY CARDAN PIN, UPPER & LOWER LOCK LINK PINS, LOCK LINK CENTER PIN, TRIANGULATION LINK PINS, LOCK LINK/BANANA LINK PIN, CUFF PINS & LOWER (SPRINGS) PIN - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS, BUSH FLANGES & FITTINGS.

321156-01-2 RH	RH MAIN LANDING GEAR PARTS	Threshold	Interval
ATA : 32			6 Years
Zone : 741			
Ref. Doc. : 321100-200-019			
Effectivity : Not Effective			

RH MAIN LANDING GEAR PARTS

DETAILED INSPECTION OF RH MAIN LANDING GEAR, UPPER & LOWER SIDESTAY, UPPER & LOWER CARDANS AND NUTS, UPPER & LOWER LOCK LINKS, LOCKSTAY CARDAN, CUFF, TRIANGULATION LINK, BANANA LINKS, UPPER & LOWER CARDAN PINS, SIDESTAY PIVOT PIN, UPPER PIN (SPRINGS), LOCKSTAY CARDAN PIN, UPPER & LOWER LOCK LINK PINS, LOCK LINK CENTER PIN, TRIANGULATION LINK PINS, LOCK LINK/BANANA LINK PIN, CUFF PINS & LOWER (SPRINGS) PIN - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS, BUSH FLANGES & FITTINGS.

322141-01-1	NOSE LANDING GEAR PARTS	Threshold	Interval
ATA : 32			6 Years
Zone : 711			
Ref. Doc. : 322100-200-018			
Effectivity : Not Effective			

NOSE LANDING GEAR PARTS

DETAILED INSPECTION OF NOSE LANDING GEAR, BARREL, SLIDING TUBE AND TURNING TUBE EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.

PREPARATION NOTE: AIRCRAFT JACKED, SLIDING TUBE FULLY EXTENDED.;

322142-01-1 NOSE LANDING GEAR PARTS	Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 322100-200-013 Effectivity : Not Effective NOSE LANDING GEAR PARTS DETAILED INSPECTION OF NOSE LANDING GEAR, TORQUE LINKS - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.		6 Years
322143-01-1 NOSE LANDING GEAR PARTS	Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 322100-200-014 Effectivity : Not Effective NOSE LANDING GEAR PARTS DETAILED INSPECTION OF NOSE LANDING GEAR, FORESTAY UPPER PANEL, LOWER LINK AND UNIVERSAL JOINT - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.		6 Years
322145-01-1 NOSE LANDING GEAR PARTS	Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 322100-200-009 Effectivity : Not Effective NOSE LANDING GEAR PARTS DETAILED INSPECTION OF NOSE LANDING GEAR, UPPER BARREL HINGE PINS, FORESTAY BARREL PIN, ACTUATING CYLINDER PINS, RETAINING NUT SHOCK ASSY, TORQUE LINK PINS, TORQUE LINK APEX PIN AND NUT, UPPER PANEL TO STRUCTURE PINS, UPPER PANEL TO UNIVERSAL JOINT PIN, LOCK LINK CENTRE PIN, LOWER LOCK LINK PIN, LOWER LOCK LINK TO UNIVERSAL JOINT PIN AND CROSS PIN - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.		6 Years

322151-01-1 NOSE LANDING GEAR PARTS		Threshold	Interval
ATA : 32 Zone : 711 Ref. Doc. : 322100-200-015 Effectivity : Not Effective			6 Years
NOSE LANDING GEAR PARTS			
DETAILED INSPECTION OF NOSE LANDING GEAR, ACTUATING CYLINDER - EXTERNAL SURFACES, EXCEPT WHERE COVERED BY DRESSINGS AND BUSH FLANGES.			
528101-01-1-RH RH MLG DOOR FWD AND AFT FITTING		Threshold	Interval
ATA : 32 Zone : 744 Ref. Doc. : 528100-200-001 Effectivity : OM-BYA, OM-BYK			6 Years
RH MLG DOOR FWD AND AFT FITTING			
DETAILED INSPECTION OF RH MLG DOOR, FORWARD AND AFT FITTINGS			
521104-01-1 FWD PAX/CREW DOOR INTERNAL STRUCTURE		Threshold	Interval
ATA : 52 Zone : 831, 841 Ref. Doc. : 521100-200-002 Effectivity : OM-BYA, OM-BYK			6 Years
FWD PAX/CREW DOOR INTERNAL STRUCTURE			
DETAILED INSPECTION OF FORWARD PASSENGER/CREW DOOR, INTERNAL STRUCTURE, LH/RH			
PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;			

521304-01-1AFT PAX/CREW DOOR INTERNAL STRUCTURE	Threshold	Interval
<p>ATA : 52 Zone : 832, 842 Ref. Doc. : 521300-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>AFT PAX/CREW DOOR INTERNAL STRUCTURE</p> <p>DETAILED INSPECTION OF AFT PASSENGER/CREW DOOR, INTERNAL STRUCTURE, LH/RH</p> <p>PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;</p>		6 Years
522102-01-4EMERGENCY EXITS STRUCTURE	Threshold	Interval
<p>ATA : 52 Zone : 834, 844 Ref. Doc. : 522100-200-001 Effectivity : OM-BYA, OM-BYK</p> <p>EMERGENCY EXITS STRUCTURE</p> <p>DETAILED INSPECTION OF EMERGENCY EXITS, INTERNAL STRUCTURE AND LOAD TRANSMITTING PROFILE, LH/RH</p> <p>PREPARATION NOTE: LINING AND INSULATION REMOVED;</p>		6 Years
523103-01-1FWD CARGO DOOR INTERNAL STRUCTURE	Threshold	Interval
<p>ATA : 52 Zone : 825 Ref. Doc. : 523111-200-001 Effectivity : OM-BYA, OM-BYK</p> <p>FWD CARGO DOOR INTERNAL STRUCTURE</p> <p>DETAILED INSPECTION OF FORWARD CARGO COMPARTMENT DOOR, INTERNAL STRUCTURE</p> <p>PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;</p>		6 Years

523109-01-1 FWD CARGO DOOR LOCKING HOOKS		Threshold	Interval
ATA : 52 Zone : 825 Ref. Doc. : 523111-200-005 Effectivity : OM-BYA, OM-BYK FWD CARGO DOOR LOCKING HOOKS DETAILED INSPECTION OF LOCKING HOOKS AND FORK FITTINGS OF FORWARD CARGO COMPARTMENT DOOR AT ALL FRAMES, BETWEEN LONGERON 4 AND LONGERON 5 (6 PLACES)			6 Years
523213-01-1 AFT CARGO DOOR INTERNAL STRUCTURE		Threshold	Interval
ATA : 52 Zone : 826 Ref. Doc. : 523211-200-007 Effectivity : OM-BYA, OM-BYK AFT CARGO DOOR INTERNAL STRUCTURE DETAILED INSPECTION OF AFT CARGO COMPARTMENT DOOR, INTERNAL STRUCTURE PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;			6 Years
523219-01-1 AFT CARGO DOOR FITTINGS EXTERNAL AREA		Threshold	Interval
ATA : 52 Zone : 826 Ref. Doc. : 523211-200-009 Effectivity : OM-BYA, OM-BYK AFT CARGO DOOR FITTINGS EXTERNAL AREA DETAILED INSPECTION OF LOCKING HOOKS AND FORK FITTINGS OF AFT CARGO COMPARTMENT DOOR AT ALL FRAMES, BETWEEN LONGERON 4 AND LONGERON 5 (6 PLACES)			6 Years

524121-01-1 AFT AVIONIC DOOR INTERNAL STRUCTURE		Threshold	Interval
ATA : 52 Zone : 824 Ref. Doc. : 524114-200-001 Effectivity : OM-BYA, OM-BYK AFT AVIONIC DOOR INTERNAL STRUCTURE DETAILED INSPECTION OF AFT AVIONICS COMPARTMENT ACCESS DOOR, INTERNAL STRUCTURE			6 Years
524131-01-1 LATERAL RIGHT AVIONIC DOOR		Threshold	Interval
ATA : 52 Zone : 822 Ref. Doc. : 524113-200-001 Effectivity : OM-BYA, OM-BYK LATERAL RIGHT AVIONIC DOOR DETAILED INSPECTION OF LATERAL RIGHT AVIONICS COMPARTMENT ACCESS DOOR, INTERNAL STRUCTURE PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;			6 Years
524141-01-1 LATERAL LEFT AVIONIC DOOR		Threshold	Interval
ATA : 52 Zone : 812 Ref. Doc. : 524112-200-001 Effectivity : OM-BYA, OM-BYK LATERAL LEFT AVIONIC DOOR DETAILED INSPECTION OF LATERAL LEFT AVIONICS COMPARTMENT ACCESS DOOR, INTERNAL STRUCTURE PREPARATION NOTE: LINING REMOVED; INSULATION REMOVED;			6 Years

526101-01-1	ENTRANCE STAIRS DOOR	Threshold	Interval
ATA : 52			6 Years
Zone : 813			
Ref. Doc. : 526100-200-003			
Effectivity : OM-BYA, OM-BYK			
ENTRANCE STAIRS DOOR			
DETAILED INSPECTION OF ENTRANCE STAIRS DOOR, INTERNAL STRUCTURE			

528101-01-1-LH	LH MLG DOOR FWD AND AFT FITTING	Threshold	Interval
ATA : 52			6 Years
Zone : 734			
Ref. Doc. : 528100-200-001			
Effectivity : OM-BYA, OM-BYK			
LH MLG DOOR FWD AND AFT FITTING			
DETAILED INSPECTION OF LH MLG DOOR, FORWARD AND AFT FITTINGS			

528211-01-1	NLG MAIN DOOR HINGES	Threshold	Interval
ATA : 52			6 Years
Zone : 713, 714			
Ref. Doc. : 528200-200-001			
Effectivity : OM-BYA, OM-BYK			
NLG MAIN DOOR HINGES			
DETAILED INSPECTION OF NLG, MAIN DOOR HINGES, LH/RH			

528221-01-1	NLG SECONDARY DOOR HINGES	Threshold	Interval
ATA : 52			6 Years
Zone : 715, 716			
Ref. Doc. : 528200-200-002			
Effectivity : OM-BYA, OM-BYK			
NLG SECONDARY DOOR HINGES			
DETAILED INSPECTION OF NLG, SECONDARY DOOR HINGES, LH/RH			

53-010-060S-1-2550-L	Pressure Bulkhead at FR 35 fwd Face. Detailed visual Inspection of Pressure Bulkhead forward Face at	Threshold	Interval
ATA : 53 Zone : 137, 138 Ref. Doc. : A319-EB53-0244 Effectivity : AMM 533100-210-012 OM-BYA		10 Years	6 Years

Pressure Bulkhead at FR 35 fwd Face.

Detailed visual Inspection of Pressure Bulkhead forward Face at FR 35 and Pressure Deck upper Surface between FR 35 and FR 36, including connections to Center Wing Box at FR 35 and FR 36.

Note 1: Insulation Recirculation Filter, Air Conditioning Ducts and potable Water Tank removed

Note 2: Apply Type 1 grade 2 or 3 temporary protection.

531102-01-3	FWD PAX/CREW DOOR	Threshold	Interval
ATA : 53 Zone : 220 Ref. Doc. : 531100-210-001 Effectivity : OM-BYA, OM-BYK			8 500 Cycles 6 Years

FWD PAX/CREW DOOR

DETAILED INSPECTION OF FORWARD PASSENGER/CREW DOOR FRAME, UPPER CORNERS, EXTERNAL SURFACE, LH/RH

531123-01-1	LAT LAP JOINT FR 01-24	Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : 531100-210-010 Effectivity : Not Effective		6 Years	6 Years

*** TASK DELETED ***

531163-01-1	FWD PAX/CREW DOOR SURROUND	Threshold	Interval
ATA : 53 Zone : 221, 222 Ref. Doc. : 531100-210-019 Effectivity : OM-BYA, OM-BYK		6 Years	6 Years

FWD PAX/CREW DOOR SURROUND

GENERAL VISUAL INSPECTION OF INTERNAL STRUCTURE AROUND FORWARD PASSENGER/CREW DOOR, ABOVE CABIN FLOOR LEVEL, BETWEEN FR 15 AND FR 21 AND BETWEEN STRINGER 8 AND STRINGER 23, LH/RH, EXCLUDING THE LOWER CORNERS OF THE DOOR ENTRANCE AREA AT FR 16 AND FR 20, BETWEEN STRINGER 22 AND 23, LH/RH.

NOTE: EXCLUDED AREA COVERED BY TASK 531166-01-2

PREPARATION NOTE: CEILING PANELS REMOVED; LINING REMOVED; GALLEYS AND TOILETS REMOVED (IF INSTALLED); INSULATION REMOVED;

531164-01-1	FUSELAGE FR 15-21	Threshold	Interval
ATA : 53 Zone : 125, 126 Ref. Doc. : 531100-210-801 Effectivity : OM-BYA, OM-BYK		6 Years	6 Years

FUSELAGE FR 15-21

DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE, BELOW FORWARD PASSENGER/CREW DOOR AND CABIN FLOOR LEVEL, FROM FR 15 TO FR 21 AND BETWEEN STRINGER 28 LH AND STRINGER 28 RH.

PREPARATION NOTE: LEFT HAND SIDE GASKET REMOVED (IF INSTALLED); INSULATION REMOVED;

531166-01-2	FUSELAGE FR 16-20	Threshold	Interval
ATA : 53 Zone : 221, 222 Ref. Doc. : 531100-220-006 Effectivity : OM-BYA, OM-BYK		6 Years	6 Years

FUSELAGE FR 16-20

DETAILED INSPECTION OF FWD PASSENGER/CREW DOOR CUTOUT LOWER CORNERS INTERNAL STRUCTURE ABOVE CABIN FLOOR LEVEL, AT FR 16 AND FR 20 FROM STRINGER 22 TO STRINGER 23 AND AROUND GIRT BAR FITTINGS, LH/RH.

PREPARATION NOTE: GIRT BAR FITTING REMOVED; BLANKING PLATE REMOVED;

531167-01-1 AREA BELOW BATTERIES		Threshold	Interval
ATA : 53 Zone : 126 Ref. Doc. : 531100-210-036 Effectivity : OM-BYA, OM-BYK AREA BELOW BATTERIES DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE, BELOW BATTERIES, BETWEEN FR 10 AND FR 16, RH		6 Years	6 Years
531169-01-1 FUSELAGE FR 12-15		Threshold	Interval
ATA : 53 Zone : 123 124 125 126 Ref. Doc. : 531100-210-804 Effectivity : OM-BYA, OM-BYK FUSELAGE FR 12-15 GENERAL VISUAL INSPECTION OF FUSELAGE INTERNAL STRUCTURE, BELOW GALLEY AND TOILET, BETWEEN FR 12 AND FR 15 AND BETWEEN STRINGER 23 LH AND STRINGER 23 RH, EXCLUDING STRUCTURE FROM FR 12 TO FR 14 UNDER HEAT EXCHANGER PANELS. PREPARATION NOTE: INSULATION REMOVED;		6 Years	6 Years
531171-01-1 NLG SECONDARY DOOR HINGE SUPPORTS		Threshold	Interval
ATA : 53 Zone : 123, 124 Ref. Doc. : 531100-210-020 Effectivity : OM-BYA, OM-BYK NLG SECONDARY DOOR HINGE SUPPORTS DETAILED INSPECTION OF NLG, SECONDARY DOOR HINGE SUPPORTS ON FUSELAGE, LH/RH			6 Years

531176-01-1 COCKPIT SIDE WINDOWS FRAMEWORK	Threshold	Interval
<div>ATA : 53 Zone : 200 Ref. Doc. : 531100-210-041 Effectivity : Not Effective</div> <div>COCKPIT SIDE WINDOWS FRAMEWORK</div> <div>DETAILED INSPECTION OF COCKPIT SIDE WINDOWS, EXTERNAL VISIBLE PORTION OF FRAMEWORK, BETWEEN FR 4 AND FR 12, LH/RH</div>		6 Years
531178-01-1 DELETED BY A319 LUMP REV 49	Threshold	Interval
<div>ATA : 53 Zone : 200 Ref. Doc. : Effectivity : Not Effective</div> <div>DELETED BY A319 LUMP REV 49</div>		6 Years
531181-01-1 FUSELAGE INTL STRUCT FR15-21, STR23-28	Threshold	Interval
<div>ATA : 53 Zone : 129 Ref. Doc. : 531100-210-035 Effectivity : OM-BYA, OM-BYK</div> <div>FUSELAGE INTL STRUCT FR15-21, STR23-28</div> <div>DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE FROM FR15 TO FR21, BETWEEN STRINGER 23 AND STRINGER 28, INCLUDING CABIN CROSSBEAMS, LH/RH.</div> <div>NOTE: TII TPS MAY BE LIMITED TO LOWER SURFACE OF CABIN FLOOR STRUCTURE BETWEEN FR15 AND FR21</div> <div>PREPARATION NOTE: CABIN FLOOR PANELS REMOVED; STAIRS DEPLOYED;</div>		6 Years

531189-01-2	FLOOR STRUCTURE FR 12 TO 21	Threshold	Interval
ATA : 53 Zone : 211, 212, 221, 222, 231, 232 Ref. Doc. : 531100-210-049 Effectivity : OM-BYA, OM-BYK FLOOR STRUCTURE FR 12 TO 21 DETAILED INSPECTION OF CABIN FLOOR STRUCTURE BETWEEN FR 12 AND FR 21 PREPARATION NOTE: CABIN FLOOR PANELS; GALLEYS; TOILET REMOVAL/INSTALLATION ;			6 Years
531194-01-2	FLOOR STRUCTURE FR 21 TO 24	Threshold	Interval
ATA : 53 Zone : 221, 222, 231, 232 Ref. Doc. : 531100-220-003 Effectivity : OM-BYK FLOOR STRUCTURE FR 21 TO 24 DETAILED INSPECTION OF CABIN FLOOR STRUCTURE, BELOW AND 0.5M AROUND GALLEYS AND TOILETS, BETWEEN FR 21 AND FR 24 PREPARATION NOTE: CABIN FLOOR PANELS; GALLEYS; TOILET REMOVAL/INSTALLATION ;		6 Years	6 Years
532105-01-1	FLOOR STRUCTURE FR 24 TO FR 35	Threshold	Interval
ATA : 53 Zone : 231, 232 Ref. Doc. : 532100-220-001 Effectivity : OM-BYA, OM-BYK FLOOR STRUCTURE FR 24 TO FR 35 DETAILED INSPECTION OF CABIN FLOOR STRUCTURE, BELOW AND 0.5M AROUND GALLEYS AND TOILETS, BETWEEN FR 24 AND FR 35 PREPARATION NOTE: CABIN FLOOR PANELS; GALLEYS; TOILET REMOVAL/INSTALLATION ;			6 Years

532137-03-1	FWD CARGO DOOR CUTOUT PANELS	Threshold	Interval
ATA : 53 Zone : 100, 132 Ref. Doc. : 532100-220-819 Effectivity : OM-BYA, OM-BYK			6 Years

FWD CARGO DOOR CUTOUT PANELS

DETAILED INSPECTION OF FORWARD CARGO DOOR CUTOUT PANELS, UPPER AND LOWER CORNERS, EXTERNAL SURFACE.

532170-01-6	FWD CARGO DOOR LOCK FITTINGS AND SURROUNDING STRUCTURE	Threshold	Interval
ATA : 53 Zone : 132 Ref. Doc. : 532100-210-006 Effectivity : OM-BYA, OM-BYK			6 Years

FWD CARGO DOOR LOCK FITTINGS AND SURROUNDING STRUCTURE

GENERAL VISUAL INSPECTION OF FORWARD CARGO DOOR LOCK FITTINGS AND SURROUNDING STRUCTURE, EXTERNAL PORTION

NOTE:
INSPECTION BETWEEN FR 25 AND FR 27A (6 PLACES).

532175-01-1	FWD CARGO DOOR CUT OUT	Threshold	Interval
ATA : 53 Zone : 132 Ref. Doc. : 532100-200-011 Effectivity : OM-BYA, OM-BYK			6 Years

FWD CARGO DOOR CUT OUT

DETAILED INSPECTION OF INTERNAL STRUCTURE AROUND FORWARD CARGO DOOR CUTOUT, FROM FR 24 TO FR 29 AND BETWEEN STRINGER 23 AND STRINGER 38, RH

PREPARATION NOTE: CARGO FLOOR PANELS REMOVED; FWD ACT(S) REMOVED (IF INSTALLED); LINING AND INSULATION REMOVED;

532180-01-2	FUSELAGE FR 24-35	Threshold	Interval
ATA : 53 Zone : 133, 134, 137, 138 Ref. Doc. : 532100-200-013 Effectivity : OM-BYA, OM-BYK FUSELAGE FR 24-35 DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE INCLUDING FORWARD FACE OF PRESSURE BULKHEAD, FROM STRINGER 38 LH/RH TO BOTTOM CENTERLINE NOTE: INSPECTION BETWEEN FR 24 AND FR 35. TYPE 2 TPS MAY BE LIMITED TO FUSELAGE INTERNAL STRUCTURE FROM FR 34 TO FR 35, AND FORWARD FACE OF PRESSURE BULKHEAD, FROM STRINGER 38, LH/RH TO BOTTOM CENTERLINE. PREPARATION NOTE: CARGO FLOOR PANELS REMOVED; FWD ACT(S) REMOVED (IF INSTALLED);			6 Years

533105-01-6-LH	LH MLG BAY SIDE PANELS	Threshold	Interval
ATA : 53 Zone : 147 Ref. Doc. : 533100-210-003 Effectivity : OM-BYA, OM-BYK LH MLG BAY SIDE PANELS DETAILED INSPECTION OF LH MLG BAY FUSELAGE SIDE PANELS INSIDE MLG BAY, BETWEEN FR 42 AND FR 46, INCLUDING SLANTED FRAMES AND SIDE BOX, LH		56 400 Hours 13 100 Cycles	38 700 Hours 9 000 Cycles 6 Years

533105-01-6-RH	RH MLG BAY SIDE PANELS	Threshold	Interval
ATA : 53 Zone : 148 Ref. Doc. : 533100-210-003 Effectivity : OM-BYA, OM-BYK RH MLG BAY SIDE PANELS DETAILED INSPECTION OF RH MLG BAY FUSELAGE SIDE PANELS INSIDE MLG BAY, BETWEEN FR 42 AND FR 46, INCLUDING SLANTED FRAMES AND SIDE BOX			38 700 Hours 9 000 Cycles 6 Years

533111-01-5 PRESSURE DECK MEMBRANES LWR SURFACE	Threshold	Interval
ATA : 53 Zone : 147, 148 Ref. Doc. : 533100-210-006 Effectivity : OM-BYA, OM-BYK PRESSURE DECK MEMBRANES LWR SURFACE DETAILED INSPECTION OF LOWER SURFACE OF PRESSURE DECK MEMBRANES, BETWEEN FR 42 AND FR 46, INCLUDING CONNECTIONS TO LONGITUDINAL BEAMS, SIDE BOXES, SUPPORT RIBS, REAR SPAR OF CENTER WING BOX AND PRESSURE BULKHEAD, LH/RH		6 Years
533129-01-2 EMERGENCY EXIT CUTOUTS	Threshold	Interval
ATA : 53 Zone : 241, 242 Ref. Doc. : 533100-210-009 Effectivity : OM-BYA, OM-BYK EMERGENCY EXIT CUTOUTS DETAILED INSPECTION OF INTERNAL STRUCTURE AROUND EMERGENCY EXIT CUTOUTS, BETWEEN FR 39 AND FR 41, BOTH SIDES, FROM STRINGER 10 TO STRINGER 23, LH/RH PREPARATION NOTE: CABIN AIR OUTLET ASSEMBLY; LINING REMOVED; RISER DUCT; INSULATION REMOVED;		6 Years
533135-01-2-1485-A FLOOR STRUCTURE FR 64 TO FR 70	Threshold	Interval
ATA : 53 Zone : 146 Ref. Doc. : AMM-S Effectivity : 53-31-35-220-801 OM-BYK FLOOR STRUCTURE FR 64 TO FR 70 DETAILED VISUAL INSPECTION OF CABIN FLOOR STRUCTURE BELOW AND 0.5M AROUND LAVATORIES AND GALLEY BETWEEN FR 64 AND FR 70. NOTE 1: APPLY TYPE I TEMPORARY PROTECTION PLUS A SUBSEQUENT APPLICATION OF TYPE II TEMPORARY PROTECTION. PREPARATION NOTE: CABIN FLOOR PANELS, GALLEY, AND TOILETS REMOVED.	6 Years	6 Years (+3 Months / -3 Months)

533136-01-1-LH	MAIN LANDING GEAR BAY	Threshold	Interval
ATA : 53 Zone : 147 Ref. Doc. : 533100-210-023 Effectivity : OM-BYA, OM-BYK			6 Years
LH MAIN LANDING GEAR BAY			
GENERAL VISUAL INSPECTION OF LH MLG BAY			

533136-01-1-RH	RH MAIN LANDING GEAR BAY	Threshold	Interval
ATA : 53 Zone : 148 Ref. Doc. : 533100-210-023 Effectivity : OM-BYA, OM-BYK			6 Years
RH MAIN LANDING GEAR BAY			
GENERAL VISUAL INSPECTION OF RH MLG BAY			

533152-01-1	PRESSURE BULKHEAD AT FR 35 FWD FACE	Threshold	Interval
ATA : 53 Zone : 137, 138 Ref. Doc. : 533100-210-012 Effectivity : OM-BYA, OM-BYK			6 Years
PRESSURE BULKHEAD AT FR 35 FWD FACE			
DETAILED INSPECTION OF PRESSURE BULKHEAD FORWARD FACE			
NOTE: INSPECTION AT FR 35 AND PRESSURE DECK UPPER SURFACE, BETWEEN FR 35 AND FR 36, INCLUDING CONNECTIONS TO CENTER WING BOX AT FR 35 AND FR 36.			
PREPARATION NOTE: AIR DUCT; INSULATION REMOVED; RECIRCULATION FILTER REMOVED;			

533154-01-1-RH	RH MLG DOORS FITTINGS	Threshold	Interval
ATA : 53 Zone : 148 Ref. Doc. : 533100-210-014 Effectivity : OM-BYA, OM-BYK			6 Years
RH MLG DOORS FITTINGS			
DETAILED INSPECTION OF HINGE AND ACTUATOR FITTINGS FOR RH MLG DOORS AT KEELBEAM			

534107-01-1	FUSELAGE INTERNAL STRUCTURE FR 46-65	Threshold	Interval
ATA : 53 Zone : 153, 154, 163, 164 Ref. Doc. : 534100-210-014 Effectivity : OM-BYA, OM-BYK			6 Years
FUSELAGE INTERNAL STRUCTURE FR 46-65			
DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE, BETWEEN FR 46 AND FR 65, INCLUDING AFT FACE OF PRESSURE BULKHEAD FROM STRINGER 38, LH/RH TO BOTTOM CENTER LINE.			
NOTE: CREDIT CAN BE TAKEN FROM PREVIOUS ACCOMPLISHMENT OF TASK 534107-01-4.			
PREPARATION NOTE: CARGO FLOOR PANELS REMOVED; ACT(S) REMOVED (IF INSTALLED);			

534132-02-1	AFT PAX/CREW DOOR CUTOUT UPR CORNER	Threshold	Interval
ATA : 53 Zone : 260 Ref. Doc. : 534100-220-833 Effectivity : OM-BYA, OM-BYK			6 Years
AFT PAX/CREW DOOR CUTOUT UPR CORNER			
DETAILED INSPECTION OF AFT PASSENGER/CREW DOOR CUTOUT, UPPER CORNERS, INCLUDING SKIN AND INTERNALLY THE VISIBLE PORTION OF THE INTERNAL DOUBLER LH/RH.			

534135-01-4 AFT PAX/CREW DOOR CUTOUT	Threshold	Interval
<p>ATA : 53 Zone : 261, 262, 263, 264 Ref. Doc. : 534100-210-003 Effectivity : OM-BYA, OM-BYK</p> <p>AFT PAX/CREW DOOR CUTOUT</p> <p>GENERAL VISUAL INSPECTION OF INTERNAL STRUCTURE AROUND AFT PASSENGER/CREW DOOR CUTOUT, ABOVE CABIN FLOOR LEVEL, BETWEEN FR 65 AND FR 69 AND FROM STRINGER 6 TO STRINGER 23, LH/RH, EXCLUDING THE LOWER CORNERS OF THE DOOR ENTRANCE AREA AT FR 66 AND FR 68, BETWEEN STRINGER 22 AND 23, LH/RH</p> <p>NOTE: EXCLUDED AREA COVERED BY TASKS 534143-01-1 OR 534143-01-3.</p> <p>PREPARATION NOTE: LINING AND INSULATION REMOVED;</p>		6 Years
534143-01-3 FUSELAGE INTERNAL STRUCTURE FR 66-68	Threshold	Interval
<p>ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-210-834 Effectivity : Not Effective</p> <p>FUSELAGE INTERNAL STRUCTURE FR 66-68</p> <p>DETAILED INSPECTION OF AFT PASSENGER/CREW DOOR CUTOUT LOWER CORNERS INTERNAL STRUCTURE, ABOVE CABIN FLOOR LEVEL, AT FR 66 AND FR 68 FROM STRINGER 22 TO STRINGER 23 AND AROUND GIRT BAR FITTINGS, LH/RH</p> <p>PREPARATION NOTE: LINING AND INSULATION REMOVED; GIRT BAR FITTING REMOVED; BLANKING PLATE REMOVED;</p>	6 Years	6 Years (+3 Months / -3 Months)
534144-01-1 FUSELAGE INTERNAL STRUCTURE FR 65-70	Threshold	Interval
<p>ATA : 53 Zone : 171, 172 Ref. Doc. : 534100-210-030 Effectivity : OM-BYA, OM-BYK</p> <p>FUSELAGE INTERNAL STRUCTURE FR 65-70</p> <p>DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE, BELOW CABIN FLOOR PANELS INCLUDING FLOOR STRUCTURE, FROM FR 65 TO FR 70</p> <p>PREPARATION NOTE: INSULATION REMOVED;</p>		6 Years

534147-01-2 FLOOR STRUCTURE FR 47/51 TO 70	Threshold	Interval
<p>ATA : 53 Zone : 251, 252, 261, 262 Ref. Doc. : 534100-210-037 Effectivity : OM-BYA, OM-BYK</p> <p>FLOOR STRUCTURE FR 47/51 TO 70</p> <p>DETAILED INSPECTION OF CABIN FLOOR STRUCTURE, BELOW AND 0.5M AROUND GALLEYS AND TOILETS</p> <p>NOTE: - INSPECTION FROM FR 47/51 TO FR 70, EXCEPT AREA BETWEEN FR 66 AND FR 68 AND LATERAL SHEAR PLATES BETWEEN FR 68 AND FR 70.</p> <p>PREPARATION NOTE: CABIN FLOOR PANELS; GALLEYS; TOILET REMOVAL/INSTALLATION;</p>		6 Years
534148-01-3 FUSELAGE UNDER BELLY FAIRING	Threshold	Interval
<p>ATA : 53 Zone : 190 Ref. Doc. : 534100-210-802 Effectivity : OM-BYA, OM-BYK</p> <p>FUSELAGE UNDER BELLY FAIRING</p> <p>FUSELAGE UNDER BELLY FAIRING</p> <p>GENERAL VISUAL INSPECTION OF FUSELAGE EXTERNAL SURFACE</p> <p>PREPARATION NOTE: BELLY FAIRING;</p>		6 Years
534150-01-2 AFT CARGO DOOR CUTOUT	Threshold	Interval
<p>ATA : 53 Zone : 152, 162 Ref. Doc. : 534100-210-004 Effectivity : OM-BYA, OM-BYK</p> <p>AFT CARGO DOOR CUTOUT</p> <p>DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE AROUND AFT CARGO DOOR CUTOUT</p> <p>NOTE: INSPECTION FROM FR 55 TO FR 60 AND BETWEEN STRINGER 23 AND STRINGER 38.</p> <p>PREPARATION NOTE: REAR ACT REMOVED (IF INSTALLED); INSULATION REMOVED;</p>		6 Years

534159-02-1AFT CARGO DOOR CUTOUT UPR/LWR CORNERS	Threshold	Interval
<div data-bbox="208 156 584 284">ATA : 53 Zone : 152, 154, 252 Ref. Doc. : 534100-210-031 Effectivity : OM-BYA, OM-BYK</div> <div data-bbox="208 316 779 339">AFT CARGO DOOR CUTOUT UPR/LWR CORNERS</div> <div data-bbox="208 368 1485 392">DETAILED INSPECTION OF AFT CARGO DOOR CUTOUT UPPER AND LOWER CORNERS, EXTERNAL SURFACE.</div>		6 Years
534195-01-2CABIN FLOOR STRUCTURE AFT ENTRANCE AREA	Threshold	Interval
<div data-bbox="208 528 557 655">ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-210-835 Effectivity : OM-BYA</div> <div data-bbox="208 687 788 711">CABIN FLOOR STRUCTURE AFT ENTRANCE AREA</div> <div data-bbox="208 740 2101 796">DETAILED INSPECTION OF CABIN FLOOR STRUCTURE AND STRUCTURE BELOW AFT ENTRANCE AREA; BETWEEN FR 66 AND FR 68 AND LATERAL SHEAR PLATES BETWEEN FR 68 AND FR 70.</div>		6 Years
535101-01-1REAR PRESSURE BULKHEAD AFT FACE	Threshold	Interval
<div data-bbox="208 903 584 1031">ATA : 53 Zone : 311, 312 Ref. Doc. : 535100-210-001 Effectivity : OM-BYA, OM-BYK</div> <div data-bbox="208 1062 672 1086">REAR PRESSURE BULKHEAD AFT FACE</div> <div data-bbox="208 1115 2166 1171">DETAILED INSPECTION OF REAR PRESSURE BULKHEAD COMPLETE AFT FACE, AND FUSELAGE INTERNAL STRUCTURE, BETWEEN FR 70 AND FR 71, FROM STRINGER 26, LH/RH TO BOTTOM CENTER LINE</div> <div data-bbox="208 1200 2136 1256">NOTE: TPS MAY BE LIMITED TO FUSELAGE INTERNAL STRUCTURE FROM FR 70 TO FR 71, AND AFT FACE OF PRESSURE BULKHEAD, FROM STRINGER 26, LH/RH TO BOTTOM CENTERLINE</div> <div data-bbox="208 1279 721 1303">PREPARATION NOTE: PROTECTIVE SHIELD;</div>		6 Years

551010-01-1 THS SUPPORT AND ATTACH FITTINGS	Threshold	Interval
<p>ATA : 55 Zone : 333, 343 Ref. Doc. : 551600-200-001 Effectivity : OM-BYA, OM-BYK</p> <p>THS SUPPORT AND ATTACH FITTINGS</p> <p>DETAILED INSPECTION OF HORIZONTAL STABILIZER, REAR SUPPORT FITTINGS, UPPER AND LOWER ATTACH FITTINGS AND SURROUNDING EXTERNAL STRUCTURE, LH/RH</p>		6 Years
551020-01-1 ELEVATOR HINGE SUPPORTS AND FITTINGS	Threshold	Interval
<p>ATA : 55 Zone : 334, 344 Ref. Doc. : 551600-200-004 Effectivity : OM-BYA, OM-BYK</p> <p>ELEVATOR HINGE SUPPORTS AND FITTINGS</p> <p>DETAILED INSPECTION OF HORIZONTAL STABILIZER, HINGE FITTINGS, SUPPORT RIBS AND ACTUATOR FITTINGS FOR THE ELEVATOR AND Y LOAD FITTINGS, LH/RH</p>		6 Years
552002-01-1 ELEVATOR HINGE SUPPORT AND ACT. FTG.	Threshold	Interval
<p>ATA : 55 Zone : 335, 345 Ref. Doc. : 552000-200-003 Effectivity : OM-BYA, OM-BYK</p> <p>ELEVATOR HINGE SUPPORT AND ACT. FTG.</p> <p>DETAILED INSPECTION OF ELEVATOR, HINGE FITTINGS AND ACTUATOR FITTINGS, LH/RH</p>		6 Years
553004-01-1 VERT STABILIZER ATTACH FITTINGS	Threshold	Interval
<p>ATA : 55 Zone : 323 Ref. Doc. : 553600-210-001 Effectivity : OM-BYA, OM-BYK</p> <p>VERT STABILIZER ATTACH FITTINGS</p> <p>DETAILED INSPECTION OF VERTICAL STABILIZER, ATTACH FITTINGS, INCLUDING LOAD INTRODUCTION AREA AT SKIN PANELS</p>		6 Years

553005-01-1 RUDDER HINGE ARMS AND ACTUATOR		Threshold	Interval
ATA : 55 Zone : 325 Ref. Doc. : 553000-210-001 Effectivity : OM-BYA, OM-BYK RUDDER HINGE ARMS AND ACTUATOR DETAILED INSPECTION OF RUDDER HINGE ARM 1,2,3,4 AND 5 AND FIN ACTUATOR FITTINGS (ACTUATOR 1, 2 AND 3)			6 Years
553006-01-1 RUDDER HINGE ARM 6 AND 7		Threshold	Interval
ATA : 55 Zone : 325 Ref. Doc. : 553000-210-002 Effectivity : OM-BYK RUDDER HINGE ARM 6 AND 7 DETAILED INSPECTION OF RUDDER HINGE ARM 6 AND 7			6 Years
554003-01-1 RUDDER SIDE PANELS		Threshold	Interval
ATA : 55 Zone : 300 Ref. Doc. : 554000-210-001 Effectivity : OM-BYA, OM-BYK RUDDER SIDE PANELS SPECIAL DETAILED INSPECTION (US) OF RUDDER SIDE PANELS, IN AREA OF RUDDER BEARINGS, IN THE BOOSTER AREA AND AROUND TRAILING EDGE FASTENERS AND HOISTING POINTS, LH/RH.			6 Years

554005-01-1	RUDDER FITTINGS,ACT. ATTACH FITTINGS	Threshold	Interval
ATA : 55 Zone : 326 Ref. Doc. : 554000-210-004 Effectivity : OM-BYA, OM-BYK			6 Years
RUDDER FITTINGS,ACT. ATTACH FITTINGS			
DETAILED INSPECTION OF RUDDER ATTACH FITTING 1,2,3,4 AND 5 AND RUDDER ACTUATOR ATTACH FITTINGS (ACTUATOR 1, 2 AND 3)			
554006-01-1	RUDDER ATTACH FITTING 6 AND 7	Threshold	Interval
ATA : 55 Zone : 326 Ref. Doc. : 554000-210-005 Effectivity : OM-BYA, OM-BYK			6 Years
RUDDER ATTACH FITTING 6 AND 7			
DETAILED INSPECTION OF RUDDER ATTACH FITTING 6 AND 7			
554008-01-1	RUDDER SIDE PANELS	Threshold	Interval
ATA : 55 Zone : 300 Ref. Doc. : 554000-220-001 Effectivity : OM-BYA, OM-BYK			6 Years
RUDDER SIDE PANELS			
SPECIAL DETAILED INSPECTION (THERMOGRAPHIC) OF THE HONEYCOMB CORE OF THE RUDDER SIDE PANELS, LH / RH.			

554009-01-1 RUDDER SIDE PANELS	Threshold	Interval
ATA : 55 Zone : 300 Ref. Doc. : 554000-210-006 Effectivity : OM-BYA, OM-BYK RUDDER SIDE PANELS SPECIAL DETAILED INSPECTION (ELCH TEST) OF THE BONDING LAYERS BETWEEN RUDDER SIDE PANEL HONEYCOMB STRUCTURE AND EXTERNAL SKINS OF THE RUDDER SIDE PANELS, LH / RH.		6 Years
562101-01-1 WINDOW PANES	Threshold	Interval
ATA : 56 Zone : 221, 222, 231, 232, 241, 242, 251, 252, 261, 262 Ref. Doc. : 562113-200-001 Effectivity : OM-BYA, OM-BYK WINDOW PANES DETAILED INSPECTION OF CABIN WINDOW PANES, INCLUDING WINDOW PANES IN DOORS		6 Years
571122-01-1 CENTER WING BOX REAR SPAR	Threshold	Interval
ATA : 57 Zone : 147, 148 Ref. Doc. : 571000-200-012 Effectivity : OM-BYA, OM-BYK CENTER WING BOX REAR SPAR DETAILED INSPECTION OF CENTER WING BOX, REAR SPAR AFT FACE		6 Years
572001-01-1-LH OUTER WING FRONT SPAR FWD FACE	Threshold	Interval
ATA : 57 Zone : 521 Ref. Doc. : 572000-220-004 Effectivity : OM-BYA, OM-BYK LH OUTER WING FRONT SPAR FWD FACE DETAILED INSPECTION OF LH OUTER WING, FRONT SPAR FORWARD FACE, BETWEEN RIB 1 AND RIB 8, INCLUDING VICINITY OF CUTOUTS FOR SLAT TRACKS 1,2,3 AND 4		6 Years

572001-01-1-RH	RH OUTER WING FRONT SPAR FWD FACE	Threshold	Interval
ATA : 57 Zone : 621 Ref. Doc. : 572000-220-004 Effectivity : OM-BYA, OM-BYK			6 Years
RH OUTER WING FRONT SPAR FWD FACE			
DETAILED INSPECTION OF RH OUTER WING, FRONT SPAR FORWARD FACE, BETWEEN RIB 1 AND RIB 8, INCLUDING VICINITY OF CUTOUTS FOR SLAT TRACKS 1,2,3 AND 4			

572007-01-6-LH	LH OUTER WING REAR SPAR AFT FACE	Threshold	Interval
ATA : 57 Zone : 571 Ref. Doc. : 572000-200-005 Effectivity : OM-BYA, OM-BYK		68 300 Hours 15 900 Cycles	45 500 Hours 10 600 Cycles 6 Years
LH OUTER WING REAR SPAR AFT FACE			
DETAILED INSPECTION OF LH OUTER WING, REAR SPAR, AFT FACE, BETWEEN RIB 1 AND GEAR SUPPORT RIB 5, INCLUDING REAR SPAR ANGLE			

572007-01-6-RH	RH OUTER WING REAR SPAR AFT FACE	Threshold	Interval
ATA : 57 Zone : 671 Ref. Doc. : 572000-200-005 Effectivity : OM-BYA, OM-BYK		68 300 Hours 15 900 Cycles	45 500 Hours 10 600 Cycles 6 Years
RH OUTER WING REAR SPAR AFT FACE			
DETAILED INSPECTION OF RH OUTER WING, REAR SPAR, AFT FACE, BETWEEN RIB 1 AND GEAR SUPPORT RIB 5, INCLUDING REAR SPAR ANGLE			

572040-01-2-LH	LH OUTER WING BOTTOM SKIN CUTOUTS	Threshold	Interval
ATA : 57 Zone : 54 Ref. Doc. : 572000-200-001 Effectivity : OM-BYA, OM-BYK			6 Years
LH OUTER WING BOTTOM SKIN CUTOUTS			
DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN, UPPER AND LOWER SURFACES, AROUND ACCESS DOOR CUTOUTS IN RIB BAY 2-3 AND RIB BAY 6-7			

572040-01-2-RH	RH OUTER WING BOTTOM SKIN CUTOUTS	Threshold	Interval
ATA : 57 Zone : 640 Ref. Doc. : 572000-200-001 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING BOTTOM SKIN CUTOUTS

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN, UPPER AND LOWER SURFACES, AROUND ACCESS DOOR CUTOUTS IN RIB BAY 2-3 AND RIB BAY 6-7

572049-03-1-LH	LH OUTER WING BOTTOM SKIN DRAIN HOLES	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574100-200-802 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING BOTTOM SKIN DRAIN HOLES

DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN, LOWER SURFACE AT DRAIN HOLES FOR TRACK CANS, 1,2,3,& 4 (RIB BAYS 1-2, 2-3, 4-5, 5-6); DRY BAY DRAIN HOLE IN RIB BAY 6-7; MAGNETIC LEVEL INDICATOR HOLE ADJACENT TO RIB 6; MLG PICK UP RAIL HOLE FORWARD OF REAR SPAR INBOARD OF RIB 5

572049-03-1-RH	RH OUTER WING BOTTOM SKIN DRAIN HOLES	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-802 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING BOTTOM SKIN DRAIN HOLES

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN, LOWER SURFACE AT DRAIN HOLES FOR TRACK CANS, 1,2,3,& 4 (RIB BAYS 1-2, 2-3, 4-5, 5-6); DRY BAY DRAIN HOLE IN RIB BAY 6-7; MAGNETIC LEVEL INDICATOR HOLE ADJACENT TO RIB 6; MLG PICK UP RAIL HOLE FORWARD OF REAR SPAR INBOARD OF RIB 5

572062-01-1-LH	LH OUTER WING FIXED TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 571, 574 Ref. Doc. : 572000-220-003 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING FIXED TRAILING EDGE

DETAILED INSPECTION OF LH OUTER WING, FIXED TRAILING EDGE, REAR SPAR AFT FACE, BETWEEN GEAR SUPPORT RIB 5 AND RIB 8

APPLICATION OF TPS TYPE 1 PLUS A SUBSEQUENT APPLICATION OF TPS TYPE 2

572062-01-1-RH	RH OUTER WING FIXED TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 671, 674 Ref. Doc. : 572000-220-003 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING FIXED TRAILING EDGE

DETAILED INSPECTION OF RH OUTER WING, FIXED TRAILING EDGE, REAR SPAR AFT FACE, BETWEEN GEAR SUPPORT RIB 5 AND RIB 8

APPLICATION OF TPS TYPE 1 PLUS A SUBSEQUENT APPLICATION OF TPS TYPE 2

572063-01-1-LH	LH OUTER WING BOTTOM SKIN LWR SURFACE	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 572000-200-031 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING BOTTOM SKIN LWR SURFACE

DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN, LOWER SURFACE, AREA COVERED BY FUEL PUMP WIRING HARNESS FAIRINGS.

PREPARATION NOTE: FUEL PUMP FAIRINGS; WIRING HARNESS DISPLACED;

572063-01-1-RH	RH OUTER WING FRONT SPAR FWD FACE	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 572000-220-004 Effectivity : OM-BYA, OM-BYK RH OUTER WING FRONT SPAR FWD FACE DETAILED INSPECTION OF RH OUTER WING, FRONT SPAR FORWARD FACE, BETWEEN RIB 1 AND RIB 8, INCLUDING VICINITY OF CUTOUTS FOR SLAT TRACKS 1,2,3 AND 4			6 Years

572065-01-1-LH	LH OUTER WING TOP SKIN LOWER SURFACE	Threshold	Interval
ATA : 57 Zone : 571 Ref. Doc. : 572100-220-809 Effectivity : OM-BYA, OM-BYK LH OUTER WING TOP SKIN LOWER SURFACE DETAILED INSPECTION OF LH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 1 TO GEAR SUPPORT RIB 5			6 Years

572065-01-1-RH	RH OUTER WING TOP SKIN LOWER SURFACE	Threshold	Interval
ATA : 57 Zone : 671 Ref. Doc. : 572100-220-809 Effectivity : OM-BYA, OM-BYK RH OUTER WING TOP SKIN LOWER SURFACE DETAILED INSPECTION OF RH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 1 TO GEAR SUPPORT RIB 5			6 Years

572066-01-1-LH	LH OUTER WING TOP SKIN LOWER SURFACE	Threshold	Interval
ATA : 57 Zone : 571, 574 Ref. Doc. : 572100-220-810 Effectivity : OM-BYA, OM-BYK LH OUTER WING TOP SKIN LOWER SURFACE DETAILED INSPECTION OF LH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM GEAR SUPPORT RIB 5 TO RIB 8			6 Years

572066-01-1-RH	RH OUTER WING TOP SKIN LOWER SURFACE	Threshold	Interval
ATA : 57 Zone : 671, 674 Ref. Doc. : 572100-220-810 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING TOP SKIN LOWER SURFACE

DETAILED INSPECTION OF RH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM GEAR SUPPORT RIB 5 TO RIB 8

572111-01-4-LH	LH OUTER WING REAR SPAR AFT FACE RIB 8-11	Threshold	Interval
ATA : 57 Zone : 574, 575 Ref. Doc. : 572100-200-002 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING REAR SPAR AFT FACE RIB 8-11

DETAILED INSPECTION OF LH OUTER WING, REAR SPAR AFT FACE, FROM RIB 8 TO RIB 11

572111-01-4-RH	RH OUTER WING REAR SPAR AFT FACE RIB 8-11	Threshold	Interval
ATA : 57 Zone : 574, 575 Ref. Doc. : 572100-200-002 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING REAR SPAR AFT FACE RIB 8-11

DETAILED INSPECTION OF RH OUTER WING, REAR SPAR AFT FACE, FROM RIB 8 TO RIB 11

572112-01-4-LH	OUTER WING REAR SPAR AFT FACE RIB11-27	Threshold	Interval
ATA : 57 Zone : 575 Ref. Doc. : 572100-200-003 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING REAR SPAR AFT FACE RIB 11-27

DETAILED INSPECTION OF LH OUTER WING, REAR SPAR AFT FACE, BETWEEN RIB 11 AND RIB 27, INCLUDING JOINT PLATE AT RIB 22.

572112-01-4-RH RH OUTER WING REAR SPAR AFT FACE RIB 11-27	Threshold	Interval
ATA : 57 Zone : 675 Ref. Doc. : 572100-200-003 Effectivity : OM-BYA, OM-BYK RH OUTER WING REAR SPAR AFT FACE RIB 11-27 DETAILED INSPECTION OF RH OUTER WING, REAR SPAR AFT FACE, BETWEEN RIB 11 AND RIB 27, INCLUDING JOINT PLATE AT RIB 22.		6 Years
572122-02-1-LH LH OUTER WING TOP SKIN RIB 19-20	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 572100-200-032 Effectivity : OM-BYA, OM-BYK LH OUTER WING TOP SKIN RIB 19-20 DETAILED INSPECTION OF LH OUTER WING TOP SKIN, UPPER SURFACE AROUND MANUAL REFUELLING APERTURE BETWEEN RIB 19 AND RIB 20		6 Years
572122-02-1-RH RH OUTER WING TOP SKIN RIB 19-20	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 572100-200-032 Effectivity : OM-BYA, OM-BYK RH OUTER WING TOP SKIN RIB 19-20 DETAILED INSPECTION OF RH OUTER WING TOP SKIN, UPPER SURFACE AROUND MANUAL REFUELLING APERTURE BETWEEN RIB 19 AND RIB 20		6 Years
572139-01-2-LH LH OUTER WING BOTTOM SKIN RIB BAY CUTOUTS	Threshold	Interval
ATA : 57 Zone : 540 Ref. Doc. : 572100-200-004 Effectivity : OM-BYA, OM-BYK LH OUTER WING BOTTOM SKIN RIB BAY CUTOUTS DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN, UPPER AND LOWER SURFACES AROUND ACCESS DOOR CUTOUTS IN RIB BAYS 8-9, 9-10, 10-11, 11-12 AND 12-13		6 Years

572139-01-2-RH	RH OUTER WING BOTTOM SKIN RIB BAY CUTOUTS	Threshold	Interval
ATA : 57 Zone : 640 Ref. Doc. : 572100-200-004 Effectivity : OM-BYA, OM-BYK			6 Years
RH OUTER WING BOTTOM SKIN RIB BAY CUTOUTS			
DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN, UPPER AND LOWER SURFACES AROUND ACCESS DOOR CUTOUTS IN RIB BAYS 8-9, 9-10, 10-11, 11-12 AND 12-13			

572140-01-2-LH	LH OUTER WING BOTTOM SKIN CUTOUTS	Threshold	Interval
ATA : 57 Zone : 540, 550, 560 Ref. Doc. : 572100-200-021 Effectivity : OM-BYA, OM-BYK			6 Years
LH OUTER WING BOTTOM SKIN CUTOUTS			
DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN LOWER SURFACES, AROUND ACCESS DOOR CUTOUTS IN ALL BAYS, BETWEEN RIB 13 AND RIB 27			

572140-01-2-RH	RH OUTER WING BOTTOM SKIN CUTOUTS	Threshold	Interval
ATA : 57 Zone : 640, 650, 660 Ref. Doc. : 572100-200-021 Effectivity : OM-BYA, OM-BYK			6 Years
RH OUTER WING BOTTOM SKIN CUTOUTS			
DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN LOWER SURFACES, AROUND ACCESS DOOR CUTOUTS IN ALL BAYS, BETWEEN RIB 13 AND RIB 27			

572153-01-1-LH	LH OUTER WING BOTTOM SKIN DRAIN HOLES	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 572100-200-025 Effectivity : OM-BYA, OM-BYK			6 Years
LH OUTER WING BOTTOM SKIN DRAIN HOLES			
DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN LOWER SURFACE, AT DRAIN HOLES FOR SLAT CANS 5,6,7,8,9,10,11 AND 12 (RIB BAYS 9-10, 11-12, 13-14, 16-17, 18-19, 21-22, 23-24 & 25-26) DRY BAY DRAIN HOLES IN RIB BAY 26-27 AND MAGNETIC LEVEL INDICATOR POSITIONS ADJACENT TO RIB 9 AND RIB 12			

572153-01-1-RH	RH OUTER WING BOTTOM SKIN DRAIN HOLES	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 572100-200-025 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING BOTTOM SKIN DRAIN HOLES

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN LOWER SURFACE, AT DRAIN HOLES FOR SLAT CANS 5,6,7,8,9,10,11 AND 12 (RIB BAYS 9-10, 11-12, 13-14, 16-17, 18-19, 21-22, 23-24 & 25-26) DRY BAY DRAIN HOLES IN RIB BAY 26-27 AND MAGNETIC LEVEL INDICATOR POSITIONS ADJACENT TO RIB 9 AND RIB 12

572164-01-1-RH	RH OUTER WING BOTTOM SKIN FUEL DRAIN	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-005 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING BOTTOM SKIN FUEL DRAIN

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN LOWER SURFACE AT FUEL TANK WATER DRAIN HOLES BETWEEN RIB 15-16 AND RIB 22-23.

572178-01-1-LH	LH OUTER WING	Threshold	Interval
ATA : 57 Zone : 574, 575 Ref. Doc. : 572100-220-811 Effectivity : OM-BYA, OM-BYK			6 Years

LH OUTER WING

DETAILED INSPECTION OF LH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 8 TO RIB 11

572178-01-1-RH	RH OUTER WING	Threshold	Interval
ATA : 57 Zone : 674, 675 Ref. Doc. : 572100-220-811 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING

DETAILED INSPECTION OF RH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 8 TO RIB 11

572179-01-1-LH LH OUTER WING	Threshold	Interval
ATA : 57 Zone : 575 Ref. Doc. : 572100-220-812 Effectivity : OM-BYA, OM-BYK LH OUTER WING DETAILED INSPECTION OF LH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 11 TO RIB 27	6 Years	6 Years (+3 Months / -3 Months)
572179-01-1-RH RH OUTER WING	Threshold	Interval
ATA : 57 Zone : 675 Ref. Doc. : 572100-220-812 Effectivity : OM-BYA, OM-BYK RH OUTER WING DETAILED INSPECTION OF RH OUTER WING, TOP SKIN, LOWER SURFACE, OVERHANG FROM RIB 11 TO RIB 27		6 Years
572607-01-1 FLAP TRACK BEAMS FWD SPIGOT ATTACH	Threshold	Interval
ATA : 57 Zone : 531, 532, 533, 631, 632, 633 Ref. Doc. : 572600-200-006 Effectivity : OM-BYA, OM-BYK FLAP TRACK BEAMS FWD SPIGOT ATTACH DETAILED INSPECTION OF OUTER WING, FLAP TRACK BEAMS 2,3,4 FORWARD SPIGOT PINS, BOLTS AND FITTINGS.	6 Years	6 Years
572610-02-1-LH LH WING FLAP TRACK BEAMS AFT SPIGOT	Threshold	Interval
ATA : 57 Zone : 531, 532, 533 Ref. Doc. : 572600-200-010 Effectivity : OM-BYA, OM-BYK LH WING FLAP TRACK BEAMS AFT SPIGOT DETAILED INSPECTION OF LH OUTER WING, FLAP TRACK BEAMS 2,3,4 AFT SPIGOT PREPARATION NOTE: FLAPS EXTENDED;		6 Years

572610-02-1-RH RH WING FLAP TRACK BEAMS AFT SPIGOT		Threshold	Interval
ATA : 57 Zone : 631,632,633 Ref. Doc. : 572600-200-010 Effectivity : OM-BYA, OM-BYK RH WING FLAP TRACK BEAMS AFT SPIGOT DETAILED INSPECTION OF RH OUTER WING, FLAP TRACK BEAMS 2,3,4 AFT SPIGOT PREPARATION NOTE: FLAPS EXTENDED;			6 Years
572651-01-1 OUTER WING REAR SPAR JACK FITTING		Threshold	Interval
ATA : 57 Zone : 571, 671 Ref. Doc. : 572600-200-007 Effectivity : OM-BYK OUTER WING REAR SPAR JACK FITTING DETAILED INSPECTION OF OUTER WING, REAR SPAR AFT FACE RETRACTION JACK FITTING PREPARATION NOTE: RETRACTION ANCHORAGE ACTUATOR REMOVED; BEARING ASSEMBLY REMOVED;		6 Years	6 Years
572651-01-2-LH LH OUTER WING REAR SPAR JACK FITTING		Threshold	Interval
ATA : 57 Zone : 571 Ref. Doc. : 572600-200-007 Effectivity : OM-BYA LH OUTER WING REAR SPAR JACK FITTING DETAILED INSPECTION OF LH OUTER WING, REAR SPAR AFT FACE RETRACTION JACK FITTING APPLICATION OF TPS TYPE 1 PLUS A SUBSEQUENT APPLICATION OF TPS TYPE 2			6 Years

572651-01-2-RH	RH OUTER WING REAR SPAR JACK FITTING	Threshold	Interval
ATA : 57			6 Years
Zone : 671			
Ref. Doc. : 572600-200-007			
Effectivity : OM-BYA			

RH OUTER WING REAR SPAR JACK FITTING

DETAILED INSPECTION OF RH OUTER WING, REAR SPAR AFT FACE RETRACTION JACK FITTING

APPLICATION OF TPS TYPE 1 PLUS A SUBSEQUENT APPLICATION OF TPS TYPE 2

574101-01-2-LH	LH WING FIXED LE ROLLER PIN HOLES	Threshold	Interval
ATA : 57			6 Years
Zone : 521, 522			
Ref. Doc. : 574100-200-012			
Effectivity : OM-BYA, OM-BYK			

LH WING FIXED LE ROLLER PIN HOLES

DETAILED INSPECTION OF LH OUTER WING, FIXED LEADING EDGE, ROLLER PIN HOLES AND OTHER CUTOUTS IN TRACK RIB 1 TO 12

574101-01-2-RH	RH WING FIXED LE ROLLER PIN HOLES	Threshold	Interval
ATA : 57			6 Years
Zone : 621,622			
Ref. Doc. : 574100-200-014			
Effectivity : OM-BYA, OM-BYK			

RH WING FIXED LE ROLLER PIN HOLES

DETAILED INSPECTION OF RH OUTER WING, FIXED LEADING EDGE, ROLLER PIN HOLES AND OTHER CUTOUTS IN TRACK RIB 1 TO 12

574106-01-3-LH	LH WING FIXED LE BOTTOM ATTACH JOINT	Threshold	Interval
ATA : 57 Zone : 521, 522 Ref. Doc. : 574100-200-014 Effectivity : OM-BYA, OM-BYK			6 Years

LH WING FIXED LE BOTTOM ATTACH JOINT

DETAILED INSPECTION OF LH OUTER WING, FIXED LEADING EDGE, BOTTOM ATTACHMENT JOINT ON TRACK RIB 1 TO 12

574106-01-3-RH	RH WING FIXED LE BOTTOM ATTACH JOINT	Threshold	Interval
ATA : 57 Zone : 621, 622 Ref. Doc. : 574100-200-014 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING FIXED LE BOTTOM ATTACH JOINT

DETAILED INSPECTION OF RH OUTER WING, FIXED LEADING EDGE, BOTTOM ATTACHMENT JOINT ON TRACK RIB 1 TO 12

574112-01-1-LH	LH WING FIXED LE MAIN BOTTOM WING SKIN	Threshold	Interval
ATA : 57 Zone : 521, 522 Ref. Doc. : 574100-200-015 Effectivity : Not Effective			6 Years

LH WING FIXED LE MAIN BOTTOM WING SKIN

DETAILED INSPECTION OF LH OUTER WING, FIXED LEADING EDGE, BOTTOM WING SKIN, UPPER AND LOWER SURFACES, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27, INCLUDING SIGHTING ROD HOLES IN RIB BAY 8-9 AND RIB BAY 26-27, LIFTING BEAM HOLES AND DRAIN HOLES

574112-01-1-RH	RH WING FIXED LE MAIN BOTTOM WING SKIN	Threshold	Interval
ATA : 57 Zone : 621, 622 Ref. Doc. : 574100-200-015 Effectivity : Not Effective			6 Years

RH WING FIXED LE MAIN BOTTOM WING SKIN

DETAILED INSPECTION OF RH OUTER WING, FIXED LEADING EDGE, BOTTOM WING SKIN, UPPER AND LOWER SURFACES, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27, INCLUDING SIGHTING ROD HOLES IN RIB BAY 8-9 AND RIB BAY 26-27, LIFTING BEAM HOLES AND DRAIN HOLES

574112-04-1-RH	RH WING - LEADING EDGE	Threshold	Interval
ATA : 57 Zone : 621, 622 Ref. Doc. : AMM : 574100-210-802 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING LEADING EDGE

GENERAL VISUAL INSPECTION OF OUTER WING, FIXED LEADING EDGE, BOTTOM WING SKIN, UPPER SURFACE, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27 INCLUDING SIGHTING ROD HOLES IN RIB BAY 8-9 AND RIB BAY 26-27, LIFTING BEAM HOLES AND DRAIN HOLES.

574113-01-1-LH	LH WING - FIXED LE TOP WING SKIN	Threshold	Interval
ATA : 57 Zone : 521, 522 Ref. Doc. : 574100-200-016 Effectivity : Not Effective			6 Years

LH WING - FIXED LE TOP WING SKIN

DETAILED INSPECTION OF LH OUTER WING, FIXED LEADING EDGE TOP WING SKIN, UPPER AND LOWER SURFACES, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27

574113-01-1-RH	RH WING - FIXED LE TOP WING SKIN	Threshold	Interval
ATA : 57 Zone : 621, 622 Ref. Doc. : 574100-200-016 Effectivity : Not Effective			6 Years

RH WING - FIXED LE TOP WING SKIN

DETAILED INSPECTION OF RH OUTER WING, FIXED LEADING EDGE TOP WING SKIN, UPPER AND LOWER SURFACES, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27

574201-01-1-LH LH WING - SLAT 1, TRACKS 1-4		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574100-200-002 Effectivity : OM-BYA, OM-BYK LH WING SLAT 1, TRACKS 1-4 DETAILED INSPECTION OF LH WING SLAT 1, TRACKS 1 TO 4 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED, LH/RH PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years
574201-01-1-RH RH WING SLAT 1, TRACKS 1-4		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-002 Effectivity : OM-BYA, OM-BYK RH WING SLAT 1, TRACKS 1-4 DETAILED INSPECTION OF RH WING SLAT 1, TRACKS 1 TO 4 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED, LH/RH PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years
574202-01-1 SLAT 1 TRACKS 1-4 ATTACHMENTS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574200-200-001 Effectivity : OM-BYK SLAT 1 TRACKS 1-4 ATTACHMENTS DETAILED INSPECTION OF SLAT 1, TRACKS 1 TO 4 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH PREPARATION NOTE: BOLTS SUCCESSIVELY REMOVED; SLATS FULLY EXTENDED;		12 Years	6 Years

574202-01-2-RH	RH WING SLAT 1 TRACKS 1-4 ATTACHMENTS	Threshold	Interval
ATA : 57			6 Years
Zone : 600			
Ref. Doc. : 574200-200-001			
Effectivity : OM-BYA			

RH WING SLAT 1 TRACKS 1-4 ATTACHMENTS

DETAILED INSPECTION OF RH WING SLAT 1, TRACKS 1 TO 4 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH

PREPARATION NOTE: SLATS FULLY EXTENDED;

574205-01-1-LH	LH WING - SLAT 1 TRAILING EDGE	Threshold	Interval
ATA : 57			6 Years
Zone : 500			
Ref. Doc. : 574200-200-006			
Effectivity : OM-BYA, OM-BYK			

LH WING SLAT 1 TRAILING EDGE

DETAILED INSPECTION OF LH WING SLAT 1, TRAILING EDGE, LOWER FACE, LH

PREPARATION NOTE: SLATS FULLY EXTENDED;

574205-01-1-RH	RH WING SLAT 1 TRAILING EDGE	Threshold	Interval
ATA : 57			6 Years
Zone : 600			
Ref. Doc. : 574200-200-006			
Effectivity : OM-BYA, OM-BYK			

RH WING SLAT 1 TRAILING EDGE

DETAILED INSPECTION OF RH WING SLAT 1, TRAILING EDGE, LOWER FACE, RH

PREPARATION NOTE: SLATS FULLY EXTENDED;

574206-01-1-LH LH WING - SLAT 1 PINION AND RACK TEETH		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574200-220-801 Effectivity : OM-BYA, OM-BYK LH WING SLAT 1 PINION AND RACK TEETH DETAILED INSPECTION OF LH WING SLAT 1, PINION AND RACK TEETH, LH			6 Years
574206-01-1-RH RH WING SLAT 1 PINION AND RACK TEETH		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574200-220-801 Effectivity : OM-BYA, OM-BYK RH WING SLAT 1 PINION AND RACK TEETH DETAILED INSPECTION OF RH WING SLAT 1, PINION AND RACK TEETH, RH			6 Years
574301-01-1-LH LH WING - SLAT 2 TRACK 5-6 ROLLER CONTACT AREA		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574100-200-008 Effectivity : OM-BYA, OM-BYK LH WING SLAT 2 TRACK 5-6 ROLLER CONTACT AREA DETAILED INSPECTION OF LH WING SLAT 2, TRACKS 5 AND 6 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years

574301-01-1-RH	RH WING - SLAT 2 TRACK 5-6 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-008 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING SLAT 2 TRACK 5-6 ROLLER CONTACT AREA

DETAILED INSPECTION OF RH WING SLAT 2, TRACKS 5 AND 6 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED

PREPARATION NOTE: SLATS FULLY EXTENDED;

574302-01-1	SLAT 2 TRACK 5-6 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574300-200-008 Effectivity : OM-BYK		12 Years	6 Years

SLAT 2 TRACK 5-6 ATTACHMENTS

DETAILED INSPECTION OF SLAT 2, TRACKS 5 AND 6 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH

PREPARATION NOTE: BOLTS SUCCESSIVELY REMOVED; SLATS FULLY EXTENDED;

574302-01-2-RH	RH WING SLAT 2 TRACK 5-6 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574300-200-008 Effectivity : OM-BYA			6 Years

RH WING SLAT 2 TRACK 5-6 ATTACHMENTS

DETAILED INSPECTION OF RH WING SLAT 2, TRACKS 5 AND 6 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES

PREPARATION NOTE: SLATS FULLY EXTENDED;

574305-01-1-LH LH WING - SLAT 2 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574300-200-001 Effectivity : OM-BYA, OM-BYK LH WING SLAT 2 TRAILING EDGE DETAILED INSPECTION OF LH WING SLAT 2, TRAILING EDGE, LOWER FACE PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years
574305-01-1-RH RH WING SLAT 2 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574300-200-001 Effectivity : OM-BYA, OM-BYK RH WING SLAT 2 TRAILING EDGE DETAILED INSPECTION OF RH WING SLAT 2, TRAILING EDGE, LOWER FACE PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years
574306-01-1-LH LH WING - SLAT 2 PINION AND RACK TEETH		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574300-220-801 Effectivity : OM-BYA, OM-BYK LH WING SLAT 2 PINION AND RACK TEETH DETAILED INSPECTION OF LH WING SLAT 2, PINION AND RACK TEETH			6 Years

574306-01-1-RH	RH WING SLAT 2 PINION AND RACK TEETH	Threshold	Interval
ATA : 57			6 Years
Zone : 600			
Ref. Doc. : 574300-220-801			
Effectivity : OM-BYA, OM-BYK			
RH WING SLAT 2 PINION AND RACK TEETH			
DETAILED INSPECTION OF RH WING SLAT 2, PINION AND RACK TEETH			

574401-01-1-LH	LH WING - SLAT 3 TRACK 7-8 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57			6 Years
Zone : 500			
Ref. Doc. : 574100-200-009			
Effectivity : OM-BYA, OM-BYK			
LH WING SLAT 3 TRACK 7-8 ROLLER CONTACT AREA			
DETAILED INSPECTION OF LH WING SLAT 3, TRACKS 7 AND 8 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED			
PREPARATION NOTE: SLATS FULLY EXTENDED;			

574401-01-1-RH	RH WING - SLAT 3 TRACK 7-8 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57			6 Years
Zone : 600			
Ref. Doc. : 574100-200-009			
Effectivity : OM-BYA, OM-BYK			
RH WING SLAT 3 TRACK 7-8 ROLLER CONTACT AREA			
DETAILED INSPECTION OF RH WING SLAT 3, TRACKS 7 AND 8 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED			
PREPARATION NOTE: SLATS FULLY EXTENDED;			

574402-01-1	SLAT 3 TRACK 7-8 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574400-200-010 Effectivity : OM-BYK		12 Years	6 Years

SLAT 3 TRACK 7-8 ATTACHMENTS

DETAILED INSPECTION OF SLAT 3, TRACKS 7 AND 8 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH

PREPARATION NOTE: BOLTS SUCCESSIVELY REMOVED; SLATS FULLY EXTENDED;

574402-01-2-RH	RH WING - SLAT 3 TRACK 7-8 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574400-200-010 Effectivity : OM-BYA			6 Years

RH WING SLAT 3 TRACK 7-8 ATTACHMENTS

DETAILED INSPECTION OF RH WING SLAT 3, TRACKS 7 AND 8 ATTACHMENTS, INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES

PREPARATION NOTE: SLATS FULLY EXTENDED;

574405-01-1-LH	LH WING - SLAT 3 TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574400-200-009 Effectivity : OM-BYA, OM-BYK			6 Years

LH WING SLAT 3 TRAILING EDGE

DETAILED INSPECTION OF LH WING SLAT 3, TRAILING EDGE, LOWER FACE

PREPARATION NOTE: SLATS FULLY EXTENDED;

574405-01-1-RH	RH WING SLAT 3 TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574400-200-009 Effectivity : OM-BYA, OM-BYK RH WING SLAT 3 TRAILING EDGE DETAILED INSPECTION OF RH WING SLAT 3, TRAILING EDGE, LOWER FACE PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years

574406-01-1-LH	LH WING - SLAT 3 PINION AND RACK TEETH	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574400-220-802 Effectivity : OM-BYA, OM-BYK LH WING SLAT 3 PINION AND RACK TEETH DETAILED INSPECTION OF LH WING SLAT 3, PINION AND RACK TEETH			6 Years

574406-01-1-RH	RH WING SLAT 3 PINION AND RACK TEETH	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574400-220-802 Effectivity : OM-BYA, OM-BYK RH WING SLAT 3 PINION AND RACK TEETH DETAILED INSPECTION OF RH WING SLAT 3, PINION AND RACK TEETH			6 Years

574501-01-1-LH	LH WING - SLAT 4 TRACK 9-10 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574100-200-010 Effectivity : OM-BYA, OM-BYK			6 Years

LH WING - SLAT 4 TRACK 9-10 ROLLER CONTACT AREA

DETAILED INSPECTION OF LH WING SLAT 4, TRACKS 9 AND 10 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED

PREPARATION NOTE: SLATS FULLY EXTENDED;

574501-01-1-RH	RH WING - SLAT 4 TRACK 9-10 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-010 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING SLAT 4 TRACK 9-10 ROLLER CONTACT AREA

DETAILED INSPECTION OF RH WING SLAT 4, TRACKS 9 AND 10 :
VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED

574502-01-1	SLAT 4 TRACK 9-10 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574500-200-008 Effectivity : OM-BYK		12 Years	6 Years

SLAT 4 TRACK 9-10 ATTACHMENTS

DETAILED INSPECTION OF SLAT 4, TRACKS 9 AND 10 ATTACHMENTS INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH

PREPARATION NOTE: BOLTS SUCCESSIVELY REMOVED; SLATS FULLY EXTENDED;

574502-01-2-RH	RH WING - SLAT 4 TRACK 9-10 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574500-200-008 Effectivity : OM-BYA			6 Years

RH WING SLAT 4 TRACK 9-10 ATTACHMENTS

DETAILED INSPECTION OF RH WING SLAT 4, TRACKS 9 AND 10 ATTACHMENTS INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES

PREPARATION NOTE: SLATS FULLY EXTENDED;

574505-01-1-LH	LH WING - SLAT 4 TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574500-200-007 Effectivity : OM-BYA, OM-BYK			6 Years

LH WING SLAT 4 TRAILING EDGE

DETAILED INSPECTION OF LH WING SLAT 4, TRAILING EDGE, LOWER FACE

PREPARATION NOTE: SLATS FULLY EXTENDED;

574505-01-1-RH	RH WING SLAT 4 TRAILING EDGE	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574500-200-007 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING SLAT 4 TRAILING EDGE

DETAILED INSPECTION OF RH WING SLAT 4, TRAILING EDGE, LOWER FACE

PREPARATION NOTE: SLATS FULLY EXTENDED;

574506-01-1-LH	LH WING - SLAT 4 PINION AND RACK TEETH	Threshold	Interval
ATA : 57			6 Years
Zone : 500			
Ref. Doc. : 574500-220-801			
Effectivity : OM-BYA, OM-BYK			
LH WING SLAT 4 PINION AND RACK TEETH			
DETAILED INSPECTION OF LH WING SLAT 4, PINION AND RACK TEETH.			

574506-01-1-RH	RH WING SLAT 4 PINION AND RACK TEETH	Threshold	Interval
ATA : 57			6 Years
Zone : 600			
Ref. Doc. : 574500-220-801			
Effectivity : OM-BYA, OM-BYK			
RH WING SLAT 4 PINION AND RACK TEETH			
DETAILED INSPECTION OF RH WING SLAT 4, PINION AND RACK TEETH.			

574601-01-1-LH	LH WING - SLAT 5 TRACK 11-12 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57			6 Years
Zone : 500			
Ref. Doc. : 574100-200-011			
Effectivity : OM-BYA, OM-BYK			
LH WING SLAT 5 TRACK 11-12 ROLLER CONTACT AREA			
DETAILED INSPECTION OF LH WING SLAT 5, TRACKS 11 AND 12 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED			
PREPARATION NOTE: SLATS FULLY EXTENDED;			

574601-01-1-RH	RH WING - SLAT 5 TRACK 11-12 ROLLER CONTACT AREA	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574100-200-011 Effectivity : OM-BYA, OM-BYK			6 Years

RH WING SLAT 5 TRACK 11-12 ROLLER CONTACT AREA

DETAILED INSPECTION OF RH WING SLAT 5, TRACKS 11 AND 12 : VISIBLE PART OF ROLLER CONTACT AREA WHEN SLAT IS FULLY EXTENDED

PREPARATION NOTE: SLATS FULLY EXTENDED;

574602-01-1	SLAT 5 TRACK 11-12 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574600-200-008 Effectivity : OM-BYK		12 Years	6 Years

SLAT 5 TRACK 11-12 ATTACHMENTS

DETAILED INSPECTION OF SLAT 5, TRACKS 11 AND 12 ATTACHMENTS INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES, LH/RH

PREPARATION NOTE: BOLTS SUCCESSIVELY REMOVED; SLATS FULLY EXTENDED;

574602-01-2-RH	RH WING - SLAT 5 TRACK 11-12 ATTACHMENTS	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574600-200-008 Effectivity : OM-BYA			6 Years

RH WING SLAT 5 TRACK 11-12 ATTACHMENTS

DETAILED INSPECTION OF RH WING SLAT 5, TRACKS 11 AND 12 ATTACHMENTS INCLUDING TRACK RIB LUGS, TRACK LUGS, BOLTS, LINKS AND SIDE PLATES

PREPARATION NOTE: SLATS FULLY EXTENDED;

574605-01-1-LH LH WING - SLAT 5 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574600-200-007 Effectivity : OM-BYA, OM-BYK LH WING SLAT 5 TRAILING EDGE DETAILED INSPECTION OF LH WING SLAT 5, TRAILING EDGE, LOWER FACE PREPARATION NOTE: SLATS FULLY EXTENDED;			6 Years
574605-01-1-RH RH WING - SLAT 5 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574600-200-007 Effectivity : OM-BYA, OM-BYK RH WING SLAT 5 TRAILING EDGE DETAILED INSPECTION OF RH WING SLAT 5, TRAILING EDGE, LOWER FACE			6 Years
574606-01-1-LH LH WING - SLAT 5 PINION AND RACK TEETH		Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574600-220-801 Effectivity : OM-BYA, OM-BYK LH WING SLAT 5 PINION AND RACK TEETH DETAILED INSPECTION OF LH WING SLAT 5, PINION AND RACK TEETH			6 Years
574606-01-1-RH RH WING - SLAT 5 PINION AND RACK TEETH		Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 574600-220-801 Effectivity : OM-BYA, OM-BYK RH WING SLAT 5 PINION AND RACK TEETH DETAILED INSPECTION OF RH WING SLAT 5, PINION AND RACK TEETH			6 Years

575107-01-1-LH	LH WING - TRAILING EDGE SPOILER 2-5 FITTINGS	Threshold	Interval
ATA : 57			6 Years
Zone : 575, 583, 584, 585, 586			
Ref. Doc. : 575100-220-009			
Effectivity : OM-BYA, OM-BYK			

LH WING TRAILING EDGE SPOILER 2-5 FITTINGS

DETAILED INSPECTION OF LH OUTER WING, TRAILING EDGE, SPOILERS 2,3,4 AND 5 ACTUATOR AND HINGE FITTINGS

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;

575107-01-1-RH	RH WING - TRAILING EDGE SPOILER 2-5 FITTINGS	Threshold	Interval
ATA : 57			6 Years
Zone : 675, 683, 684, 685, 686			
Ref. Doc. : 575100-220-009			
Effectivity : OM-BYA, OM-BYK			

RH WING TRAILING EDGE SPOILER 2-5 FITTINGS

DETAILED INSPECTION OF RH OUTER WING, TRAILING EDGE, SPOILERS 2,3,4 AND 5 ACTUATOR AND HINGE FITTINGS

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;

575120-03-1-LH	LH WING - TRAILING EDGE AILERON HINGE PINS	Threshold	Interval
ATA : 57			6 Years
Zone : 575, 590			
Ref. Doc. : 575100-220-016			
Effectivity : OM-BYA, OM-BYK			

LH WING - TRAILING EDGE AILERON HINGE PINS

DETAILED INSPECTION OF LH OUTER WING, TRAILING EDGE, AILERON HINGE PINS 1 TO 5

PREPARATION NOTE: PINS REMOVED;

575120-03-1-RH	RH WING - TRAILING EDGE AILERON HINGE PINS	Threshold	Interval
ATA : 57 Zone : 675, 690 Ref. Doc. : 575100-220-016 Effectivity : OM-BYA, OM-BYK RH WING - TRAILING EDGE AILERON HINGE PINS DETAILED INSPECTION OF RH OUTER WING, TRAILING EDGE, AILERON HINGE PINS 1 TO 5 PREPARATION NOTE: PINS REMOVED;			6 Years
575121-01-1-LH	LH WING - TRAILING EDGE AILERON ACTUATOR FITTING	Threshold	Interval
ATA : 57 Zone : 575, 590 Ref. Doc. : 575100-220-003 Effectivity : OM-BYA, OM-BYK LH WING TRAILING EDGE AILERON ACTUATOR FITTING DETAILED INSPECTION OF LH OUTER WING, TRAILING EDGE, AILERON, INBOARD AND OUTBOARD ACTUATOR FITTINGS			6 Years
575121-01-1-RH	RH WING - TRAILING EDGE AILERON ACTUATOR FITTING	Threshold	Interval
ATA : 57 Zone : 675, 690 Ref. Doc. : 575100-220-003 Effectivity : OM-BYA, OM-BYK RH WING TRAILING EDGE AILERON ACTUATOR FITTING DETAILED INSPECTION OF RH OUTER WING, TRAILING EDGE, AILERON, INBOARD AND OUTBOARD ACTUATOR FITTINGS			6 Years
575150-01-2-LH	LH OUTER WING - MLG SUPPORT RIBS	Threshold	Interval
ATA : 57 Zone : 571 Ref. Doc. : 575100-200-005 Effectivity : OM-BYA LH OUTER WING MLG SUPPORT RIBS DETAILED INSPECTION OF LH OUTER WING, MLG SUPPORT RIB 5, OUTBOARD AND INBOARD FACES			6 Years

575150-01-2-RH RH OUTER WING - MLG SUPPORT RIBS		Threshold	Interval
ATA : 57 Zone : 671 Ref. Doc. : 575100-200-005 Effectivity : OM-BYA, OM-BYK RH OUTER WING MLG SUPPORT RIBS DETAILED INSPECTION OF RH OUTER WING, MLG SUPPORT RIB 5, OUTBOARD AND INBOARD FACES			6 Years
575151-02-1-RH RH WING - TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 673, 674 Ref. Doc. : 575100-210-804 Effectivity : OM-BYA, OM-BYK RH WING TRAILING EDGE GENERAL VISUAL INSPECTION OF RH OUTER WING, TRAILING EDGE, FALSE REAR SPAR, FORWARD AND AFT FACES			6 Years
575151-03-1 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : Ref. Doc. : AMM : 575100-210-805 Effectivity : OM-BYA, OM-BYK TRAILING EDGE GENERAL VISUAL INSPECTION OF OUTER WING, TRAILING EDGE, FALSE REAR SPAR, FORWARD AND AFT FACES			6 Years
575167-01-1-LH LH OUTER WING - BOTTOM SKIN UPPER SURFACE		Threshold	Interval
ATA : 57 Zone : 574 Ref. Doc. : 575100-200-011 Effectivity : OM-BYA, OM-BYK LH OUTER WING BOTTOM SKIN UPPER SURFACE DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN PANEL NO. 3, UPPER SURFACE, BETWEEN REAR SPAR AND FALSE REAR SPAR, AND BETWEEN GEAR SUPPORT RIB 5 AND RIB 8.			6 Years

575167-01-1-RH	RH OUTER WING - BOTTOM SKIN UPPER SURFACE	Threshold	Interval
ATA : 57 Zone : 674 Ref. Doc. : 575100-200-011 Effectivity : OM-BYA, OM-BYK			6 Years

RH OUTER WING BOTTOM SKIN UPPER SURFACE

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN PANEL NO. 3, UPPER SURFACE, BETWEEN REAR SPAR AND FALSE REAR SPAR, AND BETWEEN GEAR SUPPORT RIB 5 AND RIB 8.

575254-01-1	INBOARD FLAP TRACK 2 DRIVE LEVER	Threshold	Interval
ATA : 57 Zone : 531, 631 Ref. Doc. : 575200-200-006 Effectivity : Not Effective		6 Years	6 Years (+3 Months / -3 Months)

INBOARD FLAP TRACK 2 DRIVE LEVER

DETAILED INSPECTION OF OUTER WING, INBOARD FLAP TRACK 2, DRIVE LEVER

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;

575303-02-4	OUTBOARD FLAP TRACK 3 ATTACH AREAS	Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-003 Effectivity : OM-BYK			6 Years

OUTBOARD FLAP TRACK 3 ATTACH AREAS

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, FRONT SPAR SPLICES AND ATTACHMENT AREAS AT TRACK 3, INTERNAL AND EXTERNAL, LH/RH

NOTE:
INSPECTION IS THROUGH INSPECTION HOLES

PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;

575305-01-1	OUTBOARD FLAP TRACK 4 ATTACH AREAS	Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-200-006 Effectivity : OM-BYK			6 Years

OUTBOARD FLAP TRACK 4 ATTACH AREAS

DETAILED INSPECTION OF OUTBOARD FLAP, FRONT SPAR SPLICES AND ATTACHMENT AREAS AT TRACK 4, INTERNAL AND EXTERNAL, LH/RH

NOTE:

THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575305-02-1.

PREPARATION NOTE: FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;

575305-02-1	OUTBOARD FLAP TRACK 4 ATTACH AREAS	Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-009 Effectivity : OM-BYK			6 Years

OUTBOARD FLAP TRACK 4 ATTACH AREAS

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, FRONT SPAR SPLICES AND ATTACHMENT AREAS AT TRACK 4, INTERNAL AND EXTERNAL, LH/RH

NOTE:

INSPECTION IS THROUGH INSPECTION HOLES.

THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575305-01-1.

PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;

575354-01-1	OUTBOARD FLAP TRACK 3-4 DRIVE LEVERS	Threshold	Interval
ATA : 57 Zone : 532, 533, 632, 633 Ref. Doc. : 575300-200-010 Effectivity : Not Effective		6 Years	6 Years (+3 Months / -3 Months)

OUTBOARD FLAP TRACK 3-4 DRIVE LEVERS

DETAILED INSPECTION OF OUTER WING OUTBOARD FLAP TRACK 3 AND 4 DRIVE LEVERS

PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;

712211-03-2-LH	LH ENGINE - AFT ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 450 Ref. Doc. : 712211-210-042 Effectivity : OM-BYA, OM-BYK			6 Years
LH ENGINE AFT ENGINE MOUNT			
DETAILED INSPECTION OF AFT ENGINE MOUNT INSTALLATION EXPOSED SURFACES			

712211-03-2-RH	RH ENGINE - AFT ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 460 Ref. Doc. : 712211-210-042 Effectivity : OM-BYA, OM-BYK			6 Years
RH ENGINE AFT ENGINE MOUNT			
DETAILED INSPECTION OF AFT ENGINE MOUNT INSTALLATION EXPOSED SURFACES			

783209-01-1-LH	LH ENGINE - THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 451, 452 Ref. Doc. : AMM : 783200-220-811 Effectivity : OM-BYA, OM-BYK			6 Years
LH ENGINE THRUST REVERSER			
DETAILED INSPECTION OF LH ENGINE THRUST REVERSER V-GROOVE ADAPTER RING.			

783209-01-1-RH	RH ENGINE - THRUST REVERSER	Threshold	Interval
ATA : 78 Zone : 461, 462 Ref. Doc. : AMM : 783200-220-811 Effectivity : OM-BYA, OM-BYK			6 Years
RH ENGINE THRUST REVERSER			
DETAILED INSPECTION OF RH ENGINE THRUST REVERSER V-GROOVE ADAPTER RING.			



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

12 YE STRUCTURAL CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 167

521101-01-1	FWD PAX/CREW DOOR STOP ASSEMBLIES	Threshold	Interval
ATA : 52		12 Years	12 Years
Zone : 831, 841			(+3 Months / -3 Months)
Ref. Doc. : 521100-200-001			
Effectivity : OM-BYA, OM-BYK			

FWD PAX/CREW DOOR STOP ASSEMBLIES

DETAILED INSPECTION OF DOOR STOP ASSEMBLIES ON FORWARD PASSENGER/CREW DOOR, LH/RH

521301-01-1	AFT PAX/CREW DOOR STOP ASSEMBLIES	Threshold	Interval
ATA : 52		12 Years	12 Years
Zone : 832, 842			
Ref. Doc. : 521300-200-001			
Effectivity : OM-BYA, OM-BYK			

AFT PAX/CREW DOOR STOP ASSEMBLIES

DETAILED INSPECTION OF DOOR STOP ASSEMBLIES ON AFT PASSENGER/CREW DOOR, LH/RH

523108-01-3	FWD CARGO DOOR FITTINGS EXTERNAL AREA	Threshold	Interval
ATA : 52		12 Years	12 Years
Zone : 825			(+3 Months / -3 Months)
Ref. Doc. : 523111-200-004			
Effectivity : OM-BYA, OM-BYK			

FWD CARGO DOOR FITTINGS EXTERNAL AREA

DETAILED INSPECTION OF FORWARD CARGO COMPARTMENT DOOR, HINGE FITTINGS AND ATTACHMENT AREA, EXTERNAL

NOTE:

APPLICATION OF TPS IS LIMITED TO THE INNER SIDE OF HINGE FITTINGS

PREPARATION NOTE: DOOR OPENED;

523218-01-1AFT CARGO DOOR FITTINGS EXTERNAL AREA	Threshold	Interval
<p>ATA : 52 Zone : 826 Ref. Doc. : 523211-200-008 Effectivity : OM-BYA, OM-BYK</p> <p>AFT CARGO DOOR FITTINGS EXTERNAL AREA</p> <p>DETAILED INSPECTION OF AFT CARGO COMPARTMENT DOOR HINGE FITTINGS AND ATTACHMENT AREA, EXTERNAL. NOTE: APPLICATION OF TPS IS LIMITED TO THE INNER SIDE OF HINGE FITTING</p>	12 Years	12 Years
523218-01-2TASK DELETED BY MPD REVISION 46	Threshold	Interval
<p>ATA : 52 Zone : 826 Ref. Doc. : 523211-200-008 Effectivity : Not Effective</p> <p>AFT CARGO DOOR FITTINGS EXTERNAL AREA</p> <p>DETAILED INSPECTION OF AFT CARGO COMPARTMENT DOOR HINGE FITTINGS AND ATTACHMENT AREA, EXTERNAL. NOTE: APPLICATION OF TPS IS LIMITED TO THE INNER SIDE OF HINGE FITTING</p> <p>PREPARATION NOTE: DOOR OPENED;</p>	12 Years	12 Years
524111-01-1FWD AVIONIC DOOR INTERNAL STRUCTURE	Threshold	Interval
<p>ATA : 52 Zone : 811 Ref. Doc. : 524111-200-001 Effectivity : OM-BYA, OM-BYK</p> <p>FWD AVIONIC DOOR INTERNAL STRUCTURE</p> <p>DETAILED INSPECTION OF FORWARD AVIONICS COMPARTMENT ACCESS DOOR, INTERNAL STRUCTURE, INCLUDING HINGE ARMS</p> <p>PREPARATION NOTE: DOOR FLOOR PANELS REMOVED;</p>	12 Years	12 Years

531151-01-1 DOOR STOP FITTINGS		Threshold	Interval
ATA : 53 Zone : 221, 222 Ref. Doc. : 531100-210-017 Effectivity : OM-BYA, OM-BYK DOOR STOP FITTINGS DETAILED INSPECTION OF DOOR STOP FITTINGS ON FR 16 AND FR 20, LH/RH PREPARATION NOTE: LINING REMOVED;		12 Years	12 Years (+3 Months / -3 Months)
531161-01-1 NLG BAY ALL PANELS		Threshold	Interval
ATA : 53 Zone : 123, 124 Ref. Doc. : 531100-210-803 Effectivity : OM-BYA, OM-BYK NLG BAY ALL PANELS GENERAL VISUAL INSPECTION OF NLG BAY, ALL PANELS, LH/RH		12 Years	12 Years
531175-01-1 FWD FACE OF FRONT PRESSURE BULKHEAD		Threshold	Interval
ATA : 53 Zone : 110 Ref. Doc. : 531100-210-040 Effectivity : OM-BYA, OM-BYK FWD FACE OF FRONT PRESSURE BULKHEAD DETAILED INSPECTION OF FORWARD FACE OF FRONT PRESSURE BULKHEAD ATTACHED TO FR 1 PREPARATION NOTE: PROTECTIVE SHIELD;		12 Years	12 Years (+3 Months / -3 Months)

531177-01-1	COCKPIT WINDSHIELD FRAME	Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 531100-210-042 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

COCKPIT WINDSHIELD FRAME

DETAILED INSPECTION OF COCKPIT WINDSHIELD, EXTERNAL PORTION OF FRAMEWORK COVERED BY RETAINERS AND INTERNAL PORTION OF RETAINERS.

PREPARATION NOTE: WINDSHIELD RETAINERS;

531180-01-1	FWD PAX/CREW DOOR UNDER SCUFF-PLATE	Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : 531100-210-044 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

FWD PAX/CREW DOOR UNDER SCUFF-PLATE

DETAILED INSPECTION OF FORWARD PASSENGER/CREW DOOR CUTOUT, UNDERNEATH THE SCUFF-PLATE, LH/RH

PREPARATION NOTE: SCUFF PLATES REMOVED;

531186-01-1	AFT FACE OF FWD PRESSURE BULKHEAD	Threshold	Interval
ATA : 53 Zone : 211, 212 Ref. Doc. : 531100-210-046 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years

AFT FACE OF FWD PRESSURE BULKHEAD

DETAILED INSPECTION OF AFT FACE OF FORWARD PRESSURE BULKHEAD, ABOVE COCKPIT FLOOR LEVEL, INCLUDING FR 1, AS FAR AS VISIBLE

PREPARATION NOTE: INSULATION DISPLACED; WIRING BUNDLES DISPLACED;

531187-01-1	COCKPIT WINDOW FRAMES	Threshold	Interval
ATA : 53 Zone : 211, 212 Ref. Doc. : 531100-210-047 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

COCKPIT WINDOW FRAMES

DETAILED INSPECTION OF COCKPIT WINDOW FRAMES AND CLOSING PANELS, INTERNAL STRUCTURE (FR 12 AND FORWARD).

PREPARATION NOTE: INSULATION DISPLACED; LINING REMOVED; ELECTRONIC DEVICES DISPLACED;

531188-01-1	COCKPIT FLOOR STRUCTURE	Threshold	Interval
ATA : 53 Zone : 211, 212 Ref. Doc. : 531100-210-048 Effectivity : OM-BYA, OM-BYK		12 Years (+3 Months / -3 Months)	12 Years (+3 Months / -3 Months)

COCKPIT FLOOR STRUCTURE

DETAILED INSPECTION OF COCKPIT FLOOR STRUCTURE, BETWEEN FR 1 AND FR 12

PREPARATION NOTE: COCKPIT FLOOR PANELS; RUBBER LEVELLING STRIPS;

531190-01-2	FLOOR STRUCTURE FR 21 TO FR 24	Threshold	Interval
ATA : 53 Zone : 221, 222, 231, 232 Ref. Doc. : 531100-210-805 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

FLOOR STRUCTURE FR 21 TO FR 24

GENERAL VISUAL INSPECTION OF CABIN FLOOR STRUCTURE, EXCLUDING AREAS BELOW GALLEYS AND TOILETS, BETWEEN FR 21 AND FR 24

PREPARATION NOTE: CABIN FLOOR PANELS;

531191-01-1	AFT FACE OF FWD PRESSURE BULKHEAD	Threshold	Interval
ATA : 53 Zone : 121, 122 Ref. Doc. : 531100-220-002 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

AFT FACE OF FWD PRESSURE BULKHEAD

DETAILED INSPECTION OF AFT FACE OF FORWARD PRESSURE BULKHEAD, BELOW COCKPIT FLOOR LEVEL, INCLUDING FR 1 AND STRINGER CONNECTIONS.

NOTE: IF CORROSION IS FOUND ON THE PRESSURE BULKHEAD ABOVE THE AVIONICS FLOOR PANELS THE COMPLETE AFT FACE (UPPER AND LOWER AREAS) OF THE PRESSURE BULKHEAD IS TO BE INSPECTED.

PREPARATION NOTE: FORWARD AVIONICS BAY FLOOR PANELS REMOVED; INSULATION DISPLACED; WIRING BUNDLES DISPLACED;

531192-01-1	FUSELAGE FR 1 TO 12	Threshold	Interval
ATA : 53 Zone : 121, 122, 125, 126 Ref. Doc. : 531100-210-806 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

FUSELAGE FR 1 TO 12

GENERAL VISUAL INSPECTION OF FUSELAGE INTERNAL STRUCTURE AND FLOOR STRUCTURE, INCLUDING NLG BAY PANELS, BETWEEN FR 1 AND FR 12, BELOW COCKPIT FLOOR PANELS

NOTE: TPS MAY BE LIMITED TO FUSELAGE INTERNAL STRUCTURE BETWEEN FR1 AND FR12 AND AFT FACE OF PRESSURE BULKHEAD, FROM STRINGER 32, LH/RH TO BOTTOM CENTERLINE

PREPARATION NOTE: AIR DUCT; FORWARD AVIONICS BAY FLOOR PANELS REMOVED; INSULATION REMOVED;

531193-01-1 FUSELAGE FR 20 TO 24		Threshold	Interval
ATA : 53 Zone : 127, 128 Ref. Doc. : 531100-210-807 Effectivity : OM-BYA, OM-BYK FUSELAGE FR 20 TO 24 GENERAL VISUAL INSPECTION OF FUSELAGE INTERNAL STRUCTURE AND FLOOR STRUCTURE, INCLUDING NLG BAY AFT FACE, BETWEEN FR 20 AND FR 24, BELOW CABIN FLOOR PANELS NOTE: TPS MAY BE LIMITED TO FUSELAGE INTERNAL STRUCTURE BETWEEN FR 20 AND FR 24, FROM STRINGER 32, LH/RH TO BOTTOM CENTERLINE PREPARATION NOTE: AVIONICS BAY FLOOR PANELS REMOVED;		12 Years	12 Years
531198-01-1 NOSE FORWARD FUSELAGE		Threshold	Interval
ATA : 53 Zone : 125, 126, 221, 222, 223, 224 Ref. Doc. : 531100-200-802 Effectivity : OM-BYA, OM-BYK NOSE FORWARD FUSELAGE SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF FUSELAGE INTERNAL STRUCTURE, FROM FR 12 TO FR 14, UNDER HEAT EXCHANGER PANELS. PREPARATION NOTE: LINING REMOVED, INSULATION DISPLACED, HOLES IN HEAT EXCHANGER PANELS;		24 Years	12 Years
532102-01-1 FLOOR STRUCTURE FR 24-35		Threshold	Interval
ATA : 53 Zone : 231, 232 Ref. Doc. : 532100-210-001 Effectivity : OM-BYA, OM-BYK FLOOR STRUCTURE FR 24-35 GENERAL VISUAL INSPECTION OF CABIN FLOOR STRUCTURE, EXCLUDING AREAS BELOW GALLEYS AND TOILETS (IF INSTALLED), BETWEEN FR 24 AND FR 35 PREPARATION NOTE: CABIN FLOOR PANELS;		12 Years	12 Years

532132-01-3 FWD CARGO DOOR HINGE FITTING	Threshold	Interval
<p>ATA : 53 Zone : 100, 132 Ref. Doc. : 532100-200-027 Effectivity : OM-BYA, OM-BYK</p> <p>FWD CARGO DOOR HINGE FITTING</p> <p>DETAILED INSPECTION OF FUSELAGE FORWARD CARGO DOOR HINGE FITTING AND EXTERNAL ATTACHMENT AREA</p> <p>NOTE: TPS APPLICATION IS LIMITED TO THE INNER SIDE OF THE HINGE FITTINGS</p> <p>PREPARATION NOTE: DOOR OPENED AND CLOSED;</p>	12 Years	12 Years
532135-01-2 FWD CARGO DOOR CUTOUT LATERAL FRAMES	Threshold	Interval
<p>ATA : 53 Zone : 132 Ref. Doc. : 532100-210-002 Effectivity : OM-BYA, OM-BYK</p> <p>FWD CARGO DOOR CUTOUT LATERAL FRAMES</p> <p>GENERAL VISUAL INSPECTION OF FORWARD CARGO DOOR CUTOUT, VISIBLE PART OF LATERAL FR 24A AND FR 28</p>		12 Years
532196-01-1 FWD CARGO DOOR ECCENTRIC BOLTS	Threshold	Interval
<p>ATA : 53 Zone : 132 Ref. Doc. : 532100-200-005 Effectivity : OM-BYA, OM-BYK</p> <p>FWD CARGO DOOR ECCENTRIC BOLTS</p> <p>DETAILED INSPECTION OF FORWARD CARGO DOOR ECCENTRIC BOLTS OF LOCKING MECHANISM AT LOCK FITTINGS, BETWEEN FR 24A AND FR 28.</p> <p>PREPARATION NOTE: ECCENTRIC BOLTS REMOVED;</p>	12 Years	12 Years

533103-01-1	AFT PRESSURE BULKHEAD AFT FACE	Threshold	Interval
ATA : 53 Zone : 151, 152 Ref. Doc. : 533100-210-008 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

AFT PRESSURE BULKHEAD AFT FACE

DETAILED INSPECTION OF PRESSURE BULKHEAD AT FR 46, AFT FACE, INCLUDING VERTICAL BEAMS, ABOVE CARGO FLOOR LEVEL

PREPARATION NOTE: ACT(S) REMOVED (IF INSTALLED); INSULATION REMOVED;

533131-01-1	ADF1 ANTENNA SKIN CUTOUT	Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 533100-210-011 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

ADF1 ANTENNA SKIN CUTOUT

DETAILED INSPECTION OF SKIN AROUND ADF 1 ANTENNA CUTOUT, BETWEEN FR 44 AND FR 45 AND BETWEEN STRINGER 1, LH/RH, EXTERNAL SURFACE

PREPARATION NOTE: COVER OF ANTENNA AND ANTENNA REMOVED;

533135-01-1	FUSELAGE FR 36-46	Threshold	Interval
ATA : 53 Zone : 145, 146 Ref. Doc. : 533100-210-031 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

FUSELAGE FR 36-46

GENERAL VISUAL INSPECTION OF FUSELAGE INTERNAL STRUCTURE BELOW CABIN FLOOR PANELS, INCLUDING CABIN FLOOR STRUCTURE BETWEEN FR 36 AND FR 46

NOTE: CAN BE PERFORMED AT SAME TIME AS TASK 571157-01-1

PREPARATION NOTE: CABIN FLOOR PANELS; INSULATION REMOVED;

533135-01-1-1485-A	FUSELAGE FR 44-64	Threshold	Interval
ATA : 53		12 Years	12 Years (+3 Months / -3 Months)
Zone : 145, 146			
Ref. Doc. : AMM-S			
Effectivity : 53-31-35-210-801 OM-BYK			

FUSELAGE FR 44-64

GENERAL VISUAL INSPECTION OF FUSELAGE STRUCTURE BELOW CABIN FLOOR PANELS, INCLUDING CABIN FLOOR STRUCTURE BETWEEN FR 46 AND 64.

CABIN FLOOR PANELS AND INSULATION REMOVED.

PREPARATION NOTE: CABIN FLOOR PANELS AND INSULATION REMOVED.

533151-01-3	KEELBEAM BOX	Threshold	Interval
ATA : 53			12 Years
Zone : 147, 148, 191, 192, 195, 196			
Ref. Doc. : 533100-210-007			
Effectivity : OM-BYA, OM-BYK			

KEELBEAM BOX

DETAILED INSPECTION OF KEELBEAM BOX

NOTE:
INSPECTION BETWEEN FR 35 AND FR 47/51.

533153-02-1	PRESSURE BULKHEAD AT FR 35 AFT FACE	Threshold	Interval
ATA : 53			12 Years
Zone : 191, 192			
Ref. Doc. : 533100-210-807			
Effectivity : OM-BYA, OM-BYK			

PRESSURE BULKHEAD AT FR 35 AFT FACE

GENERAL VISUAL INSPECTION OF PRESSURE BULKHEAD AFT FACE AND LOWER SKIN OF PRESSURE DECK LOWER SURFACE

NOTE: INSPECTION AT FR 35 AND LOWER SKIN OF PRESSURE DECK LOWER SURFACE, BETWEEN FR 35 AND FR 36.

533154-01-1-LH LH MLG DOORS FITTINGS		Threshold	Interval
ATA : 53 Zone : 147 Ref. Doc. : 533100-210-014 Effectivity : OM-BYA, OM-BYK LH MLG DOORS FITTINGS DETAILED INSPECTION OF HINGE AND ACTUATOR FITTINGS FOR LH MLG DOORS AT KEELBEAM			12 Years
534111-01-5 TASK DELETED BY MPD REVISION 46		Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 534100-210-002 Effectivity : Not Effective ADF2 ANTENNA SKIN CUTOUT DETAILED INSPECTION OF SKIN AROUND ADF2 ANTENNA CUTOUT, BETWEEN STRINGER 1, LH/RH, EXTERNAL SURFACE NOTE: INSPECTION BETWEEN FR 52 AND FR 53. FOR PRE 20053 AIRCRAFT RETROFITTED, THRESHOLD IS TO BE COUNTED FROM EMBODIMENT OF MOD 20053 VIA SB. PREPARATION NOTE: COVER OF ANTENNA AND ANTENNA REMOVED;		12 Years	12 Years
534111-01-8 ADF 2 ANTENNA SKIN CUTOUT		Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : AMM : 534100-210-002 Effectivity : OM-BYA ADF 2 ANTENNA SKIN CUTOUT DETAILED INSPECTION OF SKIN AROUND ADF 2 ANTENNACUT OUT, BETWEEN STRINGER 1, LH/RH, EXTERNAL SURFACE NOTE: INSPECTION BETWEEN FR 52 AND FR 53. PREP.: COVER OF ANTENNA AND ANTENNA REMOVED;		24 Years	12 Years

534112-01-5 VHF3 ANTENNA SKIN CUTOUT		Threshold	Interval
ATA : 53 Zone : 200 Ref. Doc. : 534100-210-019 Effectivity : OM-BYA, OM-BYK VHF3 ANTENNA SKIN CUTOUT DETAILED INSPECTION OF SKIN AROUND VHF 3 ANTENNA CUTOUT, BETWEEN STRINGER 1, LH/RH, EXTERNAL SURFACE NOTE: INSPECTION BETWEEN FR 56 AND FR 57. PREPARATION NOTE: ANTENNA REMOVED;		24 Years	12 Years
534134-01-1 DOOR STOP FITTINGS FR 66 AND 68		Threshold	Interval
ATA : 53 Zone : 261, 262 Ref. Doc. : 534100-210-029 Effectivity : OM-BYA, OM-BYK DOOR STOP FITTINGS FR 66 AND 68 DETAILED INSPECTION OF DOOR STOP FITTINGS ON FR 66 AND FR 68, LH/RH PREPARATION NOTE: LINING REMOVED;		12 Years	12 Years
534136-01-1 AFT PAX/CREW DOOR UNDER SCUFF-PLATE		Threshold	Interval
ATA : 53 Zone : 100 Ref. Doc. : 534100-210-041 Effectivity : OM-BYA, OM-BYK AFT PAX/CREW DOOR UNDER SCUFF-PLATE DETAILED INSPECTION OF AFT PASSENGER/CREW DOOR CUTOUT, UNDERNEATH THE SCUFF PLATE, LH/RH PREPARATION NOTE: SCUFF PLATE;		12 Years	12 Years

534146-01-2 CABIN FLOOR STRUCTURE FR 47/51 TO FR 70		Threshold	Interval
ATA : 53 Zone : 251, 252, 261, 262 Ref. Doc. : 534100-210-801 Effectivity : OM-BYA, OM-BYK CABIN FLOOR STRUCTURE FR 47/51 TO FR 70 GENERAL VISUAL INSPECTION OF CABIN FLOOR STRUCTURE, EXCLUDING AREAS BELOW GALLEYS AND TOILETS AND DOOR ENTRANCE AREA, FROM FR 47/51 TO FR 70 PREPARATION NOTE: CABIN FLOOR PANELS;		12 Years	12 Years
534152-01-4 AFT CARGO DOOR HINGE FITTINGS INTERNAL		Threshold	Interval
ATA : 53 Zone : 252 Ref. Doc. : 534100-210-005 Effectivity : OM-BYA, OM-BYK AFT CARGO DOOR HINGE FITTINGS INTERNAL DETAILED INSPECTION OF FUSELAGE INTERNAL STRUCTURE AT INTERNAL ATTACHMENT AREA OF AFT CARGO DOOR HINGE FITTINGS, FROM FR 55 TO FR 60, BETWEEN STRINGER 22 AND STRINGER 23 PREPARATION NOTE: INSULATION REMOVED; REAR ACT REMOVED (IF INSTALLED);		24 Years	12 Years
534153-01-2 AFT CARGO DOOR HINGE FITTINGS EXTERNAL		Threshold	Interval
ATA : 53 Zone : 152 Ref. Doc. : 534100-210-006 Effectivity : OM-BYA, OM-BYK AFT CARGO DOOR HINGE FITTINGS EXTERNAL DETAILED INSPECTION OF FUSELAGE AFT CARGO DOOR HINGE FITTINGS AND EXTERNAL ATTACHMENT AREA NOTE: APPLICATION OF TPS IS LIMITED TO THE INNER SIDE OF HINGE FITTINGS		12 Years	12 Years

534155-01-4	AFT CARGO DOOR ECCENTRIC BOLTS	Threshold	Interval
ATA : 53 Zone : 154 Ref. Doc. : 534100-210-025 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

AFT CARGO DOOR ECCENTRIC BOLTS

DETAILED INSPECTION OF AFT CARGO DOOR ECCENTRIC BOLTS OF LOCKING MECHANISM AT LOCK FITTINGS, BETWEEN FR 56 AND FR 58A (6 PLACES)

PREPARATION NOTE: ECCENTRIC BOLTS REMOVED;

534157-01-7	AFT CARGO DOOR LOCK FITTING	Threshold	Interval
ATA : 53 Zone : 152 Ref. Doc. : 534100-210-038 Effectivity : OM-BYA, OM-BYK			12 Years

AFT CARGO DOOR LOCK FITTING

GENERAL VISUAL INSPECTION OF AFT CARGO DOOR LOCK FITTINGS AND SURROUNDING STRUCTURE, EXTERNAL PORTION (6 PLACES)

NOTE:
- BETWEEN FR 56 AND FR 58A

534160-01-4	AFT CARGO DOOR CUTOUT LATERAL FRAMES	Threshold	Interval
ATA : 53 Zone : 152 Ref. Doc. : 534100-210-803 Effectivity : OM-BYA, OM-BYK			12 Years

AFT CARGO DOOR CUTOUT LATERAL FRAMES

GENERAL VISUAL INSPECTION OF AFT CARGO DOOR CUTOUT, VISIBLE PART OF LATERAL FRAMES

NOTE: INSPECTION OF FR 55A AND FR 59.

535113-01-1	FUSELAGE SKIN AT THS CUTOUT	Threshold	Interval
ATA : 53 Zone : 311, 312 Ref. Doc. : 535100-210-004 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
FUSELAGE SKIN AT THS CUTOUT			
DETAILED INSPECTION OF FUSELAGE SKIN AT HORIZONTAL STABILIZER CUTOUT AT FORWARD, UPPER AND LOWER CORNERS, LH/RH			

535115-01-1	FRAME 74 SPLICES	Threshold	Interval
ATA : 53 Zone : 311, 312 Ref. Doc. : 535100-210-005 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
FRAME 74 SPLICES			
DETAILED INSPECTION OF FR 74, SPLICES AT STRINGER 12 AND STRINGER 19, LH/RH, INTERNAL STRUCTURE			

535117-01-1	HORIZONTAL STABILIZER ATTACHMENT	Threshold	Interval
ATA : 53 Zone : 311, 312 Ref. Doc. : 535100-210-007 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
HORIZONTAL STABILIZER ATTACHMENT			
DETAILED INSPECTION OF HORIZONTAL STABILIZER ATTACHMENT AND BACK UP STRUCTURE AT FR 77, FROM STRINGER 8 TO STRINGER 21, LH/RH			

535121-01-1	REAR PRESSURE BULKHEAD BLW CABIN FLOOR	Threshold	Interval
ATA : 53 Zone : 171, 172 Ref. Doc. : 535100-210-002 Effectivity : OM-BYA, OM-BYK			12 Years
REAR PRESSURE BULKHEAD BLW CABIN FLOOR			
DETAILED INSPECTION OF REAR PRESSURE BULKHEAD, FORWARD FACE, BELOW CABIN FLOOR LEVEL			

535123-01-1 REAR PRESSURE BULKHEAD ABV CABIN FLOOR		Threshold	Interval
ATA : 53 Zone : 261, 262 Ref. Doc. : 535100-210-008 Effectivity : OM-BYA, OM-BYK REAR PRESSURE BULKHEAD ABV CABIN FLOOR DETAILED INSPECTION OF REAR PRESSURE BULKHEAD, FORWARD FACE, ABOVE CABIN FLOOR LEVEL PREPARATION NOTE: GALLEYS; INSULATION REMOVED; TOILET REMOVAL/INSTALLATION ;		12 Years	12 Years
535126-01-1 FUSELAGE AND VERT STAB ATTACH FITTINGS		Threshold	Interval
ATA : 53 Zone : 323 Ref. Doc. : 535100-210-018 Effectivity : OM-BYA, OM-BYK FUSELAGE AND VERT STAB ATTACH FITTINGS GENERAL VISUAL INSPECTION OF FUSELAGE EXTERNAL SURFACE AND VERTICAL STABILIZER ATTACHMENT FITTING, UNDERNEATH VERTICAL STABILIZER/FUSELAGE FAIRINGS PREPARATION NOTE: FAIRINGS;		12 Years	12 Years
535151-01-1 TAIL CONE ATTACH FITTINGS		Threshold	Interval
ATA : 53 Zone : 311, 312, 313, 314 Ref. Doc. : 535100-210-009 Effectivity : OM-BYA, OM-BYK TAIL CONE ATTACH FITTINGS DETAILED INSPECTION OF TAIL CONE ATTACHMENT FITTINGS AT FR 77 AND FR 78		12 Years	12 Years

545104-01-1-1	NO.1 ENGINE PYLON LOWER SPAR UPPER SURFACE	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-027 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

NO.1 ENGINE PYLON LOWER SPAR UPPER SURFACE

DETAILED INSPECTION OF PYLON, LOWER SPAR, UPPER SURFACE, BETWEEN RIB 2 AND RIB 3, AND RIB 4 AND RIB 8

NOTE: THIS TASK MUST BE PERFORMED AT THE SAME TIME AS TASK 545104-02-1

545104-01-1-2	NO.2 ENGINE PYLON LOWER SPAR UPPER SURFACE	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-027 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

NO.2 ENGINE PYLON LOWER SPAR UPPER SURFACE

DETAILED INSPECTION OF PYLON, LOWER SPAR, UPPER SURFACE, BETWEEN RIB 2 AND RIB 3, AND RIB 4 AND RIB 8

NOTE: THIS TASK MUST BE PERFORMED AT THE SAME TIME AS TASK 545104-02-1

545104-02-1-1	NO.1 ENGINE PYLON LOWER SPAR UPPER SURFACE	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-028 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

NO.1 ENGINE PYLON LOWER SPAR UPPER SURFACE

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF PYLON, LOWER SPAR, UPPER SURFACE, BETWEEN RIB 1 AND RIB 2, AND RIB 3 AND RIB 4, AND RIB 8 AND RIB 10.

NOTE: THIS TASK MUST BE PERFORMED AT THE SAME TIME AS TASK 545104-01-1

545104-02-1-2	NO.2 ENGINE PYLON LOWER SPAR UPPER SURFACE	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-028 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)
NO.2 ENGINE PYLON LOWER SPAR UPPER SURFACE			
SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF PYLON, LOWER SPAR, UPPER SURFACE, BETWEEN RIB 1 AND RIB 2, AND RIB 3 AND RIB 4, AND RIB 8 AND RIB 10.			
NOTE: THIS TASK MUST BE PERFORMED AT THE SAME TIME AS TASK 545104-01-1			
545106-01-1-1	NO.1 ENGINE PYLON LWR SPAR	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-004 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
NO.1 ENGINE PYLON LWR SPAR			
DETAILED INSPECTION OF PYLON, LOWER SPAR, BETWEEN RIB 1 AND RIB 10, LOWER SURFACE			
545106-01-1-2	NO.2 ENGINE PYLON LWR SPAR	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-004 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)
NO.2 ENGINE PYLON LWR SPAR			
DETAILED INSPECTION OF PYLON, LOWER SPAR, BETWEEN RIB 1 AND RIB 10, LOWER SURFACE			
545107-01-3-1	NO.1 ENGINE AFT ATTACH BEAM	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-005 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years
ENGINE AFT ATTACH BEAM			
DETAILED INSPECTION OF ENGINE AFT ATTACHMENT BEAM			

545107-01-3-2	NO.2 ENGINE AFT ATTACH BEAM	Threshold	Interval
ATA : 54		24 Years	12 Years (+3 Months / -3 Months)
Zone : 425			
Ref. Doc. : 545100-200-005			
Effectivity : OM-BYA, OM-BYK			
ENGINE AFT ATTACH BEAM			
DETAILED INSPECTION OF ENGINE AFT ATTACHMENT BEAM			

545116-01-1-1	NO.1 ENGINE PYLON/WING ATTACH FITTING RIB4	Threshold	Interval
ATA : 54		12 Years	12 Years
Zone : 415			
Ref. Doc. : 545100-200-009			
Effectivity : OM-BYA, OM-BYK			
NO.1 ENGINE PYLON/WING ATTACH FITTING RIB4			
DETAILED INSPECTION OF SHACKLES, SLEEVES AND BOLTS OF PYLON TO WING ATTACHMENT FITTINGS AT RIB 4			
PREPARATION NOTE: BOLTS REMOVED; SHACKLES; SLEEVES; ENGINE REMOVED;			

545116-01-1-2	NO.2 ENGINE PYLON/WING ATTACH FITTING RIB4	Threshold	Interval
ATA : 54		12 Years	12 Years (+3 Months / -3 Months)
Zone : 425			
Ref. Doc. : 545100-200-009			
Effectivity : OM-BYA, OM-BYK			
NO.2 ENGINE PYLON/WING ATTACH FITTING RIB4			
DETAILED INSPECTION OF SHACKLES, SLEEVES AND BOLTS OF PYLON TO WING ATTACHMENT FITTINGS AT RIB 4			
PREPARATION NOTE: BOLTS REMOVED; SHACKLES; SLEEVES; ENGINE REMOVED;			

545117-01-1-1	NO.1 ENGINE PYLON SPIGOT	Threshold	Interval
ATA : 54		12 Years	12 Years
Zone : 415			
Ref. Doc. : 545100-200-010			
Effectivity : OM-BYA, OM-BYK			

NO.1 ENGINE PYLON SPIGOT

DETAILED INSPECTION OF PYLON SPIGOT RECEPTACLE UPPER SURFACE, INCLUDING FITTING BORE, AND UPPER SPAR SURROUNDING SURFACE

PREPARATION NOTE: BALL JOINT;

545117-01-1-2	NO.2 ENGINE PYLON SPIGOT	Threshold	Interval
ATA : 54		12 Years	12 Years (+3 Months / -3 Months)
Zone : 425			
Ref. Doc. : 545100-200-010			
Effectivity : OM-BYA, OM-BYK			

NO.2 ENGINE PYLON SPIGOT

DETAILED INSPECTION OF PYLON SPIGOT RECEPTACLE UPPER SURFACE, INCLUDING FITTING BORE, AND UPPER SPAR SURROUNDING SURFACE

PREPARATION NOTE: BALL JOINT;

545124-01-1-1	NO.1 ENGINE PYLON/WING AFT ATTACH FITTING SLEEVES	Threshold	Interval
ATA : 54		12 Years	12 Years
Zone : 415			
Ref. Doc. : 545100-200-014			
Effectivity : OM-BYA, OM-BYK			

NO.1 ENGINE PYLON/WING AFT ATTACH FITTING SLEEVES

DETAILED INSPECTION OF PYLON TO WING AFT ATTACHMENT FITTING, SLEEVES AND BOLTS

PREPARATION NOTE: BOLTS REMOVED; SHACKLES; SLEEVES; ENGINE REMOVED;

545124-01-1-2	NO.2 ENGINE PYLON/WING AFT ATTACH FITTING SLEEVES	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-014 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

NO.2 ENGINE PYLON/WING AFT ATTACH FITTING SLEEVES

DETAILED INSPECTION OF PYLON TO WING AFT ATTACHMENT FITTING, SLEEVES AND BOLTS

PREPARATION NOTE: BOLTS REMOVED; SHACKLES; SLEEVES; ENGINE REMOVED;

545170-01-1-1	NO.1 ENGINE PYLON PYRAMID MATING FACE	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-025 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years

NO.1 ENGINE PYLON PYRAMID MATING FACE

DETAILED INSPECTION OF PYLON, PYRAMID MATING FACE WITH THE ENGINE FORWARD MOUNT FITTING

PREPARATION NOTE: ENGINE REMOVED;

545170-01-1-2	NO.2 ENGINE PYLON PYRAMID MATING FACE	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-025 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

NO.2 ENGINE PYLON PYRAMID MATING FACE

DETAILED INSPECTION OF PYLON, PYRAMID MATING FACE WITH THE ENGINE FORWARD MOUNT FITTING

PREPARATION NOTE: ENGINE REMOVED;

545171-01-1-1	NO.1 ENGINE PYLON ENGINE AFT ATTACHMENT BEAM	Threshold	Interval
ATA : 54 Zone : 415 Ref. Doc. : 545100-200-026 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

NO.1 ENGINE PYLON ENGINE AFT ATTACHMENT BEAM

DETAILED INSPECTION OF PYLON, ENGINE AFT ATTACHMENT BEAM MATING FACE WITH THE ENGINE AFT MOUNT FITTING

PREPARATION NOTE: ENGINE REMOVED;

545171-01-1-2	NO.2 ENGINE PYLON ENGINE AFT ATTACHMENT BEAM	Threshold	Interval
ATA : 54 Zone : 425 Ref. Doc. : 545100-200-026 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years (+3 Months / -3 Months)

NO.2 ENGINE PYLON ENGINE AFT ATTACHMENT BEAM

DETAILED INSPECTION OF PYLON, ENGINE AFT ATTACHMENT BEAM MATING FACE WITH THE ENGINE AFT MOUNT FITTING

PREPARATION NOTE: ENGINE REMOVED;

551001-01-1	THS JACK FITTING	Threshold	Interval
ATA : 55 Zone : 333,343 Ref. Doc. : 551634-200-001 Effectivity : OM-BYA, OM-BYK			12 Years

THS JACK FITTING

DETAILED INSPECTION OF HORIZONTAL STABILIZER, JACK FITTING AND SURROUNDING EXTERNAL STRUCTURE

551012-01-1 THS SPARBOX INTERNAL STRUCTURE		Threshold	Interval
ATA : 55 Zone : 333, 343 Ref. Doc. : 551000-210-001 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
THS SPARBOX INTERNAL STRUCTURE			
DETAILED INSPECTION OF HORIZONTAL STABILIZER, INTERNAL STRUCTURE OF TORQUE BOX, INBOARD OF FUSELAGE FAIRINGS			
PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;			
551019-01-1 THS TORQUE BOX INTERNAL STRUCTURE		Threshold	Interval
ATA : 55 Zone : 333, 343 Ref. Doc. : 551000-210-002 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
THS TORQUE BOX INTERNAL STRUCTURE			
DETAILED INSPECTION OF HORIZONTAL STABILIZER, INTERNAL STRUCTURE OF TORQUE BOX, OUTBOARD OF FUSELAGE FAIRINGS, LH/RH			
PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;			
552004-01-1 ELEVATOR SKIN PANELS		Threshold	Interval
ATA : 55 Zone : 300 Ref. Doc. : 552000-200-001 Effectivity : OM-BYA, OM-BYK			12 Years
ELEVATOR SKIN PANELS			
SPECIAL DETAILED (TAP TEST) INSPECTION OF ELEVATOR, TOP AND BOTTOM SKIN PANELS IN AREA OF HINGE SUPPORTS 2, 3 AND 4 AND ACTUATOR FITTINGS 1 AND 2, LH/RH			

552005-01-1ELEVATOR PANELS INTERNAL STRUCTURE	Threshold	Interval
<div data-bbox="208 156 584 284">ATA : 55 Zone : 335, 345 Ref. Doc. : 552000-200-002 Effectivity : OM-BYA, OM-BYK</div> <div data-bbox="208 316 719 339">ELEVATOR PANELS INTERNAL STRUCTURE</div> <div data-bbox="208 368 1361 392">DETAILED INSPECTION OF ELEVATOR PANELS, INTERNAL STRUCTURE AS FAR AS VISIBLE, LH/RH</div> <div data-bbox="208 421 904 445">PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;</div>	12 Years	12 Years
552006-01-2ELEVATOR OUTBOARD RIB	Threshold	Interval
<div data-bbox="208 555 557 683">ATA : 55 Zone : 335, 345 Ref. Doc. : 552000-200-005 Effectivity : OM-BYA</div> <div data-bbox="208 715 526 738">ELEVATOR OUTBOARD RIB</div> <div data-bbox="208 767 848 823">DETAILED INSPECTION OF ELEVATOR OUTBOARD RIB, EXTERNAL SURFACE, LH/RH</div> <div data-bbox="208 852 645 876">PREPARATION NOTE: ELEVATOR TIP;</div>	12 Years	12 Years
553003-01-1VERT STABILIZER CENTER BOX	Threshold	Interval
<div data-bbox="208 986 584 1114">ATA : 55 Zone : 321, 322, 323, 324 Ref. Doc. : 553000-200-001 Effectivity : OM-BYA, OM-BYK</div> <div data-bbox="208 1145 580 1169">VERT STABILIZER CENTER BOX</div> <div data-bbox="208 1198 2161 1254">DETAILED INSPECTION OF VERTICAL STABILIZER, CENTER BOX, INTERNAL STRUCTURE AS FAR AS VISIBLE, FRONT SPAR FORWARD FACE AND UPPER CLOSING RIB, UPPER SURFACE</div> <div data-bbox="208 1283 904 1307">PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;</div>	12 Years	12 Years

554004-01-1 RUDDER SIDE PANELS INTERNAL SURFACES	Threshold	Interval
ATA : 55 Zone : 326 Ref. Doc. : 554000-210-003 Effectivity : OM-BYA, OM-BYK RUDDER SIDE PANELS INTERNAL SURFACES DETAILED INSPECTION OF RUDDER SIDE PANELS, INTERNAL SURFACES NOTE: ALTERNATIVE ACCESS: 325AR 325BR 325CR 325DR 325ER 326AT PREPARATION NOTE: PEELABLE HOLE COVERS REMOVED;	12 Years	12 Years
571109-01-1 CENTER WING BOX REAR SPAR	Threshold	Interval
ATA : 57 Zone : 147, 148 Ref. Doc. : 571000-200-004 Effectivity : Not Effective CENTER WING BOX REAR SPAR DETAILED INSPECTION OF CENTER WING BOX, REAR SPAR, AROUND ACCESS DOOR CUTOUTS	12 Years	12 Years (+3 Months / -3 Months)
571154-01-1 CENTER WING BOX LOWER SKIN	Threshold	Interval
ATA : 57 Zone : 191, 192, 195, 196 Ref. Doc. : 571000-200-019 Effectivity : OM-BYA, OM-BYK CENTER WING BOX LOWER SKIN DETAILED INSPECTION OF CENTER WING BOX, LOWER SKIN LOWER SURFACE, FROM FR 36 TO FR 42, BETWEEN RIB 1 LH AND RIB 1 RH, INCLUDING LOWER SPLICE AT RIB 1, AS FAR AS VISIBLE		12 Years

571155-01-1 CENTER WING BOX LOWER SKIN		Threshold	Interval
ATA : 57 Zone : 191, 192, 195, 196 Ref. Doc. : 571000-200-016 Effectivity : OM-BYA, OM-BYK CENTER WING BOX LOWER SKIN DETAILED INSPECTION OF CENTER WING BOX, LOWER SKIN LOWER SURFACE, FROM FR 36 TO FR 42 BETWEEN RIB 1 LH AND RIB 1 RH, COVERED BY VAPOR SEAL PREPARATION NOTE: AIR CONDITIONING PACKS; VAPOR SEAL (IF INSTALLED); HEAT SHIELDS REMOVED;		24 Years	12 Years
571156-01-1 CENTER WING BOX FRONT SPAR		Threshold	Interval
ATA : 57 Zone : 137, 138 Ref. Doc. : 571000-200-020 Effectivity : OM-BYA, OM-BYK CENTER WING BOX FRONT SPAR DETAILED INSPECTION OF CENTER WING BOX, FRONT SPAR, FORWARD FACE PREPARATION NOTE: FWD ACT(S) REMOVED (IF INSTALLED); LINING REMOVED; INSULATION REMOVED;		12 Years	12 Years
571157-01-1 CENTER WING BOX UPPER SKIN		Threshold	Interval
ATA : 57 Zone : 145, 146 Ref. Doc. : 571000-200-021 Effectivity : OM-BYA, OM-BYK CENTER WING BOX UPPER SKIN DETAILED INSPECTION OF CENTER WING BOX, UPPER SKIN UPPER SURFACE AND BEAMS, INCLUDING FRAME FEET BETWEEN FR 36 AND FR 42. NOTE: - CAN BE PERFORMED AT SAME TIME AS 533135-01-1 - TPS MAY BE LIMITED TO CENTER WING BOX, UPPER SKIN BEAMS, BETWEEN FR 36 AND FR 42 PREPARATION NOTE: CABIN FLOOR PANELS REMOVED;		12 Years	12 Years

571199-01-1 OUTER WING BOX EXTERNAL SURFACE	Threshold	Interval
ATA : 57 Zone : 540, 640 Ref. Doc. : 571000-200-022 Effectivity : OM-BYA, OM-BYK OUTER WING BOX EXTERNAL SURFACE DETAILED INSPECTION OF OUTER WING BOX, OUTBOARD SURFACE OF RIB 1 AND UPPER SURFACE OF TRIFORM FITTING, BETWEEN FRONT SPAR AND REAR SPAR	12 Years	12 Years
572002-01-1 OUTER WING FRONT SPAR ROOT JOINT FTG	Threshold	Interval
ATA : 57 Zone : 540, 640 Ref. Doc. : 572000-200-003 Effectivity : OM-BYA, OM-BYK OUTER WING FRONT SPAR ROOT JOINT FTG DETAILED INSPECTION OF OUTER WING, FRONT SPAR, AFT FACE, UPPER AND LOWER ROOT JOINT FITTINGS	24 Years	12 Years
572010-01-2 OUTER WING REAR SPAR ROOT JOINT FTG	Threshold	Interval
ATA : 57 Zone : 540, 640 Ref. Doc. : 572000-200-007 Effectivity : OM-BYA, OM-BYK OUTER WING REAR SPAR ROOT JOINT FTG DETAILED INSPECTION OF OUTER WING, REAR SPAR FORWARD FACE, UPPER AND LOWER ROOT JOINT FITTINGS.	24 Years	12 Years
572022-01-1 OUTER WING TOP SKIN LWR SURFACE	Threshold	Interval
ATA : 57 Zone : 521, 540, 621, 640 Ref. Doc. : 572000-200-011 Effectivity : OM-BYA, OM-BYK OUTER WING TOP SKIN LWR SURFACE DETAILED INSPECTION OF OUTER WING, TOP SKIN, LOWER SURFACE PYLON REINFORCING PLATE	12 Years	12 Years

572052-01-1	OUTER WING BOTTOM SKIN ROOT JOINT FTG	Threshold	Interval
ATA : 57 Zone : 540, 640 Ref. Doc. : 572000-200-025 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years (+3 Months / -3 Months)

OUTER WING BOTTOM SKIN ROOT JOINT FTG

DETAILED INSPECTION OF OUTER WING, BOTTOM SKIN ROOT JOINT FITTINGS ON STRINGER 8 AND STRINGER 11

572054-01-2	OUTER WING BOTTOM SKIN PUMP APERTURES	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 572000-200-002 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years

OUTER WING BOTTOM SKIN PUMP APERTURES

DETAILED INSPECTION OF OUTER WING, BOTTOM SKIN LOWER SURFACE AT FUEL PUMP APERTURES AND ADJACENT HOLES BETWEEN RIB 1 AND RIB 2

PREPARATION NOTE: FUEL PUMP;

572054-02-1-LH	LH OUTER WING BOTTOM SKIN PUMP APERTURES	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 572000-220-805 Effectivity : OM-BYA, OM-BYK			12 Years

LH OUTER WING BOTTOM SKIN PUMP APERTURES

DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN, LOWER SURFACE AT HOLES ADJACENT TO FUEL PUMP APERTURES BETWEEN RIB 1 AND RIB 2

TPS MUST NOT BE APPLIED

572054-02-1-RH	RH OUTER WING BOTTOM SKIN PUMP APERTURES	Threshold	Interval
ATA : 57 Zone : 600 Ref. Doc. : 572000-220-805 Effectivity : OM-BYA, OM-BYK			12 Years

RH OUTER WING BOTTOM SKIN PUMP APERTURES

DETAILED INSPECTION OF RH OUTER WING, BOTTOM SKIN, LOWER SURFACE AT HOLES ADJACENT TO FUEL PUMP APERTURES BETWEEN RIB 1 AND RIB 2

572101-01-2	OUTER WING FRT SPAR FWD FACE RIB 8-22	Threshold	Interval
ATA : 57 Zone : 522, 622 Ref. Doc. : 572100-200-006 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years

OUTER WING FRT SPAR FWD FACE RIB 8-22

DETAILED INSPECTION OF OUTER WING, FRONT SPAR FORWARD FACE, BETWEEN RIB 8 AND RIB 22, INCLUDING ALL CUTOUTS

572106-01-1	OUTER WING FRT SPAR FWD FACE RIB 22-27	Threshold	Interval
ATA : 57 Zone : 522, 622 Ref. Doc. : 572100-200-007 Effectivity : OM-BYA, OM-BYK		24 Years	12 Years (+3 Months / -3 Months)

OUTER WING FRT SPAR FWD FACE RIB 22-27

DETAILED INSPECTION OF OUTER WING, FRONT SPAR, FORWARD FACE BETWEEN RIB 22 AND RIB 27, INCLUDING ALL CUTOUTS.

572161-01-11	MAIN STRUCTURE	Threshold	Interval
ATA : 57 Zone : 540, 550, 560, 640, 650, 660 Ref. Doc. : 572100-200-030 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

MAIN STRUCTURE

DETAILED INSPECTION OF OUTER WING, BOTTOM SKIN, ACCESS DOORS BETWEEN RIB 13 AND RIB 27

572164-01-1-LH	LH OUTER WING BOTTOM SKIN FUEL DRAIN	Threshold	Interval
ATA : 57 Zone : 500 Ref. Doc. : 574100-200-005 Effectivity : OM-BYA, OM-BYK			12 Years

LH OUTER WING BOTTOM SKIN FUEL DRAIN

DETAILED INSPECTION OF LH OUTER WING, BOTTOM SKIN LOWER SURFACE AT FUEL TANK WATER DRAIN HOLES BETWEEN RIB 15-16 AND RIB 22-23.

572650-01-1	OUTER WING REAR SPAR SIDESTAY FITTING	Threshold	Interval
ATA : 57 Zone : 571, 671 Ref. Doc. : 572600-200-008 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

OUTER WING REAR SPAR SIDESTAY FITTING

DETAILED INSPECTION OF OUTER WING, REAR SPAR AFT FACE SIDESTAY FITTING

APPLICATION OF TPS TYPE 1 PLUS A SUBSEQUENT APPLICATION OF TPS TYPE 2

572652-01-1	OUTER WING	Threshold	Interval
ATA : 57 Zone : 571, 671 Ref. Doc. : 572600-210-802 Effectivity : Not Effective		12 Years	12 Years (+3 Months / -3 Months)

OUTER WING

GENERAL VISUAL INSPECTION OF OUTER WING, REAR SPAR, AFT FACE, FORWARD PINTLE FITTING

572653-01-1	FLAP TRACK 2 AFT ATTACH FITTINGS	Threshold	Interval
ATA : 57 Zone : 531, 532, 533, 631, 632, 633 Ref. Doc. : 572600-200-001 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

FLAP TRACK 2 AFT ATTACH FITTINGS

DETAILED INSPECTION OF OUTER WING, FLAP TRACK 2, AFT ATTACHMENT FITTINGS ON WING BOTTOM SKIN AT FALSE REAR SPAR, AND FLAP TRACK 3 & 4, AFT ATTACHMENT FITTINGS AT REAR SPAR

572656-01-1	OUTER WING PYLON SPIGOT	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 572600-200-002 Effectivity : Not Effective		24 Years	12 Years (+3 Months / -3 Months)

OUTER WING PYLON SPIGOT

DETAILED INSPECTION OF OUTER WING, PYLON SPIGOT FITTING

PREPARATION NOTE: BALL JOINT REMOVED; PYLON FAIRINGS REMOVED; SLEEVE REMOVED;

572657-01-1	OUTER WING PYLON AFT FITTING LUG	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 572600-200-003 Effectivity : Not Effective		24 Years	12 Years (+3 Months / -3 Months)

OUTER WING PYLON AFT FITTING LUG

DETAILED INSPECTION OF OUTER WING, AFT PYLON ATTACHMENT FITTING LUG

PREPARATION NOTE: PYLON FAIRINGS REMOVED;

572658-01-1	OUTER WING BOTTOM SKIN TRACK BEAM FTG	Threshold	Interval
ATA : 57		12 Years	12 Years (+3 Months / -3 Months)
Zone : 531, 532, 533, 631, 632, 633			
Ref. Doc. : 572600-200-009			
Effectivity : Not Effective			

OUTER WING BOTTOM SKIN TRACK BEAM FTG

DETAILED INSPECTION OF OUTER WING, BOTTOM SKIN LOWER SURFACE, FORWARD ATTACHMENT FITTING FOR FLAP TRACK BEAMS 2,3 & 4

574112-04-1-LH	LH WING LEADING EDGE	Threshold	Interval
ATA : 57			12 Years
Zone : 521, 522			
Ref. Doc. : AMM : 574100-210-802			
Effectivity : OM-BYA, OM-BYK			

LH WING LEADING EDGE

GENERAL VISUAL INSPECTION OF OUTER WING, FIXED LEADING EDGE, BOTTOM WING SKIN, UPPER SURFACE, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27 INCLUDING SIGHTING ROD HOLES IN RIB BAY 8-9 AND RIB BAY 26-27, LIFTING BEAM HOLES AND DRAIN HOLES.

574113-03-1-LH	LH WING - LEADING EDGE	Threshold	Interval
ATA : 57			12 Years
Zone : 521, 522			
Ref. Doc. : AMM : 574100-210-803			
Effectivity : OM-BYA, OM-BYK			

LH WING - LEADING EDGE

GENERAL VISUAL INSPECTION OF OUTER WING, FIXED LEADING EDGE, TOP WING SKIN, LOWER SURFACE, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27.

574113-03-1-RH	RH WING - LEADING EDGE	Threshold	Interval
ATA : 57 Zone : 621, 622 Ref. Doc. : AMM : 574100-210-803 Effectivity : OM-BYA, OM-BYK			12 Years

RH WING - LEADING EDGE

GENERAL VISUAL INSPECTION OF OUTER WING, FIXED LEADING EDGE, TOP WING SKIN, LOWER SURFACE, FORWARD OF FRONT SPAR, FROM RIB 1 TO RIB 27.

574204-01-1	SLAT 1 SKIN CONNECTIONS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574200-200-004 Effectivity : Not Effective		24 Years	12 Years (+3 Months / -3 Months)

SLAT 1 SKIN CONNECTIONS

DETAILED INSPECTION OF SLAT 1, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.

NOTE:

DETAILED INSPECTION IS OF EXTERNAL STRUCTURE OF SLAT 1.

PREPARATION NOTE: SLATS FULLY EXTENDED;

574204-02-1	SLAT 1 SKIN CONNECTIONS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574200-200-005 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

SLAT 1 SKIN CONNECTIONS

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF SLAT 1, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.

NOTE: SDET INSPECTION IS OF INTERNAL STRUCTURE OF SLAT 1 (ENDOSCOPE).

PREPARATION NOTE: SLATS FULLY EXTENDED;

574304-01-1 SLAT 2 SKIN CONNECTIONS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574300-200-002 Effectivity : Not Effective		12 Years	12 Years (+3 Months / -3 Months)
SLAT 2 SKIN CONNECTIONS DETAILED INSPECTION OF SLAT 2, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH NOTE: DET INSPECTION IS OF EXTERNAL STRUCTURE OF SLAT 2. PREPARATION NOTE: SLATS FULLY EXTENDED;			
574304-02-2 SLAT 2 SKIN CONNECTIONS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574300-200-003 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years
SLAT 2 SKIN CONNECTIONS SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF SLAT 2, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH. NOTE: SDET INSPECTION IS OF INTERNAL STRUCTURE OF SLAT 2. PREPARATION NOTE: SLATS FULLY EXTENDED;			
574404-01-1 SLAT 3 SKIN CONNECTIONS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574400-200-007 Effectivity : Not Effective		24 Years	12 Years (+3 Months / -3 Months)
SLAT 3 SKIN CONNECTIONS DETAILED INSPECTION OF SLAT 3, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH NOTE: DET INSPECTION IS OF EXTERNAL STRUCTURE OF SLAT 3. PREPARATION NOTE: SLATS FULLY EXTENDED;			

574404-02-1	SLAT 3 SKIN CONNECTIONS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574400-200-008 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

SLAT 3 SKIN CONNECTIONS

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF SLAT 3, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.

NOTE: SDET INSPECTION IS OF INTERNAL STRUCTURE OF SLAT 3.

PREPARATION NOTE: SLATS FULLY EXTENDED;

574504-01-1	SLAT 4 SKIN CONNECTIONS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574500-200-005 Effectivity : Not Effective		24 Years	12 Years (+3 Months / -3 Months)

SLAT 4 SKIN CONNECTIONS

DETAILED INSPECTION OF SLAT 4, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH

NOTE:
DET INSPECTION IS OF EXTERNAL STRUCTURE OF SLAT 4.

PREPARATION NOTE: SLATS FULLY EXTENDED;

574504-02-1	SLAT 4 SKIN CONNECTIONS	Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 574500-200-006 Effectivity : OM-BYA, OM-BYK		12 Years	12 Years

SLAT 4 SKIN CONNECTIONS

SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF SLAT 4, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.

NOTE: SDET INSPECTION IS OF INTERNAL STRUCTURE OF SLAT 4.

PREPARATION NOTE: SLATS FULLY EXTENDED;

574604-01-1 SLAT 5 SKIN CONNECTIONS	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 574600-200-005 Effectivity : Not Effective</p> <p>SLAT 5 SKIN CONNECTIONS</p> <p>DETAILED INSPECTION OF SLAT 5, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.</p> <p>NOTE: DETAILED INSPECTION IS OF EXTERNAL STRUCTURE OF SLAT 5.</p> <p>PREPARATION NOTE: SLATS FULLY EXTENDED;</p>	24 Years	12 Years (+3 Months / -3 Months)
574604-02-1 SLAT 5 SKIN CONNECTIONS	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 574600-200-006 Effectivity : OM-BYA, OM-BYK</p> <p>SLAT 5 SKIN CONNECTIONS</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF SLAT 5, SKIN CONNECTIONS IN AREA OF LOWER GIRDER AT TRACK RIB STATIONS, LH/RH.</p> <p>NOTE: SDET INSPECTION IS OF INTERNAL STRUCTURE OF SLAT 5.</p> <p>PREPARATION NOTE: SLATS FULLY EXTENDED;</p>	12 Years	12 Years
575101-01-1 TRAILING EDGE FLAP ACTUATOR BRACKETS	Threshold	Interval
<p>ATA : 57 Zone : 531, 532, 533, 631, 632, 633 Ref. Doc. : 575100-220-004 Effectivity : OM-BYA, OM-BYK</p> <p>TRAILING EDGE FLAP ACTUATOR BRACKETS</p> <p>DETAILED INSPECTION OF OUTER WING, TRAILING EDGE FLAP ACTUATOR BRACKETS AT FLAP TRACKS 2,3 AND 4</p>		12 Years

575104-01-1 TRAILING EDGE SPOILER 1 HINGE FITTINGS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 575100-220-006 Effectivity : OM-BYA, OM-BYK TRAILING EDGE SPOILER 1 HINGE FITTINGS DETAILED INSPECTION OF OUTER WING, TRAILING EDGE, SPOILER 1 ACTUATOR AND HINGE FITTINGS PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;			12 Years
575106-03-1 TRAILING EDGE SPOILERS HINGE PINS		Threshold	Interval
ATA : 57 Zone : 574, 575, 582, 583, 584, 585, 586, 674, 675, 682, 683, 684, 685, 686 Ref. Doc. : 575100-210-002 Effectivity : OM-BYA, OM-BYK TRAILING EDGE SPOILERS HINGE PINS DETAILED INSPECTION OF OUTER WING TRAILING EDGE SPOILERS 1,2,3,4 AND 5 HINGE PINS PREPARATION NOTE: PINS REMOVED;			12 Years
575119-01-1 TRAILING EDGE AILERON HINGE FITTINGS		Threshold	Interval
ATA : 57 Zone : 575, 590, 675, 690 Ref. Doc. : 575100-220-001 Effectivity : OM-BYA, OM-BYK TRAILING EDGE AILERON HINGE FITTINGS DETAILED INSPECTION OF OUTER WING, TRAILING EDGE, AILERON HINGE FITTINGS 1 TO 5 AND "A" FRAMES			12 Years

575140-01-1 FLAP TRACK 1		Threshold	Interval
ATA : 57 Zone : 147, 148 Ref. Doc. : 575100-200-003 Effectivity : OM-BYA, OM-BYK FLAP TRACK 1 DETAILED INSPECTION OF FLAP TRACK 1, INCLUDING ATTACHMENT BRACKETS TO FUSELAGE, STRUT, CARRIAGE AND SWINGING LINK (PENDULUM), LH/RH PREPARATION NOTE: FLAPS EXTENDED;			12 Years
575142-01-1 TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 147, 148 Ref. Doc. : 575100-200-004 Effectivity : OM-BYA, OM-BYK TRAILING EDGE DETAILED INSPECTION OF INBOARD FLAP, INBOARD ACTUATOR DRIVE ARM, DRIVE STRUT AND OUTER PART OF TRUNNION, LH/RH PREPARATION NOTE: FLAPS EXTENDED;			12 Years
575151-02-1-LH LH WING - TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 573, 574 Ref. Doc. : 575100-210-804 Effectivity : OM-BYA, OM-BYK LH WING TRAILING EDGE GENERAL VISUAL INSPECTION OF LH OUTER WING, TRAILING EDGE, FALSE REAR SPAR, FORWARD AND AFT FACES			12 Years

575203-01-1	Threshold	Interval
INBOARD FLAP TRUNNION ATTACH BRACKET ATA : 57 Zone : 581, 681 Ref. Doc. : 575200-200-007 Effectivity : OM-BYA, OM-BYK INBOARD FLAP TRUNNION ATTACH BRACKET DETAILED INSPECTION OF INBOARD FLAP, TRUNNION ATTACHMENT BRACKET INCLUDING INBOARD TRUNNION, LH/RH NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575203-02-1. PREPARATION NOTE: FLAPS EXTENDED; RUBBER SEALS;		12 Years
575203-02-1	Threshold	Interval
INBOARD FLAP TRUNNION ATTACH BRACKET ATA : 57 Zone : 581, 681 Ref. Doc. : 575200-220-006 Effectivity : OM-BYA, OM-BYK INBOARD FLAP TRUNNION ATTACH BRACKET SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF INBOARD FLAP, TRUNNION ATTACHMENT BRACKET INCLUDING INBOARD TRUNNION, LH/RH NOTE: - INSPECTION IS THROUGH INSPECTION HOLES - THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575203-01-1. PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;		12 Years
575205-01-1	Threshold	Interval
INBOARD FLAP DRIVE STRUT AND LEVER ATA : 57 Zone : 531, 581, 631, 681 Ref. Doc. : 575200-200-008 Effectivity : OM-BYA, OM-BYK INBOARD FLAP DRIVE STRUT AND LEVER DETAILED INSPECTION OF INBOARD FLAP, DRIVE STRUT FOR FLAP AND DRIVE LEVER FOR FLAP TRACK FAIRING, INCLUDING ATTACHMENT BRACKETS TO THE FLAP AND SURROUNDING SKIN AT TRACK 2, LH/RH PREPARATION NOTE: FLAPS EXTENDED;		12 Years

575206-01-1 INBOARD FLAP INTERNAL BRACKETS	Threshold	Interval
<p>ATA : 57 Zone : 581, 681 Ref. Doc. : 575200-220-008 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP INTERNAL BRACKETS</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF INBOARD FLAP, INTERNAL BRACKETS AT TRACK 2, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES</p> <p>PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;</p>		12 Years
575207-01-1 INBOARD FLAP CARRIAGE ATTACH BRACKET	Threshold	Interval
<p>ATA : 57 Zone : 531, 581, 631, 681 Ref. Doc. : 575200-200-009 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP CARRIAGE ATTACH BRACKET</p> <p>DETAILED INSPECTION OF INBOARD FLAP, FLAP TO CARRIAGE ATTACHMENT BRACKET AT TRACK 2, INCLUDING SURROUNDING SKIN, LH/RH</p> <p>PREPARATION NOTE: FLAPS EXTENDED;</p>		12 Years
575209-01-1 INBOARD FLAP ATTACH BRACKET OF FAIRING	Threshold	Interval
<p>ATA : 57 Zone : 477, 487, 581, 681 Ref. Doc. : 575200-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP ATTACH BRACKET OF FAIRING</p> <p>DETAILED INSPECTION OF INBOARD FLAP, ATTACHMENT BRACKET OF PYLON AFT FAIRING, INCLUDING SURROUNDING SKIN, LH/RH</p> <p>PREPARATION NOTE: PYLON FAIRINGS REMOVED;</p>		12 Years

575210-01-1 INBOARD FLAP INTERNAL SUPPORT BRACKET	Threshold	Interval
<p>ATA : 57 Zone : 581, 681 Ref. Doc. : 575200-200-003 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP INTERNAL SUPPORT BRACKET</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF INBOARD FLAP, INTERNAL SUPPORT BRACKET OF PYLON AFT FAIRING ATTACHMENT, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES</p> <p>PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;</p>		12 Years
575211-01-1 INBOARD FLAP END RIB	Threshold	Interval
<p>ATA : 57 Zone : 581, 681 Ref. Doc. : 575200-200-004 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP END RIB</p> <p>DETAILED INSPECTION OF INBOARD FLAP, END RIB, INCLUDING ROLLER AND INTERCONNECTION STRUT ATTACHMENT BRACKET, LH/RH</p> <p>PREPARATION NOTE: RUBBER SEALS; FLAPS EXTENDED;</p>		12 Years
575250-01-1 INBOARD FLAP TRACK 2 CARRIAGE	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 575200-200-005 Effectivity : OM-BYA, OM-BYK</p> <p>INBOARD FLAP TRACK 2 CARRIAGE</p> <p>DETAILED INSPECTION OF OUTER WING, INBOARD FLAP TRACK 2 CARRIAGE FORGING</p> <p>PREPARATION NOTE: FLAPS EXTENDED;</p>		12 Years

575307-01-1	OUTBOARD FLAP INBOARD RIB	Threshold	Interval
<p>ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-200-003 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP INBOARD RIB</p> <p>DETAILED INSPECTION OF OUTBOARD FLAP, INBOARD RIB, FORWARD SECTION INCLUDING ROLLER, INTERNAL AND EXTERNAL, LH/RH</p> <p>NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575307-02-1.</p> <p>PREPARATION NOTE: RUBBER SEALING REMOVED; FLAPS EXTENDED;</p>		12 Years	
575307-02-1	OUTBOARD FLAP INBOARD RIB	Threshold	Interval
<p>ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-002 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP INBOARD RIB</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, INBOARD RIB, FORWARD SECTION INCLUDING ROLLER, INTERNAL AND EXTERNAL, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575307-01-1.</p> <p>PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; RUBBER SEALS; FLAPS EXTENDED;</p>		12 Years	
575309-01-4	OUTBOARD FLAP SUPPORT TRACK 3	Threshold	Interval
<p>ATA : 57 Zone : 532, 587, 632, 687 Ref. Doc. : 575300-200-005 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP SUPPORT TRACK 3</p> <p>DETAILED INSPECTION OF OUTBOARD FLAP SUPPORT AT TRACK 3, INCLUDING RIB 5, FITTING ASSEMBLY AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH</p> <p>NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575309-02-4.</p> <p>PREPARATION NOTE: FLAPS EXTENDED;</p>		12 Years	

575309-02-4 OUTBOARD FLAP SUPPORT TRACK 3	Threshold	Interval
<p>ATA : 57 Zone : 532, 587, 632, 687 Ref. Doc. : 575300-220-004 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP SUPPORT TRACK 3</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP SUPPORT AT TRACK 3, INCLUDING RIB 5, FITTING ASSEMBLY AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575309-01-4.</p> <p>PREPARATION NOTE: FLAPS EXTENDED; COVER TAPES FROM INSPECTION HOLES REMOVED;</p>		12 Years
575311-01-1 OUTBOARD FLAP TRACK 3 DRIVE LINKAGE	Threshold	Interval
<p>ATA : 57 Zone : 532, 587, 632, 687 Ref. Doc. : 575300-200-007 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP TRACK 3 DRIVE LINKAGE</p> <p>DETAILED INSPECTION OF OUTBOARD FLAP, DRIVE LINKAGE AND DRIVE FITTING AT TRACK 3, LH/RH</p> <p>PREPARATION NOTE: FLAPS EXTENDED;</p>		12 Years
575312-02-4 OUTBOARD FLAP TRACK 3 INTERNAL SUPPORT	Threshold	Interval
<p>ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-005 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP TRACK 3 INTERNAL SUPPORT</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, INTERNAL SUPPORT AT TRACK 3, INCLUDING RIB 6, FITTING AT FRONT SPAR AND INTERNAL DOUBLER, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES.</p> <p>PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;</p>		12 Years

575313-01-1	OUTBOARD FLAP SUPPORT TRACK 4	Threshold	Interval
<div>ATA : 57</div> <div>Zone : 533, 587, 633, 687</div> <div>Ref. Doc. : 575300-200-011</div> <div>Effectivity : OM-BYK</div> <div>OUTBOARD FLAP SUPPORT TRACK 4</div> <div>DETAILED INSPECTION OF OUTBOARD FLAP, SUPPORT AT TRACK 4, INCLUDING RIB 14, FITTING ASSEMBLY, PENDULUM SUPPORT AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH</div> <div>NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575313-02-1.</div> <div>PREPARATION NOTE: FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;</div>			12 Years

575313-01-4	OUTBOARD FLAP SUPPORT TRACK 4	Threshold	Interval
<div>ATA : 57</div> <div>Zone : 533, 587, 633, 687</div> <div>Ref. Doc. : 575300-200-011</div> <div>Effectivity : OM-BYA</div> <div>OUTBOARD FLAP SUPPORT TRACK 4</div> <div>DETAILED INSPECTION OF OUTBOARD FLAP, SUPPORT AT TRACK 4, INCLUDING RIB 14, FITTING ASSEMBLY, PENDULUM SUPPORT AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH</div> <div>NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575313-02-4.</div> <div>PREPARATION NOTE: FLAPS EXTENDED;</div>			12 Years

575313-02-1	OUTBOARD FLAP SUPPORT TRACK 4	Threshold	Interval
ATA : 57 Zone : 533, 587, 633, 687 Ref. Doc. : 575300-220-010 Effectivity : OM-BYK OUTBOARD FLAP SUPPORT TRACK 4 SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, SUPPORT AT TRACK 4, INCLUDING RIB 14, FITTING ASSEMBLY, PENDULUM SUPPORT AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575313-01-1. PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;			12 Years

575313-02-4	OUTBOARD FLAP SUPPORT TRACK 4	Threshold	Interval
ATA : 57 Zone : 533, 587, 633, 687 Ref. Doc. : 575300-220-010 Effectivity : OM-BYA OUTBOARD FLAP SUPPORT TRACK 4 SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, SUPPORT AT TRACK 4, INCLUDING RIB 14, FITTING ASSEMBLY, PENDULUM SUPPORT AND ATTACHMENT STRUCTURE, INTERNAL AND EXTERNAL, LH/RH NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575313-01-4. PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;			12 Years

575315-01-1 OUTBOARD FLAP TRACK 4 DRIVE LINKAGE		Threshold	Interval
ATA : 57 Zone : 533, 587, 633, 687 Ref. Doc. : 575300-200-012 Effectivity : OM-BYK OUTBOARD FLAP TRACK 4 DRIVE LINKAGE DETAILED INSPECTION OF OUTBOARD FLAP, DRIVE LINKAGE AND DRIVE FITTING AT TRACK 4, LH/RH PREPARATION NOTE: FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;			12 Years
575315-01-4 OUTBOARD FLAP TRACK 4 DRIVE LINKAGE		Threshold	Interval
ATA : 57 Zone : 533, 587, 633, 687 Ref. Doc. : 575300-200-012 Effectivity : OM-BYA OUTBOARD FLAP TRACK 4 DRIVE LINKAGE DETAILED INSPECTION OF OUTBOARD FLAP, DRIVE LINKAGE AND DRIVE FITTING AT TRACK 4, LH/RH PREPARATION NOTE: FLAPS EXTENDED;			12 Years
575316-01-1 OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT		Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-200-013 Effectivity : OM-BYK OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT DETAILED INSPECTION OF OUTBOARD FLAP, INTERNAL SUPPORT AT TRACK 4 INCLUDING RIB 15, FITTING AT FRONT SPAR AND INTERNAL DOUBLER, LH/RH NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575316-02-1. PREPARATION NOTE: FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;			12 Years

575316-01-4	OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT	Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-200-013 Effectivity : OM-BYA			12 Years
OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT			
DETAILED INSPECTION OF OUTBOARD FLAP, INTERNAL SUPPORT AT TRACK 4, INCLUDING RIB 15, FITTING AT FRONT SPAR AND INTERNAL DOUBLER, LH/RH			
NOTE: THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575316-02-4.			
PREPARATION NOTE: FLAPS EXTENDED;			

575316-02-1	OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT	Threshold	Interval
ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-012 Effectivity : OM-BYK			12 Years
OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT			
SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, INTERNAL SUPPORT AT TRACK 4, INCLUDING RIB 15, FITTING AT FRONT SPAR AND INTERNAL DOUBLER, LH/RH			
NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575316-01-1.			
PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED; LEADING EDGE PANEL 5 REMOVED;			

575316-02-4 OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT	Threshold	Interval
<p>ATA : 57 Zone : 587, 687 Ref. Doc. : 575300-220-012 Effectivity : OM-BYA</p> <p>OUTBOARD FLAP TRACK 4 INTERNAL SUPPORT</p> <p>SPECIAL DETAILED INSPECTION (ENDOSCOPE) OF OUTBOARD FLAP, INTERNAL SUPPORT AT TRACK 4, INCLUDING RIB 15, FITTING AT FRONT SPAR AND INTERNAL DOUBLER, LH/RH</p> <p>NOTE: INSPECTION IS THROUGH INSPECTION HOLES. THIS TASK HAS TO BE PERFORMED THE SAME TIME AS TASK 575316-01-4.</p> <p>PREPARATION NOTE: COVER TAPES FROM INSPECTION HOLES REMOVED; FLAPS EXTENDED;</p>		12 Years
575350-01-1 OUTBOARD FLAP TACK 3-4 CARRIAGE	Threshold	Interval
<p>ATA : 57 Zone : 532, 533, 632, 633 Ref. Doc. : 575300-200-009 Effectivity : OM-BYA, OM-BYK</p> <p>OUTBOARD FLAP TRACK 3-4 CARRIAGE</p> <p>DETAILED INSPECTION OF OUTER WING OUTBOARD FLAP TRACK 3 AND 4 CARRIAGE FORGINGS</p> <p>PREPARATION NOTE: FLAPS EXTENDED;</p>		12 Years
576103-01-4 AILERON HINGE AND ACTUATOR FITTINGS	Threshold	Interval
<p>ATA : 57 Zone : 575, 675 Ref. Doc. : 576000-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>AILERON HINGE AND ACTUATOR FITTINGS</p> <p>DETAILED INSPECTION OF AILERON, HINGE FITTINGS AND ACTUATOR ATTACHMENT FITTINGS</p>		12 Years

576104-01-1 AILERON SKIN ATTACH TO TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 576000-200-003 Effectivity : OM-BYA, OM-BYK AILERON SKIN ATTACH TO TRAILING EDGE DETAILED INSPECTION OF AILERON, UPPER AND LOWER EXTERNAL SKINS AT ATTACHMENT TO TRAILING EDGE, INBOARD AND OUTBOARD EDGES, SPARS AND RIBS			12 Years
576106-01-1 AILERON UPPER AND LOWER SKINS		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 576000-210-001 Effectivity : OM-BYA, OM-BYK AILERON UPPER AND LOWER SKINS DETAILED INSPECTION OF AILERON, UPPER AND LOWER SKINS, EXTERNAL SURFACE			12 Years
577001-01-6 SPOILER 1 FITTING		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 577100-200-001 Effectivity : OM-BYA, OM-BYK SPOILER 1 FITTING DETAILED INSPECTION OF SPOILER 1, CENTER HINGE FITTING AND ACTUATOR BRACKET PREPARATION NOTE: FLAPS AND SPOILERS EXTENDED;			12 Years

577002-01-1 SPOILER 1 SKINS OF CENTER FITTING	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 577100-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>SPOILER 1 SKINS OF CENTER FITTING</p> <p>DETAILED INSPECTION OF SPOILER 1, UPPER AND LOWER SKINS, IN REGION OF CENTER HINGE FITTING</p> <p>PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;</p>		12 Years
577003-01-1 SPOILER 1 SKINS AT TRAILING EDGE	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 577100-200-003 Effectivity : OM-BYA, OM-BYK</p> <p>SPOILER 1 SKINS AT TRAILING EDGE</p> <p>DETAILED INSPECTION OF SPOILER 1, UPPER AND LOWER SKINS, AT TRAILING EDGE AND INBOARD AND OUTBOARD EDGES</p> <p>PREPARATION NOTE: SPOILERS EXTENDED;</p>		12 Years
577006-01-1 SPOILER 2-5 CENTRE FITTING	Threshold	Interval
<p>ATA : 57 Zone : 500, 600 Ref. Doc. : 577200-200-002 Effectivity : OM-BYA, OM-BYK</p> <p>SPOILER 2-5 CENTRE FITTING</p> <p>DETAILED INSPECTION OF SPOILER 2,3,4 AND 5, CENTER HINGE FITTINGS</p> <p>PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;</p>		12 Years

577007-01-1 SPOILER 2-5 SKINS OF CENTER FITTING		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 577500-200-001 Effectivity : OM-BYA, OM-BYK SPOILER 2-5 SKINS OF CENTER FITTING DETAILED INSPECTION OF SPOILER 2,3,4 AND 5, UPPER AND LOWER SKINS IN REGION OF CENTER HINGE FITTING PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;			12 Years
577008-01-1 SPOILER 2-5 SKINS AT TRAILING EDGE		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 577200-200-003 Effectivity : OM-BYA, OM-BYK SPOILER 2-5 SKINS AT TRAILING EDGE DETAILED INSPECTION OF SPOILER 2,3,4 AND 5, UPPER AND LOWER SKINS AT TRAILING EDGE AND INBOARD AND OUTBOARD EDGES PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;			12 Years
577009-01-1 SPOILERS 1 TO 5 EXTERNAL SURFACE		Threshold	Interval
ATA : 57 Zone : 500, 600 Ref. Doc. : 577100-210-001 Effectivity : OM-BYA, OM-BYK SPOILERS 1 TO 5 EXTERNAL SURFACE DETAILED INSPECTION OF SPOILERS 1 TO 5, UPPER AND LOWER SKINS, EXTERNAL SURFACE PREPARATION NOTE: FLAPS EXTENDED; SPOILERS EXTENDED;			12 Years

712111-02-1-LH	LH ENGINE FORWARD ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 435, 436, 451 Ref. Doc. : 712111-210-042 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE FORWARD ENGINE MOUNT

DETAILED INSPECTION OF DISASSEMBLED FORWARD ENGINE MOUNT INSTALLATION INCLUDING MATING SURFACES.

NOTE:

ACCOMPLISHMENT OF THIS INSPECTION TO BE PERFORMED WITH A MAXIMUM INTERVAL OF 12 YEARS BETWEEN MOUNT DISASSEMBLY

PREPARATION NOTE: ENGINE MOUNT DISASSEMBLED; ENGINE REMOVED;

712111-02-1-RH	RH ENGINE FORWARD ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 445, 446, 461 Ref. Doc. : 712111-210-042 Effectivity : OM-BYA, OM-BYK			12 Years

RH ENGINE FORWARD ENGINE MOUNT

DETAILED INSPECTION OF DISASSEMBLED FORWARD ENGINE MOUNT INSTALLATION INCLUDING MATING SURFACES.

NOTE:

ACCOMPLISHMENT OF THIS INSPECTION TO BE PERFORMED WITH A MAXIMUM INTERVAL OF 12 YEARS BETWEEN MOUNT DISASSEMBLY

PREPARATION NOTE: ENGINE MOUNT DISASSEMBLED; ENGINE REMOVED;

712211-01-1-LH	LH ENGINE AFT ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 451, 453, 454 Ref. Doc. : 712211-210-040 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE AFT ENGINE MOUNT

DETAILED INSPECTION OF DISASSEMBLED AFT ENGINE MOUNT INSTALLATION INCLUDING MATING SURFACES.

NOTE:

ACCOMPLISHMENT OF THIS INSPECTION TO BE PERFORMED WITH A MAXIMUM INTERVAL OF 12 YEARS BETWEEN MOUNT DISASSEMBLY

PREPARATION NOTE: ENGINE MOUNT DISASSEMBLED; ENGINE REMOVED;

712211-01-1-RH	RH ENGINE AFT ENGINE MOUNT	Threshold	Interval
ATA : 71 Zone : 461, 463, 464 Ref. Doc. : 712211-210-040 Effectivity : OM-BYA, OM-BYK			12 Years

RH ENGINE AFT ENGINE MOUNT

DETAILED INSPECTION OF DISASSEMBLED AFT ENGINE MOUNT INSTALLATION INCLUDING MATING SURFACES.

NOTE:

ACCOMPLISHMENT OF THIS INSPECTION TO BE PERFORMED WITH A MAXIMUM INTERVAL OF 12 YEARS BETWEEN MOUNT DISASSEMBLY

PREPARATION NOTE: ENGINE MOUNT DISASSEMBLED; ENGINE REMOVED;

783001-01-2-LH	LH ENGINE THRUST REV 12 O'CLOCK BEAM JUNCTION	Threshold	Interval
ATA : 78 Zone : 451, 452 Ref. Doc. : 783200-210-044 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE THRUST REV 12 O'CLOCK BEAM JUNCTION

DETAILED INSPECTION OF THRUST REVERSER 12 O'CLOCK BEAM JUNCTION WITH THE FORWARD FRAME

PREPARATION NOTE: CUT CORNERS REMOVED;

783001-01-2-RH	RH ENGINE THRUST REV 12 O'CLOCK BEAM JUNCTION	Threshold	Interval
ATA : 78 Zone : 461, 462 Ref. Doc. : 783200-210-044 Effectivity : OM-BYA, OM-BYK			12 Years
RH ENGINE THRUST REV 12 O'CLOCK BEAM JUNCTION			
DETAILED INSPECTION OF THRUST REVERSER 12 O'CLOCK BEAM JUNCTION WITH THE FORWARD FRAME			
PREPARATION NOTE: CUT CORNERS REMOVED;			

783002-01-2-LH	LH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 451, 452 Ref. Doc. : 783200-210-041 Effectivity : OM-BYA, OM-BYK			12 Years
LH ENGINE THRUST REVERSER FORWARD FRAME			
DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME TO 6 O'CLOCK BEAM JOINT			
PREPARATION NOTE: CUT CORNERS REMOVED;			
CAMO NOTE: 7.0MM HOLE ON THE 6 O'CLOCK CUT CORNER PANEL (SIDE WALL) ALLOWING BSI HAS BEEN MADE IAW ROHR SB 54-30-00 JULY 2021 CSAT PRG (OM-BYK ONLY).			

783002-01-2-RH	RH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 461, 462 Ref. Doc. : 783200-210-041 Effectivity : OM-BYA, OM-BYK			12 Years
RH ENGINE THRUST REVERSER FORWARD FRAME			
DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME TO 6 O'CLOCK BEAM JOINT			
PREPARATION NOTE: CUT CORNERS REMOVED;			
CAMO NOTE: 7.0MM HOLE ON THE 6 O'CLOCK CUT CORNER PANEL (SIDE WALL) ALLOWING BSI HAS BEEN MADE IAW ROHR SB 54-30-00 JULY 2021 CSAT PRG (OM-BYK ONLY).			

783003-01-2-LH	LH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 451, 452 Ref. Doc. : 783200-210-042 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE THRUST REVERSER FORWARD FRAME

DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME TO 3/9 O'CLOCK BEAM JOINT

PREPARATION NOTE: BRACKETS AND PIPES REMOVED; HEAT SHIELDS REMOVED;

783003-01-2-RH	RH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 461, 462 Ref. Doc. : 783200-210-042 Effectivity : OM-BYA, OM-BYK			12 Years

RH ENGINE THRUST REVERSER FORWARD FRAME

DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME TO 3/9 O'CLOCK BEAM JOINT

PREPARATION NOTE: BRACKETS AND PIPES REMOVED; HEAT SHIELDS REMOVED;

783004-02-1-LH	LH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 451, 452 Ref. Doc. : 783200-210-046 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE THRUST REVERSER FORWARD FRAME

DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME AT ACTUATOR ATTACHMENT

PREPARATION NOTE: ACTUATORS REMOVED;

783004-02-1-RH	RH ENGINE THRUST REVERSER FORWARD FRAME	Threshold	Interval
ATA : 78 Zone : 461, 462 Ref. Doc. : 783200-210-046 Effectivity : OM-BYA, OM-BYK			12 Years

RH ENGINE THRUST REVERSER FORWARD FRAME

DETAILED INSPECTION OF THRUST REVERSER FORWARD FRAME AT ACTUATOR ATTACHMENT

PREPARATION NOTE: ACTUATORS REMOVED;

783200-02-1-LH	LH ENGINE "C" DUCT HINGE FITTING	Threshold	Interval
ATA : 78 Zone : 415, 425, 451 Ref. Doc. : 783200-210-827 Effectivity : OM-BYA, OM-BYK			12 Years

LH ENGINE "C" DUCT HINGE FITTING

DETAILED INSPECTION OF "C" DUCT HINGE FITTINGS AND SURROUNDING STRUCTURE.

PREPARATION NOTE: UPPER HINGE ACCESS FAIRING;

783200-02-1-RH	RH ENGINE "C" DUCT HINGE FITTING	Threshold	Interval
ATA : 78 Zone : 452, 461, 462 Ref. Doc. : 783200-210-827 Effectivity : OM-BYA, OM-BYK			12 Years

RH ENGINE "C" DUCT HINGE FITTING

DETAILED INSPECTION OF "C" DUCT HINGE FITTINGS AND SURROUNDING STRUCTURE.

PREPARATION NOTE: UPPER HINGE ACCESS FAIRING;



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

24 YE STRUCTURAL CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 1

533130-01-1	ANTI COLLISION LIGHT SKIN CUTOUT	Threshold	Interval
ATA : 53		24 Years	12 Years
Zone : 200			
Ref. Doc. : 533100-210-010			
Effectivity : OM-BYA, OM-BYK			

ANTI COLLISION LIGHT SKIN CUTOUT

DETAILED INSPECTION OF SKIN AROUND ANTI COLLISION LIGHT CUTOUT, BETWEEN FR 40 AND FR 41 AND BETWEEN STRINGER 1, LH/RH, EXTERNAL SURFACE

PREPARATION NOTE: COVER OF ANTI-COLLISION LIGHT AND ANTI-COLLISION LIGHT REMOVED;



Maintenance Program

SSG-AMP-A319 (LUMP) ISSUE 1 REV 0

5 YE CHECK



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 9

254000-03-1	LAVATORIES	Threshold	Interval
ATA : 25			5 Years
Zone : 200			
Ref. Doc. : 254000-220-001			
Effectivity : OM-BYK			

LAVATORIES

DETAILED INSPECTION OF LAVATORY WALL AND LOWER ATTACHMENT POINTS.

282800-18-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28			5 Years
Zone : 150			
Ref. Doc. : 282800-790-004			
Effectivity : OM-BYA, OM-BYK			

ADDITIONAL CENTER TANK TRANSFER SYSTEM

FUNCTIONAL CHECK OF THE VENT/TRANSFER PIPE SHROUDS AND ACT DRAIN PIPE CONNECTORS

282800-61-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28			5 Years
Zone : 148			
Ref. Doc. : 282800-710-015			
Effectivity : OM-BYA, OM-BYK			

ADDITIONAL CENTER TANK TRANSFER SYSTEM

REMOVE AND CARRY OUT OPERATIONAL CHECK OF VENT LINE CHECK VALVES

282800-62-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28 Zone : 130 Ref. Doc. : 282800-710-010 Effectivity : OM-BYA, OM-BYK			5 Years
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
OPERATIONAL CHECK OF FORWARD ACT VENT ISOLATION VALVE			
NOTE: INTERVAL: - IF ACT NO 4 IS NOT FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT NO 4 INSTALLATION.			

282800-63-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28 Zone : 150 Ref. Doc. : 282800-710-011 Effectivity : OM-BYA, OM-BYK			5 Years
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
OPERATIONAL CHECK OF ACT 4 OVERPRESSURE PROTECTOR			
NOTE: IF ACT NO 4 IS NOT FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT NO 4 INSTALLATION.			
PREPARATION NOTE: ACT(S) NO.4 AND NO.6 REMOVED (IF INSTALLED);			

282800-64-1	ADDITIONAL CENTER TANK TRANSFER SYSTEM	Threshold	Interval
ATA : 28 Zone : 150 Ref. Doc. : 282800-710-012 Effectivity : OM-BYA, OM-BYK			5 Years
ADDITIONAL CENTER TANK TRANSFER SYSTEM			
OPERATIONAL CHECK OF FORWARD ACT ISOLATION VALVE			
NOTE: INTERVAL: - IF ACT NO 4 IS NOT FITTED WHEN TASK BECOMES DUE, TASK MAY BE POSTPONED UNTIL NEXT ACT NO 4 INSTALLATION.			

361100-01-1ENGINE BLEED AIR SUPPLY SYSTEM	Threshold	Interval
ATA : 36 Zone : 450, 460 Ref. Doc. : 361153-720-001 Effectivity : OM-BYA, OM-BYK Tags : ETOPS SIGNIFICANT SYSTEM		5 Years

ENGINE BLEED AIR SUPPLY SYSTEM

FUNCTIONAL CHECK OF OVERPRESSURE VALVE.

526000-02-1ENTRANCE STAIRS	Threshold	Interval
ATA : 52 Zone : 221 Ref. Doc. : 526100-710-002 Effectivity : OM-BYA, OM-BYK		5 Years

ENTRANCE STAIRS

OPERATIONAL CHECK OF MANUAL RELEASE MECHANISM

526000-04-1ENTRANCE STAIRS	Threshold	Interval
ATA : 52 Zone : 129 Ref. Doc. : 526100-210-002 Effectivity : OM-BYA, OM-BYK		5 Years

ENTRANCE STAIRS

CHECK OF CABLES FOR PRELOAD AND CONDITION