



# Maintenance Program

## SSG-F100-AMP Rev.1

### Phase 04



Category : All Categories

Chapters: All Chapters

Effectivity : All Tasks

Total : 20

250000-SSG-01 FIRST AID / MEDICAL KIT CHECK	Threshold	Interval
<p>ATA : 25            Zone : 200            Ref. Doc. : N/A            Effectivity : OM-BYB, OM-BYC</p> <p>FIRST AID / MEDICAL KIT CHECK</p> <p>CHECK FIRST AID KIT AND MEDICAL KIT FOR PROPER SEALING ( 2 EA FIRST AID KIT, 1 EA MEDICAL KIT ).            CHECK AND RECORD DUE (EXPIRY) DATES:</p> <p>#1 FIRST AID KIT DUE DATE : .....</p> <p>#2 FIRST AID KIT DUE DATE : .....</p> <p>MEDICAL KIT KIT DUE DATE : .....</p>		<p>6 Months            (+18 Days / -18 Days)</p>
250000-SSG-02 LIFE VESTS CHECK	Threshold	Interval
<p>ATA : 25            Zone : 200            Ref. Doc. : N/A            Effectivity : OM-BYB, OM-BYC</p> <p>LIFE VESTS</p> <p>CHECK CREW, PAX, INFANT AND SPARE LIFE VESTS FOR COMPLETENES AND PROPER STOWAGE</p>		<p>6 Months            (+18 Days / -18 Days)</p>
256102-00-01-1 LH ESCAPE SLIDE	Threshold	Interval
<p>ATA : 25            Zone : 811            Ref. Doc. : AMM 25-61-00-200-826            Effectivity : OM-BYB, OM-BYC</p> <p>LH ESCAPE SLIDE</p> <p>CHECK CORRECT PRESSURE ON GAUGE OF LH ESCAPE SLIDE BOTTLE.</p>		<p>600 Hours            6 Months            (+18 Days / -18 Days)</p>

256102-00-01-2 RH ESCAPE SLIDE	Threshold	Interval
ATA : 25 Zone : 821 Ref. Doc. : AMM 25-61-00-200-826 Effectivity : OM-BYB, OM-BYC  RH ESCAPE SLIDE  CHECK CORRECT PRESSURE ON GAUGE OF RH ESCAPE SLIDE BOTTLE.		600 Hours 6 Months (+18 Days / -18 Days)
262400-00-01 BCF TYPE EXTINGUISHING	Threshold	Interval
ATA : 26 Zone : 200 Ref. Doc. : AMM 26-24-00-200-836 Effectivity : OM-BYB, OM-BYC  BCF TYPE EXTINGUISHING  VISUAL CHECK OF SEAL WIRE OR RED DISK ON PORTABLE BCF BOTTLE EXTINGUISHER HEAD. NOTE : PERFORM THIS TASK IN ZONES 240, 250, 260, 290 AND 811		300 Hours 6 Months (+18 Days / -18 Days)
271300-00-02 FLIGHT CONTROL ELECTRICAL	Threshold	Interval
ATA : 27 Zone : 253 Ref. Doc. : AMM 27-00-00-710-815 Effectivity : OM-BYB, OM-BYC  FLIGHT CONTROL ELECTRICAL  OPERATIONAL CHECK OF FLIGHT CONTROLS SERVO VALVE STICKING CIRCUIT. NOTE : PERFORM THIS TASK IN ZONES 213 AND 253.		500 Hours 6 Months (+18 Days / -18 Days)
273500-00-03 STALL WARNING	Threshold	Interval
ATA : 27 Zone : 126 Ref. Doc. : AMM 27-35-00-220-816 Effectivity : OM-BYB, OM-BYC  STALL WARNING  CHECK PRESSURE BOTTLES NITROGEN PRE-CHARGE.		250 Hours 6 Months (+18 Days / -18 Days)

274300-00-02 HORIZONTAL STABILIZER SYSTEM	Threshold	Interval
ATA : 27 Zone : 253 Ref. Doc. : AMM 27-43-00-710-825 Effectivity : OM-BYB, OM-BYC  HORIZONTAL STABILIZER SYSTEM  OPERATIONAL CHECK OF STABILIZER SERVO VALVE STICKING CIRCUIT.		500 Hours 6 Months (+18 Days / -18 Days)
276400-00-03 LIFTDUMPERS HYDRAULIC CONTROL	Threshold	Interval
ATA : 27 Zone : 177 Ref. Doc. : AMM 27-64-02-600-816 Effectivity : OM-BYB, OM-BYC  LIFTDUMPERS HYDRAULIC CONTROL  VISUAL CHECK PRE-CHARGE OF LIFTDUMPER ACCUMULATORS.		600 Hours 6 Months (+18 Days / -18 Days)
281400-01-05 AUXILIARY TANK	Threshold	Interval
ATA : 28 Zone : 178 Ref. Doc. : AMM 28-14-00-720-815 Effectivity : OM-BYB, OM-BYC  AUXILIARY TANK  FUNCTIONAL CHECK OF AFTS VENT/OVERFLOW VALVE ISOLATION RELAYS.		600 Hours 6 Months (+18 Days / -18 Days)
281400-01-06 AUXILIARY TANK	Threshold	Interval
ATA : 28 Zone : 178 Ref. Doc. : AMM 28-14-00-720-825 Effectivity : OM-BYB, OM-BYC  AUXILIARY TANK  FUNCTIONAL CHECK OF WING TANK OVERPRESSURE PROTECTION SYSTEM OF THE AFTS.		600 Hours 6 Months (+18 Days / -18 Days)

281400-01-07	AUXILIARY TANK	Threshold	Interval
ATA : 28 Zone : 178 Ref. Doc. : AMM 28-14-00-720-835 Effectivity : OM-BYB, OM-BYC  AUXILIARY TANK  FUNCTIONAL CHECK OF AFTS TANK OVERPRESSURE RELIEF VALVES, BLEED AIR TANK PRESSURIZATION SYSTEM AND FUEL/NO-AIR VALVES.		600 Hours 6 Months (+18 Days / -18 Days)	
304100-01-01	WINDSHIELD ANTI-ICING	Threshold	Interval
ATA : 30 Zone : 254 Ref. Doc. : AMM 30-45-00-710-825 Effectivity : OM-BYB, OM-BYC  WINDSHIELD ANTI-ICING  VISUAL CHECK "WINDOW ANTI-ICING" INDICATION ON MTP/CFDU.		300 Hours 6 Months (+18 Days / -18 Days)	
324500-00-03	PARKING BRAKE MECHANISM	Threshold	Interval
ATA : 32 Zone : 220 Ref. Doc. : AMM 32-44-06-710-815 Effectivity : OM-BYB, OM-BYC  PARKING BRAKE MECHANISM  OPERATIONAL CHECK OF PARKING BRAKE SHUT-OFF VALVE.		600 Hours 6 Months (+18 Days / -18 Days)	
335000-00-03	EMERGENCY LIGHTING	Threshold	Interval
ATA : 33 Zone : 200 Ref. Doc. : AMM 33-52-00-710-835 Effectivity : OM-BYB, OM-BYC  EMERGENCY LIGHTING  OPERATIONAL CHECK OF STANDBY LIGHTING.		150 Hours 6 Months (+18 Days / -18 Days)	

VIP-332401-00-01 VIP LAVATORY ILLUMINATED SIGNS	Threshold	Interval
ATA : 33 Zone : 262 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  VIP LAVATORY ILLUMINATED SIGNS  OPERATIONAL TEST OF THE RETURN TO CABIN SIGN		6 Months (+18 Days / -18 Days)

VIP-332402-00-01 PASSENGER ILLUMINATED SIGNS	Threshold	Interval
ATA : 33 Zone : 200 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  PASSENGER ILLUMINATED SIGNS  OPERATIONAL TEST OF THE ASSEMBLY PASSENGER ILLUMINATED SIGN		6 Months (+18 Days / -18 Days)

VIP-332701-71-01 FURNITURE DECORATIVE LIGHT	Threshold	Interval
ATA : 33 Zone : 200 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  FURNITURE DECORATIVE LIGHT  OPERATIONAL TEST OF FURNITURE DECORATIVE LIGHT		6 Months (+18 Days / -18 Days)

VIP-332702-71-01 CORNER LIGHT	Threshold	Interval
ATA : 33 Zone : 200 Ref. Doc. : Effectivity : OM-BYB, OM-BYC  CORNER LIGHT  OPERATIONAL TEST OF CORNER LIGHT		6 Months (+18 Days / -18 Days)

527100-00-02 DOOR LOCK WARNING	Threshold	Interval
ATA : 52 Zone : 254 Ref. Doc. : AMM 52-70-00-220-816 Effectivity : OM-BYB, OM-BYC  DOOR LOCK WARNING  CHECK DOOR WARNING WIRING SHORT CIRCUIT INDICATION.		500 Hours 6 Months (+18 Days / -18 Days)