

plot

1.13

6.98

2.00

169.47

9.59

9.54

169.49

8.00

169.47

166.00

2.5%

zatravnenie
zahumusovanie 0,15m

S0303

Technical drawing of a road cross-section showing a drainage ditch and a road profile. The drawing includes a green line for the ground profile, a red line for the road surface, and a dashed red line for the ditch. Key features include a drainage ditch with a width of 0.15m, a road width of 169.00m, and a road grade of 3%. The drawing is labeled "SPOMACOVACÍ PRAH" and "Lovinského ulice".

Technical drawing of a road profile. The horizontal axis shows distances: 0.86, 1.51, 1.50, 0.20, 6.50, 3.34, 1.76, and 2.94. The vertical axis shows elevations: 173.29, 173.25, 173.17, 173.06, 173.08, 172.91, 172.93, 172.512/6.795, and 172.339/8.039. A red line represents the road profile, and a green line represents the existing ground. A vehicle labeled 'SO 502' is shown on the road. The profile includes a 5.13% grade, a 0.5% grade, a 22.69% grade, and a 13.9% grade. A vertical curve is indicated by a dashed red line at elevation 173.08. The drawing is labeled '170.00' and 'area BV'.

Technical drawing showing a road profile with elevations and distances. The profile is marked with a green line (existing ground) and a red line (proposed road). Key elevations are 173.64, 173.50, 173.32, 173.18, 172.93, and 172.67. Distances between points are 3.36, 7.47, 4.52, 5.52, 26.75, and 16.71. A vertical curve is indicated with a 4.71% grade and a 1.88% grade. A dashed red line indicates a vertical curve point. A blue line segment is labeled 'existující chodník' (existing sidewalk). A scale bar at the bottom shows 170.00.