

1		2		3		4	
Netolované rozměry délek ISO 2768-mK		Netolované rozměry úhlů ISO 2768-mK		Ra 6,3 ✓ (✓)			
Rozsah [mm]	Úchylky [mm]	Délka odvěsny [mm]	Úchylky [°]				
od 2000 do 4000	±2	přes 400	±0°5'				
od 1000 do 2000	±1,2	od 120 do 400	±0°10'				
od 400 do 1000	±0,8	od 50 do 120	±0°20'				
od 120 do 400	±0,5	od 10 do 50	±0°30'				
od 30 do 120	±0,3	do 10	±1°				
od 6 do 30	±0,2						
od 0,5 do 6	±0,1						
A				A			
B				B			
C				C			
D				D			
E				E			
F				F			
TVAR DLE 2D/3D DAT							
ODJEHLIT							
REV.		POPIS / DESCRIPTION		SCHVALIL / APPROVED		DATUM / DATE	
Materiál: Material:		1.0036 / S235JRG1		Povrchová úprava: Surface treatment:		Bez povrchové úpravy	
Hmotnost (kg): Mass (kg):		0,83		Název: Title:			
Štěpánská 34 110 00 Praha 1 www.ice.cz		ICE		ŽEBRO			
Tato technická dokumentace je duševním vlastnictvím firmy ICE Industrial Services a.s.. Bez souhlasu vlastníka nesmí být kopírována, publikována ani poskytnuta třetí osobě. This technical documentation is the intellectual property of the company ICE Industrial Services a.s.. Copying, publishing or disclosure to third parties without the expressed permission of the owner is forbidden.				Číslo výkresu: Drawing No.:		Revize: Revision:	
Navrhl: Designed:		Dalibor Kunc		TaO-00027		00	
Datum: Date:		18.09.2025					
Schválil: Approved:		Dalibor Kunc					
Datum: Date:		10.10.2025					
1		2		3		4	