




Item	Reference	Description	QTY
1		PIPE DN350 THICKNESS 5mm AISI-316L EN 10217-7 (WELDED)	5,5 m
2		TRANSFORMATION Ø350 - DN350 THICKNESS 5mm AISI-316L	1
3		ELBOW 90° DN350 THICKNESS 5mm SHORT RADIUS 1.5D AISI-316L EN10253-1	2
4		ELBOW 90° DN350 THICKNESS 5mm RADIUS 3D AISI-316L EN10253-1	1
5		ELBOW 45° DN350 THICKNESS 5mm RADIUS 3D AISI-316L EN10253-1	2
6		ELBOW 30° DN350 THICKNESS 5mm RADIUS 3D AISI-316L EN10253-1	2
7		FLAT FLANGE DN350 PN10 THICKNESS 8mm AISI-316L (INSERTEC FLANGE)	8
8		GASKET DN350 PN10 3mm CERAMIC FIBRE	5
9		BOLT M24x60 A4-80 DIN933	80
10		NUT M24 A4-80 DIN934	80
11		FLAT WASHER M24 A4 DIN125	160
12		GROWER WASHER M24 A4 DIN127	80
13		BOLT M10x40 A4-80 DIN933	8
14		NUT M10 A4-80 DIN934	8
15		FLAT WASHER M10 A4 DIN125	16
16		GROWER WASHER M10 A4 DIN127	8
17		INSULATION TYPE PERSONAL PROTECTION: 50 MM THICKNESS STONE WOOL ACCORDING TO ISOVER TECH WIRED MAT MT 3.1. AND 0.8 MM ALUMINUM CLADDING	9,3 m

This drawing is property of INSERTEC. Must not be copied or transferred to third parties in any way without written

Rev.	Modification								Date	Name			
erty of INTERTEC. Must not be copied or transferred to third parties in any way without written B.													
Tolerance for dimensions without tol. according to ISO 2768-mK									Date	Name	Material		
More than	0.5	3	6	30	120	400	1000	2000	Drawn	03/12/2025	RCB	AISI 316L	
Less	3	6	30	120	400	1000	2000	4000	Checked		JMR	Weight (kg)	
Machine Tool	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	Verified		BU	103.11	
Welded		±0.5	±1	±1.5	±2	±3	±4	±6	Title TMT25#1 COMBUSTION AIR SYSTEM EXHAUST ROUTE				
Customer:	2558-ALINVEST												Format: A2
													Scale: 1:15
 									Project Method:		Part Number		Revision
											2558-3321-TMT-ESR90-GEN01-91		A
											Customer Number		Sheet 1/1