



DEVIÁTOR - TYP 2 - BETO	
časť	kód

SKA VÝSTUŽ			5144
------------	--	--	------

POL.	OCEC	Ø (mm)	DĚŽKA (mm)	MET.	POČET (ks)	CELKOVÁ DĚŽKA (ks)	TVAROVÝ KÓD	KONCOVÝ HÁK	ROZMĚRY OHYBIV										INDEX	HMOTNOST (kg)
									(mm)											
									a	b	c	d	e	R	h					
1	B5008	12	1,259	8	68	68,432	31	2	2	232	332	232	332				139	53,664		
2	B5008	12	2,555	6	15	33,900	35	0	0	654	1197	191	556	1155				13,613		
3	B5008	12	2,688	8	12	31,296	21	0	0	656	1346	656						27,791		
4	B5008	12	3,290	8	12	39,480	00	0	0	3290								35,058		
5	B5008	12	3,600	8	12	43,200	00	0	0	3600								38,362		
6	B5008	12	4,611	8	44	202,884	31	2	2	1370	870	1370	870				139	186,161		
7	B5008	12	3,495	8	2	6,990	31	2	2	870	870	870	870				139	6,207		
8	B5008	12	3,405	8	96	326,400	00	0	0	3400								289,843		
9	B5008	12	2,035	8	16	32,240	25	0	0	637	844	585	842					28,629		
13	B5008	12	2,312	8	16	37,312	21	0	0	770	842	770						33,133		
14	B5008	12	1,400	8	64	89,600	21	0	0	644	162	644						79,565		
15	B5008	12	1,500	8	48	72,000	21	0	0	694	162	694						63,936		
16	B5008	12	2,550	8	48	122,400	21	0	0	1219	162	1219						108,691		
17	B5008	8	1,022	8	184	188,048	00	2	2	866							102	74,279		
20	B5008	12	2,543	8	6	15,258	35	0	0	555	193	1184	655	193				13,549		
21	B5008	8	3,782	8	4	15,128	99	0	0	208	50	6						5,916		
														HMOTNOST SPOU (kg)			1052,456			
														HMOTNOST SPOU PRE DVA DEVIATORY (kg)			2104,912			