

Technical drawing of a bridge structure, showing a plan view of a two-lane road bridge. The drawing includes dimensions, labels for components, and cross-sections.

Labels and Dimensions:

- Top Labels:**
 - 150
 - 26330
 - 26820
 - 26390
 - 150
- Left Side Labels:**
 - ZÁMOSTIE
 - ČÍSLO PODPERY (1)
 - PRIEČNY SKLON (0.229 83)
 - RÍMSOVÝ PREFABRIKÁT RH 85 dl. 1660 ±10 mm - ATYP
 - PRÁVÁ RÍMSA
 - OS CESTY III/2300
 - OS NOSNIKA
 - OS ODVODNENIA
 - ĽAVÁ RÍMSA
 - 5.55%
 - 750
 - 690
 - 775
 - 120
 - 5670
 - 7970
 - 2x2000=4000
 - 1670
 - 300
 - 4x2000=8000
- Right Side Labels:**
 - PODBIEL - CENTRUM
 - ČÍSLO PODPERY (4)
 - PRIEČNY SKLON (0.150 29)
 - RÍMSOVÝ PREFABRIKÁT RH 85 dl. 1830 ±10 mm - ATYP
 - RÍMSOVÝ PREFABRIKÁT RH 85 dl. 1660 ±10 mm - ATYP
 - TRVALO PRUŽNÁ ZÁLIEVKA
 - 6.57%
 - 775
 - 690
 - 750
 - 120
 - 5670
 - 7970
 - 2x2000=4000
 - 1670
 - 300
 - 3x2000=8000
- Bottom Labels:**
 - 79840
 - 79840
 - 39x2000=78000
 - 39x2000=78000

The figure contains three technical drawings of a bridge deck:

- Top View (Plan View):** Shows a rectangular deck with a total width of 1830 + 10 mm. The width is divided into three sections: 530 mm (left), 770 mm (center), and 530 mm (right). The center section is further divided into 385 mm (left), 1060 mm (center), and 385 mm (right). The total length is 850 mm, divided into 750 mm (left) and 100 mm (right). There are two cross-section lines labeled 'di. U = 550'.
- Right View (Side View):** Shows the deck's profile. The total height is 850 mm, with a 583 mm section for the deck and a 267 mm section for the parapet. The deck width is 120 mm, and the parapet width is 475 mm. The total width is 600 mm. There are two cross-section lines labeled 'di. U = 550'.
- Bottom View (Longitudinal Section):** Shows the deck's profile from below. The total width is 1830 + 10 mm, divided into 385 mm (left), 1060 mm (center), and 385 mm (right). The total height is 170 mm, divided into 120 mm (left) and 50 mm (right). There are two cross-section lines labeled 'di. U = 550'.

- POHLADOVÉ (VOĽNÉ) HRANY KONŠTRUKCIE ZRAZIŤ FAZETAMI 10/10 mm
 PRECÍZNE HLADKÝ BETÓN


RÍMSOVÉ PREFABRIKÁTY STN EN 206-1- C35/45 -XD3, XF4 (SK)- CL 0,2- Dmax 25 -S3

Názov	Rozmery [mm]			Počet	Objem betónu	Hmotnosť	Objem betónu	Hmotnosť
typ	Šírka B	Výška H	Dĺžka L	[ks]	[m³/ks]	[kg/ks]	[m³]	[kg]
RH85-P1	120	850	1990	4,3	0,186	673,2	8,004	2894,7
RH85-P2	120	850	1830	1	0,171	619,1	0,71	619,1
RH85-P3	120	850	1660	2	0,156	561,6	0,31	1123,2
RH85-L1	120	850	1990	4,7	0,186	673,2	8,749	3164,0
RH85-L2	120	850	1830	1	0,171	619,1	0,71	619,1
						Spolu	17,408	6294,9

AZC doska hr. 10 mm x 170 mm 187,5 bm

- NA TENTO PROJEKT SA VŤAHAJE AUTORSKÉ PRÁVO A MÔŽE SA KÓPIROVAŤ, POĎALEJ ROZŠIŘOVAŤ LEN SO SÚHLASOM AUTORA
- PROJEKTANĽ NENESIE ŽIADNU ZODPOVEDNOSŤ ZA ZMENY USKUTOČNENÉ BEZ JEHO PÍSMENNÉHO SÚHLASU
- ZHOTOVITEĽ JE POVINNÝ O ZISTENÝCH CHYBÁCH V DOKUMENTÁCII BEZODKLADNE INFORMOVAŤ PROJEKTANTA

ZMENA	DÁTUM	KRESLIL	DRUH ZMENY

Zodp. projektant	Ing. Renáta Šýkorová, PhD.	 STRUCTURING STRUKTÚRY A KONSTRUKČNÉ PRÁCE ☎ 0940 / 441018 ✉ info@structuring.eu
Navrhov.	Ing. Marián Šýkora, PhD.	
Vypracoval	Ing. Marián Ševčík	
Kontroloval	Ing. Marián Šýkora, PhD.	
Investor	Správa ciest Žilinského samosprávneho kraja	
	M. Rázusa 104, 010 01 Žilina	
Stavba	PRESTAVBA MOSTNÉHO OBJEKTU MO 2300-001 V OBCI PODBIEL	
Objekt	201-00 Most ev. č. 2300-001	Časť D
Obsah	Výkres tvaru rímsových prefabrikátov	
		Miesto stavby k. i. Podbiel, MK 94/93A Kraj Trvášdin Okres Žilinský Dátum 04/2020 Formát 10xA4 Stupeň D S P , R P Č. zákazky 2019/34.02
		Mierka 1:100, 25 Č. výkresu 7.5 Súprava