



poľad bočny



poliád čelny


Technical drawing of a rectangular frame with rounded corners. The drawing shows a grid of vertical lines and horizontal lines. The vertical lines are labeled 'p' at the top and bottom. The horizontal lines are labeled 'c' at the left and right. The corners are rounded with a radius of 90. The drawing is oriented vertically.



100 0
62 5
50 100

podorysný pohľad

Technical drawing of a rectangular object with rounded corners, showing a top-down view. The drawing includes dimensions: 100 0 (width), 62 5 (height), 50 (radius of the top-left corner), and 100 (radius of the bottom-right corner). The object has a series of vertical lines along its right edge, suggesting a ribbed or grooved surface. A small circular feature is located near the bottom right corner, and a larger circular feature is located near the top right corner. The drawing is labeled "podorysný pohľad" (top-down view) and includes a scale bar at the bottom.



| pol.č | názov a popis prvku | počet ks. | cel. dĺ. bm /m/2 | váha kg/bm | cel.váha | poznámka |
|-------|--|-----------|------------------|------------|----------|----------|
| d | noba ľavičkový-zadný, trubka Ø 51/12mm, CSN 42.57.15 | 2 | 2,0 | 2,417 | 4,83 | |
| b | — — -predná | 2 | 1,0 | 2,417 | 2,417 | |
| c | zákl. rám ľavičkový trubka Ø 51/12mm CSN 42.57.15 | 1 | 6,6 | 2,417 | 15,95 | |
| d | tvoriv sed a opier.časť trubka Ø 14/15mm, CSN 42.57.15, 01/11353.0 | 68 | 10,8,8 | 0,321 | 34,92 | |
| e | plechová pätka hr. 5mm | 3 | 0,66 | 3,92 | 0,25 | |

celková váha 1ks sedačky 58,35 kg