Specification of the CONTRACT PRICE

Item No.	Item	Measure Unit	Quantity	Unit Price	Price per Item
		-	(MU)	(EUR/Mu)	(EUR)
1	CONTRATUAL PRICE	pcs	2,000	0,00	0,00
2	PRICE FOR COMPRESSOR PH	pcsc	1,000	0,00	0,00
2.1	Design and construction of new inner hydraulic parts including evaluation				0,00
	against overtension				0,00
2.2	Elaborationof CFD study (calculated dynamics of liquids)				0,00
2.3	Design and engineering for new instruments and controls (I&C)				0,00
2.4	New assembly that includes:				0,00
2.5	New diffuzors (if the original ones are not usable)				0,00
2.6	New impeller with impeller wheels (if the original ones is not usable)				0,00
2.7	New bearings – 2 x radial and 1 x axial (if the original ones are not				0,00
2.8	New oil seals (if the original ones are not usable)				
	Note: The bearings and oil seals must be designed so that there is no				
	need for compressor casing modification in connection with their				0,00
	replacement. Should there be necessary any modification thereof, it shall				
	be included within scope of supply and CONTRACTUAL PRICE.				
2.9	New vibration sensors of the compressor (9 pcs for each unit) and their				
	installation. New holders for vibration sensors (9 pcs for each unit) and				0,00
	their installation. For details refer to paragraph 4.3 of the Specification.				
2.10	New sensors for measurement of temperature of radial bearings				
	(2 x 2 pieces) and axial bearing (4 pieces) for each unit. For details refer				0,00
	to paragraph 4.4 of the Specification.				
2.11	Production				0,00
2.12	FAT tests				0,00
2.13	Transportation				0,00
2.14	Disassembly of old parts including acoustic enclosure				0,00
2.15	Installation of new/modified assemblies at the site, minor parts (supply				
	and assembly) and assembly of the acoustic enclosure including				0,00
	tightness test				
2.16	Documentation as per paragraph 7 of the Specification				0,00
2.17	Spare parts for commissioning				0,00
2.18	Acceptance tests pursuant to paragraph 5 of the Specification including				0,00
	attandance of an independet verificator at guaranteed parameter tests				0,00
2.19	Training for operation staff				0,00
2.20	Commissioning				0,00
2.21	Set of special tools for assembly and disassembly of the new hydraulic				0.00
	assembly and rotor (1set)				0,00
2.22	Assessment of existing overvoltage regulation and modification in				0.00
	accordance with new construction, if needed				0,00
2.23	Assessment of existing oil system including main oil pump as well as				
	auxiliary oil pump and eventual modification, if needed, considering new				0,00
	scope of operation speed range 2 050 – 3 700 min ⁻¹ .				
2.24	Assessment of existing seal oil system and eventual modification, if				
	needed. The new system must not exceed oil consumption of the current				0,00
	system 24 I/24 hours.				
2.25	Modification of software at existing unit control system (Siemens PCS7)				0.00
	including modification of overvoltage regulation				0,00