

[illegible][illegible][illegible]

1.02	BOČOŠTE	37,07	PVC - PAVONE	slipovost - PAVONE	slipovost - PAVONE
1.41	DEBNA	13,30			
1.42	PRESTORI ŠATNI	31,18			
1.43	PRESTORI ŠATNI	36,76	PVC - PAVONE	slipovost - PAVONE	slipovost - PAVONE
1.44	NIK DEVIČKA	9,42	KERAM. SLAZNA - PAVONE	KERAM. OBLJUG - DNEVNA PAVONE	slipovost - cement PAVONE
1.45	HYPODENE NABRMA	1,53			
1.46	UMETNA DEVIČKA	8,88			
1.47	UPRAVNA DEVIČKA	4,28			
1.48	UMETNA OHLARO	13,35			
1.49	NIK OHLARO	13,16			
1.50	PRESTORI ŠATNI	132,17	PVC - PAVONE	slipovost - PAVONE	slipovost - PAVONE

Case/Case	Tip	Svetlost, cd/m²/typ	Pokrytie
A	Zlomená/prisadená LED svetlá	41 W, 4400 lm, 3000 K, 3000/3000/P500	8
B	Zlomená/prisadená LED svetlá	37 W, 4100 lm, 3000 K, 3000/3000/P500	7
C	Prisadená LED svetlá, OptoBry PMMA kryt, priemer 375 mm	27 W, 2900 lm, 3000 K, 3000/3000/P400	45
D	Prisadená LED svetlá, OptoBry PMMA kryt, priemer 342 mm	26 W, 2150 lm, 3000 K, 3000/3000/P400	6
E	Prisadená LED svetlá, OptoBry PMMA kryt, priemer 480 mm	34 W, 3300 lm, 3000 K, 3000/3000/P400	6
F	Zlomená/prisadená LED svetlá	26 W, 3050 lm, 3000 K, 3000/3000/P500	0
G	Zlomená/prisadená LED svetlá	35 W, 4000 lm, 3000 K, 3000/3000/P500	0
H	Zlomená/prisadená LED svetlá Blietavica, optoBry kryt	23 W, 4500 lm, 3000 K, 3000/3000/P500	0
I	LED panel 60x600 mm	25 W, 3000 lm, 3000 K, 3000/3000/P500	0

[illegible]